
THIS DRAWING IS PROPERTY OF AND PROPRIETARY TO EMERSON. THIS DRAWING AND THE INFORMATION CONTAINED HEREIN SHALL NOT BE REPRODUCED NOR DISCLOSED TO ANYONE EXCEPT THOSE REQUIRING ITS USE FOR EMERSON. AUTHORIZED PURPOSES. THIS DOCUMENT SHALL BE DESTROYED OR RETURNED TO EMERSON WHEN NO LONGER REQUIRED FOR THOSE PURPOSES.

REV	ECO NO.	DATE
0	Release	28-Feb-2018

Notes:

- 1. Material to be 0.003 to 0.005 in thick metalized polyester film (Brady B-486) or an Emerson approved equivalent.
- 2. Label material combined with printing process must be a CSA approved combination.
- 3. Rear surface adhesive must be a low energy, pressure sensitive type.
- 4 Color to be Black graphics on Silver background with Matte finish.



MATERIAL:	UNLESS OTHERWISE SPECIFIED		For Reference Only				
	DIMENSIONS ARE IN INCHES		DESIGNED BY:	DATE	♥		
	TOLERANCES DECIMALS: .X ± .030		D. Beeler	28-Feb-2018	EMERSON.	ı.	Knoxville, TN.
FINISH:			D. Beeler	28-Feb-2018			
FINISH:			LAST REVISED BY:	DATE	2140 Gen 2 FCC/IC RF Label		
	FRACTIONS:	± 1/32	RESP. ENGINEER D. Beeler	DATE			
	ANGULAR:	± 0°-30'	MANUFACTURING ENG.	DATE	CAD FILENAME	DRAWING NO./PART NO.	SCALE
ARTWORK FILENAME/REVISION LEVEL:	FINISH:	32	T. Rogers		D25805.dwg	D 0 - 0 0 -	
	DO NOT SCALE	THIS DRAWING	DOCUMENT CONTROL	DATE	FIRST USED MODEL NO. 2140	D25805	1 1 of