

Appendix 5

RF Exposure Information

FCC ID: NLB24041TX

Maximum transmitter power:

Frequency (GHz)	Maximum peak output power (dBuV/m)	Output power (mW)
2.405	84.69	0.0883
2.440	85.63	0.1096
2.475	85.61	0.1091

For FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$
for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2

Result:

$$(0.0883/5) \cdot \sqrt{2.405} = 0.0273 < 3.0$$

$$(0.1096/5) \cdot \sqrt{2.440} = 0.0342 < 3.0$$

$$(0.1091/5) \cdot \sqrt{2.475} = 0.0343 < 3.0$$

Conclusion:

No SAR is required.