



**Produkte**  
*Products*

<b>Prüfbericht - Nr.:</b> 14044899 001		<b>Seite 1 von 12</b>			
<i>Test Report No.:</i>		<i>Page 1 of 12</i>			
<b>Auftraggeber:</b> <i>Client:</i>	<b>Dickie Toys Hong Kong Ltd.</b> 19/F., Prudential Tower The Gateway, Harbour City 21 Canton Road, Tsimshatsui Kowloon, Hong Kong				
<b>Gegenstand der Prüfung:</b> <i>Test Item:</i>	<b>Short Range Device - Radio Control Toy Transmitter (27.145MHz)</b>				
<b>Bezeichnung:</b> <i>Identification:</i>	<b>27192</b>	<b>Serien-Nr.:</b> <i>Serial No.:</i>	<b>Engineering sample</b>		
<b>Wareneingangs-Nr.:</b> <i>Receipt No.:</i>	<b>A000377767-010</b>	<b>Eingangsdatum:</b> <i>Date of Receipt:</i>	<b>15.06.2016</b>		
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of test item at delivery:</i>	Test sample is not damaged and suitable for testing.				
<b>Prüfort:</b> <i>Testing Location:</i>	<b>TÜV Rheinland Hong Kong Ltd.</b> 8/F, First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong  <b>Hong Kong Productivity Council</b> HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong				
<b>Prüfgrundlage:</b> <i>Test Specification:</i>	<b>FCC Part 15 Subpart C</b> <b>ANSI C63.10-2013</b>				
<b>Prüfergebnis:</b> <i>Test Results:</i>	<b>Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.</b> The above mentioned product was tested and <b>passed</b> .				
<b>Prüflaboratorium:</b> <i>Testing Laboratory:</i>	<b>TÜV Rheinland Hong Kong Ltd.</b> 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong				
<b>geprüft/ tested by:</b>	<b>kontrolliert/ reviewed by:</b>				
25.07.2016	Joey Leung Project Manager		25.07.2016	Benny Lau Senior Project Manager	
<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>	<b>Unterschrift</b> <i>Signature</i>
<b>Sonstiges:</b> Other Aspects		<b>FCC ID: NLB27192TX</b>			
<b>Abkürzungen:</b>	P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet	<b>Abbreviations:</b>	P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested		
<p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b></p> <p><i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i></p>					

## Table of Content

	Page
<b>Cover Page</b> .....	<b>1</b>
<b>Table of Content</b> .....	<b>2</b>
<b>Product information</b> .....	<b>4</b>
Manufacturers declarations .....	4
Product function and intended use.....	4
Submitted documents.....	4
Independent Operation Modes .....	4
Related Submittal(s) Grants .....	4
Remark .....	4
<b>Test Set-up and Operation Mode</b> .....	<b>5</b>
Principle of Configuration Selection .....	5
Test Operation and Test Software.....	5
Special Accessories and Auxiliary Equipment.....	5
Countermeasures to achieve EMC Compliance.....	5
<b>Test Methodology</b> .....	<b>6</b>
Radiated Emission .....	6
Field Strength Calculation.....	6
<b>Test Setup Diagram</b> .....	<b>7</b>
<b>List of Test and Measurement Instruments</b> .....	<b>8</b>
<b>Measurement Uncertainty</b> .....	<b>9</b>
<b>Results FCC Part 15 – Subpart C</b> .....	<b>10</b>
FCC 15.203 – Antenna Requirement 1.....	Pass..... 10
FCC 15.204 – Antenna Requirement 2.....	Pass..... 10
FCC 15.207 – Conducted Emission on AC Mains .....	N/A..... 10
FCC 15.227(a) – Radiated Emission (Fundamental) .....	Pass..... 11
FCC 15.227(b) – Out Of Band Radiated Emissions.....	Pass..... 11
FCC 15.215(c) – 20 dB Bandwidth .....	Pass..... 12
Appendix 1 – Test Results.....	2 pages
Appendix 2 – Test Setup Photos.....	3 pages
Appendix 3 – EUT External Photos.....	4 pages

**Appendix 4 – EUT Internal Photos ..... 3 pages**  
**Appendix 5 – RF Exposure Information .....2 pages**

## Product information

### Manufacturers declarations

	<b>Transmitter</b>
Operating frequency range	27.145 MHz
Type of modulation	ASK
Number of channels	1
Type of antenna	Integral Antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	$V_{nor}$ : 9.0Vdc (6F22 size battery)

### Product function and intended use

The equipment under test (EUT) is a transmitter operating at 27.145MHz. It is powered by 9.0V 6F22 size battery only.

### FCC ID: NLB27192TX

<b>Models</b>	<b>Product description</b>
27192	Radio Control Toy Transmitter

### Submitted documents

Circuit Diagram  
 Block Diagram  
 Bill of material  
 User manual  
 Rating Label

### Independent Operation Modes

The basic operation mode is transmitting mode .

For further information refer to User Manual

### Related Submittal(s) Grants

This is a single application for certification of the transmitter.

### Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- No testing software is provided by the applicant.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

### Countermeasures to achieve EMC Compliance

- none

## Test Methodology

### Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013. The radiated emission measurements of the receiver part were performed according to the procedures in ANSI C63.4-2014.

For measurement below 1GHz, the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz, the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.  
R = Reading of Spectrum Analyzer in dBuV.  
AF = Antenna Factor in dB.  
CF = Cable Attenuation Factor in dB.  
FA = Filter Attenuation Factor in dB.  
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.


## Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



## List of Test and Measurement Instruments

Hong Kong Productivity Council (FCC Registration number: 90656)

### Radiated Emission

Equipment	Manufacturer	Type	S/N	Last Cal. Date	Due Date
Semi anechoic Chamber	Frankonia	Nil	Nil	14 Apr 2015	25 Apr 2017
Test Receiver	R & S	ESU40	100190	07 Dec 2015	07 Dec 2016
Bi conical Antenna	R & S	HK116	100241	01 Sep 2015	01 Sep 2017
Log Periodic Antenna	R & S	HL223	841516/017	01 Sep 2015	01 Sep 2017
Coaxial cable	Harbour	LL335	N/A	10 Jun 2016	10 Jun 2018
Microwave amplifier 0.5 26.5GHz, 25dB gain	HP	83017A	3950M00241	18 Jul 2016	18 Jul 2018
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28 Oct 2015	28 Oct 2017
Horn Antenna	EMCO	3115	9002 3347	26 Aug 2015	26 Aug 2017

### TÜV Rheinland Hong Kong Ltd

#### Radio Frequency Test

Equipment	Manufacturer	Type	S/N	Last Cal. Date	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSP30	100610	20 Jan 2016	19 Jan 2017



## Measurement Uncertainty

The estimated combined standard uncertainty for power-line conducted emissions measurements is  $\pm 3.43\text{dB}$ .

The estimated combined standard uncertainty for radiated emissions measurements is  $\pm 4.68\text{dB}$  (30MHz to 200MHz) and  $\pm 5.73\text{dB}$  (200MHz to 1000MHz) and  $\pm 5.57\text{dB}$  (above 1GHz).

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for the level of confidence is approximately 95%.

## Results FCC Part 15 – Subpart C

<b>FCC 15.203 – Antenna Requirement 1</b>	<b>Pass</b>
<p><b>FCC Requirement:</b> No antenna other than that furnished by the responsible party shall be used with the device</p> <p><b>Results:</b> Antenna type: Fixed Integral wire antenna</p> <p><b>Verdict:</b> Pass</p>	
<b>FCC 15.204 – Antenna Requirement 2</b>	<b>Pass</b>
<p><b>FCC Requirement:</b> An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.</p> <p><b>Results:</b> Only one integral antenna can be used.</p> <p><b>Verdict:</b> N/A</p>	
<b>FCC 15.207 – Conducted Emission on AC Mains</b>	<b>N/A</b>
There is no AC power input or output ports on the EUT.	

<b>FCC 15.227(a) – Radiated Emission (Fundamental)</b>		<b>Pass</b>
Test Specification : ANSI C63.10-2013 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 120kHz Supply voltage : 9.0VDC Temperature : 23°C Humidity : 50%		
Requirement: The field strength of emissions from intentional radiators operated within frequency bands shall comply with the following limit.		
<b>Results:</b> Pass		
Fundamental Frequency		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
27.144	70.0	100 / PK
27.144	63.3	80 / AV
Fundamental Frequency		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
27.144	55.2	100 / PK
27.144	48.4	80 / AV

<b>FCC 15.227(b) – Out Of Band Radiated Emissions</b>		<b>Pass</b>
Test Specification : ANSI C63.10-2013 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 120 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 9.0VDC Frequency range : 9kHz to tenth harmonic Temperature : 23°C Humidity : 50%		
Requirement: The field strength of any emissions which appear outside the assigned bands shall not exceed the general radiated limits shown in §15.209.		
<b>Results:</b> Pass		
		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74 / PK
No peak found	---	54 / AV

Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74 / PK
No peak found	---	54 / AV

FCC 15.215(c) – 20 dB Bandwidth		Pass		
Test Specification : ANSI C63.10 – 2013 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 10kHz / 30kHz Supply voltage : 9.0VDC Temperature : 23°C Humidity : 50%				
Requirement:	The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.			
<b>Results:</b>	For test protocols refer to Appendix 1, page 2-3.			
Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)
27.145	27.11936	> 26.96	27.17056	< 27.28