

**Prüfbericht - Nr.:**  
*Test Report No.:*

**14037235 001**

**Seite 1 von 2**  
*Page 1 of 2*

## Appendix 6

### RF Exposure Information

**Prüfbericht - Nr.:****14037235 001****Seite 2 von 2***Test Report No.:**Page 2 of 2*

Antenna Type: Permanent external antenna  
Antenna Gain: 0 dBi  
Nominal rated field strength: 75.2dB $\mu$ V/m at 3m  
Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 78.2dB $\mu$ V/m at 3m in frequency 27.145MHz, thus

$$\text{EIRP} = [(\text{FS} \cdot \text{D})^2 \cdot 1000 / 30] = 0.01982\text{mW}$$

$$\begin{aligned} \text{Conducted power} &= \text{Radiated Power (EIRP)} - \text{Antenna Gain} \\ &= 0.01982\text{mW}. \end{aligned}$$

The SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:

$$\begin{aligned} &= [474 \cdot (1 + \log_{10}(f(\text{MHz})))]/2 \\ &= 371.2\text{mW} \end{aligned}$$

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.