



Produkte
Products

| | | | | | |
|--|---|---|---------------------------|---------------------------------|---|
| Prüfbericht - Nr.: 14041785 001 | | | Seite 1 von 13 | | |
| <i>Test Report No.:</i> | | | <i>Page 1 of 13</i> | | |
| Auftraggeber: | | Dickie Toys Hong Kong Ltd. | | | |
| <i>Client:</i> | | 19/F., Prudential Tower, The Gateway, Harbour City, 21 Canton Road, Tsimshatsui, Kowloon, Hong Kong | | | |
| Gegenstand der Prüfung: | | Short Range Device - RC Toy Walkie Talkie (49.860MHz) | | | |
| <i>Test Item:</i> | | | | | |
| Bezeichnung: | 49026 | Serien-Nr.: | Engineering sample | | |
| <i>Identification:</i> | | <i>Serial No.:</i> | | | |
| Wareneingangs-Nr.: | A000265005-011 | Eingangsdatum: | 10.10.2015 | | |
| <i>Receipt No.:</i> | | <i>Date of Receipt:</i> | | | |
| Zustand des Prüfgegenstandes bei Anlieferung: | | Test sample received is sufficient for testing and not damaged. | | | |
| <i>Condition of test item at delivery:</i> | | | | | |
| Prüfört: | TÜV Rheinland Hong Kong Ltd. | | | | |
| <i>Testing Location:</i> | 8/F., First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong | | | | |
| | Hong Kong Productivity Council | | | | |
| | HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong | | | | |
| Prüfgrundlage: | FCC Part 15, Subpart B | | | | |
| <i>Test Specification:</i> | FCC Part 15, Subpart C | | | | |
| | ANSI C63.10-2013 | | | | |
| Prüfergebnis: | Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n). | | | | |
| <i>Test Result:</i> | <i>The test item passed the test specification(s).</i> | | | | |
| Prüflaboratorium: | TÜV Rheinland Hong Kong Ltd. | | | | |
| <i>Testing Laboratory:</i> | 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong | | | | |
| geprüft / tested by: | | kontrolliert / reviewed by: | | | |
| 26.11.2015 | Joey Leung Project Manager |  | 26.11.2015 | Sharon Li Department Manager |  |
| Datum | Name/Stellung | Unterschrift | Datum | Name/Stellung | Unterschrift |
| <i>Date</i> | <i>Name/Position</i> | <i>Signature</i> | <i>Date</i> | <i>Name/Position</i> | <i>Signature</i> |
| Sonstiges / Other Aspects: | | | | | |
| FCC ID: NLB49026TX | | | | | |
| Abkürzungen: | | P(ass) = entspricht Prüfgrundlage | Abbreviations: | | P(ass) = passed |
| F(ail) = entspricht nicht Prüfgrundlage | | | | F(ail) = failed | |
| N/A = nicht anwendbar | | | | N/A = not applicable | |
| N/T = nicht getestet | | | | N/T = not tested | |
| <p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</p> <p><i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i></p> | | | | | |

Contents

| | |
|---|--------------|
| Test Summary | 3 |
| List of Test and Measurement Instruments..... | 4 |
| General Product Information | 5 |
| Product Function and Intended Use..... | 5 |
| Ratings and System Details..... | 5 |
| Independent Operation Modes..... | 6 |
| Submitted Documents | 6 |
| Related Submittal(s) Grants | 6 |
| Test Set-up and Operation Mode..... | 7 |
| Principle of Configuration Selection | 7 |
| Test Operation and Test Software | 7 |
| Special Accessories and Auxiliary Equipment..... | 7 |
| Countermeasures to achieve EMC Compliance..... | 7 |
| Test Methodology | 8 |
| Radiated Emission..... | 8 |
| Field Strength Calculation | 8 |
| Results FCC Part 15 – Subpart B | 9 |
| Subclause 15.107 – Conducted Emission on AC Mains | N/A.....9 |
| Subclause 15.109 (b) – Spurious Radiated Emissions | Pass10 |
| Results FCC Part 15 – Subpart C | 11 |
| Subclause 15.203 – Antenna Requirement..... | Pass11 |
| Subclause 15.215(c) – Bandwidth Measurement | Pass11 |
| Subclause 15.235(a) – Radiated Emission of Carrier Frequency..... | Pass12 |
| Subclause 15.235(b) – Spurious Radiated Emissions | Pass13 |
| Appendix 1 Test Protocol | |
| Appendix 2 Test Setup | |
| Appendix 3 EUT External Photo | |
| Appendix 4 EUT Internal Photo | |
| Appendix 5 FCCID Label, Block Diagram, Schematics, BOM and User manual | |
| Appendix 6 RF Exposure Information | |

www.tuv.com

Test Summary

Conducted Emissions

Result: N/A

Bandwidth Measurement

Result: Pass

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Radiated Emission

| Equipment used | Manufacturer | Model No. | S/N | Cal. Interval | Last Cal. Date |
|--|--------------|--------------|------------|---------------|----------------|
| Semi-anechoic Chamber | Frankonia | Nil | Nil | 1 year | 14 Apr 2015 |
| Cable | Hubersuhner | SUCOFLEX 104 | 72799 /6 | 2 years | 31 Mar 2014 |
| Test Receiver | R & S | ESU26 | 100050 | 1 year | 12 Feb 2015 |
| Log Periodic Antenna | R & S | HL223 | 841516/020 | 2 year | 01 Sep 2014 |
| Coaxial cable | Harbour | LL335 | N/A | 2 year | 10 Jun 2014 |
| Microwave amplifier 0.5-26.5GHz, 25dB gain | HP | 83017A | 3123A00437 | 2 years | 14 Jul 2014 |
| High Pass Filter (cutoff freq. =1000MHz) | Trilithic | 23042 | 9829213 | 2 years | 29 Oct 2015 |
| Active Loop Antenna | EMCO | 6502 | 9107-2651 | 1 year | 15 Aug 2015 |

TÜV Rheinland Hong Kong Ltd.

Bandwidth Measurement

| Equipment used | Manufacturer | Model No. | S/N | Cal. Interval | Last Cal. Date |
|-------------------|--------------|-----------|--------|---------------|----------------|
| Spectrum Analyzer | R & S | FSP 3 | 100561 | 1 year | 28 May 2015 |

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a RC toy walkie talkie operating at 49.860MHz. The EUT has a switch and a push button.

FCC ID: NLB49026TX

| Models | Product description |
|-------------|---------------------------------|
| 20 111 8176 | Radio Control Toy Walkie Talkie |

Ratings and System Details

| | |
|--------------------|--|
| | Transmitter |
| Frequency range | : 49.860MHz |
| Number of channels | : 1 |
| Type of antenna | : Permanently attached wire antenna with 0dBi gain |
| Power supply | : Battery operated 9V |
| Ports | : none |
| Protection Class | : III |

www.tuv.com

Independent Operation Modes

The basic operation mode is voice transmission and reception.

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork
- Bill of material

Related Submittal(s) Grants

This is a single application for certification of the transmitter and superregenerative receiver.

www.tuv.com

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.10-2013.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where

- FS = Field Strength in dBuV/m at 3 meters.
- R = Reading of Spectrum Analyzer in dBuV.
- AF = Antenna Factor in dB.
- CF = Cable Attenuation Factor in dB.
- FA = Filter Attenuation Factor in dB.
- PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Results FCC Part 15 – Subpart B

Subclause 15.107 – Conducted Emission on AC Mains

N/A

| | | |
|-----------------------|---|---------------------------------|
| Test Specification | : | FCC Part 15 Subclause 15.107(a) |
| Measurement Procedure | : | ANSI 63.10-2013 |
| Port of Testing | : | AC Mains Input Port |
| Detector Function | : | Quasi-peak and Average |
| Resolution Bandwidth | : | 9 kHz |
| Supply Voltage | : | 120VAC 60Hz |
| Mode of Operation | : | N/A |
| Temperature | : | N/A |
| Humidity | : | N/A |

This test is not applicable due to EUT is powered by 9V battery only. The EUT is not designed to be connected to the public utility (AC) power line.

Subclause 15.109 (b) – Spurious Radiated Emissions
Pass

Test Specification : FCC Part 15 Subclause 15.109
 Measurement Procedure : ANSI 63.10-2013
 Port of Testing : Enclosure
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Quasi Peak
 Resolution Bandwidth : 120 kHz
 Supply Voltage : DC 9V
 Measuring Frequency Range : 9kHz – 1GHz
 Mode of Operation : Receiving
 Temperature : 23°C
 Humidity : 53%

Polarization: Vertical

| Frequency (MHz) | Field strength at 3m (dBuV/m) | Limit at 3m (dBuV/m) | Delta to Limit (dB) |
|-----------------|-------------------------------|----------------------|---------------------|
| 47.910 | 17.2 | 40.0 | -22.8 |
| No peak found | --- | 43.5 | --- |
| No peak found | --- | 46.0 | --- |

Polarization: Horizontal

| Frequency (MHz) | Field strength at 3m (dBuV/m) | Limit at 3m (dBuV/m) | Delta to Limit (dB) |
|-----------------|-------------------------------|----------------------|---------------------|
| No peak found | --- | 40.0 | --- |
| No peak found | --- | 43.5 | --- |
| No peak found | --- | 46.0 | --- |

Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Requirement

Pass

Requirement : No antenna other than that furnished by the responsible party shall be used with the device

Result : Permanent attached antenna

Subclause 15.215(c) – Bandwidth Measurement

Pass

Test Specification : ANSI C63.10-2013
Port of Testing : Antenna port
Detector Function : Peak
Mode of Operation : Transmitting
Supply Voltage : DC 9V

The field strength of any emissions appearing at the lower edge 49.82 MHz and upper edge 49.90 MHz are 64.42 dB and 62.16 dB below the carrier respectively.

For test results refer to Appendix 1.

Subclause 15.235(a) – Radiated Emission of Carrier Frequency
Pass

Test Specification : FCC Part 15 Subclause 15.235(a)
 Measurement Procedure : ANSI 63.10-2013
 Port of Testing : Enclosure
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Peak and Average
 Measurement BW : 120 kHz
 Supply Voltage : DC 9V
 Mode of Operation : Transmitting mode
 Temperature : 23°C
 Humidity : 53%

Polarization: Vertical

| Detector function | Frequency (MHz) | Measured Field strength at 3m (dB μ V/m) | Delta to Limit (dB) |
|-------------------|-----------------|--|---------------------|
| Peak | 49.859 | 72.4 | -27.6 |
| Average | 49.859 | 72.2 | -7.8 |

Polarization: Horizontal

| Detector function | Frequency (MHz) | Measured Field strength at 3m (dB μ V/m) | Delta to Limit (dB) |
|-------------------|-----------------|--|---------------------|
| Peak | 49.859 | 52.8 | -47.2 |
| Average | 49.859 | 52.6 | -27.4 |

Limit
Subclause 15.227(a)

| Frequency within the band | Peak Emission | | Average Emission | |
|---------------------------|---------------|--------------|------------------|--------------|
| | (μ V/m) | dB μ V/m | (μ V/m) | dB μ V/m |
| 49.82 – 49.90 MHz | 100,000 | 100.0 | 10,000 | 80.0 |

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Subclause 15.235(b) – Spurious Radiated Emissions
Pass

Test Specification : FCC Part 15 Subclause 15.209
 Measurement Procedure : ANSI 63.10-2013
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Quasi Peak
 Measurement BW : 120 kHz
 Supply Voltage : DC 9V
 Measuring Frequency Range : 30 - 1000MHz
 Mode of Operation : Transmitting mode
 Temperature : 23°C
 Humidity : 53%

Polarization: Vertical

| Frequency (MHz) | Field strength at 3m (dBuV/m) | Limit at 3m (dBuV/m) | Delta to Limit (dB) |
|-----------------|-------------------------------|----------------------|---------------------|
| 99.719 | 30.4 | 43.5 | -13.1 |
| 149.579 | 38.6 | 43.5 | -4.9 |
| 199.439 | 32.1 | 43.5 | -11.4 |
| 598.318 | 30.7 | 46.0 | -15.3 |
| 698.038 | 31.7 | 46.0 | -14.3 |
| 797.758 | 35.5 | 46.0 | -10.5 |

Polarization: Horizontal

| Frequency (MHz) | Field strength at 3m (dBuV/m) | Limit at 3m (dBuV/m) | Delta to Limit (dB) |
|-----------------|-------------------------------|----------------------|---------------------|
| 99.719 | 23.4 | 43.5 | -19.6 |
| 149.579 | 30.2 | 43.5 | -13.3 |
| 199.439 | 29.4 | 43.5 | -14.1 |
| 249.299 | 24.1 | 46.0 | -21.9 |
| 797.758 | 29.9 | 46.0 | -16.1 |

Remark: (1) ' * ' indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.
 (2) There is no spurious emission found between lowest oscillating frequency to 30 MHz.

Limit
Subclause 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

| Frequency (MHz) | Field strength (µV/m) | Field strength (dBµV/m) | Measurement distance (m) |
|-----------------|-----------------------|-----------------------------|--------------------------|
| 30-88 | 100 | $20 \cdot \log(100) = 40.0$ | 3 |
| 88-216 | 150 | $20 \cdot \log(150) = 43.5$ | 3 |
| 216-960 | 200 | $20 \cdot \log(200) = 46.0$ | 3 |
| 960-2500 | 500 | $20 \cdot \log(500) = 54.0$ | 3 |

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.