

Introduction

This is a Bluetooth USB Dongle with class 2 output power. It uses CSR BC04 single chip Bluetooth IC and is Bluetooth v2.1+EDR specification supported, and works on 2.4GHz ISM Band.

It works with notebook and desktop PCs. Simply plug it into notebook or desktop PCs' USB connectors; you can then use the many profiles provided and communicate with other Bluetooth devices without the tangle of cables. It will empower your information application with more mobility.

1. Functional Description

- Bluetooth v2.1+EDR compliant
- Full speed USB v1.1 Interface
- Wireless communication within a radius of 10 Meters
- Connect up to 7 different enabled Bluetooth devices
- Encryption and authentication ensure safe, secure communications
- Low power consumption

2. Specification

3.1 Interface:

- USB Version 1.1 compliance

3.2 Functions:

- Main chip: CSR BlueCore 04
- Bluetooth 2.4GHz~2.4835GHz license-free ISM Band frequency hopping
- Connections within ranges up to 32.8 feet (10 Meters in open site) (Distance varies depending on actual environment)
- Connects up to 7 BT devices in a Piconet
- Data rate: 2~3Mbps (theoretical)
- Class 2 Bluetooth radio
- Security: encrypted link, authentication
- Bluetooth profiles support includes:

Generic access profile (GAP),	Serial port profile (SPP),
Service discovery app profile (SDAP),	Generic object exchange profile (GOEP),
Object push profile (OPP),	File transfer profile (FTP),
Dial-up network profile (DUN),	LAN access profile (LAP),
Fax profile (FAX),	Headset Profile
Human Interface Device(HID)	Personal Area Network(PAN)

產企主管 核定		研發主管 核定		填寫人	
------------	--	------------	--	-----	--

PROJECT: GUBTCR42I

3.3. Mechanical

19 * 15 * 5.39 mm
(L x W x H)

3.4. Certification

CE/FCC/BQB

3.5. Environmental Operating Ranges

N/A

3.6. Power Consumption


- Idle: 9.4mA/5V
 - Typical: 48.7mA/5V
 - Max Transmit : 54.3mA/5V (peak),
 - Max Receive : 42.5mA/5V (peak)
- (Varies depending on use environment)

3.7. LED Indication

TX/RX indicator

3.8. Drivers support

Windows 2000 /XP /Vista, MAC OS 10.2 or above



產企主管 核定		研發主管 核定		填寫人	
------------	--	------------	--	-----	--