

# TEST REPORT

## Part 15 Subpart C 15.247

**Equipment under test** BABY CAMERA

**Model name** SEP-5001RDN

**Derivative model** SEP-5002RDN

**FCC ID** NLMSEP5001RDN

**Applicant** Hanwha Techwin Co., Ltd.

**Manufacturer** RDI Technology (Shenzhen) Co.,Ltd.

**Date of test(s)** 2017.01.02 ~ 2017.01.09

**Date of issue** 2017.01.09

**Issued to**

**Hanwha Techwin Co., Ltd.**

1204, Changwon-daero, Seongsan-gu Changwon-si,  
 Gyeongsangnam-do, South Korea

Tel: +82-70-7147-8361/ Fax: +82-31-8108-3717



**Issued by**

**KES Co., Ltd.**

C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,  
 Gyeonggi-do, Korea

473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea

Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
	
Kwang-yeol Choo Test engineer	Jeff Do Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.



---

### Revision history

Revision	Date of issue	Test report No.	Description
-	2017.01.09	KES-RF-17T0005	Initial



---

## TABLE OF CONTENTS

1.	General information .....	4
1.1.	EUT description .....	4
1.2.	Test configuration.....	5
1.3.	Frequency/channel operations .....	5
1.4.	Accessory information .....	5
1.5.	Device modifications.....	5
1.6.	Derivation model information .....	5
2.	Summary of tests .....	6
3.	Test results.....	7
3.1.	20 dB bandwidth .....	7
3.2.	Peak output power .....	9
3.3.	Carrier frequency separation .....	11
3.4.	Number of hopping frequency.....	12
3.5.	Time of occupancy .....	13
3.6.	Radiated restricted band and emissions.....	15
3.7.	Conducted spurious emissions & band edge .....	29
3.8.	AC conducted emissions .....	32
Appendix A.	Measurement equipment .....	34
Appendix B.	Test setup photos .....	35

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.

## 1. General information

Applicant: Hanwha Techwin Co., Ltd.  
Applicant address: 1204, Changwon-daero, Seongsan-gu, Changwon-si  
Gyeongsangnam-do, South Korea  
Test site: KES Co., Ltd.  
Test site address: C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea  
473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea  
FCC rule part(s): 15.247  
FCC ID: NLMSEP5001RDN  
Test device serial No.:  Production  Pre-production  Engineering

### 1.1. EUT description

Equipment under test BABY CAMERA  
Frequency range FHSS : 2 408 MHz ~ 2 468 MHz  
WIFI : 2 412 MHz ~ 2 462 MHz (11b/g/n\_HT20)  
2 422 MHz ~ 2 452 MHz(11n\_HT40)  
Model SEP-5001RDN  
Derivative model SEP-5002RDN  
Modulation technique FHSS, GFSK  
WIFI : DSSS, OFDM  
Number of channels FHSS : 16  
WIFI : 11(802.11b/g/n\_HT20), 7(802.11n\_HT40)  
Antenna specification Antenna type: Dipole, Peak gain: 2 dBi  
Power source AC 120 V (Adapter)

15.247(a)(1) that the rx input bandwidths shift frequencies in synchronization with the transmitted

15.247(g): The system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): The system does not coordinate it channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

#### Pseudorandom frequency hopping sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 16 RF channels.

#### Equal hopping frequency use

All channels are used equally on average.

#### Example of a 16 hopping sequence in data mode:

12, 14, 03, 16, 02, 05, 10, 06, 09, 01, 13, 07, 11, 08, 15, 04

## 1.2. Test configuration

The **Hanwha Techwin Co., Ltd. BABY CAMERA FCC ID: NLMSEP5001RDN** was tested per the guidance of ANSI C63.10-2013 and DA 00-705. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

## 1.3. Frequency/channel operations

Ch.	Frequency (MHz)
01	2408
.	.
09	2440
.	.
16	2468

## 1.4. Accessory information

Applicant	Equipment	Manufacturer	Model	Power source
Hanwha Techwin Co., Ltd.	Environment Sensor	RDI Technology (Shenzhen) Co., Ltd.	SEA-SE10	DC 5V(Mini USB)

## 1.5. Device modifications

N/A

## 1.6. Derivation model information

The circuit diagram and software of the basic model(SEP-5001RDN) and derivative(SEP-5002RDN) are fundamentally the same. But the derivative is being blocked sensor port.



## 2. Summary of tests

Reference	Test description	Test results
15.247(a)(1)(iii)	20 dB bandwidth	Pass
15.247(b)(1)	Output power	Pass
15.247(a)(1)	Channel separation	Pass
15.247(a)(1)(iii)	Number of channels	Pass
15.247(a)(1)(iii)	Time of occupancy	Pass
15.205, 15.209	Radiated restricted band and emission	Pass
15.207(d)	Conducted band edge and out of band emissions	Pass
15.207(a)	AC conducted emissions	Pass

### 3. Test results

#### 3.1. 20 dB bandwidth

##### Test procedure

DA 00-705

##### Test setting


1. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
2. RBW  $\geq$  1% of the 20 dB bandwidth
3. VBW  $\geq$  RBW
4. Sweep = auto
5. Detector function = peak
6. Sweep = auto couple
7. Trace mode = max hold

##### Limit

Not applicable

##### Test results

Frequency(MHz)	20 dB bandwidth(MHz)	Limit(MHz)
2 408	4.284	0.5
2 440	4.197	
2 468	3.386	



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.



### 3.2. Peak output power

#### Test procedure

DA 00-705

#### Test setting

1. Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
2. RBW > the 20 dB bandwidth of the emission being measured
3. VBW  $\geq$  RBW
4. Sweep = Auto
5. Detector function = Peak
6. Trace = Max hold


#### Limit

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to §15.247(b)(1), For frequency hopping systems operating in the 2 400 ~ 2 483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725 ~ 5 805 MHz band: 1 Watt.

#### Test results

Frequency(MHz)	Channel no.	Measured power (dBm)	Peak Power Limit (dBm)
2 408	01	16.81	20.97
2 440	09	16.88	20.97
2 468	16	16.61	20.97



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.

### 3.3. Carrier frequency separation

#### Test procedure

DA 00-705

#### Test Setting

1. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
2. Span = wide enough to capture the peaks of two adjacent channels
3. Resolution (or IF) Bandwidth (RBW)  $\geq 1\%$  of the span
4. Video (or Average) Bandwidth (VBW)  $\geq$  RBW
5. Sweep = auto
6. Detector function = peak
7. Trace = max hold


Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

#### Limit

According to 15.247(a)(1), frequency hopping system operating in 2 400 ~ 2 483.5 MHz. Band may have hopping channel carrier frequencies that are separated by 25 kHz or two-third of 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### Test results

Frequency(MHz)	Channel no.	Channel Separation (MHz)
2 440	09	4.009



### 3.4. Number of hopping frequency

#### Test procedure

DA 00-705

#### Test setting

1. The EUT must have its hopping function enabled.
2. Frequency range: 2 400 MHz ~ 2 483.5 MHz
3. Span = the frequency band of operation
4. RBW = 300 kHz ( $\geq 1\%$  of the span)
5. VBW = 1 MHz ( $\geq$  RBW)
6. Sweep = auto
7. Detector function = peak
8. Trace = max hold


All the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

#### Limit

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2 400 ~ 2 483.5 MHz bands shall use at least 15 hopping frequencies.

#### Test results

Frequency	Number of hopping frequency	Limit
2 408 ~ 2 468 MHz	16	$\geq 15$



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.

### **3.5. Time of occupancy**

#### **Test procedure**

DA 00-705

#### **Test setting**


1. The EUT must have its hopping function enabled.
2. Span = zero span, centered on a hopping channel
4. RBW = 1 MHz
5. VBW = 1 MHz ( $\geq$  RBW)
6. Sweep = as necessary to capture the entire dwell time per hopping channel
7. Detector function = peak
8. Trace = max hold

#### **Limit**

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2 400 ~ 2 483.5 MHz band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 6.4 second period.

A period time =  $0.4(s) \times 16 = 6.4(s)$

Frequency (MHz)	Burst time (ms)	Burst number	Time of occupancy (ms)	Limit (ms)
2 440	2.174	156	339.144	400




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.


### 3.6 Radiated restricted band and emissions

#### Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.



### Test procedure

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. Spectrum analyzer settings for  $f < 1$  GHz:
  - Span = wide enough to fully capture the emission being measured
  - RBW = 100 kHz
  - VBW  $\geq$  RBW
  - Sweep = auto
  - Detector function = quasi peak
  - Trace = max hold
8. Spectrum analyzer settings for  $f \geq 1$  GHz: Peak
  - Span = wide enough to fully capture the emission being measured
  - RBW = 1 MHz
  - VBW  $\geq$  RBW
  - Sweep = auto
  - Detector function = peak
  - Trace = max hold
9. Spectrum analyzer settings for  $f \geq 1$  GHz: Average
  - Span = wide enough to fully capture the emission being measured
  - RBW = 1 MHz
  - VBW  $\geq 1/T$  Hz, where T= pulse width in seconds
  - Sweep = auto
  - Detector function = average
  - Trace = max hold
10. Duty Cycle Correction Factor (16 channel hopping)
  - a. Time to cycle through all channels =  $\Delta t = \tau[\text{ms}] \times 16$  channels = 34.784 ms, where  $\tau$  = pulse width
  - b.  $100 \text{ ms} / \Delta t[\text{ms}] = H \rightarrow$  Round up to next highest integer,  $H' = 1$
  - c. Worst Case Dwell Time =  $\tau[\text{ms}] \times H' = 2.174$  ms
  - d. Duty Cycle Correction =  $20 \log (\text{Worst Case Dwell Time} / 100\text{ms}) \text{ dB} = -33.25 \text{ dB}$

**Note:**

1. The spectrum is measured from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1 GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20 dB of the respective limits were not reported.
2. When Average result is different from peak result over 20 dB (over-averaging), according to 15.35 (c), as a “duty cycle correction factor”, pulse averaging with 20 log(duty cycle) has to be used.  
Duty cycle correction factor =  $20\log(\text{dwell time}/100 \text{ ms})$
3. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
4. Average test would be performed if the peak result were greater than the average limit.
5. Field strength(dB $\mu$ V/m) = Level(dB $\mu$ V) + Correction factors(dB/m) + Cable loss(dB) + or  $F_d$ (dB)
6. Correction factors(dB/m) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB)
7. Margin(dB) = Limit(dB $\mu$ V/m) - Field strength(dB $\mu$ V/m)
8. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.
9.  $f < 30 \text{ MHz}$ , extrapolation factor of 40 dB/decade of distance.  $F_d = 40\log(D_m / D_s)$   
 $f \geq 30 \text{ MHz}$ , extrapolation factor of 20 dB/decade of distance.  $F_d = 20\log(D_m / D_s)$

Where:

- $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters

**Limit**

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :


Frequency (MHz)	Distance (Meters)	Radiated ( $\mu V/m$ )
0.009 ~ 0.490	300	2 400 / F(kHz)
0.490 ~ 1.705	30	24 000 / F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

**Test results (Below 30 MHz)**

Mode: GFSK  
 Distance of measurement: 3 meter  
 Channel: 09 (Worst case)


Frequency (MHz)	Level (dB $\mu$ V)	Ant. Pol. (H/V)	CF (dB)	F <sub>d</sub> (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
No spurious emissions were detected within 20 dB of the limit							



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.

**Test results (Below 1 000 MHz)**

Mode: GFSK  
 Distance of measurement: 3 meter  
 Channel: 09 (Worst case)




**Note.**

1. All spurious emission at channels are almost the same below 1 GHz, so that middle channel was chosen at representative in final test.
2. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.


**Test results (Above 1 000 MHz)**

Mode:                     GFSK                      
 Distance of measurement:           3 meter            
 Channel:                     01                    

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2341.31	53.16	Peak	H	-1.96	-	51.20	74.00	22.80
2347.04	53.46	Peak	V	-1.95	-	51.51	74.00	22.49
2347.20	52.57	Peak	H	-1.95	-	50.62	74.00	23.38
2347.20	55.30	Peak	V	-1.95	-	53.35	74.00	20.65
3315.00	36.86	Peak	V	0.17	-	37.03	74.00	36.97
7852.00	36.01	Peak	H	12.78	-	48.79	74.00	25.21



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.



Mode: GFSK  
 Distance of measurement: 3 meter  
 Channel: 09

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2347.30	50.54	Peak	H	-1.95	-	48.59	74.00	25.41
2347.90	51.48	Peak	V	-1.94	-	49.54	74.00	24.46
3250.00	35.34	Peak	V	0.23	-	35.57	74.00	38.43
3640.00	35.35	Peak	H	0.97	-	36.32	74.00	37.68



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.





**KES Co., Ltd.**


C-3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-RF-17T0005  
Page (25 ) of (35)



Mode: GFSK  
Distance of measurement: 3 meter  
Channel: 16

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2133.10	51.00	Peak	V	-2.46	-	48.54	74.00	25.46
2346.60	50.63	Peak	H	-1.95	-	48.68	74.00	25.32
2483.85	54.80	Peak	H	-1.60	-	53.20	74.00	20.80
2484.02	52.22	Peak	V	-1.60	-	50.62	74.00	23.38
3271.00	36.36	Peak	H	0.21	-	36.57	74.00	37.43
3380.00	36.02	Peak	V	0.10	-	36.12	74.00	37.88

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.

**Test results (18 GHz to 30 GHz)**

Mode:                     GFSK                      
 Distance of measurement:           3 meter            
 Channel:                     09(Worst case)                    

Frequency (MHz)	Level (dB $\mu$ V)	Ant. Pol. (H/V)	CF (dB)	F <sub>d</sub> (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
No spurious emissions were detected within 20dB of the limit							



**Note.**

1. Average test would be performed if the peak result were greater than the average limit.
2. Actual = Reading + AFCL(Ant. factor – Amp. gain + Cable loss) + DCF(Duty cycle correction factor)
3. Duty cycle correction factor = 20log(dwel time/100 ms)

### **3.7 Conducted spurious emissions & band edge**

#### **Test procedure**

DA 00-705


#### **Test setting**

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.
2. RBW = 100 kHz
3. VBW  $\geq$  300 kHz
4. Detector = Peak
5. Number of sweep points  $\geq 2 \times$  Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize


#### **Limit**

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

### Test results



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.

### 3.8. AC conducted emissions

#### Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB $\mu$ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

#### Note:

1. All AC line conducted spurious emission are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and the appropriate frequencies. All data rates and modes were investigated for conducted spurious emission. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.
2. Both Cable loss and LISN factor are included in measurement level(QP Level or AV Level)



### Test results

Hot Line																																																																																																				
	<b>Final Result</b> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>QuasiPeak (dBµV)</th> <th>CAverage (dBµV)</th> <th>Limit (dBµV)</th> <th>Margin (dB)</th> <th>Meas. Time (ms)</th> <th>Bandwidth (kHz)</th> <th>Line</th> <th>Corr. (dB)</th> </tr> </thead> <tbody> <tr><td>0.185000</td><td>---</td><td>27.92</td><td>54.26</td><td>26.34</td><td>1000.0</td><td>9.000</td><td>L1</td><td>21.0</td></tr> <tr><td>0.185000</td><td>46.40</td><td>---</td><td>64.26</td><td>17.86</td><td>1000.0</td><td>9.000</td><td>L1</td><td>21.0</td></tr> <tr><td>1.530000</td><td>---</td><td>9.44</td><td>46.00</td><td>36.56</td><td>1000.0</td><td>9.000</td><td>L1</td><td>20.0</td></tr> <tr><td>1.530000</td><td>17.66</td><td>---</td><td>56.00</td><td>38.34</td><td>1000.0</td><td>9.000</td><td>L1</td><td>20.0</td></tr> <tr><td>4.875000</td><td>---</td><td>10.97</td><td>46.00</td><td>35.03</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>4.875000</td><td>16.19</td><td>---</td><td>56.00</td><td>39.81</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>6.675000</td><td>---</td><td>14.64</td><td>50.00</td><td>35.36</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>6.675000</td><td>22.76</td><td>---</td><td>60.00</td><td>37.24</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>6.720000</td><td>---</td><td>14.63</td><td>50.00</td><td>35.37</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> <tr><td>6.720000</td><td>22.89</td><td>---</td><td>60.00</td><td>37.11</td><td>1000.0</td><td>9.000</td><td>L1</td><td>19.8</td></tr> </tbody> </table>	Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	0.185000	---	27.92	54.26	26.34	1000.0	9.000	L1	21.0	0.185000	46.40	---	64.26	17.86	1000.0	9.000	L1	21.0	1.530000	---	9.44	46.00	36.56	1000.0	9.000	L1	20.0	1.530000	17.66	---	56.00	38.34	1000.0	9.000	L1	20.0	4.875000	---	10.97	46.00	35.03	1000.0	9.000	L1	19.8	4.875000	16.19	---	56.00	39.81	1000.0	9.000	L1	19.8	6.675000	---	14.64	50.00	35.36	1000.0	9.000	L1	19.8	6.675000	22.76	---	60.00	37.24	1000.0	9.000	L1	19.8	6.720000	---	14.63	50.00	35.37	1000.0	9.000	L1	19.8	6.720000	22.89	---	60.00	37.11	1000.0	9.000	L1	19.8
Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)																																																																																												
0.185000	---	27.92	54.26	26.34	1000.0	9.000	L1	21.0																																																																																												
0.185000	46.40	---	64.26	17.86	1000.0	9.000	L1	21.0																																																																																												
1.530000	---	9.44	46.00	36.56	1000.0	9.000	L1	20.0																																																																																												
1.530000	17.66	---	56.00	38.34	1000.0	9.000	L1	20.0																																																																																												
4.875000	---	10.97	46.00	35.03	1000.0	9.000	L1	19.8																																																																																												
4.875000	16.19	---	56.00	39.81	1000.0	9.000	L1	19.8																																																																																												
6.675000	---	14.64	50.00	35.36	1000.0	9.000	L1	19.8																																																																																												
6.675000	22.76	---	60.00	37.24	1000.0	9.000	L1	19.8																																																																																												
6.720000	---	14.63	50.00	35.37	1000.0	9.000	L1	19.8																																																																																												
6.720000	22.89	---	60.00	37.11	1000.0	9.000	L1	19.8																																																																																												
Neutral Line																																																																																																				
	<b>Final Result</b> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>QuasiPeak (dBµV)</th> <th>CAverage (dBµV)</th> <th>Limit (dBµV)</th> <th>Margin (dB)</th> <th>Meas. Time (ms)</th> <th>Bandwidth (kHz)</th> <th>Line</th> <th>Corr. (dB)</th> </tr> </thead> <tbody> <tr><td>0.165000</td><td>---</td><td>27.89</td><td>55.21</td><td>27.32</td><td>1000.0</td><td>9.000</td><td>N</td><td>21.0</td></tr> <tr><td>0.165000</td><td>48.16</td><td>---</td><td>65.21</td><td>17.05</td><td>1000.0</td><td>9.000</td><td>N</td><td>21.0</td></tr> <tr><td>0.210000</td><td>---</td><td>23.85</td><td>53.21</td><td>29.36</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.9</td></tr> <tr><td>0.210000</td><td>43.85</td><td>---</td><td>63.21</td><td>19.36</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.9</td></tr> <tr><td>1.345000</td><td>---</td><td>11.43</td><td>46.00</td><td>34.57</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.0</td></tr> <tr><td>1.345000</td><td>18.71</td><td>---</td><td>56.00</td><td>37.29</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.0</td></tr> <tr><td>28.900000</td><td>---</td><td>13.37</td><td>50.00</td><td>36.63</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.5</td></tr> <tr><td>28.900000</td><td>23.36</td><td>---</td><td>60.00</td><td>36.64</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.5</td></tr> <tr><td>29.830000</td><td>---</td><td>13.67</td><td>50.00</td><td>36.33</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.6</td></tr> <tr><td>29.830000</td><td>22.27</td><td>---</td><td>60.00</td><td>37.73</td><td>1000.0</td><td>9.000</td><td>N</td><td>20.6</td></tr> </tbody> </table>	Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	0.165000	---	27.89	55.21	27.32	1000.0	9.000	N	21.0	0.165000	48.16	---	65.21	17.05	1000.0	9.000	N	21.0	0.210000	---	23.85	53.21	29.36	1000.0	9.000	N	20.9	0.210000	43.85	---	63.21	19.36	1000.0	9.000	N	20.9	1.345000	---	11.43	46.00	34.57	1000.0	9.000	N	20.0	1.345000	18.71	---	56.00	37.29	1000.0	9.000	N	20.0	28.900000	---	13.37	50.00	36.63	1000.0	9.000	N	20.5	28.900000	23.36	---	60.00	36.64	1000.0	9.000	N	20.5	29.830000	---	13.67	50.00	36.33	1000.0	9.000	N	20.6	29.830000	22.27	---	60.00	37.73	1000.0	9.000	N	20.6
Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)																																																																																												
0.165000	---	27.89	55.21	27.32	1000.0	9.000	N	21.0																																																																																												
0.165000	48.16	---	65.21	17.05	1000.0	9.000	N	21.0																																																																																												
0.210000	---	23.85	53.21	29.36	1000.0	9.000	N	20.9																																																																																												
0.210000	43.85	---	63.21	19.36	1000.0	9.000	N	20.9																																																																																												
1.345000	---	11.43	46.00	34.57	1000.0	9.000	N	20.0																																																																																												
1.345000	18.71	---	56.00	37.29	1000.0	9.000	N	20.0																																																																																												
28.900000	---	13.37	50.00	36.63	1000.0	9.000	N	20.5																																																																																												
28.900000	23.36	---	60.00	36.64	1000.0	9.000	N	20.5																																																																																												
29.830000	---	13.67	50.00	36.33	1000.0	9.000	N	20.6																																																																																												
29.830000	22.27	---	60.00	37.73	1000.0	9.000	N	20.6																																																																																												

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The test results in the report only apply to the tested sample.

## Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum Analyzer	R&S	FSV30	100736	1 year	2017.07.06
Spectrum Analyzer	R&S	FSV40	101002	1 year	2017.07.06
8360B Series Swept Signal Generator	HP	83630B	3844A00786	1 year	2017.01.25
PSG Analog Signal Generator	Agilent	E8257C	US42340237	1 year	2017.07.05
Attenuator	Keysight	8493C	82509	1 year	2017.01.25
Attenuator	HP	8493C	08961	1 year	2017.07.05
Loop Antenna	R&S	HFH2-Z2.335.4711.52	826532	2 years	2017.03.03
Trilog-broadband antenna	SCHWARZBECK	VULB 9163	9168-713	2 years	2017.05.15
Horn Antenna	A.H.	SAS-571	781	2 years	2017.05.07
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170550	2 years	2017.04.30
High Pass Filter	WAINWRIGHT INSTRUMENT	WHJS3000-10TT	1	1 year	2017.07.04
Low Pass Filter	WEINSCHL	WLK1.0/18G-10TT	1	1 year	2017.07.04
Preamplifier	HP	8449B	3008A00538	1 year	2017.07.05
Broadband Amplifier	SCHWARZBECK	BBV-9721	PS9721-003	1 year	2017.01.25
EMI Test Receiver	R&S	ESR3	101781	1 year	2017.05.03
EMI Test Receiver	R&S	ESU26	100552	1 year	2017.04.24
EMI Test Receiver	R&S	ESR3	101783	1 year	2017.05.03
LISN	R&S	ENV216	101137	1 year	2017.02.04

### Peripheral devices

Device	Manufacturer	Model No.	Serial No.
-	-	-	-