

## RF exposure

According to FCC part 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Average time
(A) Limits for Occupational / Control Exposures				
300 – 1 500	--	--	f/300	6
1 500 - 100000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300 – 1 500	--	--	f/1500	6
1 500 – 100 000	--	--	1	30

f= frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \times G) / (4 \times \pi \times R^2)$

Where,

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in  $\text{mW}$

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1 \text{ mW/cm}^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### Results - Worst case

#### - 2.4G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm( $\text{mW/cm}^2$ )	Limit ( $\text{mW/cm}^2$ )
802.11n(HT20)	MIMO	16.00	6.14	0.03256	1
802.11n(HT40)	MIMO	15.00	6.14	0.02587	1

**- 5.2G**

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11ac(VHT20)	MIMO	15.00	5.72	0.02348	1
802.11ac(VHT40)	MIMO	15.00	5.72	0.02348	1
802.11ac(VHT80)	MIMO	13.00	5.72	0.01482	1

**- 5.3G**

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11ac(VHT20)	MIMO	15.00	5.72	0.02348	1
802.11ac(VHT40)	MIMO	15.00	5.72	0.02348	1
802.11ac(VHT80)	MIMO	13.00	5.72	0.01482	1

**- 5.5G**

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11ac(VHT20)	MIMO	14.00	6.45	0.02207	1
802.11ac(VHT40)	MIMO	14.00	6.45	0.02207	1
802.11ac(VHT80)	MIMO	12.00	6.45	0.01392	1

**- 5.8G**

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11ac(VHT20)	MIMO	14.00	8.63	0.03645	1
802.11ac(VHT40)	MIMO	14.00	8.63	0.03645	1
802.11ac(VHT80)	MIMO	12.00	8.63	0.02300	1