

## RF exposure

According to FCC part 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Average time
(A) Limits for Occupational / Control Exposures				
300 – 1 500	--	--	f/300	6
1 500 - 100000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300 – 1 500	--	--	f/1500	6
1 500 – 100 000	--	--	1	30

f= frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \times G) / (4 \times \pi \times R^2)$

Where,

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### Results - Worst case

#### - 5.2G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11ac(VHT20)	SISO	9.00	2.72	0.00296	1
802.11ac(VHT40)	SISO	7.50	2.72	0.00209	1
802.11ac(VHT80)	SISO	7.50	2.72	0.00209	1

#### - 5.3G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11ac(VHT20)	SISO	8.00	2.72	0.00235	1
802.11ac(VHT40)	SISO	6.50	2.72	0.00166	1
802.11ac(VHT80)	SISO	6.50	2.72	0.00166	1

**- 5.5G**

<b>Operation mode</b>		<b>Max tune-up Average power (dBm)</b>	<b>Antenna gain (dBi)</b>	<b>Power density at 20 cm(mW/cm<sup>2</sup>)</b>	<b>Limit (mW/cm<sup>2</sup>)</b>
802.11ac(VHT20)	SISO	8.00	3.45	0.00278	1
802.11ac(VHT40)	SISO	7.50	3.45	0.00248	1
802.11ac(VHT80)	SISO	7.50	3.45	0.00248	1

**- 5.8G**

<b>Operation mode</b>		<b>Max tune-up Average power (dBm)</b>	<b>Antenna gain (dBi)</b>	<b>Power density at 20 cm(mW/cm<sup>2</sup>)</b>	<b>Limit (mW/cm<sup>2</sup>)</b>
802.11ac(VHT20)	SISO	12.00	5.63	0.01153	1
802.11ac(VHT40)	SISO	8.50	5.63	0.00515	1
802.11ac(VHT80)	SISO	8.50	5.63	0.00515	1