

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

TEST REPORT For FCC

Test Report No. : 2008100005
Date of Issue : October 03, 2008
FCC ID : NLMURF-SA010
Model/Type No. : URF-SA010
Kind of Product : UHF RFID Fixed Reader
Applicant : SAMSUNG TECHWIN CO., LTD
Applicant Address : 145-3 Sangdaewon 1 dong, Chungwon-ku, Sunghnam City,
Kyungki-do, Korea
Manufacturer : SAMSUNG TECHWIN CO., LTD
Manufacturer Address : 145-3 Sangdaewon 1 dong, Chungwon-ku, Sunghnam City,
Kyungki-do, Korea
Contact Person : Won Joo - Jung / Engineer
Telephone : +82-31-740-88765
Received Date : September 10, 2008
Test period : Start : September 23, 2008 End : October 03, 2008
Test Results : In Compliance Not in Compliance

The test results presented in this report relate only to the object tested.

Tested by



Kyu-Chul, Shin
Test Engineer
Date: October 03, 2008

Reviewed by



Young-Joon, Park
Technical Manager
Date: October 03, 2008

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

REPORT REVISION HISTORY

Date	Revision	Page No
October 03, 2008	Issued (2008100005)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
1.0 General Product Description	4
1.1 Tested Frequency	4
1.2 Model Differences	5
1.3 Device Modifications	5
1.4 Peripheral Devices	5
1.5 Calibration Details of Equipment Used for Measurement	5
1.6 Test Facility.....	5
1.7 Laboratory Accreditations and Listings	6
2.0 Summary of tests	7
2.1 Transmitter Requirements	8
2.1.1 Carrier Frequency Separation	8
2.1.2 Number of Hopping Frequencies	10
2.1.3 Occupied Bandwidth.....	12
2.1.4 Time of Occupancy (Dwell Time)	16
2.1.5 Maximum peak Conducted Output Power.....	19
2.1.6 Band-edge.....	22
2.1.7 Field Strength of Emissions	28
2.1.8 Conducted Voltage Emissions	35
APPENDIX A – Test Equipment Used For Tests	42

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

1.0 General Product Description

Equipment model name : URF-SA010
Serial number : Prototype
EUT condition : Pre-production, not damaged
Antenna type : Patch antenna Gain 5.19dBi
Frequency Range : 902.75MHz ~ 927.25 MHz
RF power : 27.76dBm - Conducted
Number of channels : 50CH
Channel Spacing : 0.5MHz
Channel Access Protocol : Frequency Hopping
Type of Modulation : GFSK
Power Source : DC 9V

1.1 Tested Frequency

	LOW	MID	HIGH
Frequency (MHz)	902.75	914.25	927.25

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

1.2 Model Differences

Not applicable

1.3 Device Modifications

The following modifications were necessary for compliance:

1.4 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
I.T.E Power Supply (for EUT)	AULT KOREA Corp.	JPW140KA0900N05	-	-
Personal Computer	COMWINS COM.	DB-P73	BL5497DQ300027K	DoC
LCD Monitor	HEWLETT-PACKARD COMPANY	HSTND-2L05	CNN5130R5D	DoC
UHF Panel Antenna	SAMSUNG TECHWIN CO., LTD	SAU-06-USS	20070112	-
Mouse(PS/2)	SUZHOU LOGITECH ELECTRONICS CO., LTD.	M-S69	-	DoC
Keyboard(PS/2)	HEWLETT-PACKARD COMPANY	5219	BN50702141	DoC
Notebook PC	T o s h i b a	PSL4K-00L00K	Z7037782R	DoC

1.5 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.






1.6 Test Facility

The measurement facility is located at 386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea.

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

1.7 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	 93250
JAPAN	VCCI	10 meter Open Area Test Site and one conducted site.	 R-948, C-986
KOREA	MIC	EMI (10 meter Open Area Test Site and two conducted sites) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 No. 51, KR0025
International	KOLAS	EMC	
Europe	GLAS	EMC EN 55011, EN 55022, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 50130-4, EN 55024, EN 61204-3, EN 60601-1-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11	 No.13000796-02

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

2.0 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 50 hops		C
15.247(a)	Occupoed Bandwidth	< 500 KHz		C
15.247	Time of Occupancy	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 /15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:
- FCC Part 15.247, ANSI C63.4-2003

2.1 Transmitter Requirements

2.1.1 Carrier Frequency Separation

Test Location

RF Test Room

Test Procedures

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled. After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 5 MHz

RBW = 100 kHz (1% of the span) Sweep = auto

VBW = 100 kHz (RBW) Detector function = peak

Trace = max hold




Figure 1 : Measurement setup for the carrier frequency separation

Limit

The EUT shall have hopping channel carrier frequencies separated minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Results

Carrier Frequency Separation (MHz)	Result
0.5	Complies

See next pages for actual measured spectrum plots.


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Carrier Frequency Separation



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

2.1.2 Number of Hopping Frequencies

Test Location

RF Test Room

Test Procedures

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Frequency range Start = 902 MHz, Stop = 928 MHz


RBW = 300 kHz (1% of the span)

Sweep = auto

VBW = 300 kHz (RBW)

Detector function = peak

Trace = max hold



Limit

The EUT in the 902MHz ~ 928MHz band shall use at least 50 channels.

Test Results

Total number of Hopping Channels	Result
50	Complies

See next pages for actual measured spectrum plots.


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Number of Hopping Frequencies



2.1.3 Occupied Bandwidth

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 500kHz


RBW = 3 kHz (1% of the span)

Sweep = auto

VBW = 10 kHz (RBW)

Detector function = peak

Trace = max hold



Limit

The maximum allowed 20dB bandwidth of the hopping channel is 500kHz

Test Results

Frequency (MHz)	20dB bandwidth (KHz)	99% bandwidth (KHz)	Result
902.75	55.00	61.00	Complies
914.25	55.00	57.00	Complies
927.25	52.00	60.00	Complies

See next pages for actual measured spectrum plots.


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

20 dB Bandwidth Low Channel



Mid Channel




CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

20 dB Bandwidth High Channel




CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea


Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

99% Bandwidth Low Channel



Mid Channel




CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

99% Bandwidth High Channel



2.1.4 Time of Occupancy (Dwell Time)

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Test Location

RF Test Room

Test Procedures

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

Span = zero


RBW = 3 kHz

Trace = max hold

VBW = 10 KHz (RBW)

Detector function = peak

Sweep = as necessary to capture the entire dwell time per hopping channel



Limit

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period .

Test Results

Dwell time= 0.247sec

Time between occupancy = 21.12sec

Time of Occupancy = period / time between occupancy * dwell time

Therefore -> (20/21.12)*0.247=0.2339second < 0.4second


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea


Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Dwell time



Time between occupancy



2.1.5 Maximum peak Conducted Output Power

Test Location

RF Test Room

Test Procedures

The maximum peak conducted output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

Span = 20 MHz (approximately 5 times of the 20 dB bandwidth)


RBW = 3 MHz (greater than the 20 dB bandwidth of the EUT)

VBW = 3 MHz (RBW)

Detector function = peak

Trace = max hold

Sweep = auto



Limit

< 1 W

Test Results

Frequency (MHz)	Peak output power(dBm)	Peak output power(mW)	Result
902.75	27.69	587.49	Complies
914.25	27.76	597.04	Complies
927.25	27.65	582.10	Complies

See next pages for actual measured spectrum plots.



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Maximum peak Conducted Output Power




CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com



2.1.6 Band-edge

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

RBW = 100 kHz


VBW = 100 kHz (RBW)

Span = 100 MHz

Trace = max hold

Detector function = peak

Sweep = auto



Limit

> 20 dBc

Test Results

All conducted emission in any 100 kHz bandwidth outside of the spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Band – edge (with Hopping)





CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com


Band – edge (without Hopping)



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Band – edge (at 20 dB blow) – Low channel Frequency Range = 30 MHz ~ 10th harmonic




CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Band – edge (at 20 dB blow) – Mid channel Frequency Range = 30 MHz ~ 10th harmonic




CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Band – edge (at 20 dB blow) – High channel Frequency Range = 30 MHz ~ 10th harmonic



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

2.1.7 Field Strength of Emissions

Test Location

Testing was performed at a test distance of 3 meter Open Area Test Site

Test Procedures

The height of the measuring antenna was varied between 1 to 4 m and the table was rotated a full revolution in order to obtain maximum values of the electric field intensity. The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

The spectrum analyzer is set to:


Below 1GHz :

RBW=100KHz/VBW=300KHz/Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz/Sweep=AUTO

(b) AVERAGE: RBW=1MHz/VBW=10Hz/Sweep=AUTO



Limit

- 15.209(a)

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m
30-88	100**	40
88-216	150**	43.5
216-960	200**	46
Above 960	500	54

** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Test Results

EUT	UHF RFID FIXED READER	Measurement Detail	
Model	URF-SA010	Frequency Range	Below 1000MHz
Channel	-	Detector function	Quasi-Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
254.25	39.5	6.5	Quasi-Peak

Test Data

[RS-232 mode]

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
42.00	19.0	V	1.0	12.9	0.2	40.0	32.1	7.9
95.26	22.5	V	1.0	9.3	0.8	43.5	32.6	10.9
119.52	21.6	H	2.0	10.0	1.1	43.5	32.7	10.8
198.25	24.2	H	1.7	7.3	1.5	43.5	33.0	10.5
240.00	26.5	H	1.8	9.1	1.9	46.0	37.5	8.5
254.25	27.8	V	1.5	9.7	2.0	46.0	39.5	6.5

H : Horizontal, V : Vertical

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

[LAN mode]

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
94.13	22.0	V	1.0	9.3	0.8	43.5	32.1	11.4
115.25	23.3	H	1.8	9.9	1.0	43.5	34.2	9.3
153.50	27.8	V	1.2	7.6	1.3	43.5	32.7	10.8
190.05	27.9	H	2.0	7.1	1.5	43.5	36.5	7.0
216.25	28.2	H	1.9	8.1	1.7	46.0	38.0	8.0
631.10	15.6	V	1.4	17.6	3.9	46.0	37.1	8.9

H : Horizontal, V : Vertical

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

[USB mode]

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
111.26	22.2	H	1.8	9.8	1.0	43.5	33.0	10.5
117.65	23.4	V	2.0	9.9	1.0	43.5	34.3	9.2
147.25	27.8	V	1.2	7.8	1.3	43.5	32.7	10.8
221.05	23.3	V	1.4	8.2	1.7	46.0	33.2	12.8
240.00	25.2	H	1.0	9.1	1.9	46.0	36.2	9.8
260.05	21.7	V	1.9	9.8	2.1	46.0	33.6	12.4

H : Horizontal, V : Vertical

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

Test Results

EUT	UHF RFID FIXED READER	Measurement Detail	
Model	URF-SA010	Frequency Range	1-25GHz
Frequency	902.75MHz	Detector function	Average/Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
2708.22	52.19/60.70	1.81/13.3	Average/Peak

Test Data

Frequency [MHz]	Reading A/P [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits/ Detector A/P [dBuV/m]	Result A/P [dBuV/m]
				Antenna	Amp. Gain	Cable		
2708.22	53.79/62.3	V	1	29.9	33.0	1.5	54.0 /74.0	52.19/60.70

*No emission Were detected at level greater than 20dB below limit.

Restricted band edge test data

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits [dBuV/m]	Result [dBuV/m]
				Antenna	Amp. Gain	Cable		
No emissions were detected at a level greater than 20dB below limit.								

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

Test Results

EUT	UHF RFID FIXED READER	Measurement Detail	
Model	URF-SA010	Frequency Range	1-25GHz
Frequency	914.25MHz	Detector function	Average/Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
2742.78	51.63/60.37	2.37/12.49	Average/Peak

Test Data

Frequency [MHz]	Reading A/P [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits/ Detector A/P [dBuV/m]	Result A/P [dBuV/m]
				Antenna	Amp. Gain	Cable		
2742.78	53.23/61.97	V	1	29.9	33.0	1.5	54.0 /74.0	51.63/13.63

*No emission Were detected at level greater than 20dB below limit.

Restricted band edge test data

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits [dBuV/m]	Result [dBuV/m]
				Antenna	Amp. Gain	Cable		
No emissions were detected at a level greater than 20dB below limit.								

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

Test Results

EUT	UHF RFID FIXED READER	Measurement Detail	
Model	URF-SA010	Frequency Range	1-25GHz
Frequency	927.25MHz	Detector function	Average/Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
1854.5	47.93/59.43	6.07/14.57	Average/Peak

Test Data

Frequency [MHz]	Reading A/P [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits/ Detector A/P [dBuV/m]	Result A/P [dBuV/m]
				Antenna	Amp. Gain	Cable		
1854.5	51.13/62.63	V	1	28.2	32.9	1.5	54.0 /74.0	47.93/59.43

*No emission Were detected at level greater than 20dB below limit.

Restricted band edge test data

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits [dBuV/m]	Result [dBuV/m]
				Antenna	Amp. Gain	Cable		
No emissions were detected at a level greater than 20dB below limit.								

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

2.1.8 Conducted Voltage Emissions

Test Location

Shielded Room

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency.

Test Results

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
0.19	56.4	7.6	Quasi-peak

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

Test Data

[RS-232 mode]

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
	LISN	Cable		Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
				[dBuV]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dB]
5.15	0.2	0.7	H	60.0	47.1	48.0	12.0	50.0	38.1	39.0	11.0
5.26	0.2	0.7	N	60.0	47.5	48.4	11.6	50.0	39.7	40.6	9.4
5.32	0.2	0.7	H	60.0	48.5	49.4	10.6	50.0	40.7	41.6	8.4
5.33	0.2	0.7	N	60.0	48.3	49.2	10.8	50.0	40.7	41.6	8.4
5.38	0.2	0.7	H	60.0	48.0	48.9	11.1	50.0	39.7	40.6	9.4
5.52	0.2	0.7	N	60.0	48.5	49.4	10.6	50.0	38.0	38.9	11.1

H : HOT, N : NEUTRAL


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea


Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

[HOT]



[NEUTRAL]



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

[LAN mode]

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
	LISN	Cable		Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
				[dBuV]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dB]
5.08	0.2	0.7	N	60.0	45.9	46.8	13.2	50.0	40.2	41.1	8.9
5.28	0.2	0.7	H	60.0	46.9	47.8	12.2	50.0	39.9	40.8	9.2
5.33	0.2	0.7	N	60.0	48.2	49.1	10.9	50.0	40.3	41.2	8.8
5.34	0.2	0.7	H	60.0	47.0	47.9	12.1	50.0	39.9	40.8	9.2
5.47	0.2	0.7	H	60.0	46.8	47.7	12.3	50.0	38.8	39.7	10.3
5.52	0.2	0.7	N	60.0	47.7	48.6	11.4	50.0	38.3	39.2	10.8

H : HOT, N : NEUTRAL


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea


Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

[HOT]



[NEUTRAL]



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
 Tel: +82-31-339-9970 Fax: +82-31-339-9855
 www.e-ctk.com

[USB mode]

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
	LISN	Cable		Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
				[dBuV]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dB]
0.19	0.1	0.4	N	64.0	55.9	56.4	7.6	54.0	40.5	41.0	13.0
5.35	0.2	0.7	H	60.0	47.5	48.4	11.6	50.0	39.4	40.3	9.7
5.42	0.2	0.7	H	60.0	48.9	49.8	10.2	50.0	41.4	42.3	7.7
5.57	0.2	0.7	N	60.0	48.6	49.5	10.5	50.0	38.7	39.6	10.4
12.11	0.5	0.8	H	60.0	45.5	46.8	13.2	50.0	39.5	40.8	9.2
24.22	1.0	0.8	H	60.0	48.3	50.1	9.9	50.0	45.2	47.0	3.0

H : HOT, N : NEUTRAL


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea


Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

[HOT]



[NEUTRAL]



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
1	Spectrum Analyzer	Agilent	8564E	3551A0041	2008-11-01
2	Spectrum Analyzer	HP	E4403B	US39440619	2009-09-03
3	Spectrum Analyzer	Rohde & Schwarz	FSP-30	100994	2008-11-19
4	EMI Test Receiver	Rohde & Schwarz	ESVS30	826638/008	2009-03-07
5	ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014	2010-06-12
6	LOOP ANTENNA	EMCO	6502	9107-2652	2008-10-17
7	LOOP ANTENNA	EMCO	6502	9607-3020	2010-03-06
8	System Power Supply	HP	6032A	3440A-10521	2009-07-07
9	EPM Series Power Meter	HP	E4418A	GB38272734	2008-11-03
10	Power Sensor	HP	8481A	331BA92056	2008-11-03
11	Power Sensor	HP	8482B	331BA05406	2008-11-03
12	Audio Analyzer	HP	8903B	2747A03432	2008-11-01
13	ESG-D Series Signal Generator	Agilent	E4432B	US40054094	2008-11-01
14	SYNTHESIZED SWEEPER	HP	8341B	2819A01563	2008-11-22
15	Modulation Analyzer	HP	8901B	3438A05228	2008-11-08
16	Attenuator	HP	8494A	3308A33351	2008-11-06
17	Attenuator	HP	8496A	3308A15142	2008-11-06
18	Temp&Humi Chamber	Kunpoong	KP-1000	2002KP050041	2009-01-21
19	Temp&Humi Chamber	Kunpoong	KP-RC2000	2002KP650042	2009-01-21
20	EMC Analyzer	Agilent	E7405A	MY45110859	2008-01-09
21	Horn Antenna	ETS-Lindgren	3115	00078894	2008-11-29
22	Horn Antenna	ETS-Lindgren	3115	00078895	2008-11-29
23	Horn Antenna	ETS-Lindgren	3116	00062504	2008-11-27
24	Horn Antenna	ETS-Lindgren	3116	00062916	2008-11-27
25	Dipole Antenna	SCHWARZBECK	VHA 9103	VHA91032557	2009-11-27
26	Dipole Antenna	SCHWARZBECK	UHA 9105	UHA91052417	2009-11-27
27	OPT H64 AMPLIFIER	HP	8447F	3113A06814	2009-02-28
28	PREAMPLIFIER	Agilent	8449B	3008A02307	2008-11-05
29	Radio Communication Tester	Rohde & Schwarz	CMU200	106765	2009-02-09
30	Band Reject Filter	Wainwright Instruments	WRCG824	-	2009-04-16
31	Band Reject Filter	Wainwright Instruments	WRCG1750	-	2009-04-16
32	Field Strength Meter	Rohde & Schwarz	ESHS30	862024/001	2009-03-04
33	LISN	Rohde & Schwarz	ESH3-Z5	100207	2008-12-20
34	LISN	EMCO	3825/2	9206-1971	2008-12-20