



A D T

FCC TEST REPORT (15.247)

REPORT NO.: RF130722C16-6

MODEL NO.: 0P4E230

FCC ID: NM80P4E230

RECEIVED: Jul. 16, 2013

TESTED: Jul. 30, 2013 ~ Aug. 02, 2013

ISSUED: Sep. 05, 2013

APPLICANT: HTC Corporation

ADDRESS: No. 23, Xinghua Rd., Taoyuan City, Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1. CERTIFICATION.....	6
2. SUMMARY OF TEST RESULTS.....	7
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES.....	9
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	10
3.3 DESCRIPTION OF SUPPORT UNITS.....	14
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST	14
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	14
4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)	15
4.1 RADIATED EMISSION AND BANDEdge MEASUREMENT	15
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT	15
4.1.2 TEST INSTRUMENTS	16
4.1.3 TEST PROCEDURES.....	17
4.1.4 DEVIATION FROM TEST STANDARD	17
4.1.5 TEST SETUP	18
4.1.6 EUT OPERATING CONDITIONS.....	18
4.1.7 TEST RESULTS	19
4.2 CONDUCTED EMISSION MEASUREMENT	29
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	29
4.2.2 TEST INSTRUMENTS	29
4.2.3 TEST PROCEDURES.....	30
4.2.4 DEVIATION FROM TEST STANDARD	30
4.2.5 TEST SETUP	31
4.2.6 EUT OPERATING CONDITIONS.....	31
4.2.7 TEST RESULTS	32
4.3 6dB BANDWIDTH MEASUREMENT	34
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	34
4.3.2 TEST SETUP	34
4.3.3 TEST INSTRUMENTS	34
4.3.4 TEST PROCEDURE	34
4.3.5 DEVIATION FROM TEST STANDARD	34
4.3.6 EUT OPERATING CONDITIONS.....	34
4.3.7 TEST RESULTS	35
4.4 CONDUCTED OUTPUT POWER	36
4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	36
4.4.2 TEST SETUP	36
4.4.3 TEST INSTRUMENTS	36
4.4.4 TEST PROCEDURES.....	36
4.4.5 DEVIATION FROM TEST STANDARD	36
4.4.6 EUT OPERATING CONDITIONS.....	36
4.4.7 TEST RESULTS	37
4.5 POWER SPECTRAL DENSITY MEASUREMENT	38
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	38
4.5.2 TEST SETUP	38



A D T

4.5.3 TEST INSTRUMENTS	38
4.5.4 TEST PROCEDURE	38
4.5.5 DEVIATION FROM TEST STANDARD	38
4.5.6 EUT OPERATING CONDITION	38
4.5.7 TEST RESULTS	39
4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT	40
4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT	40
4.6.2 TEST SETUP	40
4.6.3 TEST INSTRUMENTS	40
4.6.4 TEST PROCEDURE	40
4.6.5 DEVIATION FROM TEST STANDARD	41
4.6.6 EUT OPERATING CONDITION	41
4.6.7 TEST RESULTS	41
5. TEST TYPES AND RESULTS (FOR 5.0GHz BAND)	45
5.1 RADIATED EMISSION AND BANDEdge MEASUREMENT	45
5.1.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT	45
5.1.2 TEST INSTRUMENTS	46
5.1.3 TEST PROCEDURES.....	46
5.1.4 DEVIATION FROM TEST STANDARD	46
5.1.5 TEST SETUP	46
5.1.6 EUT OPERATING CONDITIONS.....	46
5.1.7 TEST RESULTS	47
5.2 CONDUCTED EMISSION MEASUREMENT	56
5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	56
5.2.2 TEST INSTRUMENTS	56
5.2.3 TEST PROCEDURES.....	56
5.2.4 DEVIATION FROM TEST STANDARD	56
5.2.5 TEST SETUP	56
5.2.6 EUT OPERATING CONDITIONS.....	56
5.2.7 TEST RESULTS	57
5.3 6dB BANDWIDTH MEASUREMENT	59
5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	59
5.3.2 TEST SETUP	59
5.3.3 TEST INSTRUMENTS	59
5.3.4 TEST PROCEDURE	59
5.3.5 DEVIATION FROM TEST STANDARD	59
5.3.6 EUT OPERATING CONDITIONS.....	59
5.3.7 TEST RESULTS	60
5.4 MAXIMUM OUTPUT POWER.....	61
5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	61
5.4.2 TEST SETUP	61
5.4.3 INSTRUMENTS	61
5.4.4 TEST PROCEDURES.....	61
5.4.5 DEVIATION FROM TEST STANDARD	61
5.4.6 EUT OPERATING CONDITIONS.....	61
5.4.7 TEST RESULTS	62
5.5 POWER SPECTRAL DENSITY MEASUREMENT	63
5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	63
5.5.2 TEST SETUP.....	63
5.5.3 TEST INSTRUMENTS	63



A D T

5.5.4 TEST PROCEDURE.....	63
5.5.5 DEVIATION FROM TEST STANDARD	63
5.5.6 EUT OPERATING CONDITION	63
5.5.7 TEST RESULTS	64
5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT	65
5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT	65
5.6.2 TEST SETUP	65
5.6.3 TEST INSTRUMENTS	65
5.6.4 TEST PROCEDURE	65
5.6.5 DEVIATION FROM TEST STANDARD	65
5.6.6 EUT OPERATING CONDITION	65
5.6.7 TEST RESULTS	65
6. PHOTOGRAPHS OF THE TEST CONFIGURATION	69
7. INFORMATION ON THE TESTING LABORATORIES	70
8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	71



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130722C16-6	Original release	Sep. 05, 2013



A D T

1. CERTIFICATION

PRODUCT: Smartphone

MODEL NO.: 0P4E230

BRAND: HTC

APPLICANT: HTC Corporation

TESTED: Jul. 30, 2013 ~ Aug. 02, 2013

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment (model: 0P4E230) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Ivonne Wu , DATE : Sep. 05, 2013

Ivonne Wu / Senior Specialist

APPROVED BY : Sam Chen , DATE : Sep. 05, 2013

Sam Chen / Assistant Manager



A D T

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -6.73dB at 0.43125MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -4.93dB at 2484.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Smartphone
MODEL NO.	0P4E230
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion battery)
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b:11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to MCS7
OPERATING FREQUENCY	2.4GHz: 2412 ~ 2462MHz 5.0GHz: 5745 ~ 5825MHz
NUMBER OF CHANNEL	2.4GHz: 11 for 802.11b, 802.11g, 802.11n (20MHz) 5.0GHz: 5 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz)
OUTPUT POWER	332.660mW for 2412 ~ 2462MHz 217.771mW for 5745 ~ 5825MHz
ANTENNA TYPE	2.4GHz: PIFA antenna with -3dBi gain 5.0GHz: PIFA antenna with -4dBi gain
ANTENNA CONNECTOR	NA
DATA CABLE	Refer to Note as below
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Refer to Note as below

NOTE:

1. This report is issued as a duplicate report to BV ADT report no.: 130716C20-6. The difference compared with original report is adding WCDMA Band IV, removing LTE band 7 by software, changing model name and FCC ID. The verified result for EUT of FCC ID: NM80P4E230 was not worse than FCC ID: NM80P4E200. Therefore, the original data was kept in this report.
2. The EUT's accessories list refers to Ext. Pho.
3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 DESCRIPTION OF TEST MODES

FOR 2.4GHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

FOR 5.0GHz (5745 ~ 5805MHz):

5 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz



A D T

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

FOR 2.4GHz:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE≥1G: Radiated Emission above 1GHz RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6.0

POWER LINE CONDUCTED EMISSION TEST:

TEST CONDITION
BT Link + WLAN (2.4G) Link + Earphone + USB Cable + Adapter



A D T

BANDEdge MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	MCS0

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
PLC	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao



A D T

FOR 5.0GHz (5745 ~ 5825MHz):

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane.

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6.0
802.11n (20MHz)	149 to 165	149, 157, 165	OFDM	BPSK	MCS0
802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n (20MHz)	149 to 165	149	OFDM	BPSK	MCS0

POWER LINE CONDUCTED EMISSION TEST:

TEST CONDITION
BT Link + WLAN (5G) Link + Earphone + USB Cable + Adapter



A D T

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11a	149 to 165	149, 165	OFDM	BPSK	6.0
802.11n (20MHz)	149 to 165	149, 165	OFDM	BPSK	MCS0
802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0

ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6.0
802.11n (20MHz)	149 to 165	149, 157, 1165	OFDM	BPSK	MCS0
802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0


TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
PLC	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2009

KDB 558074 D01 DTS Meas Guidance v03r01

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_BV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUe DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 15, 2013	Apr. 14, 2014
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2012	Dec. 16, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Mar. 25, 2013	Mar. 24, 2014
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Jan. 07, 2013	Jan. 06, 2014
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 25, 2012	Dec. 24, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier EMCI	EMC 012645	980115	Dec. 28, 2012	Dec. 27, 2013
Preamplifier EMCI	EMC 184045	980116	Dec. 28, 2012	Dec. 27, 2013
Preamplifier EMCI	EMC 330H	980112	Dec. 28, 2012	Dec. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable Worken	RG-213	NA	Dec. 29, 2012	Dec. 28, 2013
Software	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Power Meter	ML2495A	1232002	Aug. 10, 2012	Aug. 09, 2013
Power Sensor	MA2411B	1207325	Aug. 15, 2012	Aug. 14, 2013

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 10.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 690701.
 6. The IC Site Registration No. is IC 7450F-10.



A D T

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.



A D T

4.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL		Channel 1		FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2388	39.38	46.43	54	-14.62	26.91	3.54	37.5	103	45	Average
2388	51.43	58.48	74	-22.57	26.91	3.54	37.5	103	45	Peak
2412	103.2	110.22			26.96	3.54	37.52	103	45	Average
2412	106.35	113.37			26.96	3.54	37.52	103	45	Peak
2486	38.69	45.26	54	-15.31	27.15	3.6	37.32	103	45	Average
2486	51.17	57.74	74	-22.83	27.15	3.6	37.32	103	45	Peak
4824	42.68	59	54	-11.32	30.99	5.77	53.08	102	16	Average
4824	47.24	63.56	74	-26.76	30.99	5.77	53.08	102	16	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2358	35.97	43.15	54	-18.03	26.81	3.5	37.49	100	181	Average
2358	49.7	56.88	74	-24.3	26.81	3.5	37.49	100	181	Peak
2412	95.5	102.52			26.96	3.54	37.52	100	181	Average
2412	98.61	105.63			26.96	3.54	37.52	100	181	Peak
2496	35.9	42.33	54	-18.1	27.2	3.62	37.25	100	181	Average
2496	51	57.43	74	-23	27.2	3.62	37.25	100	181	Peak
4824	39.56	55.88	54	-14.44	30.99	5.77	53.08	102	113	Average
4824	44.61	60.93	74	-29.39	30.99	5.77	53.08	102	113	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL					
CHANNEL	Channel 6		FREQUENCY RANGE				1GHz ~ 25GHz	
INPUT POWER (SYSTEM)	120Vac, 60 Hz			DETECTOR FUNCTION			Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH			TESTED BY			Anson Lin	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2388	35.69	42.74	54	-18.31	26.91	3.54	37.5	102	44	Average
2388	49.92	56.97	74	-24.08	26.91	3.54	37.5	102	44	Peak
2437	104.41	111.25			27.06	3.56	37.46	102	44	Average
2437	108.02	114.86			27.06	3.56	37.46	102	44	Peak
2484	38.28	44.85	54	-15.72	27.15	3.6	37.32	102	44	Average
2484	52.4	58.97	74	-21.6	27.15	3.6	37.32	102	44	Peak
4874	40.19	56.38	54	-13.81	31.06	5.8	53.05	100	156	Average
4874	48.62	64.81	74	-25.38	31.06	5.8	53.05	100	156	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2374	35.04	42.16	54	-18.96	26.86	3.52	37.5	100	183	Average
2374	50.61	57.73	74	-23.39	26.86	3.52	37.5	100	183	Peak
2437	95.86	102.7			27.06	3.56	37.46	100	183	Average
2437	99.47	106.31			27.06	3.56	37.46	100	183	Peak
2490	35.51	42.01	54	-18.49	27.2	3.62	37.32	100	183	Average
2490	50.2	56.7	74	-23.8	27.2	3.62	37.32	100	183	Peak
4874	41.03	57.22	54	-12.97	31.06	5.8	53.05	100	184	Average
4874	50.12	66.31	74	-23.88	31.06	5.8	53.05	100	184	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL		Channel 11		FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2338	35.48	42.68	54	-18.52	26.77	3.5	37.47	102	43	Average
2338	50.31	57.51	74	-23.69	26.77	3.5	37.47	102	43	Peak
2462	103.98	110.69			27.1	3.58	37.39	102	43	Average
2462	107.52	114.23			27.1	3.58	37.39	102	43	Peak
2484	43.69	50.26	54	-10.31	27.15	3.6	37.32	102	43	Average
2484	69.07	75.64	74	-4.93	27.15	3.6	37.32	102	43	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2378	35.1	42.22	54	-18.9	26.86	3.52	37.5	117	186	Average
2378	49.77	56.89	74	-24.23	26.86	3.52	37.5	117	186	Peak
2462	95.2	101.91			27.1	3.58	37.39	117	186	Average
2462	99.5	106.21			27.1	3.58	37.39	117	186	Peak
2484	40.32	46.89	54	-13.68	27.15	3.6	37.32	117	186	Average
2484	69.02	75.59	74	-4.98	27.15	3.6	37.32	117	186	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2462MHz: Fundamental frequency.



A D T

802.11g

EUT TEST CONDITION			MEASUREMENT DETAIL				
CHANNEL		Channel 1			FREQUENCY RANGE		1GHz ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz			DETECTOR FUNCTION		Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH			TESTED BY		Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.82	48.89	54	-12.18	26.91	3.54	37.52	104	155	Average
2390	58.04	65.11	74	-15.96	26.91	3.54	37.52	104	155	Peak
2412	94.78	101.8			26.96	3.54	37.52	104	155	Average
2412	103.77	110.79			26.96	3.54	37.52	104	155	Peak
2484	36.01	42.58	54	-17.99	27.15	3.6	37.32	104	155	Average
2484	50.45	57.02	74	-23.55	27.15	3.6	37.32	104	155	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	39.59	46.66	54	-14.41	26.91	3.54	37.52	119	136	Average
2390	55.37	62.44	74	-18.63	26.91	3.54	37.52	119	136	Peak
2412	91.41	98.43			26.96	3.54	37.52	119	136	Average
2412	100.76	107.78			26.96	3.54	37.52	119	136	Peak
2500	34.85	41.28	54	-19.15	27.2	3.62	37.25	119	136	Average
2500	50.23	56.66	74	-23.77	27.2	3.62	37.25	119	136	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 6		FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2344	34.09	41.31	54	-19.91	26.77	3.5	37.49	102	153	Average
2344	49.66	56.88	74	-24.34	26.77	3.5	37.49	102	153	Peak
2437	96.17	103.01			27.06	3.56	37.46	102	153	Average
2437	105.92	112.76			27.06	3.56	37.46	102	153	Peak
2484	37.39	43.96	54	-16.61	27.15	3.6	37.32	102	153	Average
2484	51.17	57.74	74	-22.83	27.15	3.6	37.32	102	153	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2378	33.72	40.84	54	-20.28	26.86	3.52	37.5	100	82	Average
2378	50.41	57.53	74	-23.59	26.86	3.52	37.5	100	82	Peak
2437	88.79	95.63			27.06	3.56	37.46	100	82	Average
2437	98.37	105.21			27.06	3.56	37.46	100	82	Peak
2492	34.61	41.04	54	-19.39	27.2	3.62	37.25	100	82	Average
2492	49.8	56.23	74	-24.2	27.2	3.62	37.25	100	82	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL		Channel 11		FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2384	33.86	40.98	54	-20.14	26.86	3.52	37.5	103	45	Average
2384	50.61	57.73	74	-23.39	26.86	3.52	37.5	103	45	Peak
2462	96.16	102.87			27.1	3.58	37.39	103	45	Average
2462	106.31	113.02			27.1	3.58	37.39	103	45	Peak
2484	46.77	53.34	54	-7.23	27.15	3.6	37.32	103	45	Average
2484	63.69	70.26	74	-10.31	27.15	3.6	37.32	103	45	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2344	33.46	40.68	54	-20.54	26.77	3.5	37.49	112	122	Average
2344	50.22	57.44	74	-23.78	26.77	3.5	37.49	112	122	Peak
2462	91.55	98.26			27.1	3.58	37.39	112	122	Average
2462	101.63	108.34			27.1	3.58	37.39	112	122	Peak
2484	40.68	47.25	54	-13.32	27.15	3.6	37.32	112	122	Average
2484	58.75	65.32	74	-15.25	27.15	3.6	37.32	112	122	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2462MHz: Fundamental frequency.



A D T

802.11n (20MHz)

EUT TEST CONDITION			MEASUREMENT DETAIL					
CHANNEL		Channel 1			FREQUENCY RANGE		1GHz ~ 25GHz	
INPUT POWER (SYSTEM)		120Vac, 60 Hz			DETECTOR FUNCTION		Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH			TESTED BY		Anson Lin	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	40.16	47.23	54	-13.84	26.91	3.54	37.52	104	139	Average
2390	57.23	64.3	74	-16.77	26.91	3.54	37.52	104	139	Peak
2412	92.57	99.59			26.96	3.54	37.52	104	139	Average
2412	101.9	108.92			26.96	3.54	37.52	104	139	Peak
2494	35.65	42.08	54	-18.35	27.2	3.62	37.25	104	139	Average
2494	50.76	57.19	74	-23.24	27.2	3.62	37.25	104	139	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	37.6	44.67	54	-16.4	26.91	3.54	37.52	119	127	Average
2390	52.73	59.8	74	-21.27	26.91	3.54	37.52	119	127	Peak
2412	87.62	94.64			26.96	3.54	37.52	119	127	Average
2412	97.23	104.25			26.96	3.54	37.52	119	127	Peak
2494	34.46	40.89	54	-19.54	27.2	3.62	37.25	119	127	Average
2494	50.1	56.53	74	-23.9	27.2	3.62	37.25	119	127	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 6		FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2368	33.63	40.8	54	-20.37	26.81	3.52	37.5	103	136	Average
2368	50.42	57.59	74	-23.58	26.81	3.52	37.5	103	136	Peak
2437	92.79	99.63			27.06	3.56	37.46	103	136	Average
2437	102.31	109.15			27.06	3.56	37.46	103	136	Peak
2484	35.82	42.39	54	-18.18	27.15	3.6	37.32	103	136	Average
2484	51.27	57.84	74	-22.73	27.15	3.6	37.32	103	136	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2358	33.45	40.63	54	-20.55	26.81	3.5	37.49	117	126	Average
2358	50.67	57.85	74	-23.33	26.81	3.5	37.49	117	126	Peak
2437	87.6	94.44			27.06	3.56	37.46	117	126	Average
2437	97.02	103.86			27.06	3.56	37.46	117	126	Peak
2486	34.59	41.16	54	-19.41	27.15	3.6	37.32	117	126	Average
2486	51.25	57.82	74	-22.75	27.15	3.6	37.32	117	126	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL		Channel 11		FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2354	33.47	40.65	54	-20.53	26.81	3.5	37.49	100	147	Average
2354	49.87	57.05	74	-24.13	26.81	3.5	37.49	100	147	Peak
2462	92.89	99.6			27.1	3.58	37.39	100	147	Average
2462	102.32	109.03			27.1	3.58	37.39	100	147	Peak
2484	43.55	50.12	54	-10.45	27.15	3.6	37.32	100	147	Average
2484	58.72	65.29	74	-15.28	27.15	3.6	37.32	100	147	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2334	33.29	40.56	54	-20.71	26.72	3.48	37.47	118	133	Average
2334	50.13	57.4	74	-23.87	26.72	3.48	37.47	118	133	Peak
2462	88.03	94.74			27.1	3.58	37.39	118	133	Average
2462	97.6	104.31			27.1	3.58	37.39	118	133	Peak
2484	38.93	45.5	54	-15.07	27.15	3.6	37.32	118	133	Average
2484	52.86	59.43	74	-21.14	27.15	3.6	37.32	118	133	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 2462MHz: Fundamental frequency.



A D T

BELOW 1GHz WORST-CASE DATA: 802.11g

EUT TEST CONDITION			MEASUREMENT DETAIL						
CHANNEL		Channel 6			FREQUENCY RANGE		30MHz ~ 1GHz		
INPUT POWER (SYSTEM)		120Vac, 60 Hz			DETECTOR FUNCTION		Peak (PK) Quasi-peak (QP)		
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH			TESTED BY		Anson Lin		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
56.19	29.37	47.56	40	-10.63	12.35	0.8	31.34	100	291	QP
165.54	19.07	37.29	43.5	-24.43	12.15	1.42	31.79	100	164	Peak
256.53	23.68	42.03	46	-22.32	11.68	1.85	31.88	100	274	Peak
336.4	19.77	35.59	46	-26.23	13.82	2.18	31.82	100	132	Peak
638.1	24.71	33.54	46	-21.29	20.07	3.2	32.1	100	204	Peak
949.6	28.11	32.07	46	-17.89	23.79	4.07	31.82	100	166	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
39.45	33.57	50.37	40	-6.43	13.54	0.65	30.99	100	138	Peak
56.19	31.4	49.59	40	-8.6	12.35	0.8	31.34	100	262	QP
201.72	14.65	35.35	43.5	-28.85	9.44	1.6	31.74	100	162	Peak
367.9	18.66	33.73	46	-27.34	14.56	2.3	31.93	100	331	Peak
629.7	25.49	34.49	46	-20.51	19.96	3.18	32.14	100	263	Peak
933.5	28.62	32.86	46	-17.38	23.69	4.04	31.97	100	128	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor



A D T

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 09, 2012	Nov. 08, 2013
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 28, 2012	Dec. 27, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 21, 2012	Dec. 20, 2013
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 02, 2013	Jul. 01, 2014
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.



A D T

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA :

PHASE		Line 1		6dB BANDWIDTH		9kHz	
-------	--	--------	--	---------------	--	------	--

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]	(dB)	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	(dB)
1	0.21250	0.17	38.82	31.64	38.99	31.81	63.11	53.11	-24.11	-21.29
2	0.43125	0.21	46.50	40.29	46.71	40.50	57.23	47.23	-10.52	-6.73
3	0.93516	0.26	43.87	35.14	44.13	35.40	56.00	46.00	-11.87	-10.60
4	3.19141	0.33	41.39	34.59	41.72	34.92	56.00	46.00	-14.28	-11.08
5	6.82813	0.40	35.85	26.86	36.25	27.26	60.00	50.00	-23.75	-22.74
6	13.55859	0.50	40.07	38.10	40.57	38.60	60.00	50.00	-19.43	-11.40

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 2	6dB BANDWIDTH	9kHz
--------------	--------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20859	0.18	38.48	29.51	38.66	29.69	63.26	53.26	-24.60	-23.57
2	0.43516	0.25	45.01	37.95	45.26	38.20	57.15	47.15	-11.89	-8.95
3	0.94688	0.23	40.40	32.38	40.63	32.61	56.00	46.00	-15.37	-13.39
4	1.98047	0.28	38.80	32.06	39.08	32.34	56.00	46.00	-16.92	-13.66
5	8.42969	0.46	30.50	22.67	30.96	23.13	60.00	50.00	-29.04	-26.87
6	13.56250	0.57	36.47	35.61	37.04	36.18	60.00	50.00	-22.96	-13.82

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	7.59	0.5	PASS
6	2437	8.05	0.5	PASS
11	2462	8.11	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.49	0.5	PASS
6	2437	16.47	0.5	PASS
11	2462	16.46	0.5	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.61	0.5	PASS
6	2437	17.69	0.5	PASS
11	2462	17.68	0.5	PASS

4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



A D T

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	123.880	20.93	30	PASS
6	2437	109.396	20.39	30	PASS
11	2462	118.304	20.73	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	285.102	24.55	30	PASS
6	2437	332.660	25.22	30	PASS
11	2462	269.153	24.3	30	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	162.930	22.12	30	PASS
6	2437	161.808	22.09	30	PASS
11	2462	161.065	22.07	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. Set the RBW = 3 kHz, VBW = 10 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6



A D T

4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-4.84	8	PASS
6	2437	-5.01	8	PASS
11	2462	-5.17	8	PASS

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-10.68	8	PASS
6	2437	-11.71	8	PASS
11	2462	-12.03	8	PASS

802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-13.11	8	PASS
6	2437	-15.53	8	PASS
11	2462	-14.49	8	PASS




A D T

4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



A D T

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

802.11b


CH 1



CH 6



CH 11







A D T

802.11g


CH 1



CH 6



CH 11







A D T

802.11n (20MHz)


CH 1



CH 6



CH 11





A D T

5. TEST TYPES AND RESULTS (FOR 5.0GHz BAND)

5.1 RADIATED EMISSION AND BANDEdge MEASUREMENT

5.1.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{uV/m}) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

5.1.2 TEST INSTRUMENTS

Same as item 4.1.2.

5.1.3 TEST PROCEDURES

Same as item 4.1.3.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

5.1.5 TEST SETUP

Same as item 4.1.5.

5.1.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



A D T

5.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA : 802.11a

EUT TEST CONDITION			MEASUREMENT DETAIL					
CHANNEL		Channel 149			FREQUENCY RANGE		1GHz ~ 40GHz	
INPUT POWER (SYSTEM)		120Vac, 60 Hz			DETECTOR FUNCTION		Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH			TESTED BY		Johnson Liao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	50.56	50.44	72.41	-21.85	31.96	5.59	37.43	100	36	Average
5725	63.27	63.15	81.75	-18.48	31.96	5.59	37.43	100	36	Peak
5745	92.41	92.29			31.99	5.6	37.47	100	36	Average
5745	101.75	101.63			31.99	5.6	37.47	100	36	Peak
5850	38.72	38.42	72.41	-33.69	32.15	5.66	37.51	100	36	Average
5850	53.91	53.61	81.75	-27.84	32.15	5.66	37.51	100	36	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	52.6	52.48	74.17	-21.57	31.96	5.59	37.43	110	120	Average
5725	67.86	67.74	83.95	-16.09	31.96	5.59	37.43	110	120	Peak
5745	94.17	94.05			31.99	5.6	37.47	110	120	Average
5745	103.95	103.83			31.99	5.6	37.47	110	120	Peak
5850	38.83	38.53	74.17	-35.34	32.15	5.66	37.51	110	120	Average
5850	53.43	53.13	83.95	-30.52	32.15	5.66	37.51	110	120	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5745MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 157	FREQUENCY RANGE		1GHz ~ 40GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz	DETECTOR FUNCTION		Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH	TESTED BY		Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	40.24	40.12	73.47	-33.23	31.96	5.59	37.43	102	48	Average
5725	53.13	53.01	82.27	-29.14	31.96	5.59	37.43	102	48	Peak
5785	93.47	93.35			32.04	5.62	37.54	102	48	Average
5785	102.27	102.15			32.04	5.62	37.54	102	48	Peak
5850	39.5	39.2	73.47	-33.97	32.15	5.66	37.51	102	48	Average
5850	54.05	53.75	82.27	-28.22	32.15	5.66	37.51	102	48	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	41.93	41.81	76.1	-34.17	31.96	5.59	37.43	113	146	Average
5725	55.05	54.93	85.06	-30.01	31.96	5.59	37.43	113	146	Peak
5785	96.1	95.98			32.04	5.62	37.54	113	146	Average
5785	105.06	104.94			32.04	5.62	37.54	113	146	Peak
5850	40.46	40.16	76.1	-35.64	32.15	5.66	37.51	113	146	Average
5850	54.19	53.89	85.06	-30.87	32.15	5.66	37.51	113	146	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5785MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL			
CHANNEL		Channel 165			FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz			DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH			TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	39.15	39.03	73.41	-34.26	31.96	5.59	37.43	101	49	Average
5725	53.69	53.57	82.15	-28.46	31.96	5.59	37.43	101	49	Peak
5825	93.41	93.18			32.12	5.64	37.53	101	49	Average
5825	102.15	101.92			32.12	5.64	37.53	101	49	Peak
5850	44.9	44.6	73.41	-28.51	32.15	5.66	37.51	101	49	Average
5850	58.11	57.81	82.15	-24.04	32.15	5.66	37.51	101	49	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	39.67	39.55	76.24	-36.57	31.96	5.59	37.43	110	153	Average
5725	54.17	54.05	85.03	-30.86	31.96	5.59	37.43	110	153	Peak
5825	96.24	96.01			32.12	5.64	37.53	110	153	Average
5825	105.03	104.8			32.12	5.64	37.53	110	153	Peak
5850	46.63	46.33	76.24	-29.61	32.15	5.66	37.51	110	153	Average
5850	60.81	60.51	85.03	-24.22	32.15	5.66	37.51	110	153	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5825MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

802.11n (20MHz)

EUT TEST CONDITION			MEASUREMENT DETAIL						
CHANNEL		Channel 149			FREQUENCY RANGE		1GHz ~ 40GHz		
INPUT POWER (SYSTEM)		120Vac, 60 Hz			DETECTOR FUNCTION		Peak (PK) Average (AV)		
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH			TESTED BY		Johnson Liao		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	52.66	52.54	72.98	-20.32	31.96	5.59	37.43	100	37	Average
5725	66.2	66.08	82.29	-16.09	31.96	5.59	37.43	100	37	Peak
5745	92.98	92.86			31.99	5.6	37.47	100	37	Average
5745	102.29	102.17			31.99	5.6	37.47	100	37	Peak
5850	39.06	38.76	72.98	-33.92	32.15	5.66	37.51	100	37	Average
5850	53.73	53.43	82.29	-28.56	32.15	5.66	37.51	100	37	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	54.7	54.58	75.06	-20.36	31.96	5.59	37.43	122	126	Average
5725	68.72	68.6	84.14	-15.42	31.96	5.59	37.43	122	126	Peak
5745	95.06	94.94			31.99	5.6	37.47	122	126	Average
5745	104.14	104.02			31.99	5.6	37.47	122	126	Peak
5850	39.23	38.93	75.06	-35.83	32.15	5.66	37.51	122	126	Average
5850	52.72	52.42	84.14	-31.42	32.15	5.66	37.51	122	126	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5745MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 157		FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	40.16	40.04	72.44	-32.28	31.96	5.59	37.43	100	19	Average
5725	53.66	53.54	81.75	-28.09	31.96	5.59	37.43	100	19	Peak
5785	92.44	92.32			32.04	5.62	37.54	100	19	Average
5785	101.75	101.63			32.04	5.62	37.54	100	19	Peak
5850	39.5	39.2	72.44	-32.94	32.15	5.66	37.51	100	19	Average
5850	54.86	54.56	81.75	-26.89	32.15	5.66	37.51	100	19	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	42.57	42.45	76.99	-34.42	31.96	5.59	37.43	102	164	Average
5725	55.31	55.19	85.99	-30.68	31.96	5.59	37.43	102	164	Peak
5785	96.99	96.87			32.04	5.62	37.54	102	164	Average
5785	105.99	105.87			32.04	5.62	37.54	102	164	Peak
5850	41.26	40.96	76.99	-35.73	32.15	5.66	37.51	102	164	Average
5850	54.73	54.43	85.99	-31.26	32.15	5.66	37.51	102	164	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5785MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL				
CHANNEL		Channel 165		FREQUENCY RANGE		1GHz ~ 40GHz	
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION		Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY		Johnson Liao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	39.08	38.96	73.5	-34.42	31.96	5.59	37.43	100	48	Average
5725	53.89	53.77	82.42	-28.53	31.96	5.59	37.43	100	48	Peak
5825	93.5	93.27			32.12	5.64	37.53	100	48	Average
5825	102.42	102.19			32.12	5.64	37.53	100	48	Peak
5850	46.93	46.63	73.5	-26.57	32.15	5.66	37.51	100	48	Average
5850	63.41	63.11	82.42	-19.01	32.15	5.66	37.51	100	48	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	40.65	40.53	76.38	-35.73	31.96	5.59	37.43	122	148	Average
5725	54.46	54.34	85.01	-30.55	31.96	5.59	37.43	122	148	Peak
5825	96.38	96.15			32.12	5.64	37.53	122	148	Average
5825	105.01	104.78			32.12	5.64	37.53	122	148	Peak
5850	48.47	48.17	76.38	-27.91	32.15	5.66	37.51	122	148	Average
5850	62.89	62.59	85.01	-22.12	32.15	5.66	37.51	122	148	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5825MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

802.11n (40MHz)

EUT TEST CONDITION			MEASUREMENT DETAIL					
CHANNEL		Channel 151	FREQUENCY RANGE			1GHz ~ 40GHz		
INPUT POWER (SYSTEM)		120Vac, 60 Hz	DETECTOR FUNCTION			Peak (PK) Average (AV)		
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH	TESTED BY			Johnson Liao		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	53.98	53.86	68.89	-14.91	31.96	5.59	37.43	100	27	Average
5725	64.39	64.27	77.72	-13.33	31.96	5.59	37.43	100	27	Peak
5755	88.89	88.75			32.01	5.6	37.47	100	27	Average
5755	97.72	97.58			32.01	5.6	37.47	100	27	Peak
5850	39.13	38.83	68.89	-29.76	32.15	5.66	37.51	100	27	Average
5850	54.04	53.74	77.72	-23.68	32.15	5.66	37.51	100	27	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	55.89	55.77	70.73	-14.84	31.96	5.59	37.43	121	124	Average
5725	68.61	68.49	79.63	-11.02	31.96	5.59	37.43	121	124	Peak
5755	90.73	90.59			32.01	5.6	37.47	121	124	Average
5755	99.63	99.49			32.01	5.6	37.47	121	124	Peak
5850	39.4	39.1	70.73	-31.33	32.15	5.66	37.51	121	124	Average
5850	53.9	53.6	79.63	-25.73	32.15	5.66	37.51	121	124	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5755MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 159		FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	40.15	40.03	69.4	-29.25	31.96	5.59	37.43	100	48	Average
5725	53.54	53.42	78.28	-24.74	31.96	5.59	37.43	100	48	Peak
5795	89.4	89.24			32.07	5.63	37.54	100	48	Average
5795	98.28	98.12			32.07	5.63	37.54	100	48	Peak
5850	41.89	41.59	69.4	-27.51	32.15	5.66	37.51	100	48	Average
5850	56.44	56.14	78.28	-21.84	32.15	5.66	37.51	100	48	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	42.33	42.21	73.06	-30.73	31.96	5.59	37.43	113	148	Average
5725	54.19	54.07	82.07	-27.88	31.96	5.59	37.43	113	148	Peak
5795	93.06	92.9			32.07	5.63	37.54	113	148	Average
5795	102.07	101.91			32.07	5.63	37.54	113	148	Peak
5850	43.65	43.35	73.06	-29.41	32.15	5.66	37.51	113	148	Average
5850	55.42	55.12	82.07	-26.65	32.15	5.66	37.51	113	148	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. 5795MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

BELOW 1GHz WORST-CASE DATA : 802.11n (20MHz)

EUT TEST CONDITION			MEASUREMENT DETAIL						
CHANNEL		Channel 149			FREQUENCY RANGE		30MHz ~ 1GHz		
INPUT POWER (SYSTEM)		120Vac, 60 Hz			DETECTOR FUNCTION		Peak (PK) Quasi-peak (QP)		
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH			TESTED BY		Johnson Liao		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
56.19	29.85	48.04	40	-10.15	12.35	0.8	31.34	100	133	QP
186.6	16.49	36.37	43.5	-27.01	10.33	1.53	31.74	100	144	Peak
263.55	21.78	39.94	46	-24.22	11.88	1.88	31.92	100	219	Peak
409.9	18.92	32.91	46	-27.08	15.54	2.46	31.99	100	264	Peak
660.5	24.84	33.16	46	-21.16	20.34	3.28	31.94	100	129	Peak
933.5	27.84	32.08	46	-18.16	23.69	4.04	31.97	100	146	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
41.34	32.86	49.67	40	-7.14	13.56	0.68	31.05	100	233	QP
55.85	32	50.19	40	-8	12.35	0.8	31.34	100	162	QP
254.1	16.2	34.66	46	-29.8	11.59	1.85	31.9	100	294	Peak
398	18.42	32.83	46	-27.58	15.28	2.42	32.11	100	131	Peak
638.8	24.47	33.28	46	-21.53	20.08	3.21	32.1	100	164	Peak
885.9	27.95	32.7	46	-18.05	23.32	3.92	31.99	100	177	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor



A D T

5.2 CONDUCTED EMISSION MEASUREMENT

5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

5.2.2 TEST INSTRUMENTS

Same as item 4.2.2.

5.2.3 TEST PROCEDURES

Same as item 4.2.3.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

5.2.5 TEST SETUP

Same as item 4.2.5.

5.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

5.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA :

PHASE		Line 1		6dB BANDWIDTH		9kHz	
-------	--	--------	--	---------------	--	------	--

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.28672	0.19	36.50	29.09	36.69	29.28	60.62	50.62	-23.93	-21.34
2	0.42344	0.21	46.58	38.75	46.79	38.96	57.38	47.38	-10.59	-8.42
3	0.98984	0.27	44.79	36.01	45.06	36.28	56.00	46.00	-10.94	-9.72
4	2.33984	0.30	41.80	34.12	42.10	34.42	56.00	46.00	-13.90	-11.58
5	6.51563	0.40	35.87	27.75	36.27	28.15	60.00	50.00	-23.73	-21.85
6	13.55859	0.50	39.93	38.06	40.43	38.56	60.00	50.00	-19.57	-11.44

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 2	6dB BANDWIDTH	9kHz
--------------	--------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.28281	0.21	37.52	30.47	37.73	30.68	60.73	50.73	-23.00	-20.05
2	0.44688	0.25	45.44	39.49	45.69	39.74	56.93	46.93	-11.24	-7.19
3	0.95078	0.23	40.26	31.80	40.49	32.03	56.00	46.00	-15.51	-13.97
4	2.15234	0.29	42.46	35.00	42.75	35.29	56.00	46.00	-13.25	-10.71
5	7.35938	0.44	32.68	24.81	33.12	25.25	60.00	50.00	-26.88	-24.75
6	13.56250	0.57	36.47	35.57	37.04	36.14	60.00	50.00	-22.96	-13.86

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value





A D T

5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

5.3.2 TEST SETUP

Same as item 4.3.2.

5.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.3.4 TEST PROCEDURE

Same as item 4.3.4.

5.3.5 DEVIATION FROM TEST STANDARD

No deviation.

5.3.6 EUT OPERATING CONDITIONS

Same as item 4.3.6.



A D T

5.3.7 TEST RESULTS

802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	16.4	0.5	PASS
157	5785	16.47	0.5	PASS
165	5825	16.44	0.5	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	17.63	0.5	PASS
157	5785	17.7	0.5	PASS
165	5825	17.71	0.5	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
151	5755	36.44	0.5	PASS
159	5795	36.5	0.5	PASS



A D T

5.4 MAXIMUM OUTPUT POWER

5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 5725–5850 MHz bands: 1 Watt (30dBm)

5.4.2 TEST SETUP

Same as Item 4.4.2.

5.4.3 INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.4.4 TEST PROCEDURES

Same as Item 4.4.4.

5.4.5 DEVIATION FROM TEST STANDARD

No deviation.

5.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



A D T

5.4.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
149	5745	207.491	23.17	30	PASS
157	5785	201.372	23.04	30	PASS
165	5825	212.324	23.27	30	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
149	5745	217.771	23.38	30	PASS
157	5785	216.272	23.35	30	PASS
165	5825	215.278	23.33	30	PASS

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
151	5755	200.447	23.02	30	PASS
159	5795	189.671	22.78	30	PASS



A D T

5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST SETUP

Same as item 4.5.2.

5.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.5.4 TEST PROCEDURE.

Same as item 4.5.4.

5.5.5 DEVIATION FROM TEST STANDARD

No deviation.

5.5.6 EUT OPERATING CONDITION

Same as item 4.3.6.



A D T

5.5.7 TEST RESULTS

802.11a

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
149	5745	-12.59	8	PASS
157	5785	-12.77	8	PASS
165	5825	-12.60	8	PASS

802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
149	5745	-11.75	8	PASS
157	5785	-12.90	8	PASS
165	5825	-13.46	8	PASS

802.11n (40MHz)

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	Limit (dBm/3kHz)	PASS /FAIL
151	5755	-14.79	8	PASS
159	5795	-15.49	8	PASS



A D T

5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST SETUP

Same as Item 4.6.2

5.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.6.4 TEST PROCEDURE

Same as Item 4.6.4

5.6.5 DEVIATION FROM TEST STANDARD

No deviation.

5.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.6.7 TEST RESULTS


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

802.11a


CH 149



CH 157



CH 165







A D T

802.11n (20MHz)


CH 149



CH 157



CH 165







A D T

802.11n (40MHz)

CH 151



CH 159





A D T

6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---