



# FCC TEST REPORT (15.247)

**REPORT NO.:** RF131023C29  
**MODEL NO.:** 0P6B200  
**FCC ID:** NM80P6B200  
**RECEIVED:** Oct. 23, 2013  
**TESTED:** Dec. 14, 2013 ~ Jan. 07, 2014  
**ISSUED:** Jan. 09, 2014

**APPLICANT:** HTC Corporation

**ADDRESS:** No. 23,Xinghua Rd.,Taoyuan 330,Taiwan,R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,  
New Taipei City, Taiwan ( R.O.C )

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



# TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	5
1. CERTIFICATION.....	6
2. SUMMARY OF TEST RESULTS .....	7
2.1 MEASUREMENT UNCERTAINTY.....	7
3. GENERAL INFORMATION .....	8
3.1 GENERAL DESCRIPTION OF EUT .....	8
3.2 DESCRIPTION OF TEST MODES.....	9
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
3.3 DESCRIPTION OF SUPPORT UNITS.....	14
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST .....	14
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	17
4. TEST TYPES AND RESULTS (FOR 2.4GHZ BAND).....	18
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	18
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	18
4.1.2 TEST INSTRUMENTS.....	19
4.1.3 TEST PROCEDURES .....	20
4.1.4 DEVIATION FROM TEST STANDARD .....	20
4.1.5 TEST SETUP .....	21
4.1.6 EUT OPERATING CONDITIONS .....	22
4.1.7 TEST RESULTS.....	23
4.2 CONDUCTED EMISSION MEASUREMENT .....	35
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	35
4.2.2 TEST INSTRUMENTS.....	35
4.2.3 TEST PROCEDURES .....	36
4.2.4 DEVIATION FROM TEST STANDARD .....	36
4.2.5 TEST SETUP .....	37
4.2.6 EUT OPERATING CONDITIONS .....	37
4.2.7 TEST RESULTS.....	38
4.3 6dB BANDWIDTH MEASUREMENT .....	40
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	40
4.3.2 TEST SETUP .....	40
4.3.3 TEST INSTRUMENTS.....	40
4.3.4 TEST PROCEDURE .....	40
4.3.5 DEVIATION FROM TEST STANDARD .....	40
4.3.6 EUT OPERATING CONDITIONS .....	40
4.3.7 TEST RESULTS.....	41
4.4 CONDUCTED OUTPUT POWER .....	43
4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	43
4.4.2 TEST SETUP .....	43
4.4.3 TEST INSTRUMENTS.....	43
4.4.4 TEST PROCEDURES .....	43
4.4.5 DEVIATION FROM TEST STANDARD .....	43
4.4.6 EUT OPERATING CONDITIONS .....	43
4.4.7 TEST RESULTS.....	44
4.5 POWER SPECTRAL DENSITY MEASUREMENT.....	45
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	45
4.5.2 TEST SETUP .....	45
4.5.3 TEST INSTRUMENTS.....	45
4.5.4 TEST PROCEDURE .....	45
4.5.5 DEVIATION FROM TEST STANDARD .....	45
4.5.6 EUT OPERATING CONDITION.....	45
4.5.7 TEST RESULTS.....	46



- 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT ..... 48
  - 4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT ..... 48
  - 4.6.2 TEST SETUP ..... 48
  - 4.6.3 TEST INSTRUMENTS ..... 48
  - 4.6.4 TEST PROCEDURE ..... 48
  - 4.6.5 DEVIATION FROM TEST STANDARD ..... 49
  - 4.6.6 EUT OPERATING CONDITION ..... 49
  - 4.6.7 TEST RESULTS ..... 49
- 5. TEST TYPES AND RESULTS (FOR 5.0GHz BAND) ..... 53
  - 5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT ..... 53
    - 5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT ..... 53
    - 5.1.2 TEST INSTRUMENTS ..... 54
    - 5.1.3 TEST PROCEDURES ..... 54
    - 5.1.4 DEVIATION FROM TEST STANDARD ..... 54
    - 5.1.5 TEST SETUP ..... 54
    - 5.1.6 EUT OPERATING CONDITIONS ..... 54
    - 5.1.7 TEST RESULTS ..... 55
  - 5.2 CONDUCTED EMISSION MEASUREMENT ..... 65
    - 5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT ..... 65
    - 5.2.2 TEST INSTRUMENTS ..... 65
    - 5.2.3 TEST PROCEDURES ..... 65
    - 5.2.4 DEVIATION FROM TEST STANDARD ..... 65
    - 5.2.5 TEST SETUP ..... 65
    - 5.2.6 EUT OPERATING CONDITIONS ..... 65
    - 5.2.7 TEST RESULTS ..... 66
  - 5.3 6dB BANDWIDTH MEASUREMENT ..... 68
    - 5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT ..... 68
    - 5.3.2 TEST SETUP ..... 68
    - 5.3.3 TEST INSTRUMENTS ..... 68
    - 5.3.4 TEST PROCEDURE ..... 68
    - 5.3.5 DEVIATION FROM TEST STANDARD ..... 68
    - 5.3.6 EUT OPERATING CONDITIONS ..... 68
    - 5.3.7 TEST RESULTS ..... 69
  - 5.4 MAXIMUM OUTPUT POWER ..... 71
    - 5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT ..... 71
    - 5.4.2 TEST SETUP ..... 71
    - 5.4.3 INSTRUMENTS ..... 71
    - 5.4.4 TEST PROCEDURES ..... 71
    - 5.4.5 DEVIATION FROM TEST STANDARD ..... 71
    - 5.4.6 EUT OPERATING CONDITIONS ..... 71
    - 5.4.7 TEST RESULTS ..... 72
  - 5.5 POWER SPECTRAL DENSITY MEASUREMENT ..... 73
    - 5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT ..... 73
    - 5.5.2 TEST SETUP ..... 73
    - 5.5.3 TEST INSTRUMENTS ..... 73
    - 5.5.4 TEST PROCEDURE ..... 73
    - 5.5.5 DEVIATION FROM TEST STANDARD ..... 73
    - 5.5.6 EUT OPERATING CONDITION ..... 73
    - 5.5.7 TEST RESULTS ..... 74
  - 5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT ..... 76
    - 5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT ..... 76
    - 5.6.2 TEST SETUP ..... 76
    - 5.6.3 TEST INSTRUMENTS ..... 76
    - 5.6.4 TEST PROCEDURE ..... 76
    - 5.6.5 DEVIATION FROM TEST STANDARD ..... 76



A D T

5.6.6 EUT OPERATING CONDITION.....	76
5.6.7 TEST RESULTS.....	76
6. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	80
7. INFORMATION ON THE TESTING LABORATORIES .....	81
8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	82



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF131023C29	Original release	Jan. 09, 2014



A D T

## 1. CERTIFICATION

**PRODUCT:** Smartphone  
**MODEL NO.:** 0P6B200  
**BRAND:** HTC  
**APPLICANT:** HTC Corporation  
**TESTED:** Dec. 14, 2013 ~ Jan. 07, 2014  
**TEST SAMPLE:** PRODUCTION UNIT  
**STANDARDS:** **FCC Part 15, Subpart C (Section 15.247)**  
ANSI C63.10-2009

The above equipment (model: 0P6B200) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Ivonne Wu , **DATE** : Jan. 09, 2014  
Ivonne Wu / Supervisor

**APPROVED BY** : Sam Chen , **DATE** : Jan. 09, 2014  
Sam Chen / Senior Project Engineer



## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.22dB at 13.56250MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.15dB at 2483.50MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Smartphone
<b>MODEL NO.</b>	0P6B200
<b>POWER SUPPLY</b>	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion battery)
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to MCS7 802.11ac: up to V9
<b>OPERATING FREQUENCY</b>	<b>2.4GHz:</b> 2412 ~ 2462MHz <b>5.0GHz:</b> 5745 ~ 5825MHz
<b>NUMBER OF CHANNEL</b>	<b>2.4GHz:</b> 11 for 802.11b, 802.11g, 802.11n (20MHz) <b>5.0GHz:</b> 5 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz) 1 for 802.11ac (80MHz)
<b>OUTPUT POWER</b>	146.893mW for 2412 ~ 2462MHz 238.232mW for 5745 ~ 5825MHz
<b>ANTENNA TYPE</b>	<b>2.4GHz:</b> PIFA antenna with -2dBi gain <b>5.0GHz:</b> PIFA antenna with -3.5dBi gain
<b>ANTENNA CONNECTOR</b>	NA
<b>DATA CABLE</b>	Refer to Note as below
<b>I/O PORTS</b>	Refer to user's manual
<b>ACCESSORY DEVICES</b>	Refer to Note as below

**NOTE:**

- The EUT's accessories list refers to Ext. Pho.
- There're 2 configurations for the EUT listed as below.  
Main Sample (A): Battery 1 + LCD Panel 1  
2<sup>nd</sup> Sample (B): Battery 2 + LCD Panel 2  
◇ Only the worst test data was presented in the report.
- The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



### 3.2 DESCRIPTION OF TEST MODES

#### FOR 2.4GHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

#### FOR 5.0GHz (5745 ~ 5825MHz):

5 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY
155	5775MHz

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

#### FOR 2.4GHz:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE $<$ 1G	PLC	APCM	
A	√	√	√	√	Main sample
B	√	√	-	-	2 <sup>nd</sup> sample

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz

**RE $<$ 1G**: Radiated Emission below 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane** for mode A and **Z-plane** for mode B.

#### **RADIATED EMISSION TEST (ABOVE 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
B	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0

#### **RADIATED EMISSION TEST (BELOW 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0

#### **POWER LINE CONDUCTED EMISSION TEST:**

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0



**BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	MCS0

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
PLC	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
APCM	25deg. C, 65%RH	120Vac, 60Hz	Demon Lin



A D T

**FOR 5.0GHz (5745 ~ 5825MHz):**

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	Main sample

Where **RE≥1G**: Radiated Emission above 1GHz      **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane.

**RADIATED EMISSION TEST (ABOVE 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6.0
	802.11n (20MHz)	149 to 165	149, 157, 165	OFDM	BPSK	MCS0
	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0
	802.11ac (80MHz)	155	155	OFDM	BPSK	V0

**RADIATED EMISSION TEST (BELOW 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11n (20MHz)	149 to 165	149	OFDM	BPSK	MCS0

**POWER LINE CONDUCTED EMISSION TEST:**

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11n (20MHz)	149 to 165	149	OFDM	BPSK	MCS0



**BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11a	149 to 165	149, 165	OFDM	BPSK	6.0
	802.11n (20MHz)	149 to 165	149, 165	OFDM	BPSK	MCS0
	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0
	802.11ac (80MHz)	155	155	OFDM	BPSK	V0

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6.0
	802.11n (20MHz)	149 to 165	149, 157, 165	OFDM	BPSK	MCS0
	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0
	802.11ac (80MHz)	155	155	OFDM	BPSK	V0


**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
PLC	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
APCM	25deg. C, 65%RH	120Vac, 60Hz	Demon Lin

### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

#### 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST





A D T

### 3.4 DUTY CYCLE TEST SIGNAL

#### 2.4GHz

If duty cycle is < 98%

**802.11b:** Duty cycle =  $8.237/8.429 = 0.977$ , Duty factor =  $10 * \log(1/0.977) = 0.10$

**802.11g:** Duty cycle =  $1.362/1.578 = 0.863$ , Duty factor =  $10 * \log(1/0.863) = 0.64$

**802.11n (20MHz):** Duty cycle =  $1.266/1.482 = 0.854$ , Duty factor =  $10 * \log(1/0.854) = 0.69$





A D T

### 5725MHz ~ 5850MHz


If duty cycle is < 98%

**802.11a:** Duty cycle = 1.354/1.570 = 0.862, Duty factor =  $10 * \log(1/0.862) = 0.64$

**802.11n (20MHz):** Duty cycle = 1.266/1.490 = 0.850, Duty factor =  $10 * \log(1/0.850) = 0.70$

**802.11n (40MHz):** Duty cycle = 637.82/839.74 = 0.763, Duty factor =  $10 * \log(1/0.763) = 1.17$

**802.11ac (80MHz):** Duty cycle = 251.60/451.92 = 0.557, Duty factor =  $10 * \log(1/0.557) = 2.54$





### **3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**ANSI C63.10-2009**

**KDB 558074 D01 DTS Meas Guidance v03r01**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

## 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 15, 2013	Apr. 14, 2014
Spectrum Analyzer ROHDE & SCHWARZ	FSU-26	101645	Jul. 16, 2013	Jul. 15, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Mar. 25, 2013	Mar. 24, 2014
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Jan. 07, 2013	Jan. 06, 2014
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Jan. 07, 2013	Jan. 06, 2014
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier EMCI	EMC 330H	980112	Dec. 28, 2012	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Power Meter	ML2495A	1232002	Aug. 23, 2013	Aug. 22, 2014
Power Sensor	MA2411B	1207325	Aug. 23, 2013	Aug. 22, 2014

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 10.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 690701.
6. The IC Site Registration No. is IC 7450F-10.

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

### 4.1.5 TEST SETUP

Frequency Range 30MHz ~ 1GHz



Frequency Range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).



A D T

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



A D T

### 4.1.7 TEST RESULTS

#### ABOVE 1GHz WORST-CASE DATA

#### TEST MODE A

#### 802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2350	40.76	39.06	54	-13.24	31.87	5.33	35.5	192	63	Average
2350	54.94	53.24	74	-19.06	31.87	5.33	35.5	192	63	Peak
2412	106.44	104.52			31.96	5.43	35.47	192	63	Average
2412	108.77	106.85			31.96	5.43	35.47	192	63	Peak
2494	43.16	40.94	54	-10.84	32.1	5.53	35.41	192	63	Average
2494	56	53.78	74	-18	32.1	5.53	35.41	192	63	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2372	40.79	39.01	54	-13.21	31.9	5.37	35.49	114	349	Average
2372	55.25	53.47	74	-18.75	31.9	5.37	35.49	114	349	Peak
2412	102.87	100.95			31.96	5.43	35.47	114	349	Average
2412	105.35	103.43			31.96	5.43	35.47	114	349	Peak
2486	41.2	38.99	54	-12.8	32.1	5.53	35.42	114	349	Average
2486	55.75	53.54	74	-18.25	32.1	5.53	35.42	114	349	Peak

#### REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2346	40.77	39.07	54	-13.23	31.87	5.33	35.5	188	64	Average
2346	56.16	54.46	74	-17.84	31.87	5.33	35.5	188	64	Peak
2437	105.07	103.06			32.01	5.46	35.46	188	64	Average
2437	108.57	106.56			32.01	5.46	35.46	188	64	Peak
2490	42.21	40	54	-11.79	32.1	5.53	35.42	188	64	Average
2490	56.99	54.78	74	-17.01	32.1	5.53	35.42	188	64	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2386	40.85	39.01	54	-13.15	31.93	5.4	35.49	110	349	Average
2386	55.53	53.69	74	-18.47	31.93	5.4	35.49	110	349	Peak
2437	102.58	100.57			32.01	5.46	35.46	110	349	Average
2437	105	102.99			32.01	5.46	35.46	110	349	Peak
2488	42.2	39.99	54	-11.8	32.1	5.53	35.42	110	349	Average
2488	55.4	53.19	74	-18.6	32.1	5.53	35.42	110	349	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2358	41.81	40.07	54	-12.19	31.87	5.37	35.5	184	60	Average
2358	55.59	53.85	74	-18.41	31.87	5.37	35.5	184	60	Peak
2462	106.23	104.13			32.04	5.5	35.44	184	60	Average
2462	108.89	106.79			32.04	5.5	35.44	184	60	Peak
2483.5	46.17	44.02	54	-7.83	32.07	5.5	35.42	184	60	Average
2483.5	56.43	54.28	74	-17.57	32.07	5.5	35.42	184	60	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2368	40.83	39.05	54	-13.17	31.9	5.37	35.49	109	350	Average
2368	55.54	53.76	74	-18.46	31.9	5.37	35.49	109	350	Peak
2462	103.13	101.03			32.04	5.5	35.44	109	350	Average
2462	105.88	103.78			32.04	5.5	35.44	109	350	Peak
2483.5	44.43	42.28	54	-9.57	32.07	5.5	35.42	109	350	Average
2483.5	55.48	53.33	74	-18.52	32.07	5.5	35.42	109	350	Peak

**REMARKS:**

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
2. 2462MHz: Fundamental frequency.



A D T

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.08	45.22	54	-6.92	31.93	5.4	35.47	190	63	Average
2390	62.14	60.28	74	-11.86	31.93	5.4	35.47	190	63	Peak
2412	100.35	98.43			31.96	5.43	35.47	190	63	Average
2412	107.12	105.2			31.96	5.43	35.47	190	63	Peak
2488	42.79	40.58	54	-11.21	32.1	5.53	35.42	190	63	Average
2488	55.48	53.27	74	-18.52	32.1	5.53	35.42	190	63	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.92	43.06	54	-9.08	31.93	5.4	35.47	114	351	Average
2390	57.8	55.94	74	-16.2	31.93	5.4	35.47	114	351	Peak
2412	95.65	93.73			31.96	5.43	35.47	114	351	Average
2412	103.36	101.44			31.96	5.43	35.47	114	351	Peak
2500	42.89	40.67	54	-11.11	32.1	5.53	35.41	114	351	Average
2500	55.42	53.2	74	-18.58	32.1	5.53	35.41	114	351	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2354	41.72	40.02	54	-12.28	31.87	5.33	35.5	192	60	Average
2354	55.01	53.31	74	-18.99	31.87	5.33	35.5	192	60	Peak
2437	99.34	97.33			32.01	5.46	35.46	192	60	Average
2437	107.05	105.04			32.01	5.46	35.46	192	60	Peak
2484	41.16	38.98	54	-12.84	32.1	5.5	35.42	192	60	Average
2484	55.28	53.1	74	-18.72	32.1	5.5	35.42	192	60	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2382	43.85	42.01	54	-10.15	31.93	5.4	35.49	112	350	Average
2382	55.74	53.9	74	-18.26	31.93	5.4	35.49	112	350	Peak
2437	97.1	95.09			32.01	5.46	35.46	112	350	Average
2437	104.63	102.62			32.01	5.46	35.46	112	350	Peak
2484	42.16	39.98	54	-11.84	32.1	5.5	35.42	112	350	Average
2484	55.6	53.42	74	-18.4	32.1	5.5	35.42	112	350	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2356	40.49	38.75	54	-13.51	31.87	5.37	35.5	184	60	Average
2356	55.31	53.57	74	-18.69	31.87	5.37	35.5	184	60	Peak
2462	97.53	95.43			32.04	5.5	35.44	184	60	Average
2462	106.26	104.16			32.04	5.5	35.44	184	60	Peak
2483.5	52.42	50.27	54	-1.58	32.07	5.5	35.42	184	60	Average
2483.5	69.28	67.13	74	-4.72	32.07	5.5	35.42	184	60	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2388	43.01	41.17	54	-10.99	31.93	5.4	35.49	109	350	Average
2388	55.8	53.96	74	-18.2	31.93	5.4	35.49	109	350	Peak
2462	95.03	92.93			32.04	5.5	35.44	109	350	Average
2462	103.18	101.08			32.04	5.5	35.44	109	350	Peak
2483.5	49.22	47.07	54	-4.78	32.07	5.5	35.42	109	350	Average
2483.5	66.55	64.4	74	-7.45	32.07	5.5	35.42	109	350	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.57	45.71	54	-6.43	31.93	5.4	35.47	191	65	Average
2390	60.76	58.9	74	-13.24	31.93	5.4	35.47	191	65	Peak
2412	98.47	96.55			31.96	5.43	35.47	191	65	Average
2412	106.22	104.3			31.96	5.43	35.47	191	65	Peak
2496	43.16	40.94	54	-10.84	32.1	5.53	35.41	191	65	Average
2496	55.37	53.15	74	-18.63	32.1	5.53	35.41	191	65	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.58	42.72	54	-9.42	31.93	5.4	35.47	112	349	Average
2390	56.53	54.67	74	-17.47	31.93	5.4	35.47	112	349	Peak
2412	95.62	93.7			31.96	5.43	35.47	112	349	Average
2412	103.9	101.98			31.96	5.43	35.47	112	349	Peak
2488	42.16	39.95	54	-11.84	32.1	5.53	35.42	112	349	Average
2488	55.62	53.41	74	-18.38	32.1	5.53	35.42	112	349	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2310	41.65	40.09	54	-12.35	31.79	5.3	35.53	190	63	Average
2310	55.59	54.03	74	-18.41	31.79	5.3	35.53	190	63	Peak
2437	99.19	97.18			32.01	5.46	35.46	190	63	Average
2437	106.57	104.56			32.01	5.46	35.46	190	63	Peak
2488	42.2	39.99	54	-11.8	32.1	5.53	35.42	190	63	Average
2488	55.67	53.46	74	-18.33	32.1	5.53	35.42	190	63	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2378	41.83	40.05	54	-12.17	31.9	5.37	35.49	111	350	Average
2378	54.72	52.94	74	-19.28	31.9	5.37	35.49	111	350	Peak
2437	95.6	93.59			32.01	5.46	35.46	111	350	Average
2437	103.43	101.42			32.01	5.46	35.46	111	350	Peak
2498	42.76	40.54	54	-11.24	32.1	5.53	35.41	111	350	Average
2498	55.39	53.17	74	-18.61	32.1	5.53	35.41	111	350	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2342	42.7	41.03	54	-11.3	31.84	5.33	35.5	185	62	Average
2342	55.46	53.79	74	-18.54	31.84	5.33	35.5	185	62	Peak
2462	97.06	94.96			32.04	5.5	35.44	185	62	Average
2462	105.72	103.62			32.04	5.5	35.44	185	62	Peak
2483.5	52.85	50.7	54	-1.15	32.07	5.5	35.42	185	62	Average
2483.5	69.82	67.67	74	-4.18	32.07	5.5	35.42	185	62	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2356	41.81	40.07	54	-12.19	31.87	5.37	35.5	111	348	Average
2356	55.98	54.24	74	-18.02	31.87	5.37	35.5	111	348	Peak
2462	94.13	92.03			32.04	5.5	35.44	111	348	Average
2462	102.99	100.89			32.04	5.5	35.44	111	348	Peak
2483.5	49.16	47.01	54	-4.84	32.07	5.5	35.42	111	348	Average
2483.5	67.71	65.56	74	-6.29	32.07	5.5	35.42	111	348	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

**TEST MODE B**

**802.11n (20MHz)**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.04	42.11	54	-18.96	26.91	3.54	37.52	104	22	Average
2390	49.67	56.74	74	-24.33	26.91	3.54	37.52	104	22	Peak
2462	93.84	100.55			27.1	3.58	37.39	104	22	Average
2462	103.95	110.66			27.1	3.58	37.39	104	22	Peak
2484	52.11	58.68	54	-1.89	27.15	3.6	37.32	104	22	Average
2484	68.06	74.63	74	-5.94	27.15	3.6	37.32	104	22	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.7	40.77	54	-20.3	26.91	3.54	37.52	160	350	Average
2390	48.82	55.89	74	-25.18	26.91	3.54	37.52	160	350	Peak
2462	91.51	98.22			27.1	3.58	37.39	160	350	Average
2462	101.65	108.36			27.1	3.58	37.39	160	350	Peak
2484	49.28	55.85	54	-4.72	27.15	3.6	37.32	160	350	Average
2484	67.32	73.89	74	-6.68	27.15	3.6	37.32	160	350	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.





A D T

**BELOW 1GHz WORST-CASE DATA:**

**TEST MODE A**

**802.11n (20MHz)**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
96.69	32.44	53.84	43.5	-11.06	9.42	1.28	32.1	305	211	Peak
163.38	26.97	47.2	43.5	-16.53	10.51	1.52	32.26	205	184	Peak
214.14	18.63	37.77	43.5	-24.87	11.45	1.65	32.24	168	34	Peak
512.1	20.9	30.38	46	-25.1	19.94	2.7	32.12	164	97	Peak
675.9	24.77	30.48	46	-21.23	23.36	3.05	32.12	218	37	Peak
890.8	27.82	30.95	46	-18.18	24.92	3.49	31.54	204	298	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
33.24	24.06	40.1	40	-15.94	15.47	0.74	32.25	188	209	Peak
96.96	25.95	47.31	43.5	-17.55	9.46	1.28	32.1	201	79	Peak
153.93	20.89	41.25	43.5	-22.61	10.39	1.52	32.27	167	84	Peak
540.1	21.86	30.85	46	-24.14	20.43	2.76	32.18	103	156	Peak
736.1	25.65	31.29	46	-20.35	23.33	3.16	32.13	124	155	Peak
867.7	27.51	31.15	46	-18.49	24.6	3.44	31.68	178	12	Peak

**REMARKS:** Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
 Margin value = Emission level – Limit value



A D T

**TEST MODE B**

**802.11n (20MHz)**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
63.48	25.65	44.86	40	-14.35	11.47	0.86	31.54	100	236	Peak
104.25	27	48.28	43.5	-16.5	9.53	1.09	31.9	100	142	Peak
187.68	37.87	57.84	43.5	-5.63	10.19	1.54	31.7	100	132	Peak
445.6	20.06	33.22	46	-25.94	16.23	2.6	31.99	100	179	Peak
585.6	23.54	33.34	46	-22.46	19.28	3.05	32.13	100	168	Peak
773.2	27.86	33.72	46	-18.14	21.85	3.63	31.34	100	125	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
30.54	33.52	51.93	40	-6.48	12.14	0.57	31.12	100	158	Peak
63.48	33.16	52.37	40	-6.84	11.47	0.86	31.54	100	251	Peak
174.18	30.48	49.51	43.5	-13.02	11.28	1.47	31.78	100	214	Peak
536.6	21.85	32.52	46	-24.15	18.15	2.9	31.72	100	147	Peak
666.8	24.77	32.92	46	-21.23	20.41	3.3	31.86	100	138	Peak
794.9	28.64	34.22	46	-17.36	22.16	3.68	31.42	100	269	Peak

**REMARKS:** Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
 Margin value = Emission level – Limit value

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

**Tested Date: Dec. 25, 2013**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 17, 2013	Nov. 16, 2014
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 28, 2012	Dec. 27, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100104	Dec. 06, 2013	Dec. 05, 2014
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 17, 2013	Jul. 16, 2014
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 2.
3. The VCCI Site Registration No. is C-2047.



A D T

#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

### 4.2.7 TEST RESULTS


**CONDUCTED WORST-CASE DATA :**

<b>PHASE</b>	Line 1	<b>6dB BANDWIDTH</b>	9kHz
--------------	--------	----------------------	------

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17734	0.17	36.77	26.40	36.94	26.57	64.61	54.61	-27.67	-28.04
2	0.63438	0.23	30.72	16.08	30.95	16.31	56.00	46.00	-25.05	-29.69
3	1.04688	0.27	29.60	19.04	29.87	19.31	56.00	46.00	-26.13	-26.69
4	3.65625	0.35	20.25	11.00	20.60	11.35	56.00	46.00	-35.40	-34.65
5	13.55859	0.50	39.66	34.03	40.16	34.53	60.00	50.00	-19.84	-15.47
6	20.15625	0.64	29.32	19.53	29.96	20.17	60.00	50.00	-30.04	-29.83

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






A D T

PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.17734	0.18	36.50	28.04	36.68	28.22	64.61
2	0.63438	0.24	35.64	22.25	35.88	22.49	56.00	46.00	-20.12	-23.51
3	1.36328	0.25	33.08	19.87	33.33	20.12	56.00	46.00	-22.67	-25.88
4	3.40625	0.36	27.00	17.49	27.36	17.85	56.00	46.00	-28.64	-28.15
5	13.56250	0.57	40.37	37.21	40.94	37.78	60.00	50.00	-19.06	-12.22
6	19.03906	0.71	28.44	20.65	29.15	21.36	60.00	50.00	-30.85	-28.64

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST SETUP



#### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.





#### 4.3.7 TEST RESULTS

##### 802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.51	0.5	PASS
6	2437	9.09	0.5	PASS
11	2462	8.6	0.5	PASS

##### 802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.38	0.5	PASS
6	2437	16.16	0.5	PASS
11	2462	16.38	0.5	PASS

##### 802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.61	0.5	PASS
6	2437	17.22	0.5	PASS
11	2462	17.21	0.5	PASS




A D T

### SPECTRUM PLOT OF WORST VALUE


#### 802.11b



#### 802.11g



#### 802.11n (20MHz)




## 4.4 CONDUCTED OUTPUT POWER

### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

### 4.4.2 TEST SETUP



### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



A D T

#### 4.4.7 TEST RESULTS

##### 802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	111.944	20.49	30	PASS
6	2437	110.917	20.45	30	PASS
11	2462	111.173	20.46	30	PASS

##### 802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	146.893	21.67	30	PASS
6	2437	145.211	21.62	30	PASS
11	2462	131.220	21.18	30	PASS

##### 802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	139.637	21.45	30	PASS
6	2437	138.357	21.41	30	PASS
11	2462	130.017	21.14	30	PASS

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- Set the RBW = 3 kHz, VBW = 10 kHz, Detector = peak.
- Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6



#### 4.5.7 TEST RESULTS

##### 802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-5.18	8	PASS
6	2437	-5.64	8	PASS
11	2462	-3.97	8	PASS

##### 802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-8.80	8	PASS
6	2437	-10.56	8	PASS
11	2462	-12.14	8	PASS

##### 802.11n (20MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-9.62	8	PASS
6	2437	-9.56	8	PASS
11	2462	-10.70	8	PASS




A D T

### SPECTRUM PLOT OF WORST VALUE


#### 802.11b



#### 802.11g



#### 802.11n (20MHz)




## 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

### 4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 TEST PROCEDURE

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.





A D T

## MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Ensure that the number of measurement points  $\geq$  span/RBW
4. According to measurement points to set differ measurement span.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.

### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

### 4.6.7 TEST RESULTS



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T

### 802.11b



#### CH 1



#### CH 6



#### CH 11









A D T

### 802.11g



#### CH 1



#### CH 6



#### CH 11









A D T

### 802.11n (20MHz)



#### CH 1



#### CH 6



#### CH 11



## 5. TEST TYPES AND RESULTS (FOR 5.0GHz BAND)

### 5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

#### 5.1.2 TEST INSTRUMENTS

Same as item 4.1.2.

#### 5.1.3 TEST PROCEDURES

Same as item 4.1.3.

#### 5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 5.1.5 TEST SETUP

Same as item 4.1.5.

#### 5.1.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



A D T

### 5.1.7 TEST RESULTS

#### ABOVE 1GHz WORST-CASE DATA : 802.11a

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	53.01	43.8	76.63	-23.62	34.67	8.65	34.11	110	300	Average
5725	68.45	59.24	85.34	-16.89	34.67	8.65	34.11	110	300	Peak
5745	96.63	87.38			34.7	8.66	34.11	110	300	Average
5745	105.34	96.09			34.7	8.66	34.11	110	300	Peak
5850	45.92	36.49	76.63	-30.71	34.87	8.7	34.14	110	300	Average
5850	57.26	47.83	85.34	-28.08	34.87	8.7	34.14	110	300	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	50.89	41.68	74.6	-23.71	34.67	8.65	34.11	100	50	Average
5725	65.87	56.66	82.58	-16.71	34.67	8.65	34.11	100	50	Peak
5745	94.6	85.35			34.7	8.66	34.11	100	50	Average
5745	102.58	93.33			34.7	8.66	34.11	100	50	Peak
5850	45.61	36.18	74.6	-28.99	34.87	8.7	34.14	100	50	Average
5850	57.62	48.19	82.58	-24.96	34.87	8.7	34.14	100	50	Peak

#### REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5745MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	45.85	36.64	76.6	-30.75	34.67	8.65	34.11	108	302	Average
5725	58.26	49.05	84	-25.74	34.67	8.65	34.11	108	302	Peak
5785	96.6	87.29			34.76	8.68	34.13	108	302	Average
5785	104	94.69			34.76	8.68	34.13	108	302	Peak
5850	46.1	36.67	76.6	-30.5	34.87	8.7	34.14	108	302	Average
5850	58.25	48.82	84	-25.75	34.87	8.7	34.14	108	302	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.85	35.64	74.56	-29.71	34.67	8.65	34.11	100	49	Average
5725	57.92	48.71	81.66	-23.74	34.67	8.65	34.11	100	49	Peak
5785	94.56	85.25			34.76	8.68	34.13	100	49	Average
5785	101.66	92.35			34.76	8.68	34.13	100	49	Peak
5850	45.1	35.67	74.56	-29.46	34.87	8.7	34.14	100	49	Average
5850	57.53	48.1	81.66	-24.13	34.87	8.7	34.14	100	49	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5785MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 165	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.85	35.64	75.83	-30.98	34.67	8.65	34.11	111	302	Average
5725	59.69	50.48	83.62	-23.93	34.67	8.65	34.11	111	302	Peak
5825	95.83	86.46			34.81	8.69	34.13	111	302	Average
5825	103.62	94.25			34.81	8.69	34.13	111	302	Peak
5850	46.13	36.7	75.83	-29.7	34.87	8.7	34.14	111	302	Average
5850	62.08	52.65	83.62	-21.54	34.87	8.7	34.14	111	302	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.53	35.32	73.28	-28.75	34.67	8.65	34.11	100	42	Average
5725	57.65	48.44	80.06	-22.41	34.67	8.65	34.11	100	42	Peak
5825	93.28	83.91			34.81	8.69	34.13	100	42	Average
5825	100.06	90.69			34.81	8.69	34.13	100	42	Peak
5850	46.1	36.67	73.28	-27.18	34.87	8.7	34.14	100	42	Average
5850	58.67	49.24	80.06	-21.39	34.87	8.7	34.14	100	42	Peak

**REMARKS:**

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
2. 5825MHz: Fundamental frequency.
3. 5725MHz & 5850MHz: Out of restricted band



A D T

## 802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	57.74	48.53	77.35	-19.61	34.67	8.65	34.11	100	301	Average
5725	69.71	60.5	85.93	-16.22	34.67	8.65	34.11	100	301	Peak
5745	97.35	88.1			34.7	8.66	34.11	100	301	Average
5745	105.93	96.68			34.7	8.66	34.11	100	301	Peak
5850	45.1	35.67	77.35	-32.25	34.87	8.7	34.14	100	301	Average
5850	57.78	48.35	85.93	-28.15	34.87	8.7	34.14	100	301	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	56.18	46.97	75.25	-19.07	34.67	8.65	34.11	100	49	Average
5725	69.05	59.84	82.3	-13.25	34.67	8.65	34.11	100	49	Peak
5745	95.25	86			34.7	8.66	34.11	100	49	Average
5745	102.3	93.05			34.7	8.66	34.11	100	49	Peak
5850	45.1	35.67	75.25	-30.15	34.87	8.7	34.14	100	49	Average
5850	57.37	47.94	82.3	-24.93	34.87	8.7	34.14	100	49	Peak

## REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5745MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.85	35.64	76.85	-32	34.67	8.65	34.11	110	302	Average
5725	58.11	48.9	84.23	-26.12	34.67	8.65	34.11	110	302	Peak
5785	96.85	87.54			34.76	8.68	34.13	110	302	Average
5785	104.23	94.92			34.76	8.68	34.13	110	302	Peak
5850	46.07	36.64	76.85	-30.78	34.87	8.7	34.14	110	302	Average
5850	57.61	48.18	84.23	-26.62	34.87	8.7	34.14	110	302	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.85	35.64	73.92	-29.07	34.67	8.65	34.11	100	49	Average
5725	58.7	49.49	80.55	-21.85	34.67	8.65	34.11	100	49	Peak
5785	93.92	84.61			34.76	8.68	34.13	100	49	Average
5785	100.55	91.24			34.76	8.68	34.13	100	49	Peak
5850	46.1	36.67	73.92	-27.82	34.87	8.7	34.14	100	49	Average
5850	58.79	49.36	80.55	-21.76	34.87	8.7	34.14	100	49	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5785MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 165	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.85	35.64	77.36	-32.51	34.67	8.65	34.11	108	302	Average
5725	57.42	48.21	84.54	-27.12	34.67	8.65	34.11	108	302	Peak
5825	97.36	87.99			34.81	8.69	34.13	108	302	Average
5825	104.54	95.17			34.81	8.69	34.13	108	302	Peak
5850	49.44	40.01	77.36	-27.92	34.87	8.7	34.14	108	302	Average
5850	64.62	55.19	84.54	-19.92	34.87	8.7	34.14	108	302	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.85	35.64	73.03	-28.18	34.67	8.65	34.11	100	48	Average
5725	58.35	49.14	80.02	-21.67	34.67	8.65	34.11	100	48	Peak
5825	93.03	83.66			34.81	8.69	34.13	100	48	Average
5825	100.02	90.65			34.81	8.69	34.13	100	48	Peak
5850	47.1	37.67	73.03	-25.93	34.87	8.7	34.14	100	48	Average
5850	59.71	50.28	80.02	-20.31	34.87	8.7	34.14	100	48	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5825MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band



A D T

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 151	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	46.85	37.64	70.61	-23.76	34.67	8.65	34.11	100	300	Average
5725	58	48.79	78.33	-20.33	34.67	8.65	34.11	100	300	Peak
5755	90.61	81.36			34.7	8.66	34.11	100	300	Average
5755	98.33	89.08			34.7	8.66	34.11	100	300	Peak
5850	45.1	35.67	70.61	-25.51	34.87	8.7	34.14	100	300	Average
5850	57.2	47.77	78.33	-21.13	34.87	8.7	34.14	100	300	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	46.85	37.64	68.32	-21.47	34.67	8.65	34.11	100	50	Average
5725	58.4	49.19	75.92	-17.52	34.67	8.65	34.11	100	50	Peak
5755	88.32	79.07			34.7	8.66	34.11	100	50	Average
5755	95.92	86.67			34.7	8.66	34.11	100	50	Peak
5850	45.17	35.74	68.32	-23.15	34.87	8.7	34.14	100	50	Average
5850	58.51	49.08	75.92	-17.41	34.87	8.7	34.14	100	50	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5755MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 159	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.73	35.52	71.3	-26.57	34.67	8.65	34.11	100	300	Average
5725	59.01	49.8	78.26	-19.25	34.67	8.65	34.11	100	300	Peak
5795	91.3	81.99			34.76	8.68	34.13	100	300	Average
5795	98.26	88.95			34.76	8.68	34.13	100	300	Peak
5850	46.1	36.67	71.3	-25.2	34.87	8.7	34.14	100	300	Average
5850	59.29	49.86	78.26	-18.97	34.87	8.7	34.14	100	300	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	44.85	35.64	67.12	-22.27	34.67	8.65	34.11	100	50	Average
5725	57.87	48.66	74.34	-16.47	34.67	8.65	34.11	100	50	Peak
5795	87.12	77.81			34.76	8.68	34.13	100	50	Average
5795	94.34	85.03			34.76	8.68	34.13	100	50	Peak
5850	46.13	36.7	67.12	-20.99	34.87	8.7	34.14	100	50	Average
5850	57.82	48.39	74.34	-16.52	34.87	8.7	34.14	100	50	Peak

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5795MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band



A D T

802.11ac (80MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 155	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	46.89	37.68	70.18	-23.29	34.67	8.65	34.11	100	302	Average
5725	59.97	50.76	77.34	-17.37	34.67	8.65	34.11	100	302	Peak
5775	90.18	80.9			34.73	8.67	34.12	100	302	Average
5775	97.34	88.06			34.73	8.67	34.12	100	302	Peak
5850	45.1	35.67	70.18	-25.08	34.87	8.7	34.14	100	302	Average
5850	58.82	49.39	77.34	-18.52	34.87	8.7	34.14	100	302	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	45.85	36.64	66.26	-20.41	34.67	8.65	34.11	100	50	Average
5725	58.7	49.49	74.64	-15.94	34.67	8.65	34.11	100	50	Peak
5775	86.26	76.98			34.73	8.67	34.12	100	50	Average
5775	94.64	85.36			34.73	8.67	34.12	100	50	Peak
5850	46.1	36.67	66.26	-20.16	34.87	8.7	34.14	100	50	Average
5850	57.81	48.38	74.64	-16.83	34.87	8.7	34.14	100	50	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 5775MHz: Fundamental frequency.
- 5725MHz & 5850MHz: Out of restricted band



A D T

**BELOW 1GHz WORST-CASE DATA :**

**802.11n (20MHz)**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Quasi-peak (QP)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Kay Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
56.19	16.78	40.96	40	-23.22	7.15	0.9	32.23	128	308	Peak
97.5	33.51	54.88	43.5	-9.99	9.5	1.28	32.15	148	99	Peak
165.27	28.2	48.58	43.5	-15.3	10.36	1.52	32.26	203	20	Peak
514.2	21.4	30.88	46	-24.6	19.94	2.7	32.12	104	35	Peak
784.4	26.15	31.09	46	-19.85	23.87	3.27	32.08	127	94	Peak
925.1	29.27	30.83	46	-16.73	26.2	3.53	31.29	184	298	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
32.16	26.54	41.85	40	-13.46	16.21	0.74	32.26	111	84	Peak
96.69	26.47	47.87	43.5	-17.03	9.42	1.28	32.1	246	71	Peak
156.36	23.55	43.73	43.5	-19.95	10.57	1.52	32.27	302	255	Peak
547.8	21.38	30.48	46	-24.62	20.34	2.76	32.2	113	79	Peak
808.2	26.69	31.23	46	-19.31	24.16	3.32	32.02	184	166	Peak
924.4	29.02	30.59	46	-16.98	26.2	3.53	31.3	133	302	Peak

**REMARKS:** Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value



## 5.2 CONDUCTED EMISSION MEASUREMENT

### 5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 5.2.2 TEST INSTRUMENTS

Same as item 4.2.2.

### 5.2.3 TEST PROCEDURES

Same as item 4.2.3.

### 5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

### 5.2.5 TEST SETUP

Same as item 4.2.5.

### 5.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

### 5.2.7 TEST RESULTS


**CONDUCTED WORST-CASE DATA :**

<b>PHASE</b>	Line 1	<b>6dB BANDWIDTH</b>	9kHz
--------------	--------	----------------------	------

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17734	0.17	37.32	26.67	37.49	26.84	64.61	54.61	-27.12	-27.77
2	0.53672	0.22	28.84	16.34	29.06	16.56	56.00	46.00	-26.94	-29.44
3	1.01953	0.27	29.01	13.55	29.28	13.82	56.00	46.00	-26.72	-32.18
4	4.05078	0.37	19.67	11.15	20.04	11.52	56.00	46.00	-35.96	-34.48
5	13.56250	0.50	39.83	34.31	40.33	34.81	60.00	50.00	-19.67	-15.19
6	18.87109	0.62	29.77	19.45	30.39	20.07	60.00	50.00	-29.61	-29.93

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.25938	0.20	30.90	23.15	31.10	23.35	61.45
2	0.61875	0.24	35.72	25.90	35.96	26.14	56.00	46.00	-20.04	-19.86
3	1.32813	0.25	32.98	21.37	33.23	21.62	56.00	46.00	-22.77	-24.38
4	3.03516	0.34	26.89	16.52	27.23	16.86	56.00	46.00	-28.77	-29.14
5	6.41406	0.43	25.41	16.18	25.84	16.61	60.00	50.00	-34.16	-33.39
6	13.55859	0.57	39.99	36.93	40.56	37.50	60.00	50.00	-19.44	-12.50

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value





A D T

### **5.3 6dB BANDWIDTH MEASUREMENT**

#### **5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT**

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

#### **5.3.2 TEST SETUP**

Same as item 4.3.2.

#### **5.3.3 TEST INSTRUMENTS**

Refer to section 4.1.2 to get information of above instrument.

#### **5.3.4 TEST PROCEDURE**

Same as item 4.3.4.

#### **5.3.5 DEVIATION FROM TEST STANDARD**

No deviation.

#### **5.3.6 EUT OPERATING CONDITIONS**

Same as item 4.3.6.



### 5.3.7 TEST RESULTS

#### 802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	16.37	0.5	PASS
157	5785	16.41	0.5	PASS
165	5825	16.39	0.5	PASS

#### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	17.62	0.5	PASS
157	5785	17.61	0.5	PASS
165	5825	17.62	0.5	PASS

#### 802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
151	5755	35.56	0.5	PASS
159	5795	35.27	0.5	PASS

#### 802.11ac (80MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
155	5775	75.32	0.5	PASS




A D T

### SPECTRUM PLOT OF WORST VALUE


#### 802.11a




#### 802.11n (20MHz)



#### 802.11n (40MHz)



#### 802.11ac (80MHz)



## **5.4 MAXIMUM OUTPUT POWER**

### **5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT**

For systems using digital modulation in the 5725–5850 MHz bands: 1 Watt (30dBm)

### **5.4.2 TEST SETUP**

Same as Item 4.4.2.

### **5.4.3 INSTRUMENTS**

Refer to section 4.1.2 to get information of above instrument.

### **5.4.4 TEST PROCEDURES**

Same as Item 4.4.4.

### **5.4.5 DEVIATION FROM TEST STANDARD**

No deviation.

### **5.4.6 EUT OPERATING CONDITIONS**

Same as Item 4.3.6.



## 5.4.7 TEST RESULTS

### 802.11a

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
149	5745	218.273	23.39	30	PASS
157	5785	230.675	23.63	30	PASS
165	5825	222.844	23.48	30	PASS

### 802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
149	5745	231.206	23.64	30	PASS
157	5785	238.232	23.77	30	PASS
165	5825	236.048	23.73	30	PASS

### 802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
151	5755	171.791	22.35	30	PASS
159	5795	169.044	22.28	30	PASS

### 802.11ac (80MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
155	5775	114.228	20.58	30	PASS





A D T

## **5.5 POWER SPECTRAL DENSITY MEASUREMENT**

### **5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT**

The Maximum of Power Spectral Density Measurement is 8dBm.

### **5.5.2 TEST SETUP**

Same as item 4.5.2.

### **5.5.3 TEST INSTRUMENTS**

Refer to section 4.1.2 to get information of above instrument.

### **5.5.4 TEST PROCEDURE.**

Same as item 4.5.4.

### **5.5.5 DEVIATION FROM TEST STANDARD**

No deviation.

### **5.5.6 EUT OPERATING CONDITION**

Same as item 4.3.6.



## 5.5.7 TEST RESULTS

### 802.11a

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
149	5745	-9.95	8	PASS
157	5785	-9.41	8	PASS
165	5825	-8.44	8	PASS

### 802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
149	5745	-9.32	8	PASS
157	5785	-6.83	8	PASS
165	5825	-8.42	8	PASS

### 802.11n (40MHz)

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	Limit (dBm/3kHz)	PASS /FAIL
151	5755	-14.89	8	PASS
159	5795	-15.92	8	PASS

### 802.11ac (80MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
155	5775	-19.48	8	PASS




A D T

### SPECTRUM PLOT OF WORST VALUE


#### 802.11a




#### 802.11n (20MHz)



#### 802.11n (40MHz)



#### 802.11ac (80MHz)



## **5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT**

### **5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT**

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### **5.6.2 TEST SETUP**

Same as Item 4.6.2

### **5.6.3 TEST INSTRUMENTS**

Refer to section 4.1.2 to get information of above instrument.

### **5.6.4 TEST PROCEDURE**

Same as Item 4.6.4

### **5.6.5 DEVIATION FROM TEST STANDARD**

No deviation.

### **5.6.6 EUT OPERATING CONDITION**

Same as Item 4.3.6

### **5.6.7 TEST RESULTS**



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T

802.11a



CH 149



CH 157



CH 165









A D T

### 802.11n (20MHz)



#### CH 149



#### CH 157



#### CH 165







A D T

### 802.11n (40MHz)

#### CH 151




#### CH 159



### 802.11ac (80MHz)

#### CH 155





A D T

## 6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).





## 7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## 8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---