

## FCC Test Report

### (PART 27)

**Report No.:** RF150729C02-3

**FCC ID:** NM82PQ9120

**Test Model:** 2PQ9120

**Received Date:** Jul. 29, 2015

**Test Date:** Aug. 02, 2015 ~ Sep. 02, 2015

**Issued Date:** Sep. 16, 2015

**Applicant:** HTC Corporation

**Address:** 1F, 6-3 Baoqiang Road, Xindian City, Taipei County 231, Taiwan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
(R.O.C.)

**Test Location (1):** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

**Test Location (2):** No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency.

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1 Certificate of Conformity .....</b>	<b>4</b>
<b>2 Summary of Test Results.....</b>	<b>5</b>
2.1 Measurement Uncertainty.....	5
2.2 Test Site And Instruments .....	6
<b>3 General Information .....</b>	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Configuration of System Under Test.....	8
3.2.1 Description of Support Units.....	8
3.3 Test Mode Applicability and Tested Channel Detail .....	9
3.4 EUT Operating Conditions .....	10
3.5 General Description of Applied Standards.....	10
<b>4 Test Types and Results .....</b>	<b>11</b>
4.1 Output Power Measurement .....	11
4.1.1 Limits of Output Power Measurement.....	11
4.1.2 Test Procedures.....	11
4.1.3 Test Setup.....	12
4.1.4 Test Results .....	13
4.2 Frequency Stability Measurement .....	17
4.2.1 Limits of Frequency Stability Measurement.....	17
4.2.2 Test Procedure .....	17
4.2.3 Test Setup.....	17
4.2.4 Test Results .....	18
4.3 Occupied Bandwidth Measurement.....	19
4.3.1 Limits Of Occupied Bandwidth Measurement .....	19
4.3.2 Test Procedure .....	19
4.3.3 Test Setup.....	19
4.3.4 Test Result .....	20
4.4 Band Edge Measurement .....	22
4.4.1 Limits of Band Edge Measurement .....	22
4.4.2 Test Setup.....	22
4.4.3 Test Procedures.....	22
4.4.4 Test Results .....	23
4.5 Peak To Average Ratio .....	31
4.5.1 Limits of Peak To Average Ratio Measurement .....	31
4.5.2 Test Setup.....	31
4.5.3 Test Procedures.....	31
4.5.4 Test Results .....	32
4.6 Conducted Spurious Emissions .....	34
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	34
4.6.2 Test Setup.....	34
4.6.3 Test Procedure .....	34
4.6.4 Test Results .....	35
4.7 Radiated Emission Measurement.....	37
4.7.1 Limits of Radiated Emission Measurement .....	37
4.7.2 Test Procedure .....	37
4.7.3 Deviation from Test Standard .....	37
4.7.4 Test Setup.....	37
4.7.5 Test Results .....	38
<b>5 Pictures of Test Arrangements.....</b>	<b>40</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>41</b>



A D T

### Release Control Record

Issue No.	Description	Date Issued
RF150729C02-3	Original Release	Sep. 16, 2015



A D T

## 1 Certificate of Conformity

**Product:** Smartphone

**Brand:** HTC

**Test Model:** 2PQ9120

**Sample Status:** Identical Prototype

**Applicant:** HTC Corporation

**Test Date:** Aug. 02, 2015 ~ Sep. 02, 2015

**Standards:** FCC Part 27, Subpart C, M

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**  , **Date:** Sep. 16, 2015

Ivonne Wu / Supervisor

**Approved by :**  , **Date:** Sep. 16, 2015

Kay Wu / Supervisor

## 2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(h)	Equivalent Isotropic Radiated Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049	Occupied Bandwidth	PASS	Meet the requirement of limit.
	Peak to average ratio	PASS	Meet the requirement of limit.
2.1051 27.53(l)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(m)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(m)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -13.29dB at 37.29MHz.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	2.0153 dB
	200MHz ~ 1000MHz	2.0224 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	1.0121 dB
	18GHz ~ 40GHz	1.1508 dB

## 2.2 Test Site And Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Spectrum Analyzer Agilent Technologies	N9038A	MY52260177	May 19, 2015	May 18, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna ETS-Lindgren	3117	00143293	Jan. 05, 2015	Jan. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Bluetooth Tester	CBT	100980	Apr. 27, 2015	Apr. 26, 2017
Agilent Communications Tester-Wireless	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Preamplifier Agilent	310N	187226	Jun. 29, 2015	Jun. 28, 2016
Preamplifier Agilent	83017A	MY39501357	Jun. 29, 2015	Jun. 28, 2016
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 27, 2015	Jun. 26, 2016
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 27, 2015	Jun. 26, 2016
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HsinTien Chamber 1.
  3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 149147.
  5. The IC Site Registration No. is IC7450I-1.

### 3 General Information

#### 3.1 General Description of EUT


Product	Smartphone	
Brand	HTC	
Test Model	2PQ9120	
Status of EUT	Identical Prototype	
Power Supply Rating	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion battery)	
Modulation Type	QPSK, 16QAM	
Frequency Range	LTE Band 7 (Channel Bandwidth: 5MHz)	2502.5 ~ 2567.5 MHz
	LTE Band 7 (Channel Bandwidth: 10MHz)	2505 ~ 2565 MHz
	LTE Band 7 (Channel Bandwidth: 15MHz)	2507.5 ~ 2562.5 MHz
	LTE Band 7 (Channel Bandwidth: 20MHz)	2510 ~ 2560 MHz
Max. EIRP Power	LTE Band 7 (Channel Bandwidth: 5MHz)	135.11mW
	LTE Band 7 (Channel Bandwidth: 10MHz)	137.94mW
	LTE Band 7 (Channel Bandwidth: 15MHz)	140.51mW
	LTE Band 7 (Channel Bandwidth: 20MHz)	132.34mW
Emission Designator	LTE Band 7 (Channel Bandwidth: 5MHz)	4M49W7D
	LTE Band 7 (Channel Bandwidth: 10MHz)	8M97W7D
	LTE Band 7 (Channel Bandwidth: 15MHz)	13M4G7D
	LTE Band 7 (Channel Bandwidth: 20MHz)	17M9W7D
Antenna Type	Fixed Internal Antenna	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


1. The EUT's accessories list refers to Ext. Pho.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Configuration of System Under Test

<Radiated Emission Test>



<E.I.R.P. Test>



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP	Radiated Emission
LTE Band 7	Z-plane	Z-axis

#### LTE BAND 7

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM	1 RB / 37 RB Offset
		20850 to 21350	20850, 21100 21350	20MHz	QPSK, 16QAM	1 RB / 50 RB Offset
-	Frequency Stability	20775 to 21425	21100	5MHz	QPSK	1 RB / 12 RB Offset
		20800 to 21400	21100	10MHz	QPSK	1 RB / 24 RB Offset
		20825 to 21375	21100	15MHz	QPSK	1 RB / 37 RB Offset
		20850 to 21350	21100	20MHz	QPSK	1 RB / 50 RB Offset
-	Occupied Bandwidth	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM	1 RB / 37 RB Offset
		20850 to 21350	20850, 21100 21350	20MHz	QPSK, 16QAM	1 RB / 50 RB Offset
-	Band Edge	20775 to 21425	20775, 21425	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20800 to 21400	20800, 21400	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20825 to 21375	20825, 21375	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20850 to 21350	20850, 21350	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Conducted Emission	20775 to 21425	21100	5MHz	QPSK	1 RB / 12 RB Offset
		20800 to 21400	21100	10MHz	QPSK	1 RB / 24 RB Offset
		20825 to 21375	21100	15MHz	QPSK	1 RB / 37 RB Offset
		20850 to 21350	21100	20MHz	QPSK	1 RB / 50 RB Offset
-	Radiated Emission	20850 to 21350	21100	20MHz	QPSK	1 RB / 50 RB Offset

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

**Test Condition:**

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	25deg. C, 65%RH	3.85Vdc	Charles Hsiao
Frequency Stability	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Occupied Bandwidth	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Band Edge	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Peak to Average Ratio	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Conducted Emission	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Radiated Emission	25deg. C, 65%RH	120Vac, 60Hz	Charles Hsiao

**3.4 EUT Operating Conditions**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

**3.5 General Description of Applied Standards**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 27**

**ANSI/TIA/EIA-603-C 2004**

**NOTE:** All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

The radiated peak output power shall be according to the specific rule Part 27.50(h)(2) that “User stations are limited to 2 watts” and 27.50(i) specific that “Peak transmit power must be measure over any interval of continuous transmission using instrumentation calibration in terms of rms-equivalent voltage.”

#### 4.1.2 Test Procedures

##### **EIRP Measurement:**


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 10MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$

##### **Conducted Power Measurement:**

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

#### 4.1.3 Test Setup

##### EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

##### CONDUCTED POWER MEASUREMENT:



#### 4.1.4 Test Results

##### CONDUCTED OUTPUT POWER (dBm)

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20775	Mid Ch 21100	High Ch 21425		Low Ch 20775	Mid Ch 21100	High Ch 21425	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
7 / 5M	1	0	21.81	21.45	21.46	0	20.77	20.41	20.42	1
	1	12	22.03	21.67	21.68	0	20.99	20.63	20.64	1
	1	24	21.97	21.61	21.62	0	20.93	20.57	20.58	1
	12	0	21.08	20.72	20.73	1	20.04	19.68	19.69	2
	12	6	20.95	20.59	20.60	1	19.91	19.55	19.56	2
	12	13	21.05	20.69	20.70	1	20.01	19.65	19.66	2
	25	0	21.04	20.68	20.69	1	20.00	19.64	19.65	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20800	Mid Ch 21100	High Ch 21400		Low Ch 20800	Mid Ch 21100	High Ch 21400	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
7 / 10M	1	0	21.93	21.57	21.58	0	20.89	20.53	20.54	1
	1	24	22.15	21.79	21.80	0	21.11	20.75	20.76	1
	1	49	22.09	21.73	21.74	0	21.05	20.69	20.70	1
	25	0	21.20	20.84	20.85	1	20.16	19.80	19.81	2
	25	12	21.07	20.71	20.72	1	20.03	19.67	19.68	2
	25	25	21.17	20.81	20.82	1	20.13	19.77	19.78	2
	50	0	21.16	20.80	20.81	1	20.12	19.76	19.77	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20825	Mid Ch 21100	High Ch 21375		Low Ch 20825	Mid Ch 21100	High Ch 21375	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
7 / 15M	1	0	22.04	21.68	21.69	0	21.00	20.64	20.65	1
	1	37	22.26	21.90	21.91	0	21.22	20.86	20.87	1
	1	74	22.20	21.84	21.85	0	21.16	20.80	20.81	1
	36	0	21.31	20.95	20.96	1	20.27	19.91	19.92	2
	36	19	21.18	20.82	20.83	1	20.14	19.78	19.79	2
	36	39	21.28	20.92	20.93	1	20.24	19.88	19.89	2
	75	0	21.27	20.91	20.92	1	20.23	19.87	19.88	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20850	Mid Ch 21100	High Ch 21350		Low Ch 20850	Mid Ch 21100	High Ch 21350	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
7 / 20M	1	0	22.09	21.73	21.74	0	21.05	20.69	20.70	1
	1	50	22.31	21.95	21.96	0	21.27	20.91	20.92	1
	1	99	22.25	21.89	21.90	0	21.21	20.85	20.86	1
	50	0	21.36	21.00	21.01	1	20.32	19.96	19.97	2
	50	25	21.23	20.87	20.88	1	20.19	19.83	19.84	2
	50	50	21.33	20.97	20.98	1	20.29	19.93	19.94	2
	100	0	21.32	20.96	20.97	1	20.28	19.92	19.93	2

## EIRP Power (dBm)

LTE Band 7							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20775	2502.5	-23.34	44.24	20.90	122.97	H
	21100	2535.0	-22.89	44.20	21.31	135.11	
	21425	2567.5	-23.57	44.80	21.23	132.77	
	20775	2502.5	-24.21	44.19	19.98	99.56	V
	21100	2535.0	-24.55	44.09	19.54	89.91	
	21425	2567.5	-25.96	44.50	18.54	71.43	

LTE Band 7							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20775	2502.5	-24.01	44.24	20.23	105.39	H
	21100	2535.0	-23.40	44.20	20.80	120.14	
	21425	2567.5	-23.82	44.80	20.98	125.34	
	20775	2502.5	-24.93	44.19	19.26	84.35	V
	21100	2535.0	-25.28	44.09	18.81	76.00	
	21425	2567.5	-26.14	44.50	18.36	68.53	

LTE Band 7							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20800	2505.0	-23.88	44.34	20.46	111.20	H
	21100	2535.0	-22.80	44.20	21.40	137.94	
	21400	2565.0	-23.52	44.72	21.20	131.92	
	20800	2505.0	-24.68	44.23	19.55	90.07	V
	21100	2535.0	-24.36	44.09	19.73	93.93	
	21400	2565.0	-25.75	44.41	18.66	73.38	

LTE Band 7							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20800	2505.0	-23.48	44.34	20.86	121.93	H
	21100	2535.0	-23.88	44.20	20.32	107.57	
	21400	2565.0	-23.34	44.72	21.38	137.50	
	20800	2505.0	-24.29	44.23	19.94	98.54	V
	21100	2535.0	-25.68	44.09	18.41	69.31	
	21400	2565.0	-25.82	44.41	18.59	72.21	

LTE Band 7							
Channel Bandwidth: 15MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20825	2507.5	-23.50	44.32	20.82	120.73	H
	21100	2535.0	-22.91	44.20	21.29	134.49	
	21375	2562.5	-23.61	44.85	21.24	132.98	
	20825	2507.5	-24.40	43.99	19.59	91.03	V
	21100	2535.0	-24.66	44.09	19.43	87.66	
	21375	2562.5	-25.71	44.51	18.80	75.86	

LTE Band 7							
Channel Bandwidth: 15MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20825	2507.5	-24.25	44.32	20.07	101.58	H
	21100	2535.0	-22.72	44.20	21.48	140.51	
	21375	2562.5	-24.27	44.85	20.58	114.24	
	20825	2507.5	-24.48	43.99	19.51	89.37	V
	21100	2535.0	-24.29	44.09	19.80	95.46	
	21375	2562.5	-26.17	44.51	18.34	68.23	

LTE Band 7							
Channel Bandwidth: 20MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20850.0	2510.0	-23.49	44.16	20.67	116.68	H
	21100.0	2535.0	-23.08	44.20	21.12	129.33	
	21350.0	2560.0	-23.72	44.81	21.09	128.44	
	20850.0	2510.0	-25.22	44.78	19.56	90.36	V
	21100.0	2535.0	-24.58	44.09	19.51	89.29	
	21350.0	2560.0	-25.83	44.72	18.89	77.45	

LTE Band 7							
Channel Bandwidth: 20MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	20850.0	2510.0	-24.66	44.16	19.50	89.13	H
	21100.0	2535.0	-22.98	44.20	21.22	132.34	
	21350.0	2560.0	-24.29	44.81	20.52	112.64	
	20850.0	2510.0	-26.32	44.78	18.46	70.15	V
	21100.0	2535.0	-24.34	44.09	19.75	94.36	
	21350.0	2560.0	-26.33	44.72	18.39	69.02	

## 4.2 Frequency Stability Measurement

### 4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

### 4.2.2 Test Procedure

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 4.2.3 Test Setup



#### 4.2.4 Test Results

##### Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)				Limit (ppm)	
	LTE Band 7					
	5MHz	10MHz	15MHz	20MHz		
3.85	0.0007	0.0010	0.0008	0.0002	2.5	
3.6	0.0007	0.0003	0.0006	0.0004	2.5	
4.40	0.0007	0.0002	0.0001	0.0014	2.5	

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.40Vdc.

##### Frequency Error vs. Temperature

Temp. (°C)	Frequency Error (ppm)				Limit (ppm)	
	LTE Band 7					
	5MHz	10MHz	15MHz	20MHz		
-30	0.0012	0.0005	0.0001	0.0009	2.5	
-20	0.0010	0.0011	0.0008	0.0014	2.5	
-10	0.0002	0.0015	0.0003	0.0015	2.5	
0	0.0006	0.0009	0.0003	0.0001	2.5	
10	0.0003	0.0006	0.0003	0.0005	2.5	
20	-0.0009	-0.0010	-0.0013	-0.0009	2.5	
30	-0.0007	-0.0012	-0.0001	-0.0014	2.5	
40	-0.0012	-0.0011	-0.0012	-0.0003	2.5	
50	-0.0013	-0.0014	-0.0012	-0.0008	2.5	
60	-0.0005	0.0005	0.0014	0.0008	2.5	

### 4.3 Occupied Bandwidth Measurement


#### 4.3.1 Limits Of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

#### 4.3.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

#### 4.3.3 Test Setup



#### 4.3.4 Test Result

LTE Band 7							
Channel Bandwidth: 5MHz				Channel Bandwidth: 10MHz			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20775	2502.5	4.4892	4.4896	20800	2505.0	8.9596	8.9330
21100	2535.0	4.4848	4.4904	21100	2535.0	8.9545	8.9618
21425	2567.5	4.4859	4.4868	21400	2565.0	8.9521	8.9676




## LTE Band 7


Channel Bandwidth: 15MHz				Channel Bandwidth: 20MHz			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20825	2507.5	13.417	13.416	20850	2510.0	17.859	17.869
21100	2535.0	13.429	13.423	21100	2535.0	17.882	17.887
21375	2562.5	13.416	13.407	21350	2560.0	17.857	17.864

## Spectrum Plot of Worst Value


## 15MHz / QPSK




## 15MHz / 16QAM



## 20MHz / QPSK



## 20MHz / 16QAM




## 4.4 Band Edge Measurement

### 4.4.1 Limits of Band Edge Measurement

According to FCC 27.53(l)(4) specified that power of any emission outside of the channel edge must be attenuated below the transmitting power (P) by a factor shall be not less than  $40 + 10 \log (P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log (P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than  $43 + 10 \log (P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log (P)$  dB at or below 2490.5 MHz. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed, except when the 1 megahertz band is 2495-2496 MHz, in which case a resolution bandwidth of at least one percent may be employed.


### 4.4.2 Test Setup





### 4.4.3 Test Procedures


- The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).
- The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- The center frequency of spectrum is the band edge frequency and span is 20MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (Channel bandwidth 5MHz).
- The center frequency of spectrum is the band edge frequency and span is 40MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (Channel bandwidth 10MHz).
- The center frequency of spectrum is the band edge frequency and span is 60MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz (Channel bandwidth 15MHz).
- The center frequency of spectrum is the band edge frequency and span is 80MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz (Channel bandwidth 20MHz).
- Record the max trace plot into the test report.

#### 4.4.4 Test Results


















## LTE Band 7

Channel Bandwidth: 20MHz / 16QAM


&lt;Adjacent Channel Band Edge&gt;

Channel	20850	100 RB	Channel	20850	100 RB
Low			High		



## &lt;Channel Band Edge&gt;

Channel	20850	100 RB	Channel	21350	100 RB
---------	-------	--------	---------	-------	--------




## 4.5 Peak To Average Ratio

### 4.5.1 Limits of Peak To Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

### 4.5.2 Test Setup




### 4.5.3 Test Procedures

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

#### 4.5.4 Test Results

LTE Band 7							
Channel Bandwidth: 5MHz				Channel Bandwidth: 10MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20775	2502.5	4.39	6.49	20800	2505.0	4.48	6.56
21100	2535.0	4.97	6.78	21100	2535.0	4.95	7.09
21425	2567.5	5.06	6.74	21400	2565.0	5.06	7.16




### LTE Band 7


Channel Bandwidth: 15MHz				Channel Bandwidth: 20MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20825	2507.5	4.38	6.49	20850	2510.0	5.34	6.40
21100	2535.0	4.84	7.22	21100	2535.0	5.62	6.71
21375	2562.5	4.90	7.00	21350	2560.0	5.57	6.82

### Spectrum Plot of Worst Value


#### 15MHz / QPSK




#### 15MHz / 16QAM



#### 20MHz / QPSK



#### 20MHz / 16QAM




## 4.6 Conducted Spurious Emissions

### 4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $55 + 10 \log_{10}(P)$  dB. The limit of emission is equal to -25dBm.


### 4.6.2 Test Setup





### 4.6.3 Test Procedure

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30 MHz to 26GHz for LTE Band 7 for LTE Band 41. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

#### 4.6.4 Test Results





## 4.7 Radiated Emission Measurement

### 4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $55 + 10 \log_{10}(P)$  dB. The limit of emission equal to -25dBm.

### 4.7.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
- EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15dBi.

**NOTE:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

### 4.7.3 Deviation from Test Standard

No deviation.

### 4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.7.5 Test Results

LTE Band 7


Channel Bandwidth: 20MHz / QPSK



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Date: 2015-09-02

Site : 966 chamber 1  
 Condition: PART 27(B7/B41) 3m Horizontal  
 Remark : LTE\_Band 7\_QPSK(1,50)\_20M\_CH21100  
 Tested by: Charles Hsiao  
 Plane : Z


	Freq	Read Level	Limit Level	Over Line	Over Limit	Over Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	68.61	-64.64	-51.82	-25.00	-39.64	-12.82	Peak
2	97.77	-57.32	-47.09	-25.00	-32.32	-10.23	Peak
3	192.81	-50.21	-44.34	-25.00	-25.21	-5.87	Peak
4	422.50	-70.94	-67.69	-25.00	-45.94	-3.25	Peak
5	587.00	-68.37	-68.23	-25.00	-43.37	-0.14	Peak
6	859.30	-66.67	-68.39	-25.00	-41.67	1.72	Peak
7 pp	5070.00	-44.56	-63.95	-25.00	-19.56	19.39	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14



Site : 966 chamber 1

Condition: PART 27(B7/B41) 3m Vertical

Remark : LTE\_Band 7\_QPSK(1,50)\_20M\_CH21100

Tested by: Charles Hsiao

Plane : Z

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m
1 pp	37.29	-38.29	-28.32	-25.00	-13.29	-9.97 Peak
2	71.85	-49.67	-37.15	-25.00	-24.67	-12.52 Peak
3	193.62	-56.94	-51.03	-25.00	-31.94	-5.91 Peak
4	422.50	-71.34	-68.09	-25.00	-46.34	-3.25 Peak
5	583.50	-69.00	-68.74	-25.00	-44.00	-0.26 Peak
6	814.50	-66.62	-68.47	-25.00	-41.62	1.85 Peak
7	5070.00	-46.85	-66.24	-25.00	-21.85	19.39 Peak



A D T

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab/Telecom Lab**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232  
Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---