





A D T

# FCC SAR Test Report

**Report No.** : SA160301C04  
**Applicant** : HTC Corporation  
**Address** : 1F, 6-3 Baoqiang Road, Xindian District, New Taipei City, Taiwan 231  
**Product** : Smartphone  
**FCC ID** : NM82PS6400  
**Brand** : HTC  
**Model No.** : 2PS6400  
**Standards** : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE Std 1528:2013  
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02  
KDB 248227 D01 v02r02 / KDB 447498 D01 v06 / KDB 648474 D04 v01r03  
KDB 941225 D01 v03r01 / KDB 941225 D05 v02r05 / KDB 941225 D06 v02r01  
**Sample Received Date** : Mar. 01, 2016  
**Date of Testing** : Mar. 28, 2016 ~ Apr. 07, 2016

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

**Prepared By :**   
Ivonne Wu / Supervisor  
**Approved By :**   
Eli Hsu / Supervisor



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



# Table of Contents

- Release Control Record ..... 3
- 1. Summary of Maximum SAR Value ..... 4
- 2. Description of Equipment Under Test ..... 5
- 3. SAR Measurement System ..... 6
  - 3.1 Definition of Specific Absorption Rate (SAR) ..... 6
  - 3.2 SPEAG DASY System ..... 6
    - 3.2.1 Robot..... 7
    - 3.2.2 Probes..... 8
    - 3.2.3 Data Acquisition Electronics (DAE) ..... 8
    - 3.2.4 Phantoms ..... 9
    - 3.2.5 Device Holder..... 10
    - 3.2.6 System Validation Dipoles ..... 10
    - 3.2.7 Tissue Simulating Liquids..... 11
  - 3.3 SAR System Verification ..... 14
  - 3.4 SAR Measurement Procedure ..... 15
    - 3.4.1 Area & Zoom Scan Procedure ..... 15
    - 3.4.2 Volume Scan Procedure..... 15
    - 3.4.3 Power Drift Monitoring..... 16
    - 3.4.4 Spatial Peak SAR Evaluation ..... 16
    - 3.4.5 SAR Averaged Methods ..... 16
- 4. SAR Measurement Evaluation ..... 17
  - 4.1 EUT Configuration and Setting..... 17
  - 4.2 EUT Testing Position ..... 22
    - 4.2.1 Head Exposure Conditions..... 22
    - 4.2.2 Body-worn Accessory Exposure Conditions ..... 24
    - 4.2.3 Hotspot Mode Exposure Conditions ..... 25
    - 4.2.4 Simultaneous Transmission Possibilities ..... 26
  - 4.3 Tissue Verification ..... 27
  - 4.4 System Validation..... 28
  - 4.5 System Verification..... 29
  - 4.6 Maximum Output Power..... 30
    - 4.6.1 Maximum Conducted Power ..... 30
    - 4.6.2 Measured Conducted Power Result..... 31
  - 4.7 SAR Testing Results ..... 43
    - 4.7.1 SAR Test Reduction Considerations ..... 43
    - 4.7.2 SAR Results for Head Exposure Condition ..... 45
    - 4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap) ..... 50
    - 4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap)..... 53
    - 4.7.5 SAR Measurement Variability..... 59
    - 4.7.6 Simultaneous Multi-band Transmission Evaluation ..... 60
- 5. Calibration of Test Equipment..... 72
- 6. Measurement Uncertainty ..... 73
- 7. Information on the Testing Laboratories ..... 75

Appendix A. SAR Plots of System Verification  
 Appendix B. SAR Plots of SAR Measurement  
 Appendix C. Calibration Certificate for Probe and Dipole  
 Appendix D. Photographs of EUT and Setup



### Release Control Record

Report No.	Reason for Change	Date Issued
SA160301C04	Initial release	Apr. 13, 2016

### 1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Head SAR <sub>1g</sub> (W/kg)	Highest Reported Body-worn SAR <sub>1g</sub> (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR <sub>1g</sub> (1.0 cm Gap) (W/kg)
PCE	CDMA BC0	0.19	0.27	0.27
	CDMA BC1	0.68	0.47	0.47
	CDMA BC10	0.18	0.26	0.26
	LTE 2	0.37	0.34	0.34
	LTE 4	0.66	0.55	0.59
	LTE 5	0.15	0.15	0.15
	LTE 7	0.39	0.36	0.36
	LTE 12	0.13	0.23	0.23
	LTE 13	0.07	0.14	0.14
	LTE 25	0.38	0.32	0.32
	LTE 26	0.13	0.07	0.07
LTE 41	0.22	0.21	0.21	
DTS	2.4G WLAN	0.47	0.08	0.08
NII	5.3G WLAN	0.73	0.02	N/A
	5.6G WLAN	0.57	0.02	N/A
	5.8G WLAN	0.55	0.02	0.02
DSS	Bluetooth	N/A	0	N/A
DXX	ANT+	N/A	N/A	N/A
DXX	NFC	N/A	N/A	N/A
Highest Simultaneous Transmission SAR		Head (W/kg)	Body-worn (W/kg)	Hotspot (W/kg)
PCE + DTS		0.90	0.58	0.62
PCE + NII		1.17	0.55	0.59
PCE + DTS + DSS		N/A	0.58	N/A
PCE + NII + DSS		N/A	0.55	N/A

**Note:**

- The SAR limit (**Head & Body: SAR<sub>1g</sub> 1.6 W/kg, Extremity: SAR<sub>10g</sub> 4.0 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.



## 2. Description of Equipment Under Test

<b>EUT Type</b>	Smartphone
<b>FCC ID</b>	NM82PS6400
<b>Brand Name</b>	HTC
<b>Model Name</b>	2PS6400
<b>Tx Frequency Bands (Unit: MHz)</b>	CDMA BC0 : 824.7 ~ 848.31 CDMA BC1 : 1851.25 ~ 1908.75 CDMA BC10 : 817.9 ~ 823.1 LTE Band 2 : 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M), 1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M) LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 5 : 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~ 844 (10M) LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) LTE Band 12 : 699.7 ~ 715.3 (1.4M), 700.5 ~ 714.5 (3M), 701.5 ~ 713.5 (5M), 704 ~ 711 (10M) LTE Band 13 : 779.5 ~ 784.5 (5M), 782 (10M) LTE Band 25 : 1850.7 ~ 1914.3 (1.4M), 1851.5 ~ 1913.5 (3M), 1852.5 ~ 1912.5 (5M), 1855 ~ 1910 (10M), 1857.5 ~ 1907.5 (15M), 1860 ~ 1905 (20M) LTE Band 26 : 814.7 ~ 848.3 (1.4M), 815.5 ~ 847.5 (3M), 816.5 ~ 846.5 (5M), 819 ~ 844 (10M), 821.5 ~ 841.5 (15M) LTE Band 41 : 2498.5 ~ 2687.5 (5M), 2501 ~ 2685 (10M), 2503.5 ~ 2682.5 (15M), 2506 ~ 2680 (20M) WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480 ANT+ : 2403 ~ 2480 NFC : 13.56
<b>Uplink Modulations</b>	CDMA : QPSK LTE : QPSK, 16QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK ANT+ : GFSK NFC : ASK
<b>Maximum Tune-up Conducted Power (Unit: dBm)</b>	CDMA BC0 : 25.0 CDMA BC1 : 25.0 CDMA BC10 : 25.0 LTE Band 2 : 23.5 LTE Band 4 : 24.0 LTE Band 5 : 24.0 LTE Band 7 : 23.0 LTE Band 12 : 23.5 LTE Band 13 : 23.0 LTE Band 25 : 23.5 LTE Band 26 : 24.0 LTE Band 41 : 23.5 WLAN 2.4G : 20.0 WLAN 5.2G : 17.5 WLAN 5.3G : 17.5 WLAN 5.6G : 17.5 WLAN 5.8G : 17.5 Bluetooth : 10.5
<b>Antenna Type</b>	Fixed Internal Antenna
<b>EUT Stage</b>	Production Unit

**Note:**

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

### **3. SAR Measurement System**

#### **3.1 Definition of Specific Absorption Rate (SAR)**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

#### **3.2 SPEAG DASY System**

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4/5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

# FCC SAR Test Report



**Fig-3.1 SPEAG DASY52 System Setup**

## 3.2.1 Robot

The SPEAG DASY52 systems use the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)





**Fig-3.2 SPEAG DASY52 System**

## FCC SAR Test Report


### 3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

<b>Model</b>	EX3DV4	
<b>Construction</b>	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
<b>Frequency</b>	10 MHz to 6 GHz Linearity: $\pm 0.2$ dB	
<b>Directivity</b>	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)	
<b>Dynamic Range</b>	10 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)	
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

<b>Model</b>	ES3DV3	
<b>Construction</b>	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
<b>Frequency</b>	10 MHz to 4 GHz Linearity: $\pm 0.2$ dB	
<b>Directivity</b>	$\pm 0.2$ dB in HSL (rotation around probe axis) $\pm 0.3$ dB in tissue material (rotation normal to probe axis)	
<b>Dynamic Range</b>	5 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB	
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	


### 3.2.3 Data Acquisition Electronics (DAE)


<b>Model</b>	DAE3, DAE4	
<b>Construction</b>	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
<b>Measurement Range</b>	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
<b>Input Offset Voltage</b>	$< 5$ $\mu$ V (with auto zero)	
<b>Input Bias Current</b>	$< 50$ fA	
<b>Dimensions</b>	60 x 60 x 68 mm	



# FCC SAR Test Report


## 3.2.4 Phantoms


<b>Model</b>	Twin SAM	
<b>Construction</b>	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Shell Thickness</b>	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
<b>Dimensions</b>	Length: 1000 mm Width: 500 mm Height: adjustable feet	
<b>Filling Volume</b>	approx. 25 liters	

<b>Model</b>	ELI	
<b>Construction</b>	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Shell Thickness</b>	2.0 ± 0.2 mm (bottom plate)	
<b>Dimensions</b>	Major axis: 600 mm Minor axis: 400 mm	
<b>Filling Volume</b>	approx. 30 liters	


# FCC SAR Test Report

## 3.2.5 Device Holder

<b>Model</b>	Mounting Device	
<b>Construction</b>	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
<b>Material</b>	POM	

<b>Model</b>	Laptop Extensions Kit	
<b>Construction</b>	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
<b>Material</b>	POM, Acrylic glass, Foam	


## 3.2.6 System Validation Dipoles

<b>Model</b>	D-Serial	
<b>Construction</b>	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
<b>Frequency</b>	750 MHz to 5800 MHz	
<b>Return Loss</b>	> 20 dB	
<b>Power Capability</b>	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

# FCC SAR Test Report

## 3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.



# FCC SAR Test Report

**Table-3.1 Targets of Tissue Simulating Liquid**

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
<b>For Head</b>				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
<b>For Body</b>				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

# FCC SAR Test Report


The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid**

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

### 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



**Fig-3.3 System Verification Setup**

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ( $\Delta x, \Delta y$ )	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ( $\Delta x, \Delta y$ )	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan ( $\Delta z$ )	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

**Note:**

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

#### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

## FCC SAR Test Report

---

### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.



## 4. SAR Measurement Evaluation

### 4.1 EUT Configuration and Setting

#### <Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for GSM/WCDMA/CDMA, and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

#### <Considerations Related to CDMA for Setup and Testing>

##### **CDMA 1xRTT Handsets Head SAR**

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode. Otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

##### **CDMA 1xRTT Handsets Body-worn SAR**

Body-worn SAR is measured in RC3 with the handset configured in TDSO/SO32 to transmit at full rate on FCH only with all other code channels disabled. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH + SCH<sub>n</sub>), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH<sub>n</sub>), with FCH at full rate and SCH<sub>0</sub> enabled at 9600 bps, using the highest reported SAR configuration for FCH only. The 3G SAR test reduction procedure is applied to body-worn SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn exposure in RC3.

##### **Handsets with built-in EV-DO**

The 3G SAR test reduction procedure is applied to EV-DO Rev. 0 with 1xRTT RC3 as the primary mode to determine body-worn test requirements. Otherwise, body-worn SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn exposure in RC3. The 3G SAR test reduction procedure is applied separately to Rev. A and Rev. B, with Rev. 0 as the primary mode to determine body-worn SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1xRTT RC3 as the primary mode. Otherwise, SAR is required for Rev. A or Rev. B, with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 and 3 Physical Layer configurations, using the highest reported SAR configuration for body-worn exposure in Rev. 0 or RC3, as appropriate. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with ACK Channel transmitting in all slots is configured in the downlink for Rev. 0, Rev. A and Rev. B.

# FCC SAR Test Report

## EV-DO Data Devices

SAR is measured using the F/R TAP configurations required for Rev. 0, Rev. A and Rev. B. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations. A Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots are used for Subtype 2 and 3. FTAP, FETAP and FMCTAP are all configured with a Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with ACK Channel transmitting in all slots. AT power control is in “All Bits Up” conditions for the TAP / ETAP / MCTAP. Body-worn and other body SAR are measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode. Otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn exposure in Rev. 0. SAR is required for Rev. B, Subtype 3; it is measured by applying both the “test 2” and “test 3” configurations used for power measurement.

### <Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	V	V	V	V	V	V
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
12	V	V	V	V		
13			V	V		
25	V	V	V	V	V	V
26	V	V	V	V	V	
41			V	V	V	V

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

**Note:** MPR is according to the standard and implemented in the circuit (mandatory).


# FCC SAR Test Report

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

## TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



**3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2**

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592 · Ts	2192 · Ts	2560 · Ts	7680 · Ts	2192 · Ts	2560 · Ts
1	19760 · Ts			20480 · Ts		
2	21952 · Ts			23040 · Ts		
3	24144 · Ts			25600 · Ts		
4	26336 · Ts	4384 · Ts	5120 · Ts	7680 · Ts	4384 · Ts	5120 · Ts
5	6592 · Ts			20480 · Ts		
6	19760 · Ts			23040 · Ts		
7	21952 · Ts			12800 · Ts		
8	24144 · Ts	-	-	-	-	-
9	13168 · Ts	-	-	-	-	-

**3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe**

# FCC SAR Test Report

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

### <Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

## FCC SAR Test Report

### Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

### Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for that subsequent test configuration.

### SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

### Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

<Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

**4.2 EUT Testing Position**


According to KDB 648474 D04, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

Since this tablet has receiver and it can be used in close proximity to the ear as handset. According to technical standards, this tablet was tested for SAR compliance in head described in the following subsections.

**4.2.1 Head Exposure Conditions**

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2003 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
  - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
  - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
  - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




**Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines**

# FCC SAR Test Report

## 2. Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).



**Fig-4.2 Illustration for Cheek Position**

## 3. Tilted Position

- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).



**Fig-4.3 Illustration for Tilted Position**


#### 4.2.2 Body-worn Accessory Exposure Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 D01 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance  $\leq 5 \text{ mm}$  to support compliance.




**Fig-4.4 Illustration for Body Worn Position**



**4.2.3 Hotspot Mode Exposure Conditions**

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225 D06. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed as below.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
WWAN Ant-0	✓	✓	✓	✓		✓
WWAN Ant-1	✓	✓	✓	✓	✓	
WLAN / BT Ant-0	✓	✓		✓	✓	
WLAN Ant-1	✓	✓		✓		✓
WLAN Ant-0+1	✓	✓		✓	✓	✓

# FCC SAR Test Report

## 4.2.4 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Head (Voice / VoIP)	Body-worn (Voice / VoIP)	Hotspot (Data)
1	CDMA BC0 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
2	CDMA BC1 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
3	CDMA BC10 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
4	LTE 2 (Data) + WLAN (Data)	Yes	Yes	Yes
5	LTE 4 (Data) + WLAN (Data)	Yes	Yes	Yes
6	LTE 5 (Data) + WLAN (Data)	Yes	Yes	Yes
7	LTE 7 (Data) + WLAN (Data)	Yes	Yes	Yes
8	LTE 12 (Data) + WLAN (Data)	Yes	Yes	Yes
9	LTE 13 (Data) + WLAN (Data)	Yes	Yes	Yes
10	LTE 25 (Data) + WLAN (Data)	Yes	Yes	Yes
11	LTE 26 (Data) + WLAN (Data)	Yes	Yes	Yes
12	LTE 41 (Data) + WLAN (Data)	Yes	Yes	Yes
13	CDMA BC0 (Voice / Data) + BT (Data)	No	Yes	No
14	CDMA BC1 (Voice / Data) + BT (Data)	No	Yes	No
15	CDMA BC10 (Voice / Data) + BT (Data)	No	Yes	No
16	LTE 2 (Data) + BT (Data)	No	Yes	No
17	LTE 4 (Data) + BT (Data)	No	Yes	No
18	LTE 5 (Data) + BT (Data)	No	Yes	No
19	LTE 7 (Data) + BT (Data)	No	Yes	No
20	LTE 12 (Data) + BT (Data)	No	Yes	No
21	LTE 13 (Data) + BT (Data)	No	Yes	No
22	LTE 25 (Data) + BT (Data)	No	Yes	No
23	LTE 26 (Data) + BT (Data)	No	Yes	No
24	LTE 41 (Data) + BT (Data)	No	Yes	No
25	CDMA BC0 (Voice / Data) + WLAN (Data) + BT (Data)	No	Yes	No
26	CDMA BC1 (Voice / Data) + WLAN (Data) + BT (Data)	No	Yes	No
27	CDMA BC10 (Voice / Data) + WLAN (Data) + BT (Data)	No	Yes	No
28	LTE 2 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
29	LTE 4 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
30	LTE 5 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
31	LTE 7 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
32	LTE 12 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
33	LTE 13 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
34	LTE 25 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
35	LTE 26 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
36	LTE 41 (Data) + WLAN (Data) + BT (Data)	No	Yes	No

**Note :**

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.
2. Both CDMA and LTE can transmit through either antenna-0 or antenna-1. However, only one technology (CDMA or LTE) can transmit from an antenna at a time, and the other technology transmits through the other antenna.

# FCC SAR Test Report

## 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity ( $\sigma$ )	Measured Permittivity ( $\epsilon_r$ )	Target Conductivity ( $\sigma$ )	Target Permittivity ( $\epsilon_r$ )	Conductivity Deviation (%)	Permittivity Deviation (%)
Apr. 01, 2016	Head	750	23.6	0.891	42.846	0.89	41.9	0.11	2.26
Mar. 28, 2016	Head	835	23.2	0.907	41.436	0.90	41.5	0.78	-0.15
Apr. 01, 2016	Head	835	23.5	0.927	42.957	0.90	41.5	3.00	3.51
Apr. 01, 2016	Head	1750	23.6	1.325	38.914	1.37	40.1	-3.28	-2.96
Apr. 01, 2016	Head	1900	23.6	1.455	38.358	1.40	40.0	3.93	-4.11
Mar. 30, 2016	Head	2450	23.5	1.865	37.815	1.80	39.2	3.61	-3.53
Apr. 01, 2016	Head	2600	23.2	2.045	39.300	1.96	39.0	4.34	0.77
Apr. 06, 2016	Head	5300	23.1	4.798	36.922	4.76	35.9	0.80	2.85
Mar. 31, 2016	Head	5600	23.4	5.017	35.013	5.07	35.5	-1.05	-1.37
Apr. 01, 2016	Head	5800	23.6	5.303	34.865	5.27	35.3	0.63	-1.23
Apr. 03, 2016	Body	750	23.2	0.958	55.485	0.96	55.5	-0.21	-0.03
Mar. 29, 2016	Body	835	23.3	1.004	54.412	0.97	55.2	3.51	-1.43
Apr. 02, 2016	Body	835	23.6	0.972	54.700	0.97	55.2	0.21	-0.91
Apr. 02, 2016	Body	1750	23.6	1.430	52.022	1.49	53.4	-4.03	-2.58
Apr. 02, 2016	Body	1900	23.6	1.569	51.579	1.52	53.3	3.22	-3.23
Apr. 07, 2016	Body	2450	23.5	2.027	50.875	1.95	52.7	3.95	-3.46
Apr. 03, 2016	Body	2600	23.3	2.209	51.784	2.16	52.5	2.27	-1.36
Apr. 06, 2016	Body	5300	23.1	5.301	48.428	5.42	48.9	-2.20	-0.97
Apr. 07, 2016	Body	5600	23.5	5.629	47.819	5.77	48.5	-2.44	-1.40
Apr. 07, 2016	Body	5800	23.5	5.908	47.532	6.00	48.2	-1.53	-1.39

**Note:**

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2^\circ\text{C}$ .



# FCC SAR Test Report

## 4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity ( $\sigma$ )	Measured Permittivity ( $\epsilon_r$ )	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Apr. 01, 2016	7346	Head	750	0.891	42.846	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 28, 2016	3864	Head	835	0.907	41.436	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 01, 2016	7346	Head	835	0.927	42.957	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 01, 2016	7346	Head	1750	1.325	38.914	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 01, 2016	7346	Head	1900	1.455	38.358	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 30, 2016	3650	Head	2450	1.865	37.815	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 01, 2016	7346	Head	2600	2.045	39.300	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 06, 2016	3650	Head	5300	4.798	36.922	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 31, 2016	3650	Head	5600	5.017	35.013	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 01, 2016	7346	Head	5800	5.303	34.865	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 03, 2016	7346	Body	750	0.958	55.485	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 29, 2016	3864	Body	835	1.004	54.412	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 02, 2016	7346	Body	835	0.972	54.700	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 02, 2016	7346	Body	1750	1.430	52.022	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 02, 2016	7346	Body	1900	1.569	51.579	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 07, 2016	3650	Body	2450	2.027	50.875	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 03, 2016	7346	Body	2600	2.209	51.784	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 06, 2016	3650	Body	5300	5.301	48.428	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 07, 2016	3650	Body	5600	5.629	47.819	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 07, 2016	3650	Body	5800	5.908	47.532	Pass	Pass	Pass	OFDM	N/A	Pass

# FCC SAR Test Report

## 4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Apr. 01, 2016	Head	750	8.07	1.98	7.92	-1.86	1013	7346	916
Mar. 28, 2016	Head	835	9.11	2.15	8.60	-5.60	4d121	3864	861
Apr. 01, 2016	Head	835	9.11	2.18	8.72	-4.28	4d121	7346	916
Apr. 01, 2016	Head	1750	37.00	8.57	34.28	-7.35	1055	7346	916
Apr. 01, 2016	Head	1900	38.90	9.70	38.80	-0.26	5d036	7346	916
Mar. 30, 2016	Head	2450	53.00	13.40	53.60	1.13	737	3650	1277
Apr. 01, 2016	Head	2600	56.70	14.60	58.40	3.00	1020	7346	916
Apr. 06, 2016	Head	5300	85.00	8.16	81.60	-4.00	1019	3650	1277
Mar. 31, 2016	Head	5600	83.90	8.21	82.10	-2.15	1019	3650	1277
Apr. 01, 2016	Head	5800	81.80	8.26	82.60	0.98	1019	7346	916
Apr. 03, 2016	Body	750	8.44	2.08	8.32	-1.42	1013	7346	916
Mar. 29, 2016	Body	835	9.20	2.33	9.32	1.30	4d121	3864	861
Apr. 02, 2016	Body	835	9.20	2.35	9.40	2.17	4d121	7346	916
Apr. 02, 2016	Body	1750	37.60	9.55	38.20	1.60	1055	7346	916
Apr. 02, 2016	Body	1900	40.70	10.00	40.00	-1.72	5d036	7346	916
Apr. 07, 2016	Body	2450	51.10	11.90	47.60	-6.85	737	3650	1277
Apr. 03, 2016	Body	2600	55.40	13.40	53.60	-3.25	1020	7346	916
Apr. 06, 2016	Body	5300	76.60	7.66	76.60	0.00	1019	3650	1277
Apr. 07, 2016	Body	5600	79.80	8.48	84.80	6.27	1019	3650	1277
Apr. 07, 2016	Body	5800	77.30	7.67	76.70	-0.78	1019	3650	1277

**Note:**

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.



# FCC SAR Test Report

## 4.6 Maximum Output Power

### 4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	CDMA BC0	CDMA BC1	CDMA BC10
1xRTT	25.0	25.0	25.0
1xEVDO Rev.0	25.0	25.0	25.0
1xEVDO Rev.A	25.0	25.0	25.0

Mode	LTE 2	LTE 4	LTE 5	LTE 7
QPSK / 16QAM	23.5	24.0	24.0	23.0

Mode	LTE 12	LTE 13	LTE 25	LTE 26	LTE 41
QPSK / 16QAM	23.5	23.0	23.5	24.0	23.5

Mode	Tx Antenna	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11b	Ant-0	20.0	N/A	N/A	N/A	N/A
	Ant-1					
802.11g	Ant-0	18.0	N/A	N/A	N/A	N/A
	Ant-1					
802.11a	Ant-0	N/A	17.5	17.5	17.5	17.5
	Ant-1					
802.11n HT20	Ant-0	18.0	17.5	17.5	17.5	17.5
	Ant-1					
	Ant-0+Ant-1					
802.11n HT40	Ant-0	18.0	17.5	17.5	17.5	17.5
	Ant-1					
	Ant-0+Ant-1					
802.11ac VHT80	Ant-0	N/A	17.5	17.5	17.5	17.5
	Ant-1					
	Ant-0+Ant-1					

Mode	2.4G Bluetooth
Bluetooth DH	Ch 0: 10.5 Ch 39: 10.5 Ch 78: 10.1

# FCC SAR Test Report

## 4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	CDMA BC0			CDMA BC1		
Channel	1013	384	777	25	600	1175
Frequency (MHz)	824.70	836.52	848.31	1851.25	1880.00	1908.75
1xRTT RC1+SO55	24.33	24.27	23.92	24.09	24.06	24.01
1xRTT RC3+SO55	<b>24.37</b>	24.31	23.96	<b>24.12</b>	24.10	24.06
1xRTT RC3+SO32 (FCH)	24.30	24.26	23.90	24.06	24.03	23.96
1xRTT RC3+SO32 (SCH)	24.26	24.18	23.83	24.00	23.98	23.95
1xEVDO Rev.0 RTAP 153.6	24.36	24.30	24.01	24.08	24.05	23.98
1xEVDO Rev.A RETAP 4096	24.23	24.15	23.85	23.99	23.91	23.86

Band	CDMA BC10		
Channel	476	580	684
Frequency (MHz)	817.9	820.5	823.1
1xRTT RC1+SO55	24.32	24.49	24.48
1xRTT RC3+SO55	24.33	<b>24.50</b>	24.49
1xRTT RC3+SO32 (FCH)	24.31	24.48	24.42
1xRTT RC3+SO32 (SCH)	24.22	24.35	24.31
1xEVDO Rev.0 RTAP 153.6	24.31	24.48	24.47
1xEVDO Rev.A RETAP 4096	24.21	24.31	24.23

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	22.89	<b>23.24</b>	22.89	0	21.88	<b>22.28</b>	21.88	1
	1	2	22.41	22.81	22.41	0	21.42	21.79	21.42	1
	1	5	22.22	22.67	22.22	0	21.26	21.67	21.26	1
	3	0	22.17	22.20	21.98	0	21.48	21.80	21.44	1
	3	1	22.10	22.18	21.87	0	21.33	21.70	21.35	1
	3	3	22.03	22.13	21.73	0	21.15	21.66	21.18	1
	6	0	21.34	21.80	21.42	1	20.34	20.80	20.34	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	22.95	<b>23.29</b>	22.95	0	21.95	<b>22.33</b>	21.95	1
	1	7	22.49	22.87	22.49	0	21.52	21.87	21.52	1
	1	14	22.32	22.76	22.32	0	21.37	21.76	21.37	1
	8	0	21.58	22.01	21.58	1	20.55	21.03	20.55	2
	8	3	21.27	21.77	21.27	1	20.23	20.75	20.23	2
	8	7	21.34	21.84	21.34	1	20.33	20.84	20.33	2
	15	0	21.43	21.93	21.54	1	20.48	20.95	20.48	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
2 / 5M	1	0	23.00	<b>23.34</b>	23.00	0	22.04	<b>22.39</b>	22.04	1
	1	12	22.59	22.96	22.59	0	21.59	21.97	21.59	1
	1	24	22.45	22.83	22.45	0	21.43	21.82	21.43	1
	12	0	21.67	22.14	21.67	1	20.68	21.07	20.68	2
	12	6	21.43	21.91	21.43	1	20.37	20.86	20.37	2
	12	13	21.48	21.96	21.48	1	20.45	20.90	20.45	2
	25	0	21.70	22.06	21.73	1	20.57	20.98	20.63	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150	
			1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz	
2 / 10M	1	0	23.04	<b>23.39</b>	23.04	0	22.09	<b>22.43</b>	22.09	1
	1	24	22.65	23.01	22.65	0	21.62	22.02	21.62	1
	1	49	22.53	22.90	22.53	0	21.49	21.87	21.49	1
	25	0	21.83	22.21	21.83	1	20.76	21.15	20.76	2
	25	12	21.58	22.01	21.58	1	20.52	20.93	20.52	2
	25	25	21.64	22.04	21.64	1	20.57	20.98	20.57	2
	50	0	21.79	22.14	21.72	1	20.64	21.08	20.70	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18675	Mid CH 18900	High CH 19125		Low CH 18675	Mid CH 18900	High CH 19125	
			1857.5 MHz	1880.0 MHz	1902.5 MHz		1857.5 MHz	1880.0 MHz	1902.5 MHz	
2 / 15M	1	0	23.10	<b>23.44</b>	23.10	0	22.15	<b>22.49</b>	22.15	1
	1	37	22.69	23.04	22.69	0	21.75	22.09	21.75	1
	1	74	22.58	22.93	22.58	0	21.61	21.98	21.61	1
	36	0	21.90	22.27	21.90	1	20.91	21.29	20.91	2
	36	19	21.71	22.08	21.71	1	20.68	21.10	20.68	2
	36	39	21.75	22.11	21.75	1	20.72	21.13	20.72	2
	75	0	21.86	22.20	21.90	1	20.81	21.21	20.95	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18700	Mid CH 18900	High CH 19100		Low CH 18700	Mid CH 18900	High CH 19100	
			1860.0 MHz	1880.0 MHz	1900.0 MHz		1860.0 MHz	1880.0 MHz	1900.0 MHz	
2 / 20M	1	0	23.15	<b>23.49</b>	23.15	0	22.20	<b>22.50</b>	22.20	1
	1	50	23.00	23.12	22.36	0	21.80	22.15	21.80	1
	1	99	22.82	23.01	22.11	0	21.68	22.04	21.68	1
	50	0	22.20	22.37	21.64	1	21.01	21.38	21.01	2
	50	25	21.95	22.20	21.39	1	20.81	21.18	20.81	2
	50	50	22.05	22.23	21.44	1	20.86	21.22	20.86	2
	100	0	22.17	22.31	21.49	1	21.01	21.31	20.92	2



# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 20393		Low CH 19957	Mid CH 20175	High CH 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	23.63	<b>23.70</b>	23.29	0	22.66	<b>22.75</b>	22.36	1
	1	2	23.21	23.37	22.86	0	22.27	22.41	22.05	1
	1	5	22.81	22.92	22.39	0	21.86	21.94	21.50	1
	3	0	22.32	22.54	22.93	0	21.46	21.56	21.12	1
	3	1	22.19	22.10	22.68	0	21.96	21.10	21.63	1
	3	3	22.13	22.02	22.57	0	21.86	21.01	21.53	1
	6	0	22.21	22.43	21.89	1	21.25	21.41	20.79	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	23.68	<b>23.74</b>	23.38	0	22.73	<b>22.80</b>	22.41	1
	1	7	23.38	23.45	22.99	0	22.33	22.48	22.16	1
	1	14	22.92	23.03	22.53	0	21.89	22.02	21.70	1
	8	0	22.49	22.66	22.25	1	21.40	21.57	20.99	2
	8	3	22.21	22.29	21.78	1	21.06	21.18	20.73	2
	8	7	22.03	22.21	21.75	1	20.95	21.08	20.67	2
	15	0	22.46	22.58	22.10	1	21.44	21.49	21.12	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	23.72	<b>23.79</b>	23.43	0	22.76	<b>22.84</b>	22.45	1
	1	12	23.33	23.48	23.17	0	22.34	22.50	22.19	1
	1	24	23.00	23.07	22.74	0	21.92	22.05	21.57	1
	12	0	22.61	22.68	22.22	1	21.54	21.70	21.26	2
	12	6	22.22	22.33	21.99	1	21.24	21.31	20.97	2
	12	13	22.09	22.26	21.87	1	21.10	21.26	20.85	2
	25	0	22.43	22.61	22.17	1	21.48	21.63	21.18	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	23.78	<b>23.84</b>	23.48	0	22.84	<b>22.90</b>	22.54	1
	1	24	23.48	23.54	23.23	0	22.51	22.59	22.31	1
	1	49	23.03	23.15	22.82	0	22.00	22.20	21.87	1
	25	0	22.67	22.77	22.51	1	21.68	21.81	21.35	2
	25	12	22.35	22.43	22.11	1	21.38	21.46	21.02	2
	25	25	22.24	22.38	22.01	1	21.28	21.40	20.97	2
	50	0	22.53	22.70	22.24	1	21.56	21.73	21.35	2

# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	23.84	<b>23.90</b>	23.56	0	22.88	<b>22.95</b>	22.59	1
	1	37	23.47	23.61	23.28	0	22.55	22.64	22.22	1
	1	74	23.07	23.23	22.94	0	22.14	22.25	21.91	1
	36	0	22.83	22.88	22.52	1	21.77	21.89	21.55	2
	36	19	22.49	22.56	22.27	1	21.48	21.57	21.18	2
	36	39	22.45	22.52	22.16	1	21.41	21.50	21.12	2
	75	0	22.71	22.81	22.47	1	21.73	21.82	21.39	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	23.89	<b>23.95</b>	23.62	0	22.92	<b>22.98</b>	22.64	1
	1	50	23.51	23.66	23.42	0	22.54	22.69	22.29	1
	1	99	23.15	23.30	23.05	0	22.26	22.32	22.04	1
	50	0	22.91	22.98	22.59	1	21.93	21.98	21.60	2
	50	25	22.63	22.68	22.34	1	21.62	21.66	21.40	2
	50	50	22.57	22.64	22.31	1	21.54	21.62	21.26	2
	100	0	22.86	22.91	22.57	1	21.84	21.90	21.53	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	23.40	23.31	23.27	0	22.44	22.34	22.26	1
	1	2	23.19	23.07	23.02	0	22.11	22.05	21.99	1
	1	5	<b>23.52</b>	23.46	23.37	0	<b>22.59</b>	22.51	22.47	1
	3	0	22.64	22.40	22.37	0	21.52	21.39	21.27	1
	3	1	22.44	22.27	22.24	0	21.37	21.23	21.18	1
	3	3	22.60	22.51	22.46	0	21.58	21.45	21.37	1
	6	0	21.54	21.37	21.31	1	20.52	20.32	20.29	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	23.46	23.37	23.33	0	22.51	22.44	22.39	1
	1	7	23.18	23.13	23.10	0	22.32	22.16	22.11	1
	1	14	<b>23.60</b>	23.52	23.46	0	<b>22.62</b>	22.57	22.43	1
	8	0	22.63	22.55	22.45	1	21.71	21.50	21.45	2
	8	3	22.53	22.40	22.37	1	21.48	21.39	21.34	2
	8	7	22.70	22.61	22.58	1	21.67	21.58	21.51	2
	15	0	22.64	22.49	22.45	1	21.56	21.45	21.41	2

# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	23.52	23.45	23.41	0	22.52	22.43	22.40	1
	1	12	23.35	23.22	23.19	0	22.34	22.21	22.18	1
	1	24	<b>23.65</b>	23.58	23.47	0	<b>22.67</b>	22.58	22.45	1
	12	0	22.83	22.64	22.58	1	21.72	21.62	21.53	2
	12	6	22.63	22.55	22.52	1	21.63	21.51	21.48	2
	12	13	22.79	22.72	22.68	1	21.76	21.67	21.65	2
	25	0	22.71	22.61	22.58	1	21.69	21.60	21.55	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	23.58	23.51	23.48	0	22.62	22.54	22.51	1
	1	24	23.35	23.30	23.28	0	22.44	22.31	22.29	1
	1	49	<b>23.70</b>	23.63	23.60	0	<b>22.75</b>	22.68	22.65	1
	25	0	22.87	22.77	22.73	1	21.83	21.77	21.70	2
	25	12	22.79	22.70	22.68	1	21.75	21.66	21.64	2
	25	25	22.88	22.81	22.79	1	21.88	21.82	21.76	2
	50	0	22.80	22.75	22.72	1	21.82	21.74	21.72	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20775	Mid CH 21100	High CH 21425		Low CH 20775	Mid CH 21100	High CH 21425	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
7 / 5M	1	0	22.72	22.81	<b>22.84</b>	0	21.73	21.84	<b>21.89</b>	1
	1	12	22.33	22.52	22.59	0	21.40	21.51	21.60	1
	1	24	21.95	22.02	22.14	0	20.89	21.01	21.07	1
	12	0	21.43	21.57	21.64	1	20.39	20.52	20.61	2
	12	6	21.18	21.27	21.39	1	20.09	20.21	20.27	2
	12	13	20.97	21.11	21.22	1	19.91	20.03	20.12	2
	25	0	20.94	21.04	21.09	1	19.89	19.97	20.07	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20800	Mid CH 21100	High CH 21400		Low CH 20800	Mid CH 21100	High CH 21400	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
7 / 10M	1	0	22.74	22.84	<b>22.89</b>	0	21.78	21.89	<b>21.93</b>	1
	1	24	22.35	22.54	22.65	0	21.49	21.60	21.71	1
	1	49	21.97	22.10	22.19	0	20.98	21.13	21.17	1
	25	0	21.58	21.68	21.74	1	20.49	20.69	20.73	2
	25	12	21.31	21.37	21.49	1	20.19	20.35	20.43	2
	25	25	21.10	21.25	21.28	1	20.06	20.22	20.24	2
	50	0	21.08	21.20	21.24	1	20.03	20.15	20.21	2

# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20825	Mid CH 21100	High CH 21375		Low CH 20825	Mid CH 21100	High CH 21375	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
7 / 15M	1	0	22.82	22.91	<b>22.94</b>	0	21.85	21.96	<b>21.99</b>	1
	1	37	22.52	22.62	22.65	0	21.53	21.66	21.72	1
	1	74	22.02	22.20	22.22	0	21.06	21.21	21.32	1
	36	0	21.58	21.77	21.84	1	20.67	20.74	20.84	2
	36	19	21.33	21.49	21.62	1	20.32	20.45	20.58	2
	36	39	21.27	21.37	21.41	1	20.23	20.32	20.39	2
	75	0	21.23	21.33	21.36	1	20.18	20.28	20.31	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20850	Mid CH 21100	High CH 21350		Low CH 20850	Mid CH 21100	High CH 21350	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
7 / 20M	1	0	22.87	22.96	<b>22.99</b>	0	21.90	21.96	<b>22.00</b>	1
	1	50	22.52	22.69	22.77	0	21.59	21.72	21.76	1
	1	99	22.21	22.28	22.36	0	21.19	21.30	21.39	1
	50	0	21.80	21.87	21.98	1	20.69	20.86	20.91	2
	50	25	21.50	21.61	21.73	1	20.54	20.59	20.62	2
	50	50	21.43	21.50	21.52	1	20.38	20.48	20.53	2
	100	0	21.39	21.47	21.50	1	20.33	20.43	20.47	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23017	Mid CH 23095	High CH 23173		Low CH 23017	Mid CH 23095	High CH 23173	
			699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz	
12 / 1.4M	1	0	22.38	22.42	22.50	0	21.43	21.45	21.57	1
	1	2	22.57	22.60	22.74	0	21.55	21.66	21.74	1
	1	5	22.64	22.70	<b>22.79</b>	0	21.71	21.78	<b>21.87</b>	1
	3	0	21.72	21.75	21.88	0	20.67	20.74	20.90	1
	3	1	21.75	21.76	21.94	0	20.74	20.77	20.99	1
	3	3	21.78	21.82	21.97	0	20.79	20.83	21.01	1
	6	0	21.69	21.72	21.85	1	20.64	20.67	20.92	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23025	Mid CH 23095	High CH 23165		Low CH 23025	Mid CH 23095	High CH 23165	
			700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz	
12 / 3M	1	0	22.49	22.52	22.61	0	21.51	21.54	21.62	1
	1	7	22.62	22.69	22.81	0	21.68	21.72	21.87	1
	1	14	22.76	22.77	<b>22.85</b>	0	21.76	21.82	<b>21.92</b>	1
	8	0	21.86	21.91	22.04	1	20.84	20.91	21.05	2
	8	3	21.91	21.92	22.08	1	20.91	20.92	21.09	2
	8	7	21.95	21.98	22.10	1	20.94	20.96	21.11	2
	15	0	21.84	21.86	22.02	1	20.80	20.84	21.00	2

# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23035	Mid CH 23095	High CH 23155		Low CH 23035	Mid CH 23095	High CH 23155	
			701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz	
12 / 5M	1	0	22.58	22.59	22.67	0	21.59	21.61	21.70	1
	1	12	22.72	22.75	22.81	0	21.76	21.79	21.89	1
	1	24	22.83	22.84	<b>22.91</b>	0	21.85	21.88	<b>21.96</b>	1
	12	0	22.01	22.02	22.13	1	20.99	21.01	21.13	2
	12	6	22.02	22.05	22.15	1	21.01	21.03	21.17	2
	12	13	22.07	22.09	22.17	1	21.06	21.07	21.20	2
	25	0	21.99	22.01	22.15	1	20.95	20.99	21.10	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23060	Mid CH 23095	High CH 23130		Low CH 23060	Mid CH 23095	High CH 23130	
			704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz	
12 / 10M	1	0	22.66	22.67	22.75	0	21.65	21.66	21.74	1
	1	24	22.76	22.82	22.89	0	21.79	21.84	21.91	1
	1	49	22.88	22.89	<b>22.94</b>	0	21.88	21.94	<b>22.02</b>	1
	25	0	22.15	22.16	22.23	1	21.10	21.12	21.22	2
	25	12	22.16	22.17	22.25	1	21.12	21.14	21.24	2
	25	25	22.18	22.19	22.27	1	21.16	21.17	21.26	2
	50	0	22.14	22.15	22.22	1	21.09	21.10	21.22	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23205	Mid CH 23230	High CH 23255		Low CH 23205	Mid CH 23230	High CH 23255	
			779.5 MHz	782.0 MHz	784.5 MHz		779.5 MHz	782.0 MHz	784.5 MHz	
13 / 5M	1	0	22.18	22.52	22.49	0	21.15	21.53	21.50	1
	1	12	<b>22.54</b>	22.53	22.51	0	<b>21.57</b>	21.55	21.52	1
	1	24	22.32	22.50	22.42	0	21.31	21.51	21.44	1
	12	0	21.58	21.59	21.56	1	20.53	20.57	20.54	2
	12	6	21.67	21.60	21.58	1	20.62	20.59	20.56	2
	12	13	21.55	21.57	21.55	1	20.50	20.55	20.49	2
	25	0	21.60	21.54	21.52	1	20.55	20.51	20.47	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Mid CH 23230				Mid CH 23230			
			782.0 MHz				782.0 MHz			
13 / 10M	1	0	22.98			0	21.98			1
	1	24	<b>22.99</b>			0	<b>21.99</b>			1
	1	49	22.92			0	21.92			1
	25	0	21.99			1	20.98			2
	25	12	21.96			1	20.96			2
	25	25	21.94			1	20.90			2
	50	0	21.99			1	20.92			2

# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26047	Mid CH 26365	High CH 26683		Low CH 26047	Mid CH 26365	High CH 26683	
			1850.7 MHz	1882.5 MHz	1914.3 MHz		1850.7 MHz	1882.5 MHz	1914.3 MHz	
25 / 1.4M	1	0	23.10	<b>23.25</b>	22.76	0	22.13	<b>22.29</b>	21.79	1
	1	2	23.01	23.16	22.59	0	22.05	22.19	21.69	1
	1	5	22.01	22.19	21.62	0	21.03	21.23	20.61	1
	3	0	21.96	22.17	21.55	0	20.97	21.18	21.20	1
	3	1	21.92	22.12	21.67	0	20.90	21.13	21.47	1
	3	3	21.69	21.96	21.58	0	20.75	20.97	21.32	1
	6	0	20.59	20.75	20.67	1	19.53	19.69	19.55	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26055	Mid CH 26365	High CH 26675		Low CH 26055	Mid CH 26365	High CH 26675	
			1851.5 MHz	1882.5 MHz	1913.5 MHz		1851.5 MHz	1882.5 MHz	1913.5 MHz	
25 / 3M	1	0	23.17	<b>23.30</b>	22.83	0	22.19	<b>22.34</b>	21.86	1
	1	7	23.00	23.22	22.76	0	22.03	22.23	21.75	1
	1	14	22.15	22.26	21.70	0	21.14	21.30	20.75	1
	8	0	22.07	22.23	21.65	1	21.05	21.26	20.63	2
	8	3	22.02	22.22	21.60	1	20.96	21.21	20.57	2
	8	7	21.93	22.07	21.49	1	20.92	21.05	20.47	2
	15	0	21.74	21.84	21.42	1	20.70	20.81	20.38	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26065	Mid CH 26365	High CH 26665		Low CH 26065	Mid CH 26365	High CH 26665	
			1852.5 MHz	1882.5 MHz	1912.5 MHz		1852.5 MHz	1882.5 MHz	1912.5 MHz	
25 / 5M	1	0	23.14	<b>23.28</b>	22.81	0	22.20	<b>22.35</b>	21.88	1
	1	12	23.07	23.20	22.66	0	22.14	22.27	21.71	1
	1	24	22.14	22.27	21.73	0	21.14	21.27	20.66	1
	12	0	22.06	22.21	21.68	1	21.04	21.22	20.63	2
	12	6	21.97	22.19	21.61	1	21.00	21.17	20.58	2
	12	13	21.90	22.06	21.58	1	20.88	21.04	20.45	2
	25	0	21.56	21.84	21.34	1	20.52	20.80	20.34	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26090	Mid CH 26365	High CH 26640		Low CH 26090	Mid CH 26365	High CH 26640	
			1855.0 MHz	1882.5 MHz	1910.0 MHz		1855.0 MHz	1882.5 MHz	1910.0 MHz	
25 / 10M	1	0	23.21	<b>23.35</b>	22.90	0	22.28	<b>22.40</b>	21.95	1
	1	24	23.13	23.26	22.77	0	22.14	22.32	21.81	1
	1	49	22.20	22.34	21.91	0	21.18	21.36	20.85	1
	25	0	22.16	22.30	21.80	1	21.13	21.33	20.78	2
	25	12	22.14	22.29	21.76	1	21.08	21.29	20.74	2
	25	25	21.93	22.16	21.69	1	20.95	21.13	20.55	2
	50	0	21.85	21.99	21.54	1	20.70	20.94	20.45	2

# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26115	Mid CH 26365	High CH 26615		Low CH 26115	Mid CH 26365	High CH 26615	
			1857.5 MHz	1882.5 MHz	1907.5 MHz		1857.5 MHz	1882.5 MHz	1907.5 MHz	
25 / 15M	1	0	23.27	<b>23.39</b>	22.95	0	22.31	<b>22.45</b>	22.01	1
	1	37	23.17	23.31	22.82	0	22.20	22.36	21.85	1
	1	74	22.30	22.40	21.97	0	21.33	21.45	21.01	1
	36	0	22.25	22.38	21.93	1	21.28	21.43	20.90	2
	36	19	22.23	22.37	21.91	1	21.22	21.41	20.81	2
	36	39	22.03	22.25	21.77	1	21.11	21.28	20.76	2
	75	0	21.92	22.07	21.66	1	20.83	21.07	20.65	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26140	Mid CH 26365	High CH 26590		Low CH 26140	Mid CH 26365	High CH 26590	
			1860.0 MHz	1882.5 MHz	1905.0 MHz		1860.0 MHz	1882.5 MHz	1905.0 MHz	
25 / 20M	1	0	23.33	<b>23.45</b>	23.03	0	22.38	<b>22.50</b>	22.08	1
	1	50	23.16	23.37	22.87	0	22.33	22.42	21.91	1
	1	99	22.39	22.50	22.17	0	21.46	21.53	21.16	1
	50	0	22.36	22.48	22.06	1	21.36	21.48	21.05	2
	50	25	22.35	22.47	22.05	1	21.33	21.49	21.02	2
	50	50	22.26	22.36	21.93	1	21.24	21.36	20.87	2
	100	0	22.10	22.20	21.79	1	20.98	21.19	20.78	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26697	Mid CH 26865	High CH 27033		Low CH 26697	Mid CH 26865	High CH 27033	
			814.7 MHz	831.5 MHz	848.3 MHz		814.7 MHz	831.5 MHz	848.3 MHz	
26 / 1.4M	1	0	23.11	23.06	23.22	0	22.18	22.10	22.28	1
	1	2	22.76	22.72	22.85	0	21.81	21.76	21.91	1
	1	5	23.55	23.48	<b>23.66</b>	0	22.65	22.57	<b>22.69</b>	1
	3	0	22.12	22.09	22.39	0	21.02	21.45	21.38	1
	3	1	22.10	22.08	22.17	0	21.55	21.35	21.10	1
	3	3	22.24	22.21	22.39	0	21.23	21.18	21.43	1
	6	0	22.17	22.06	22.30	1	21.18	21.05	21.32	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26705	Mid CH 26865	High CH 27025		Low CH 26705	Mid CH 26865	High CH 27025	
			815.5 MHz	831.5 MHz	847.5 MHz		815.5 MHz	831.5 MHz	847.5 MHz	
26 / 3M	1	0	23.22	23.16	23.32	0	22.21	22.17	22.32	1
	1	7	22.94	22.87	22.96	0	21.92	21.83	22.07	1
	1	14	23.62	23.58	<b>23.68</b>	0	22.64	22.61	<b>22.77</b>	1
	8	0	22.26	22.14	22.49	1	21.23	21.12	21.48	2
	8	3	22.12	22.09	22.22	1	21.12	21.05	21.18	2
	8	7	22.41	22.37	22.51	1	21.31	21.28	21.46	2
	15	0	22.31	22.21	22.46	1	21.28	21.19	21.41	2



FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26715	Mid CH 26865	High CH 27015		Low CH 26715	Mid CH 26865	High CH 27015	
			816.5 MHz	831.5 MHz	846.5 MHz		816.5 MHz	831.5 MHz	846.5 MHz	
26 / 5M	1	0	23.27	23.22	23.36	0	22.28	22.25	22.38	1
	1	12	22.99	22.93	23.04	0	22.00	21.94	22.09	1
	1	24	23.67	23.63	<b>23.77</b>	0	22.74	22.68	<b>22.82</b>	1
	12	0	22.42	22.31	22.53	1	21.37	21.28	21.52	2
	12	6	22.31	22.24	22.42	1	21.23	21.19	21.37	2
	12	13	22.49	22.44	22.61	1	21.50	21.45	21.60	2
	25	0	22.44	22.36	22.55	1	21.40	21.37	21.54	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26740	Mid CH 26865	High CH 26990		Low CH 26740	Mid CH 26865	High CH 26990	
			819.0 MHz	831.5 MHz	844.0 MHz		819.0 MHz	831.5 MHz	844.0 MHz	
26 / 10M	1	0	23.34	23.31	23.44	0	22.37	22.32	22.46	1
	1	24	23.07	23.02	23.21	0	22.06	22.04	22.14	1
	1	49	23.74	23.70	<b>23.82</b>	0	22.81	22.72	<b>22.84</b>	1
	25	0	22.53	22.44	22.70	1	21.42	21.39	21.57	2
	25	12	22.44	22.39	22.58	1	21.36	21.34	21.55	2
	25	25	22.62	22.56	22.68	1	21.64	21.52	21.69	2
	50	0	22.55	22.50	22.61	1	21.52	21.46	21.62	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26765	Mid CH 26865	High CH 26965		Low CH 26765	Mid CH 26865	High CH 26965	
			821.5 MHz	831.5 MHz	841.5 MHz		821.5 MHz	831.5 MHz	841.5 MHz	
26 / 15M	1	0	23.40	23.37	23.49	0	22.42	22.39	22.52	1
	1	37	23.16	23.10	23.25	0	22.16	22.12	22.26	1
	1	74	23.79	23.75	<b>23.86</b>	0	22.85	22.79	<b>22.92</b>	1
	36	0	22.60	22.58	22.70	1	21.59	21.56	21.68	2
	36	19	22.58	22.54	22.67	1	21.52	21.49	21.63	2
	36	39	22.69	22.66	22.77	1	21.71	21.65	21.79	2
	75	0	22.65	22.62	22.72	1	21.63	21.61	21.74	2

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39675	M-CH 40148	M-CH 40620	M-CH 41093	H-CH 41565		L-CH 39675	M-CH 40148	M-CH 40620	M-CH 41093	H-CH 41565	
			2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz		2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz	
41 / 5M	1	0	23.00	22.91	23.05	22.85	<b>23.13</b>	0	22.02	21.92	22.09	21.88	<b>22.18</b>	1
	1	12	22.07	22.01	22.15	21.96	22.26	0	21.07	21.00	21.17	20.96	21.29	1
	1	24	22.57	22.35	22.63	22.40	22.70	0	21.55	21.43	21.62	21.39	21.72	1
	12	0	21.70	21.62	21.78	21.57	21.85	1	20.72	20.61	20.80	20.40	20.90	2
	12	6	21.45	21.31	21.53	21.28	21.76	1	20.44	20.32	20.53	20.25	20.73	2
	12	13	21.38	21.29	21.48	21.24	21.61	1	20.38	20.25	20.46	20.19	20.59	2
	25	0	21.53	21.39	21.58	21.33	21.67	1	20.44	20.29	20.59	20.28	20.67	2



# FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39700	M-CH 40160	M-CH 40620	M-CH 41080	H-CH 41540		L-CH 39700	M-CH 40160	M-CH 40620	M-CH 41080	H-CH 41540	
			2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz		2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz	
41 / 10M	1	0	23.04	22.94	23.09	22.90	<b>23.18</b>	0	22.09	21.99	22.14	21.95	<b>22.23</b>	1
	1	24	22.17	22.09	22.24	22.05	22.36	0	21.21	21.12	21.25	21.05	21.36	1
	1	49	22.64	22.52	22.67	22.45	22.71	0	21.67	21.56	21.72	21.51	21.78	1
	25	0	21.81	21.74	21.90	21.62	22.00	1	20.86	20.67	20.89	20.66	21.07	2
	25	12	21.59	21.47	21.65	21.41	21.84	1	20.59	20.42	20.65	20.37	20.81	2
	25	25	21.55	21.42	21.62	21.40	21.71	1	20.51	20.38	20.60	20.35	20.71	2
	50	0	21.62	21.52	21.68	21.45	21.78	1	20.59	20.45	20.70	20.40	20.79	2

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515		L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515	
			2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz		2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz	
41 / 15M	1	0	23.09	23.00	23.14	22.97	<b>23.23</b>	0	22.13	22.02	22.19	21.99	<b>22.28</b>	1
	1	37	22.30	22.20	22.33	22.14	22.40	0	21.25	21.17	21.31	21.12	21.42	1
	1	74	22.67	22.55	22.74	22.49	22.79	0	21.66	21.61	21.74	21.54	21.81	1
	36	0	21.94	21.80	21.98	21.73	22.05	1	20.90	20.83	20.96	20.67	21.08	2
	36	19	21.71	21.62	21.76	21.56	21.92	1	20.71	20.56	20.75	20.53	20.91	2
	36	39	21.66	21.59	21.73	21.55	21.83	1	20.65	20.52	20.71	20.49	20.80	2
	75	0	21.73	21.69	21.81	21.62	21.88	1	20.69	20.64	20.78	20.58	20.87	2

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490		L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490	
			2506.0 MHz	2549.5 MHz	2593.0 MHz	2636.5 MHz	2680.0 MHz		2506.0 MHz	2549.5 MHz	2593.0 MHz	2636.5 MHz	2680.0 MHz	
41 / 20M	1	0	23.15	23.06	23.20	23.03	<b>23.28</b>	0	22.20	22.11	22.25	22.07	<b>22.33</b>	1
	1	50	22.33	22.29	22.40	22.23	22.46	0	21.34	21.30	21.41	21.24	21.48	1
	1	99	22.78	22.58	22.81	22.61	22.86	0	21.77	21.70	21.85	21.63	21.92	1
	50	0	22.00	21.93	22.08	21.87	22.14	1	21.02	20.94	21.07	20.90	21.16	2
	50	25	21.85	21.75	21.89	21.71	21.97	1	20.80	20.74	20.87	20.68	21.00	2
	50	50	21.82	21.72	21.86	21.69	21.94	1	20.75	20.67	20.82	20.64	20.92	2
	100	0	21.87	21.78	21.92	21.74	21.99	1	20.86	20.75	20.90	20.71	20.99	2

**FCC SAR Test Report**
**<WLAN 2.4G>**

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power (Ant-0)	18.12	18.22	18.05
Average Power (Ant-1)	18.09	18.01	18.04
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	3 (2422)	6 (2437)	9 (2452)
Average Power (Ant-0 + Ant-1)	16.14	16.11	16.11

**<WLAN 5.3G>**

Mode	802.11ac (VHT80)
Channel / Frequency (MHz)	58 (5290)
Average Power (Ant-0)	16.03
Average Power (Ant-1)	15.87
Average Power (Ant-0 + Ant-1)	16.05

**<WLAN 5.6G>**

Mode	802.11ac (VHT80)	
Channel / Frequency (MHz)	106 (5530)	122 (5610)
Average Power (Ant-0)	15.84	15.79
Average Power (Ant-1)	15.74	15.69
Average Power (Ant-0 + Ant-1)	15.89	15.81

**<WLAN 5.8G>**

Mode	802.11ac (VHT80)
Channel / Frequency (MHz)	155 (5775)
Average Power (Ant-0)	15.87
Average Power (Ant-1)	15.64
Average Power (Ant-0 + Ant-1)	15.90

**<Bluetooth>**

Mode	Bluetooth		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	9.17	10.09	9.03

## **4.7 SAR Testing Results**

### **4.7.1 SAR Test Reduction Considerations**

#### **<KDB 447498 D01, General RF Exposure Guidance>**

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1)  $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
- (2)  $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3)  $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz

#### **<KDB 941225 D01, 3G SAR Measurement Procedures>**

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/4$  dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the secondary mode.

#### **<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>**

##### (1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is  $> 1.45$  W/kg, SAR is required for all three RB offset configurations for that required test channel.

##### (2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

##### (3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is  $> 1/2$  dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45$  W/kg.

##### (4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is  $> 1/2$  dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is  $> 1.45$  W/kg.

## FCC SAR Test Report

---

### <KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is  $\leq 0.4$  W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is  $\leq 0.8$  W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is  $\leq 1.2$  W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is  $> 0.8$  W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is  $\leq 1.2$  W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is  $\leq 1.2$  W/kg.
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.



# FCC SAR Test Report

A D T

## 4.7.2 SAR Results for Head Exposure Condition

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)	
01	CDMA BC0	RC3+SO55	Right Cheek	1013	0	25.0	24.37	1.16	0.04	0.161	<b>0.19</b>	
	CDMA BC0	RC3+SO55	Right Cheek	1013	1	25.0	24.37	1.16	0.07	0.117	0.14	
	CDMA BC0	RC3+SO55	Right Tilted	1013	0	25.0	24.37	1.16	0.01	0.112	0.13	
	CDMA BC0	RC3+SO55	Right Tilted	1013	1	25.0	24.37	1.16	0.12	0.057	0.07	
	CDMA BC0	RC3+SO55	Left Cheek	1013	0	25.0	24.37	1.16	0	0.103	0.12	
	CDMA BC0	RC3+SO55	Left Cheek	1013	1	25.0	24.37	1.16	0.05	0.063	0.07	
	CDMA BC0	RC3+SO55	Left Tilted	1013	0	25.0	24.37	1.16	-0.11	0.073	0.08	
	CDMA BC0	RC3+SO55	Left Tilted	1013	1	25.0	24.37	1.16	-0.09	0.034	0.04	
	CDMA BC1	RC3+SO55	Right Cheek	25	0	25.0	24.12	1.22	0.05	0.083	0.10	
	CDMA BC1	RC3+SO55	Right Cheek	25	1	25.0	24.12	1.22	0.02	0.552	<b>0.68</b>	
02	CDMA BC1	RC3+SO55	Right Tilted	25	0	25.0	24.12	1.22	0.04	0.053	0.06	
	CDMA BC1	RC3+SO55	Right Tilted	25	1	25.0	24.12	1.22	0.07	0.541	0.66	
	CDMA BC1	RC3+SO55	Left Cheek	25	0	25.0	24.12	1.22	-0.05	0.166	0.20	
	CDMA BC1	RC3+SO55	Left Cheek	25	1	25.0	24.12	1.22	0.05	0.309	0.38	
	CDMA BC1	RC3+SO55	Left Tilted	25	0	25.0	24.12	1.22	0.02	0.057	0.07	
	CDMA BC1	RC3+SO55	Left Tilted	25	1	25.0	24.12	1.22	0.14	0.34	0.42	
	03	CDMA BC10	RC3+SO55	Right Cheek	580	0	25.0	24.50	1.12	-0.02	0.157	<b>0.18</b>
		CDMA BC10	RC3+SO55	Right Cheek	580	1	25.0	24.50	1.12	-0.05	0.113	0.13
CDMA BC10		RC3+SO55	Right Tilted	580	0	25.0	24.50	1.12	0.01	0.108	0.12	
CDMA BC10		RC3+SO55	Right Tilted	580	1	25.0	24.50	1.12	0.12	0.059	0.07	
CDMA BC10		RC3+SO55	Left Cheek	580	0	25.0	24.50	1.12	-0.05	0.105	0.12	
CDMA BC10		RC3+SO55	Left Cheek	580	1	25.0	24.50	1.12	0.11	0.064	0.07	
CDMA BC10		RC3+SO55	Left Tilted	580	0	25.0	24.50	1.12	0	0.074	0.08	
CDMA BC10		RC3+SO55	Left Tilted	580	1	25.0	24.50	1.12	-0.08	0	0.00	

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
04	LTE 2	QPSK20M	Right Cheek	18900	0	1	0	23.5	23.49	1.00	0.02	0.057	0.06
	LTE 2	QPSK20M	Right Cheek	18900	1	1	0	23.5	23.49	1.00	0.06	0.366	<b>0.37</b>
	LTE 2	QPSK20M	Right Cheek	18900	0	50	0	22.5	22.37	1.03	0.09	0.049	0.05
	LTE 2	QPSK20M	Right Cheek	18900	1	50	0	22.5	22.37	1.03	0.08	0.3	0.31
	LTE 2	QPSK20M	Right Tilted	18900	0	1	0	23.5	23.49	1.00	0.07	0.036	0.04
	LTE 2	QPSK20M	Right Tilted	18900	1	1	0	23.5	23.49	1.00	0.01	0.346	0.35
	LTE 2	QPSK20M	Right Tilted	18900	0	50	0	22.5	22.37	1.03	0.11	0.03	0.03
	LTE 2	QPSK20M	Right Tilted	18900	1	50	0	22.5	22.37	1.03	0.05	0.284	0.29
	LTE 2	QPSK20M	Left Cheek	18900	0	1	0	23.5	23.49	1.00	-0.02	0.117	0.12
	LTE 2	QPSK20M	Left Cheek	18900	1	1	0	23.5	23.49	1.00	0.09	0.245	0.25
	LTE 2	QPSK20M	Left Cheek	18900	0	50	0	22.5	22.37	1.03	0.07	0.096	0.10
	LTE 2	QPSK20M	Left Cheek	18900	1	50	0	22.5	22.37	1.03	0.15	0.198	0.20
	LTE 2	QPSK20M	Left Tilted	18900	0	1	0	23.5	23.49	1.00	0.11	0.039	0.04
	LTE 2	QPSK20M	Left Tilted	18900	1	1	0	23.5	23.49	1.00	0.06	0.256	0.26
	LTE 2	QPSK20M	Left Tilted	18900	0	50	0	22.5	22.37	1.03	-0.05	0.033	0.03
	LTE 2	QPSK20M	Left Tilted	18900	1	50	0	22.5	22.37	1.03	0.13	0.209	0.22



# FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
05	LTE 4	QPSK20M	Right Cheek	20175	0	1	0	24.0	23.95	1.01	0.07	0.06	0.06
	LTE 4	QPSK20M	Right Cheek	20175	1	1	0	24.0	23.95	1.01	0.06	0.649	<b>0.66</b>
	LTE 4	QPSK20M	Right Cheek	20175	0	50	0	23.0	22.98	1.00	0.11	0.044	0.04
	LTE 4	QPSK20M	Right Cheek	20175	1	50	0	23.0	22.98	1.00	0.05	0.432	0.43
	LTE 4	QPSK20M	Right Tilted	20175	0	1	0	24.0	23.95	1.01	-0.05	0.034	0.03
	LTE 4	QPSK20M	Right Tilted	20175	1	1	0	24.0	23.95	1.01	0.03	0.504	0.51
	LTE 4	QPSK20M	Right Tilted	20175	0	50	0	23.0	22.98	1.00	-0.06	0.025	0.03
	LTE 4	QPSK20M	Right Tilted	20175	1	50	0	23.0	22.98	1.00	0.02	0.332	0.33
	LTE 4	QPSK20M	Left Cheek	20175	0	1	0	24.0	23.95	1.01	-0.05	0.11	0.11
	LTE 4	QPSK20M	Left Cheek	20175	1	1	0	24.0	23.95	1.01	0.09	0.429	0.43
	LTE 4	QPSK20M	Left Cheek	20175	0	50	0	23.0	22.98	1.00	-0.02	0.081	0.08
	LTE 4	QPSK20M	Left Cheek	20175	1	50	0	23.0	22.98	1.00	0.07	0.283	0.28
	LTE 4	QPSK20M	Left Tilted	20175	0	1	0	24.0	23.95	1.01	0.06	0.035	0.04
	LTE 4	QPSK20M	Left Tilted	20175	1	1	0	24.0	23.95	1.01	0.11	0.371	0.38
	LTE 4	QPSK20M	Left Tilted	20175	0	50	0	23.0	22.98	1.00	0.08	0.026	0.03
	LTE 4	QPSK20M	Left Tilted	20175	1	50	0	23.0	22.98	1.00	0.15	0.243	0.24
06	LTE 5	QPSK10M	Right Cheek	20450	0	1	49	24.0	23.70	1.07	0.07	0.136	<b>0.15</b>
	LTE 5	QPSK10M	Right Cheek	20450	1	1	49	24.0	23.70	1.07	-0.12	0.094	0.10
	LTE 5	QPSK10M	Right Cheek	20450	0	25	25	23.0	22.88	1.03	0.01	0.110	0.11
	LTE 5	QPSK10M	Right Cheek	20450	1	25	25	23.0	22.88	1.03	0.05	0.076	0.08
	LTE 5	QPSK10M	Right Tilted	20450	0	1	49	24.0	23.70	1.07	0.12	0.094	0.10
	LTE 5	QPSK10M	Right Tilted	20450	1	1	49	24.0	23.70	1.07	0	0	0.00
	LTE 5	QPSK10M	Right Tilted	20450	0	25	25	23.0	22.88	1.03	-0.17	0.077	0.08
	LTE 5	QPSK10M	Right Tilted	20450	1	25	25	23.0	22.88	1.03	0	0	0.00
	LTE 5	QPSK10M	Left Cheek	20450	0	1	49	24.0	23.70	1.07	-0.09	0.117	0.13
	LTE 5	QPSK10M	Left Cheek	20450	1	1	49	24.0	23.70	1.07	0.15	0.078	0.08
	LTE 5	QPSK10M	Left Cheek	20450	0	25	25	23.0	22.88	1.03	0	0.097	0.10
	LTE 5	QPSK10M	Left Cheek	20450	1	25	25	23.0	22.88	1.03	-0.09	0.057	0.06
	LTE 5	QPSK10M	Left Tilted	20450	0	1	49	24.0	23.70	1.07	0.11	0.084	0.09
	LTE 5	QPSK10M	Left Tilted	20450	1	1	49	24.0	23.70	1.07	0	0	0.00
	LTE 5	QPSK10M	Left Tilted	20450	0	25	25	23.0	22.88	1.03	0.08	0.070	0.07
	LTE 5	QPSK10M	Left Tilted	20450	1	25	25	23.0	22.88	1.03	0	0	0.00
07	LTE 7	QPSK20M	Right Cheek	21350	0	1	0	23.0	22.99	1.00	-0.01	0.164	0.16
	LTE 7	QPSK20M	Right Cheek	21350	1	1	0	23.0	22.99	1.00	-0.09	0.24	0.24
	LTE 7	QPSK20M	Right Cheek	21350	0	50	0	22.0	21.98	1.00	0.03	0.121	0.12
	LTE 7	QPSK20M	Right Cheek	21350	1	50	0	22.0	21.98	1.00	-0.02	0.175	0.18
	LTE 7	QPSK20M	Right Tilted	21350	0	1	0	23.0	22.99	1.00	0.05	0.098	0.10
	LTE 7	QPSK20M	Right Tilted	21350	1	1	0	23.0	22.99	1.00	0.05	0.141	0.14
	LTE 7	QPSK20M	Right Tilted	21350	0	50	0	22.0	21.98	1.00	0.07	0.071	0.07
	LTE 7	QPSK20M	Right Tilted	21350	1	50	0	22.0	21.98	1.00	0	0.100	0.10
	LTE 7	QPSK20M	Left Cheek	21350	0	1	0	23.0	22.99	1.00	0.04	0.392	<b>0.39</b>
	LTE 7	QPSK20M	Left Cheek	21350	1	1	0	23.0	22.99	1.00	0.01	0.099	0.10
	LTE 7	QPSK20M	Left Cheek	21350	0	50	0	22.0	21.98	1.00	-0.1	0.286	0.29
	LTE 7	QPSK20M	Left Cheek	21350	1	50	0	22.0	21.98	1.00	0.08	0.073	0.07
	LTE 7	QPSK20M	Left Tilted	21350	0	1	0	23.0	22.99	1.00	-0.12	0.079	0.08
	LTE 7	QPSK20M	Left Tilted	21350	1	1	0	23.0	22.99	1.00	0.02	0.059	0.06
	LTE 7	QPSK20M	Left Tilted	21350	0	50	0	22.0	21.98	1.00	0.03	0.058	0.06
	LTE 7	QPSK20M	Left Tilted	21350	1	50	0	22.0	21.98	1.00	0.01	0.044	0.04



# FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
08	LTE 12	QPSK10M	Right Cheek	23130	0	1	49	23.5	22.94	1.14	-0.14	0.112	<b>0.13</b>
	LTE 12	QPSK10M	Right Cheek	23130	1	1	49	23.5	22.94	1.14	0.15	0.033	0.04
	LTE 12	QPSK10M	Right Cheek	23130	0	25	25	22.5	22.27	1.05	0	0.090	0.09
	LTE 12	QPSK10M	Right Cheek	23130	1	25	25	22.5	22.27	1.05	0.01	0.026	0.03
	LTE 12	QPSK10M	Right Tilted	23130	0	1	49	23.5	22.94	1.14	0.05	0.090	0.10
	LTE 12	QPSK10M	Right Tilted	23130	1	1	49	23.5	22.94	1.14	0.08	0.019	0.02
	LTE 12	QPSK10M	Right Tilted	23130	0	25	25	22.5	22.27	1.05	-0.11	0.073	0.08
	LTE 12	QPSK10M	Right Tilted	23130	1	25	25	22.5	22.27	1.05	0.07	0.015	0.02
	LTE 12	QPSK10M	Left Cheek	23130	0	1	49	23.5	22.94	1.14	-0.05	0.107	0.12
	LTE 12	QPSK10M	Left Cheek	23130	1	1	49	23.5	22.94	1.14	0.05	0.018	0.02
	LTE 12	QPSK10M	Left Cheek	23130	0	25	25	22.5	22.27	1.05	0.08	0.085	0.09
	LTE 12	QPSK10M	Left Cheek	23130	1	25	25	22.5	22.27	1.05	0.01	0.013	0.01
	LTE 12	QPSK10M	Left Tilted	23130	0	1	49	23.5	22.94	1.14	0.01	0.093	0.11
	LTE 12	QPSK10M	Left Tilted	23130	1	1	49	23.5	22.94	1.14	0.11	0.013	0.01
	LTE 12	QPSK10M	Left Tilted	23130	0	25	25	22.5	22.27	1.05	0.04	0.072	0.08
	LTE 12	QPSK10M	Left Tilted	23130	1	25	25	22.5	22.27	1.05	0.07	0.01	0.01
09	LTE 13	QPSK10M	Right Cheek	23230	0	1	24	23.0	22.99	1.00	-0.10	0.066	<b>0.07</b>
	LTE 13	QPSK10M	Right Cheek	23230	1	1	24	23.0	22.99	1.00	0.05	0.065	0.07
	LTE 13	QPSK10M	Right Cheek	23230	0	25	0	22.0	21.99	1.00	0	0.055	0.06
	LTE 13	QPSK10M	Right Cheek	23230	1	25	0	22.0	21.99	1.00	0	0.056	0.06
	LTE 13	QPSK10M	Right Tilted	23230	0	1	24	23.0	22.99	1.00	0.01	0.041	0.04
	LTE 13	QPSK10M	Right Tilted	23230	1	1	24	23.0	22.99	1.00	0	0	0.00
	LTE 13	QPSK10M	Right Tilted	23230	0	25	0	22.0	21.99	1.00		0	0.00
	LTE 13	QPSK10M	Right Tilted	23230	1	25	0	22.0	21.99	1.00	0	0	0.00
	LTE 13	QPSK10M	Left Cheek	23230	0	1	24	23.0	22.99	1.00	0.06	0.056	0.06
	LTE 13	QPSK10M	Left Cheek	23230	1	1	24	23.0	22.99	1.00	0.11	0.042	0.04
	LTE 13	QPSK10M	Left Cheek	23230	0	25	0	22.0	21.99	1.00	-0.05	0.047	0.05
	LTE 13	QPSK10M	Left Cheek	23230	1	25	0	22.0	21.99	1.00	0	0	0.00
	LTE 13	QPSK10M	Left Tilted	23230	0	1	24	23.0	22.99	1.00	0.05	0.035	0.04
	LTE 13	QPSK10M	Left Tilted	23230	1	1	24	23.0	22.99	1.00	0	0	0.00
	LTE 13	QPSK10M	Left Tilted	23230	0	25	0	22.0	21.99	1.00	0	0	0.00
	LTE 13	QPSK10M	Left Tilted	23230	1	25	0	22.0	21.99	1.00	0	0	0.00
10	LTE 25	QPSK20M	Right Cheek	26365	0	1	0	23.5	23.45	1.01	0.09	0.058	0.06
	LTE 25	QPSK20M	Right Cheek	26365	1	1	0	23.5	23.45	1.01	0.04	0.373	<b>0.38</b>
	LTE 25	QPSK20M	Right Cheek	26365	0	50	0	22.5	22.48	1.00	0.05	0.051	0.05
	LTE 25	QPSK20M	Right Cheek	26365	1	50	0	22.5	22.48	1.00	0.06	0.282	0.28
	LTE 25	QPSK20M	Right Tilted	26365	0	1	0	23.5	23.45	1.01	-0.01	0.034	0.03
	LTE 25	QPSK20M	Right Tilted	26365	1	1	0	23.5	23.45	1.01	0.07	0.343	0.35
	LTE 25	QPSK20M	Right Tilted	26365	0	50	0	22.5	22.48	1.00	-0.04	0.031	0.03
	LTE 25	QPSK20M	Right Tilted	26365	1	50	0	22.5	22.48	1.00	0.15	0.272	0.27
	LTE 25	QPSK20M	Left Cheek	26365	0	1	0	23.5	23.45	1.01	0.02	0.114	0.12
	LTE 25	QPSK20M	Left Cheek	26365	1	1	0	23.5	23.45	1.01	0.12	0.214	0.22
	LTE 25	QPSK20M	Left Cheek	26365	0	50	0	22.5	22.48	1.00	-0.05	0.102	0.10
	LTE 25	QPSK20M	Left Cheek	26365	1	50	0	22.5	22.48	1.00	0.13	0.168	0.17
	LTE 25	QPSK20M	Left Tilted	26365	0	1	0	23.5	23.45	1.01	0.14	0.039	0.04
	LTE 25	QPSK20M	Left Tilted	26365	1	1	0	23.5	23.45	1.01	-0.06	0.257	0.26
	LTE 25	QPSK20M	Left Tilted	26365	0	50	0	22.5	22.48	1.00	0.07	0.036	0.04
	LTE 25	QPSK20M	Left Tilted	26365	1	50	0	22.5	22.48	1.00	-0.01	0.202	0.20



# FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 26	QPSK15M	Right Cheek	26965	0	1	74	24.0	23.86	1.03	0.1	0.058	0.06
11	LTE 26	QPSK15M	Right Cheek	26965	1	1	74	24.0	23.86	1.03	-0.08	0.122	0.13
	LTE 26	QPSK15M	Right Cheek	26965	0	36	39	23.0	22.77	1.05	0.02	0.05	0.05
	LTE 26	QPSK15M	Right Cheek	26965	1	36	39	23.0	22.77	1.05	0.06	0.101	0.11
	LTE 26	QPSK15M	Right Tilted	26965	0	1	74	24.0	23.86	1.03	0.05	0.026	0.03
	LTE 26	QPSK15M	Right Tilted	26965	1	1	74	24.0	23.86	1.03	0.02	0.061	0.06
	LTE 26	QPSK15M	Right Tilted	26965	0	36	39	23.0	22.77	1.05	-0.11	0.02	0.02
	LTE 26	QPSK15M	Right Tilted	26965	1	36	39	23.0	22.77	1.05	0.11	0.048	0.05
	LTE 26	QPSK15M	Left Cheek	26965	0	1	74	24.0	23.86	1.03	-0.03	0.041	0.04
	LTE 26	QPSK15M	Left Cheek	26965	1	1	74	24.0	23.86	1.03	-0.15	0.08	0.08
	LTE 26	QPSK15M	Left Cheek	26965	0	36	39	23.0	22.77	1.05	0.03	0.036	0.04
	LTE 26	QPSK15M	Left Cheek	26965	1	36	39	23.0	22.77	1.05	-0.08	0.062	0.07
	LTE 26	QPSK15M	Left Tilted	26965	0	1	74	24.0	23.86	1.03	0.07	0.023	0.02
	LTE 26	QPSK15M	Left Tilted	26965	1	1	74	24.0	23.86	1.03	0.03	0.039	0.04
	LTE 26	QPSK15M	Left Tilted	26965	0	36	39	23.0	22.77	1.05	0.04	0.02	0.02
	LTE 26	QPSK15M	Left Tilted	26965	1	36	39	23.0	22.77	1.05	-0.08	0.03	0.03
	LTE 41	QPSK20M	Right Cheek	41490	0	1	0	23.5	23.28	1.05	0.03	0.085	0.09
	LTE 41	QPSK20M	Right Cheek	41490	1	1	0	23.5	23.28	1.05	0.1	0.188	0.20
	LTE 41	QPSK20M	Right Cheek	41490	0	50	0	22.5	22.14	1.09	0.05	0.064	0.07
	LTE 41	QPSK20M	Right Cheek	41490	1	50	0	22.5	22.14	1.09	0.05	0.146	0.16
	LTE 41	QPSK20M	Right Tilted	41490	0	1	0	23.5	23.28	1.05	-0.02	0.035	0.04
	LTE 41	QPSK20M	Right Tilted	41490	1	1	0	23.5	23.28	1.05	-0.01	0.129	0.14
	LTE 41	QPSK20M	Right Tilted	41490	0	50	0	22.5	22.14	1.09	0.07	0.027	0.03
	LTE 41	QPSK20M	Right Tilted	41490	1	50	0	22.5	22.14	1.09	0.03	0.101	0.11
12	LTE 41	QPSK20M	Left Cheek	41490	0	1	0	23.5	23.28	1.05	0.05	0.205	0.22
	LTE 41	QPSK20M	Left Cheek	41490	1	1	0	23.5	23.28	1.05	0.05	0.073	0.08
	LTE 41	QPSK20M	Left Cheek	41490	0	50	0	22.5	22.14	1.09	-0.02	0.155	0.17
	LTE 41	QPSK20M	Left Cheek	41490	1	50	0	22.5	22.14	1.09	0.05	0.057	0.06
	LTE 41	QPSK20M	Left Tilted	41490	0	1	0	23.5	23.28	1.05	0.03	0.084	0.09
	LTE 41	QPSK20M	Left Tilted	41490	1	1	0	23.5	23.28	1.05	0.01	0.050	0.05
	LTE 41	QPSK20M	Left Tilted	41490	0	50	0	22.5	22.14	1.09	0.01	0.065	0.07
	LTE 41	QPSK20M	Left Tilted	41490	1	50	0	22.5	22.14	1.09	-0.02	0.039	0.04

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	2.4G WLAN	802.11b	Right Cheek	6	0	20.0	18.22	1.51	0.03	0.096	0.14
	2.4G WLAN	802.11b	Right Cheek	1	1	20.0	18.09	1.55	0	0.00216	0.00
	2.4G WLAN	802.11n HT40	Right Cheek	3	0+1	18.0	16.14	1.53	0.03	0.009	0.01
	2.4G WLAN	802.11b	Right Tilted	6	0	20.0	18.22	1.51	0	0.033	0.05
	2.4G WLAN	802.11b	Right Tilted	1	1	20.0	18.09	1.55	0	0	0.00
	2.4G WLAN	802.11n HT40	Right Tilted	3	0+1	18.0	16.14	1.53	0.08	0.0051	0.01
13	2.4G WLAN	802.11b	Left Cheek	6	0	20.0	18.22	1.51	0.08	0.314	0.47
	2.4G WLAN	802.11b	Left Cheek	1	1	20.0	18.09	1.55	0	0	0.00
	2.4G WLAN	802.11n HT40	Left Cheek	3	0+1	18.0	16.14	1.53	0.02	0.068	0.10
	2.4G WLAN	802.11b	Left Tilted	6	0	20.0	18.22	1.51	0.05	0.134	0.20
	2.4G WLAN	802.11b	Left Tilted	1	1	20.0	18.09	1.55	0	0	0.00
	2.4G WLAN	802.11n HT40	Left Tilted	3	0+1	18.0	16.14	1.53	-0.01	0.034	0.05





# FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	5.3G WLAN	802.11ac-VH80	Right Cheek	58	0	17.5	16.03	1.40	0.11	0.241	0.34
	5.3G WLAN	802.11ac-VH80	Right Cheek	58	1	17.5	15.87	1.46	0	0	0.00
	5.3G WLAN	802.11ac-VH80	Right Cheek	58	0+1	17.5	16.05	1.40	-0.03	0.061	0.09
	5.3G WLAN	802.11ac-VH80	Right Tilted	58	0	17.5	16.03	1.40	0.12	0.154	0.22
	5.3G WLAN	802.11ac-VH80	Right Tilted	58	1	17.5	15.87	1.46	0	0	0.00
	5.3G WLAN	802.11ac-VH80	Right Tilted	58	0+1	17.5	16.05	1.40	0.04	0.042	0.06
14	5.3G WLAN	802.11ac-VH80	Left Cheek	58	0	17.5	16.03	1.40	-0.03	0.518	0.73
	5.3G WLAN	802.11ac-VH80	Left Cheek	58	1	17.5	15.87	1.46	0	0	0.00
	5.3G WLAN	802.11ac-VH80	Left Cheek	58	0+1	17.5	16.05	1.40	0	0.122	0.17
	5.3G WLAN	802.11ac-VH80	Left Tilted	58	0	17.5	16.03	1.40	0.11	0.446	0.63
	5.3G WLAN	802.11ac-VH80	Left Tilted	58	1	17.5	15.87	1.46	0	0	0.00
	5.3G WLAN	802.11ac-VH80	Left Tilted	58	0+1	17.5	16.05	1.40	-0.08	0.084	0.12
	5.6G WLAN	802.11ac-VH80	Right Cheek	106	0	17.5	15.84	1.47	0.11	0.134	0.20
	5.6G WLAN	802.11ac-VH80	Right Cheek	106	1	17.5	15.74	1.50	0.07	0.035	0.05
	5.6G WLAN	802.11ac-VH80	Right Cheek	106	0+1	17.5	15.89	1.45	0.03	0.048	0.07
	5.6G WLAN	802.11ac-VH80	Right Tilted	106	0	17.5	15.84	1.47	0.09	0.078	0.11
	5.6G WLAN	802.11ac-VH80	Right Tilted	106	1	17.5	15.74	1.50	0	0	0.00
	5.6G WLAN	802.11ac-VH80	Right Tilted	106	0+1	17.5	15.89	1.45	0	0	0.00
15	5.6G WLAN	802.11ac-VH80	Left Cheek	106	0	17.5	15.84	1.47	0.08	0.391	0.57
	5.6G WLAN	802.11ac-VH80	Left Cheek	106	1	17.5	15.74	1.50	-0.02	0.024	0.04
	5.6G WLAN	802.11ac-VH80	Left Cheek	106	0+1	17.5	15.89	1.45	-0.01	0.194	0.28
	5.6G WLAN	802.11ac-VH80	Left Tilted	106	0	17.5	15.84	1.47	-0.01	0.228	0.33
	5.6G WLAN	802.11ac-VH80	Left Tilted	106	1	17.5	15.74	1.50	0	0	0.00
	5.6G WLAN	802.11ac-VH80	Left Tilted	106	0+1	17.5	15.89	1.45	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Right Cheek	155	0	17.5	15.87	1.46	0.05	0.334	0.49
	5.8G WLAN	802.11ac-VH80	Right Cheek	155	1	17.5	15.64	1.53	0.01	0	0.00
	5.8G WLAN	802.11ac-VH80	Right Cheek	155	0+1	17.5	15.90	1.45	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Right Tilted	155	0	17.5	15.87	1.46	0.1	0.271	0.39
	5.8G WLAN	802.11ac-VH80	Right Tilted	155	1	17.5	15.64	1.53	0.05	0.000251	0.00
	5.8G WLAN	802.11ac-VH80	Right Tilted	155	0+1	17.5	15.90	1.45	-0.02	0	0.00
16	5.8G WLAN	802.11ac-VH80	Left Cheek	155	0	17.5	15.87	1.46	0.09	0.376	0.55
	5.8G WLAN	802.11ac-VH80	Left Cheek	155	1	17.5	15.64	1.53	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Left Cheek	155	0+1	17.5	15.90	1.45	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Left Tilted	155	0	17.5	15.87	1.46	0.06	0.303	0.44
	5.8G WLAN	802.11ac-VH80	Left Tilted	155	1	17.5	15.64	1.53	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Left Tilted	155	0+1	17.5	15.90	1.45	0.02	0	0.00



# FCC SAR Test Report

## 4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	CDMA BC0	RTAP 153.6	Front Face	1013	0	25.0	24.36	1.16	0.05	0.196	0.23
	CDMA BC0	RTAP 153.6	Front Face	1013	1	25.0	24.36	1.16	-0.03	0.024	0.03
17	CDMA BC0	RTAP 153.6	Rear Face	1013	0	25.0	24.36	1.16	0.01	0.233	0.27
	CDMA BC0	RTAP 153.6	Rear Face	1013	1	25.0	24.36	1.16	-0.05	0.039	0.05
	CDMA BC1	RTAP 153.6	Front Face	25	0	25.0	24.08	1.24	0.01	0.315	0.39
	CDMA BC1	RTAP 153.6	Front Face	25	1	25.0	24.08	1.24	0.01	0.122	0.15
18	CDMA BC1	RTAP 153.6	Rear Face	25	0	25.0	24.08	1.24	-0.06	0.377	0.47
	CDMA BC1	RTAP 153.6	Rear Face	25	1	25.0	24.08	1.24	-0.07	0.126	0.16
	CDMA BC10	RTAP 153.6	Front Face	580	0	25.0	24.48	1.13	0.03	0.196	0.22
	CDMA BC10	RTAP 153.6	Front Face	580	1	25.0	24.48	1.13	0.08	0.018	0.02
19	CDMA BC10	RTAP 153.6	Rear Face	580	0	25.0	24.48	1.13	-0.02	0.235	0.26
	CDMA BC10	RTAP 153.6	Rear Face	580	1	25.0	24.48	1.13	0.03	0.024	0.03

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 2	QPSK20M	Front Face	18900	0	1	0	23.5	23.49	1.00	0.04	0.32	0.32
	LTE 2	QPSK20M	Front Face	18900	1	1	0	23.5	23.49	1.00	0.02	0.084	0.08
	LTE 2	QPSK20M	Front Face	18900	0	50	0	22.5	22.37	1.03	0.02	0.281	0.29
	LTE 2	QPSK20M	Front Face	18900	1	50	0	22.5	22.37	1.03	0.05	0.069	0.07
20	LTE 2	QPSK20M	Rear Face	18900	0	1	0	23.5	23.49	1.00	-0.16	0.343	0.34
	LTE 2	QPSK20M	Rear Face	18900	1	1	0	23.5	23.49	1.00	-0.06	0.125	0.13
	LTE 2	QPSK20M	Rear Face	18900	0	50	0	22.5	22.37	1.03	-0.03	0.301	0.31
	LTE 2	QPSK20M	Rear Face	18900	1	50	0	22.5	22.37	1.03	0.07	0.095	0.10
	LTE 4	QPSK20M	Front Face	20175	0	1	0	24.0	23.95	1.01	0.03	0.404	0.41
	LTE 4	QPSK20M	Front Face	20175	1	1	0	24.0	23.95	1.01	0.01	0.204	0.21
	LTE 4	QPSK20M	Front Face	20175	0	50	0	23.0	22.98	1.00	0.01	0.323	0.32
	LTE 4	QPSK20M	Front Face	20175	1	50	0	23.0	22.98	1.00	0.07	0.138	0.14
21	LTE 4	QPSK20M	Rear Face	20175	0	1	0	24.0	23.95	1.01	-0.11	0.547	0.55
	LTE 4	QPSK20M	Rear Face	20175	1	1	0	24.0	23.95	1.01	-0.07	0.213	0.22
	LTE 4	QPSK20M	Rear Face	20175	0	50	0	23.0	22.98	1.00	-0.02	0.391	0.39
	LTE 4	QPSK20M	Rear Face	20175	1	50	0	23.0	22.98	1.00	0.05	0.149	0.15
	LTE 5	QPSK10M	Front Face	20450	0	1	49	24.0	23.70	1.07	0.04	0.124	0.13
	LTE 5	QPSK10M	Front Face	20450	1	1	49	24.0	23.70	1.07	-0.03	0.026	0.03
	LTE 5	QPSK10M	Front Face	20450	0	25	25	23.0	22.88	1.03	0.08	0.109	0.11
	LTE 5	QPSK10M	Front Face	20450	1	25	25	23.0	22.88	1.03	0.08	0.021	0.02
22	LTE 5	QPSK10M	Rear Face	20450	0	1	49	24.0	23.70	1.07	0.04	0.144	0.15
	LTE 5	QPSK10M	Rear Face	20450	1	1	49	24.0	23.70	1.07	-0.02	0.036	0.04
	LTE 5	QPSK10M	Rear Face	20450	0	25	25	23.0	22.88	1.03	0.01	0.124	0.13
	LTE 5	QPSK10M	Rear Face	20450	1	25	25	23.0	22.88	1.03	0.03	0.029	0.03



# FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 7	QPSK20M	Front Face	21350	0	1	0	23.0	22.99	1.00	-0.02	0.327	0.33
	LTE 7	QPSK20M	Front Face	21350	1	1	0	23.0	22.99	1.00	0.07	0.035	0.04
	LTE 7	QPSK20M	Front Face	21350	0	50	0	22.0	21.98	1.00	0.05	0.264	0.27
	LTE 7	QPSK20M	Front Face	21350	1	50	0	22.0	21.98	1.00	0.03	0.032	0.03
23	LTE 7	QPSK20M	Rear Face	21350	0	1	0	23.0	22.99	1.00	-0.02	0.361	0.36
	LTE 7	QPSK20M	Rear Face	21350	1	1	0	23.0	22.99	1.00	0.04	0.023	0.02
	LTE 7	QPSK20M	Rear Face	21350	0	50	0	22.0	21.98	1.00	-0.03	0.292	0.29
	LTE 7	QPSK20M	Rear Face	21350	1	50	0	22.0	21.98	1.00	-0.07	0.021	0.02
	LTE 12	QPSK10M	Front Face	23130	0	1	49	23.5	22.94	1.14	0.01	0.160	0.18
	LTE 12	QPSK10M	Front Face	23130	1	1	49	23.5	22.94	1.14	-0.05	0.00257	0.00
	LTE 12	QPSK10M	Front Face	23130	0	25	25	22.5	22.27	1.05	-0.03	0.141	0.15
	LTE 12	QPSK10M	Front Face	23130	1	25	25	22.5	22.27	1.05	-0.01	0.00213	0.00
24	LTE 12	QPSK10M	Rear Face	23130	0	1	49	23.5	22.94	1.14	-0.07	0.203	0.23
	LTE 12	QPSK10M	Rear Face	23130	1	1	49	23.5	22.94	1.14	0.09	0.00039	0.00
	LTE 12	QPSK10M	Rear Face	23130	0	25	25	22.5	22.27	1.05	0.06	0.177	0.19
	LTE 12	QPSK10M	Rear Face	23130	1	25	25	22.5	22.27	1.05	0.03	0.00032	0.00
	LTE 13	QPSK10M	Front Face	23230	0	1	24	23.0	22.99	1.00	0.02	0.109	0.11
	LTE 13	QPSK10M	Front Face	23230	1	1	24	23.0	22.99	1.00	0.02	0.00610	0.01
	LTE 13	QPSK10M	Front Face	23230	0	25	0	22.0	21.99	1.00	-0.04	0.096	0.10
	LTE 13	QPSK10M	Front Face	23230	1	25	0	22.0	21.99	1.00	0.01	0.00220	0.00
25	LTE 13	QPSK10M	Rear Face	23230	0	1	24	23.0	22.99	1.00	0.01	0.142	0.14
	LTE 13	QPSK10M	Rear Face	23230	1	1	24	23.0	22.99	1.00	-0.06	0.00881	0.01
	LTE 13	QPSK10M	Rear Face	23230	0	25	0	22.0	21.99	1.00	0.03	0.124	0.12
	LTE 13	QPSK10M	Rear Face	23230	1	25	0	22.0	21.99	1.00	0.03	0.00288	0.00
	LTE 25	QPSK20M	Front Face	26365	0	1	0	23.5	23.45	1.01	0.04	0.253	0.26
	LTE 25	QPSK20M	Front Face	26365	1	1	0	23.5	23.45	1.01	0.01	0.089	0.09
	LTE 25	QPSK20M	Front Face	26365	0	50	0	22.5	22.48	1.00	0.09	0.231	0.23
	LTE 25	QPSK20M	Front Face	26365	1	50	0	22.5	22.48	1.00	0.05	0.071	0.07
26	LTE 25	QPSK20M	Rear Face	26365	0	1	0	23.5	23.45	1.01	-0.14	0.317	0.32
	LTE 25	QPSK20M	Rear Face	26365	1	1	0	23.5	23.45	1.01	-0.09	0.126	0.13
	LTE 25	QPSK20M	Rear Face	26365	0	50	0	22.5	22.48	1.00	0.01	0.295	0.30
	LTE 25	QPSK20M	Rear Face	26365	1	50	0	22.5	22.48	1.00	0.08	0.097	0.10
27	LTE 26	QPSK15M	Front Face	26965	0	1	74	24.0	23.86	1.03	0.06	0.066	0.07
	LTE 26	QPSK15M	Front Face	26965	1	1	74	24.0	23.86	1.03	-0.06	0.02	0.02
	LTE 26	QPSK15M	Front Face	26965	0	36	39	23.0	22.77	1.05	0.04	0.057	0.06
	LTE 26	QPSK15M	Front Face	26965	1	36	39	23.0	22.77	1.05	0.01	0.016	0.02
	LTE 26	QPSK15M	Rear Face	26965	0	1	74	24.0	23.86	1.03	-0.1	0.049	0.05
	LTE 26	QPSK15M	Rear Face	26965	1	1	74	24.0	23.86	1.03	-0.07	0.029	0.03
	LTE 26	QPSK15M	Rear Face	26965	0	36	39	23.0	22.77	1.05	0.07	0.041	0.04
	LTE 26	QPSK15M	Rear Face	26965	1	36	39	23.0	22.77	1.05	-0.03	0.024	0.03
	LTE 41	QPSK20M	Front Face	41490	0	1	0	23.5	23.28	1.05	-0.12	0.172	0.18
	LTE 41	QPSK20M	Front Face	41490	1	1	0	23.5	23.28	1.05	0.17	0.026	0.03
	LTE 41	QPSK20M	Front Face	41490	0	50	0	22.5	22.14	1.09	0.16	0.137	0.15
	LTE 41	QPSK20M	Front Face	41490	1	50	0	22.5	22.14	1.09	-0.12	0.022	0.02
28	LTE 41	QPSK20M	Rear Face	41490	0	1	0	23.5	23.28	1.05	-0.08	0.195	0.21
	LTE 41	QPSK20M	Rear Face	41490	1	1	0	23.5	23.28	1.05	-0.02	0.012	0.01
	LTE 41	QPSK20M	Rear Face	41490	0	50	0	22.5	22.14	1.09	-0.02	0.142	0.15
	LTE 41	QPSK20M	Rear Face	41490	1	50	0	22.5	22.14	1.09	-0.14	0.009	0.01



# FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
29	2.4G WLAN	802.11b	Front Face	6	0	20.0	18.22	1.51	0.07	0.031	0.05
	2.4G WLAN	802.11b	Front Face	1	1	20.0	18.09	1.55	0.11	0.050	0.08
	2.4G WLAN	802.11n HT40	Front Face	3	0+1	18.0	16.14	1.53	0.03	0.00214	0.00
	2.4G WLAN	802.11b	Rear Face	6	0	20.0	18.22	1.51	0.19	0.017	0.03
	2.4G WLAN	802.11b	Rear Face	1	1	20.0	18.09	1.55	0.11	0.017	0.03
	2.4G WLAN	802.11n HT40	Rear Face	3	0+1	18.0	16.14	1.53	0	0	0.00
30	5.3G WLAN	802.11ac-VH80	Front Face	58	0	17.5	16.03	1.40	-0.03	0.014	0.02
	5.3G WLAN	802.11ac-VH80	Front Face	58	1	17.5	15.87	1.46	-0.06	0	0.00
	5.3G WLAN	802.11ac-VH80	Front Face	58	0+1	17.5	16.05	1.40	0.05	0.00372	0.01
	5.3G WLAN	802.11ac-VH80	Rear Face	58	0	17.5	16.03	1.40	0	0	0.00
	5.3G WLAN	802.11ac-VH80	Rear Face	58	1	17.5	15.87	1.46	0	0	0.00
	5.3G WLAN	802.11ac-VH80	Rear Face	58	0+1	17.5	16.05	1.40	0	0	0.00
31	5.6G WLAN	802.11ac-VH80	Front Face	106	0	17.5	15.84	1.47	-0.09	0.00894	0.01
	5.6G WLAN	802.11ac-VH80	Front Face	106	1	17.5	15.74	1.50	0	0.016	0.02
	5.6G WLAN	802.11ac-VH80	Front Face	106	0+1	17.5	15.89	1.45	0	0	0.00
	5.6G WLAN	802.11ac-VH80	Rear Face	106	0	17.5	15.84	1.47	0.03	0.0007736	0.00
	5.6G WLAN	802.11ac-VH80	Rear Face	106	1	17.5	15.74	1.50	0	0	0.00
	5.6G WLAN	802.11ac-VH80	Rear Face	106	0+1	17.5	15.89	1.45	0	0	0.00
32	5.8G WLAN	802.11ac-VH80	Front Face	155	0	17.5	15.87	1.46	0.08	0.015	0.02
	5.8G WLAN	802.11ac-VH80	Front Face	155	1	17.5	15.64	1.53	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Front Face	155	0+1	17.5	15.90	1.45	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Rear Face	155	0	17.5	15.87	1.46	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Rear Face	155	1	17.5	15.64	1.53	0	0	0.00
	5.8G WLAN	802.11ac-VH80	Rear Face	155	0+1	17.5	15.90	1.45	0	0	0.00

Plot No.	Band	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	Bluetooth	Front Face	39	10.5	10.09	1.10	0	0	0.00
	Bluetooth	Rear Face	39	10.5	10.09	1.10	0	0	0.00



# FCC SAR Test Report

A D T

## 4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	CDMA BC0	RTAP 153.6	Front Face	1013	0	25.0	24.36	1.16	0.05	0.196	0.23
	CDMA BC0	RTAP 153.6	Front Face	1013	1	25.0	24.36	1.16	-0.03	0.024	0.03
17	CDMA BC0	RTAP 153.6	Rear Face	1013	0	25.0	24.36	1.16	0.01	0.233	0.27
	CDMA BC0	RTAP 153.6	Rear Face	1013	1	25.0	24.36	1.16	-0.05	0.039	0.05
	CDMA BC0	RTAP 153.6	Left Side	1013	0	25.0	24.36	1.16	-0.02	0.162	0.19
	CDMA BC0	RTAP 153.6	Left Side	1013	1	25.0	24.36	1.16	-0.01	0.031	0.04
	CDMA BC0	RTAP 153.6	Right Side	1013	0	25.0	24.36	1.16	0.03	0.193	0.22
	CDMA BC0	RTAP 153.6	Right Side	1013	1	25.0	24.36	1.16	0.05	0.024	0.03
	CDMA BC0	RTAP 153.6	Top Side	1013	1	25.0	24.36	1.16	0.06	0.003	0.00
	CDMA BC0	RTAP 153.6	Bottom Side	1013	0	25.0	24.36	1.16	0.01	0.051	0.06
	CDMA BC1	RTAP 153.6	Front Face	25	0	25.0	24.08	1.24	0.01	0.315	0.39
	CDMA BC1	RTAP 153.6	Front Face	25	1	25.0	24.08	1.24	0.01	0.122	0.15
18	CDMA BC1	RTAP 153.6	Rear Face	25	0	25.0	24.08	1.24	-0.06	0.377	0.47
	CDMA BC1	RTAP 153.6	Rear Face	25	1	25.0	24.08	1.24	-0.07	0.126	0.16
	CDMA BC1	RTAP 153.6	Left Side	25	0	25.0	24.08	1.24	0.06	0.349	0.43
	CDMA BC1	RTAP 153.6	Left Side	25	1	25.0	24.08	1.24	-0.03	0.124	0.15
	CDMA BC1	RTAP 153.6	Right Side	25	0	25.0	24.08	1.24	-0.07	0.117	0.14
	CDMA BC1	RTAP 153.6	Right Side	25	1	25.0	24.08	1.24	0.04	0.003	0.00
	CDMA BC1	RTAP 153.6	Top Side	25	1	25.0	24.08	1.24	0.07	0.12	0.15
	CDMA BC1	RTAP 153.6	Bottom Side	25	0	25.0	24.08	1.24	0.04	0.325	0.40
	CDMA BC10	RTAP 153.6	Front Face	580	0	25.0	24.48	1.13	0.03	0.196	0.22
	CDMA BC10	RTAP 153.6	Front Face	580	1	25.0	24.48	1.13	0.08	0.018	0.02
19	CDMA BC10	RTAP 153.6	Rear Face	580	0	25.0	24.48	1.13	-0.02	0.235	0.26
	CDMA BC10	RTAP 153.6	Rear Face	580	1	25.0	24.48	1.13	0.03	0.024	0.03
	CDMA BC10	RTAP 153.6	Left Side	580	0	25.0	24.48	1.13	-0.01	0.167	0.19
	CDMA BC10	RTAP 153.6	Left Side	580	1	25.0	24.48	1.13	0.02	0.023	0.03
	CDMA BC10	RTAP 153.6	Right Side	580	0	25.0	24.48	1.13	0.02	0.185	0.21
	CDMA BC10	RTAP 153.6	Right Side	580	1	25.0	24.48	1.13	-0.03	0.02	0.02
	CDMA BC10	RTAP 153.6	Top Side	580	1	25.0	24.48	1.13	0.09	0.002	0.00
	CDMA BC10	RTAP 153.6	Bottom Side	580	0	25.0	24.48	1.13	0.07	0.051	0.06

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 2	QPSK20M	Front Face	18900	0	1	0	23.5	23.49	1.00	0.04	0.32	0.32
	LTE 2	QPSK20M	Front Face	18900	1	1	0	23.5	23.49	1.00	0.02	0.084	0.08
	LTE 2	QPSK20M	Front Face	18900	0	50	0	22.5	22.37	1.03	0.02	0.281	0.29
	LTE 2	QPSK20M	Front Face	18900	1	50	0	22.5	22.37	1.03	0.05	0.069	0.07
20	LTE 2	QPSK20M	Rear Face	18900	0	1	0	23.5	23.49	1.00	-0.16	0.343	0.34
	LTE 2	QPSK20M	Rear Face	18900	1	1	0	23.5	23.49	1.00	-0.06	0.125	0.13
	LTE 2	QPSK20M	Rear Face	18900	0	50	0	22.5	22.37	1.03	-0.03	0.301	0.31
	LTE 2	QPSK20M	Rear Face	18900	1	50	0	22.5	22.37	1.03	0.07	0.095	0.10
	LTE 2	QPSK20M	Left Side	18900	0	1	0	23.5	23.49	1.00	0.05	0.326	0.33
	LTE 2	QPSK20M	Left Side	18900	1	1	0	23.5	23.49	1.00	0.11	0.127	0.13
	LTE 2	QPSK20M	Left Side	18900	0	50	0	22.5	22.37	1.03	0.07	0.267	0.28
	LTE 2	QPSK20M	Left Side	18900	1	50	0	22.5	22.37	1.03	0.06	0.105	0.11
	LTE 2	QPSK20M	Right Side	18900	0	1	0	23.5	23.49	1.00	0.09	0.039	0.04
	LTE 2	QPSK20M	Right Side	18900	1	1	0	23.5	23.49	1.00	0.04	0.019	0.02
	LTE 2	QPSK20M	Right Side	18900	0	50	0	22.5	22.37	1.03	0.01	0.037	0.04
	LTE 2	QPSK20M	Right Side	18900	1	50	0	22.5	22.37	1.03	-0.02	0.016	0.02
	LTE 2	QPSK20M	Top Side	18900	1	1	0	23.5	23.49	1.00	-0.07	0.104	0.10
	LTE 2	QPSK20M	Top Side	18900	1	50	0	22.5	22.37	1.03	0.01	0.091	0.09
	LTE 2	QPSK20M	Bottom Side	18900	0	1	0	23.5	23.49	1.00	0.13	0.288	0.29
	LTE 2	QPSK20M	Bottom Side	18900	0	50	0	22.5	22.37	1.03	0.06	0.274	0.28



# FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 4	QPSK20M	Front Face	20175	0	1	0	24.0	23.95	1.01	0.03	0.404	0.41
	LTE 4	QPSK20M	Front Face	20175	1	1	0	24.0	23.95	1.01	0.01	0.204	0.21
	LTE 4	QPSK20M	Front Face	20175	0	50	0	23.0	22.98	1.00	0.01	0.323	0.32
	LTE 4	QPSK20M	Front Face	20175	1	50	0	23.0	22.98	1.00	0.07	0.138	0.14
	LTE 4	QPSK20M	Rear Face	20175	0	1	0	24.0	23.95	1.01	-0.11	0.547	0.55
	LTE 4	QPSK20M	Rear Face	20175	1	1	0	24.0	23.95	1.01	-0.07	0.213	0.22
	LTE 4	QPSK20M	Rear Face	20175	0	50	0	23.0	22.98	1.00	-0.02	0.391	0.39
	LTE 4	QPSK20M	Rear Face	20175	1	50	0	23.0	22.98	1.00	0.05	0.149	0.15
	LTE 4	QPSK20M	Left Side	20175	0	1	0	24.0	23.95	1.01	0.07	0.237	0.24
	LTE 4	QPSK20M	Left Side	20175	1	1	0	24.0	23.95	1.01	0.02	0.207	0.21
	LTE 4	QPSK20M	Left Side	20175	0	50	0	23.0	22.98	1.00	0.11	0.18	0.18
	LTE 4	QPSK20M	Left Side	20175	1	50	0	23.0	22.98	1.00	0.04	0.144	0.14
	LTE 4	QPSK20M	Right Side	20175	0	1	0	24.0	23.95	1.01	0.08	0.133	0.13
	LTE 4	QPSK20M	Right Side	20175	1	1	0	24.0	23.95	1.01	0.02	0.021	0.02
	LTE 4	QPSK20M	Right Side	20175	0	50	0	23.0	22.98	1.00	0.15	0.098	0.10
	LTE 4	QPSK20M	Right Side	20175	1	50	0	23.0	22.98	1.00	0.08	0.014	0.01
	LTE 4	QPSK20M	Top Side	20175	1	1	0	24.0	23.95	1.01	0.04	0.151	0.15
	LTE 4	QPSK20M	Top Side	20175	1	50	0	23.0	22.98	1.00	0.08	0.1	0.10
33	LTE 4	QPSK20M	Bottom Side	20175	0	1	0	24.0	23.95	1.01	0.09	0.584	0.59
	LTE 4	QPSK20M	Bottom Side	20175	0	50	0	23.0	22.98	1.00	0.13	0.468	0.47
	LTE 5	QPSK10M	Front Face	20450	0	1	49	24.0	23.70	1.07	0.04	0.124	0.13
	LTE 5	QPSK10M	Front Face	20450	1	1	49	24.0	23.70	1.07	-0.03	0.026	0.03
	LTE 5	QPSK10M	Front Face	20450	0	25	25	23.0	22.88	1.03	0.08	0.109	0.11
	LTE 5	QPSK10M	Front Face	20450	1	25	25	23.0	22.88	1.03	0.08	0.021	0.02
22	LTE 5	QPSK10M	Rear Face	20450	0	1	49	24.0	23.70	1.07	0.04	0.144	0.15
	LTE 5	QPSK10M	Rear Face	20450	1	1	49	24.0	23.70	1.07	-0.02	0.036	0.04
	LTE 5	QPSK10M	Rear Face	20450	0	25	25	23.0	22.88	1.03	0.01	0.124	0.13
	LTE 5	QPSK10M	Rear Face	20450	1	25	25	23.0	22.88	1.03	0.03	0.029	0.03
	LTE 5	QPSK10M	Left Side	20450	0	1	49	24.0	23.70	1.07	0.07	0.087	0.09
	LTE 5	QPSK10M	Left Side	20450	1	1	49	24.0	23.70	1.07	0.07	0.035	0.04
	LTE 5	QPSK10M	Left Side	20450	0	25	25	23.0	22.88	1.03	-0.07	0.074	0.08
	LTE 5	QPSK10M	Left Side	20450	1	25	25	23.0	22.88	1.03	0.02	0.028	0.03
	LTE 5	QPSK10M	Right Side	20450	0	1	49	24.0	23.70	1.07	0.05	0.102	0.11
	LTE 5	QPSK10M	Right Side	20450	1	1	49	24.0	23.70	1.07	0.07	0.017	0.02
	LTE 5	QPSK10M	Right Side	20450	0	25	25	23.0	22.88	1.03	-0.02	0.090	0.09
	LTE 5	QPSK10M	Right Side	20450	1	25	25	23.0	22.88	1.03	0.02	0.014	0.01
	LTE 5	QPSK10M	Top Side	20450	1	1	49	24.0	23.70	1.07	0.03	0.00212	0.00
	LTE 5	QPSK10M	Top Side	20450	1	25	25	23.0	22.88	1.03	-0.02	0.0017	0.00
	LTE 5	QPSK10M	Bottom Side	20450	0	1	49	24.0	23.70	1.07	0.04	0.029	0.03
	LTE 5	QPSK10M	Bottom Side	20450	0	25	25	23.0	22.88	1.03	0.08	0.025	0.03



# FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 7	QPSK20M	Front Face	21350	0	1	0	23.0	22.99	1.00	-0.02	0.327	0.33
	LTE 7	QPSK20M	Front Face	21350	1	1	0	23.0	22.99	1.00	0.07	0.035	0.04
	LTE 7	QPSK20M	Front Face	21350	0	50	0	22.0	21.98	1.00	0.05	0.264	0.27
	LTE 7	QPSK20M	Front Face	21350	1	50	0	22.0	21.98	1.00	0.03	0.032	0.03
23	LTE 7	QPSK20M	Rear Face	21350	0	1	0	23.0	22.99	1.00	-0.02	0.361	0.36
	LTE 7	QPSK20M	Rear Face	21350	1	1	0	23.0	22.99	1.00	0.04	0.023	0.02
	LTE 7	QPSK20M	Rear Face	21350	0	50	0	22.0	21.98	1.00	-0.03	0.292	0.29
	LTE 7	QPSK20M	Rear Face	21350	1	50	0	22.0	21.98	1.00	-0.07	0.021	0.02
	LTE 7	QPSK20M	Left Side	21350	0	1	0	23.0	22.99	1.00	-0.06	0.343	0.34
	LTE 7	QPSK20M	Left Side	21350	1	1	0	23.0	22.99	1.00	-0.03	0.033	0.03
	LTE 7	QPSK20M	Left Side	21350	0	50	0	22.0	21.98	1.00	0.03	0.248	0.25
	LTE 7	QPSK20M	Left Side	21350	1	50	0	22.0	21.98	1.00	-0.05	0.03	0.03
	LTE 7	QPSK20M	Right Side	21350	0	1	0	23.0	22.99	1.00	0.01	0.017	0.02
	LTE 7	QPSK20M	Right Side	21350	1	1	0	23.0	22.99	1.00	0	0	0.00
	LTE 7	QPSK20M	Right Side	21350	0	50	0	22.0	21.98	1.00	0.02	0.016	0.02
	LTE 7	QPSK20M	Right Side	21350	1	50	0	22.0	21.98	1.00	0	0	0.00
	LTE 7	QPSK20M	Top Side	21350	1	1	0	23.0	22.99	1.00	0.1	0.00614	0.01
	LTE 7	QPSK20M	Top Side	21350	1	50	0	22.0	21.98	1.00	0.03	0.00558	0.01
	LTE 7	QPSK20M	Bottom Side	21350	0	1	0	23.0	22.99	1.00	-0.01	0.167	0.17
	LTE 7	QPSK20M	Bottom Side	21350	0	50	0	22.0	21.98	1.00	-0.03	0.125	0.13
	LTE 12	QPSK10M	Front Face	23130	0	1	49	23.5	22.94	1.14	0.01	0.160	0.18
	LTE 12	QPSK10M	Front Face	23130	1	1	49	23.5	22.94	1.14	-0.05	0.00257	0.00
	LTE 12	QPSK10M	Front Face	23130	0	25	25	22.5	22.27	1.05	-0.03	0.141	0.15
	LTE 12	QPSK10M	Front Face	23130	1	25	25	22.5	22.27	1.05	-0.01	0.00213	0.00
24	LTE 12	QPSK10M	Rear Face	23130	0	1	49	23.5	22.94	1.14	-0.07	0.203	0.23
	LTE 12	QPSK10M	Rear Face	23130	1	1	49	23.5	22.94	1.14	0.09	0.00039	0.00
	LTE 12	QPSK10M	Rear Face	23130	0	25	25	22.5	22.27	1.05	0.06	0.177	0.19
	LTE 12	QPSK10M	Rear Face	23130	1	25	25	22.5	22.27	1.05	0.03	0.00032	0.00
	LTE 12	QPSK10M	Left Side	23130	0	1	49	23.5	22.94	1.14	0.01	0.137	0.16
	LTE 12	QPSK10M	Left Side	23130	1	1	49	23.5	22.94	1.14	0.02	0.00028	0.00
	LTE 12	QPSK10M	Left Side	23130	0	25	25	22.5	22.27	1.05	-0.11	0.124	0.13
	LTE 12	QPSK10M	Left Side	23130	1	25	25	22.5	22.27	1.05	0.01	0.00023	0.00
	LTE 12	QPSK10M	Right Side	23130	0	1	49	23.5	22.94	1.14	0.03	0.158	0.18
	LTE 12	QPSK10M	Right Side	23130	1	1	49	23.5	22.94	1.14	0	0	0.00
	LTE 12	QPSK10M	Right Side	23130	0	25	25	22.5	22.27	1.05	0.01	0.138	0.15
	LTE 12	QPSK10M	Right Side	23130	1	25	25	22.5	22.27	1.05	0	0	0.00
	LTE 12	QPSK10M	Top Side	23130	1	1	49	23.5	22.94	1.14	0	0	0.00
	LTE 12	QPSK10M	Top Side	23130	1	25	25	22.5	22.27	1.05	0	0	0.00
	LTE 12	QPSK10M	Bottom Side	23130	0	1	49	23.5	22.94	1.14	0.07	0.028	0.03
	LTE 12	QPSK10M	Bottom Side	23130	0	25	25	22.5	22.27	1.05	-0.05	0.024	0.03



# FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 13	QPSK10M	Front Face	23230	0	1	24	23.0	22.99	1.00	0.02	0.109	0.11
	LTE 13	QPSK10M	Front Face	23230	1	1	24	23.0	22.99	1.00	0.02	0.00610	0.01
	LTE 13	QPSK10M	Front Face	23230	0	25	0	22.0	21.99	1.00	-0.04	0.096	0.10
	LTE 13	QPSK10M	Front Face	23230	1	25	0	22.0	21.99	1.00	0.01	0.00220	0.00
25	LTE 13	QPSK10M	Rear Face	23230	0	1	24	23.0	22.99	1.00	0.01	0.142	0.14
	LTE 13	QPSK10M	Rear Face	23230	1	1	24	23.0	22.99	1.00	-0.06	0.00881	0.01
	LTE 13	QPSK10M	Rear Face	23230	0	25	0	22.0	21.99	1.00	0.03	0.124	0.12
	LTE 13	QPSK10M	Rear Face	23230	1	25	0	22.0	21.99	1.00	0.03	0.00288	0.00
	LTE 13	QPSK10M	Left Side	23230	0	1	24	23.0	22.99	1.00	0.07	0.077	0.08
	LTE 13	QPSK10M	Left Side	23230	1	1	24	23.0	22.99	1.00	-0.02	0.00420	0.00
	LTE 13	QPSK10M	Left Side	23230	0	25	0	22.0	21.99	1.00	-0.05	0.065	0.07
	LTE 13	QPSK10M	Left Side	23230	1	25	0	22.0	21.99	1.00	0.03	0.00099	0.00
	LTE 13	QPSK10M	Right Side	23230	0	1	24	23.0	22.99	1.00	0.03	0.097	0.10
	LTE 13	QPSK10M	Right Side	23230	1	1	24	23.0	22.99	1.00	-0.06	0.00349	0.00
	LTE 13	QPSK10M	Right Side	23230	0	25	0	22.0	21.99	1.00	0.07	0.084	0.08
	LTE 13	QPSK10M	Right Side	23230	1	25	0	22.0	21.99	1.00	0.05	0.00082	0.00
	LTE 13	QPSK10M	Top Side	23230	1	1	24	23.0	22.99	1.00	0.06	0.00080	0.00
	LTE 13	QPSK10M	Top Side	23230	1	25	0	22.0	21.99	1.00	0.02	0.00019	0.00
	LTE 13	QPSK10M	Bottom Side	23230	0	1	24	23.0	22.99	1.00	0.15	0.045	0.05
	LTE 13	QPSK10M	Bottom Side	23230	0	25	0	22.0	21.99	1.00	-0.06	0.038	0.04
	LTE 25	QPSK20M	Front Face	26365	0	1	0	23.5	23.45	1.01	0.04	0.253	0.26
	LTE 25	QPSK20M	Front Face	26365	1	1	0	23.5	23.45	1.01	0.01	0.089	0.09
	LTE 25	QPSK20M	Front Face	26365	0	50	0	22.5	22.48	1.00	0.09	0.231	0.23
	LTE 25	QPSK20M	Front Face	26365	1	50	0	22.5	22.48	1.00	0.05	0.071	0.07
26	LTE 25	QPSK20M	Rear Face	26365	0	1	0	23.5	23.45	1.01	-0.14	0.317	0.32
	LTE 25	QPSK20M	Rear Face	26365	1	1	0	23.5	23.45	1.01	-0.09	0.126	0.13
	LTE 25	QPSK20M	Rear Face	26365	0	50	0	22.5	22.48	1.00	0.01	0.295	0.30
	LTE 25	QPSK20M	Rear Face	26365	1	50	0	22.5	22.48	1.00	0.08	0.097	0.10
	LTE 25	QPSK20M	Left Side	26365	0	1	0	23.5	23.45	1.01	-0.05	0.267	0.27
	LTE 25	QPSK20M	Left Side	26365	1	1	0	23.5	23.45	1.01		0.14	0.14
	LTE 25	QPSK20M	Left Side	26365	0	50	0	22.5	22.48	1.00	0.06	0.246	0.25
	LTE 25	QPSK20M	Left Side	26365	1	50	0	22.5	22.48	1.00	0.14	0.106	0.11
	LTE 25	QPSK20M	Right Side	26365	0	1	0	23.5	23.45	1.01	0.11	0.076	0.08
	LTE 25	QPSK20M	Right Side	26365	1	1	0	23.5	23.45	1.01	0.08	0.018	0.02
	LTE 25	QPSK20M	Right Side	26365	0	50	0	22.5	22.48	1.00	-0.05	0.066	0.07
	LTE 25	QPSK20M	Right Side	26365	1	50	0	22.5	22.48	1.00	0.07	0.013	0.01
	LTE 25	QPSK20M	Top Side	26365	1	1	0	23.5	23.45	1.01	0.01	0.103	0.10
	LTE 25	QPSK20M	Top Side	26365	1	50	0	22.5	22.48	1.00	-0.02	0.09	0.09
	LTE 25	QPSK20M	Bottom Side	26365	0	1	0	23.5	23.45	1.01	0.06	0.28	0.28
	LTE 25	QPSK20M	Bottom Side	26365	0	50	0	22.5	22.48	1.00	0.01	0.237	0.24





# FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
27	LTE 26	QPSK15M	Front Face	26965	0	1	74	24.0	23.86	1.03	0.06	0.066	0.07
	LTE 26	QPSK15M	Front Face	26965	1	1	74	24.0	23.86	1.03	-0.06	0.02	0.02
	LTE 26	QPSK15M	Front Face	26965	0	36	39	23.0	22.77	1.05	0.04	0.057	0.06
	LTE 26	QPSK15M	Front Face	26965	1	36	39	23.0	22.77	1.05	0.01	0.016	0.02
	LTE 26	QPSK15M	Rear Face	26965	0	1	74	24.0	23.86	1.03	-0.1	0.049	0.05
	LTE 26	QPSK15M	Rear Face	26965	1	1	74	24.0	23.86	1.03	-0.07	0.029	0.03
	LTE 26	QPSK15M	Rear Face	26965	0	36	39	23.0	22.77	1.05	0.07	0.041	0.04
	LTE 26	QPSK15M	Rear Face	26965	1	36	39	23.0	22.77	1.05	-0.03	0.024	0.03
	LTE 26	QPSK15M	Left Side	26965	0	1	74	24.0	23.86	1.03	0.17	0.017	0.02
	LTE 26	QPSK15M	Left Side	26965	1	1	74	24.0	23.86	1.03	0.02	0.028	0.03
	LTE 26	QPSK15M	Left Side	26965	0	36	39	23.0	22.77	1.05	0.18	0.015	0.02
	LTE 26	QPSK15M	Left Side	26965	1	36	39	23.0	22.77	1.05	0.13	0.022	0.02
	LTE 26	QPSK15M	Right Side	26965	0	1	74	24.0	23.86	1.03	-0.03	0.02	0.02
	LTE 26	QPSK15M	Right Side	26965	1	1	74	24.0	23.86	1.03	0.03	0.019	0.02
	LTE 26	QPSK15M	Right Side	26965	0	36	39	23.0	22.77	1.05	0	0.017	0.02
	LTE 26	QPSK15M	Right Side	26965	1	36	39	23.0	22.77	1.05	0.06	0.015	0.02
	LTE 26	QPSK15M	Top Side	26965	1	1	74	24.0	23.86	1.03	0.18	0.0021	0.00
	LTE 26	QPSK15M	Top Side	26965	1	36	39	23.0	22.77	1.05	-0.12	0.00163	0.00
	LTE 26	QPSK15M	Bottom Side	26965	0	1	74	24.0	23.86	1.03	0.18	0.044	0.05
	LTE 26	QPSK15M	Bottom Side	26965	0	36	39	23.0	22.77	1.05	0.13	0.037	0.04
	LTE 41	QPSK20M	Front Face	41490	0	1	0	23.5	23.28	1.05	-0.12	0.172	0.18
	LTE 41	QPSK20M	Front Face	41490	1	1	0	23.5	23.28	1.05	0.17	0.026	0.03
	LTE 41	QPSK20M	Front Face	41490	0	50	0	22.5	22.14	1.09	0.16	0.137	0.15
	LTE 41	QPSK20M	Front Face	41490	1	50	0	22.5	22.14	1.09	-0.12	0.022	0.02
28	LTE 41	QPSK20M	Rear Face	41490	0	1	0	23.5	23.28	1.05	-0.08	0.195	0.21
	LTE 41	QPSK20M	Rear Face	41490	1	1	0	23.5	23.28	1.05	-0.02	0.012	0.01
	LTE 41	QPSK20M	Rear Face	41490	0	50	0	22.5	22.14	1.09	-0.02	0.142	0.15
	LTE 41	QPSK20M	Rear Face	41490	1	50	0	22.5	22.14	1.09	-0.14	0.009	0.01
	LTE 41	QPSK20M	Left Side	41490	0	1	0	23.5	23.28	1.05	0.06	0.191	0.20
	LTE 41	QPSK20M	Left Side	41490	1	1	0	23.5	23.28	1.05	0.14	0.035	0.04
	LTE 41	QPSK20M	Left Side	41490	0	50	0	22.5	22.14	1.09	-0.18	0.152	0.17
	LTE 41	QPSK20M	Left Side	41490	1	50	0	22.5	22.14	1.09	-0.12	0.025	0.03
	LTE 41	QPSK20M	Right Side	41490	0	1	0	23.5	23.28	1.05	-0.14	0.00	0.00
	LTE 41	QPSK20M	Right Side	41490	1	1	0	23.5	23.28	1.05	-0.17	0.00	0.00
	LTE 41	QPSK20M	Right Side	41490	0	50	0	22.5	22.14	1.09	-0.11	0.00	0.00
	LTE 41	QPSK20M	Right Side	41490	1	50	0	22.5	22.14	1.09	-0.08	0.00	0.00
	LTE 41	QPSK20M	Top Side	41490	1	1	0	23.5	23.28	1.05	-0.14	0.002	0.00
	LTE 41	QPSK20M	Top Side	41490	1	50	0	22.5	22.14	1.09	-0.08	0.001	0.00
	LTE 41	QPSK20M	Bottom Side	41490	0	1	0	23.5	23.28	1.05	-0.16	0.094	0.10
	LTE 41	QPSK20M	Bottom Side	41490	0	50	0	22.5	22.14	1.09	0.07	0.079	0.09



# FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
29	2.4G WLAN	802.11b	Front Face	6	0	20.0	18.22	1.51	0.07	0.031	0.05
	2.4G WLAN	802.11b	Front Face	1	1	20.0	18.09	1.55	0.11	0.05	<b>0.08</b>
	2.4G WLAN	802.11n HT40	Front Face	3	0+1	18.0	16.14	1.53	0.03	0.00214	0.00
	2.4G WLAN	802.11b	Rear Face	6	0	20.0	18.22	1.51	0.19	0.017	0.03
	2.4G WLAN	802.11b	Rear Face	1	1	20.0	18.09	1.55	0.11	0.017	0.03
	2.4G WLAN	802.11n HT40	Rear Face	3	0+1	18.0	16.14	1.53	0	0	0.00
	2.4G WLAN	802.11b	Right Side	6	0	20.0	18.22	1.51	0.11	0.017	0.03
	2.4G WLAN	802.11b	Right Side	1	1	20.0	18.09	1.55	0.19	0.014	0.02
	2.4G WLAN	802.11n HT40	Right Side	3	0+1	18.0	16.14	1.53	0	0	0.00
	2.4G WLAN	802.11b	Top Side	6	0	20.0	18.22	1.51	0.04	0.001	0.00
	2.4G WLAN	802.11n HT40	Top Side	3	0+1	18.0	16.14	1.53	0	0	0.00
	2.4G WLAN	802.11b	Bottom Side	1	1	20.0	18.09	1.55	0.12	0.019	0.03
	2.4G WLAN	802.11n HT40	Bottom Side	3	0+1	18.0	16.14	1.53	0	0	0.00
	32	5.8G WLAN	802.11ac-VH80	Front Face	155	0	17.5	15.87	1.46	0.08	0.015
5.8G WLAN		802.11ac-VH80	Front Face	155	1	17.5	15.64	1.53	0	0	0.00
5.8G WLAN		802.11ac-VH80	Front Face	155	0+1	17.5	15.90	1.45	0	0	0.00
5.8G WLAN		802.11ac-VH80	Rear Face	155	0	17.5	15.87	1.46	0	0	0.00
5.8G WLAN		802.11ac-VH80	Rear Face	155	1	17.5	15.64	1.53	0	0	0.00
5.8G WLAN		802.11ac-VH80	Rear Face	155	0+1	17.5	15.90	1.45	0	0	0.00
5.8G WLAN		802.11ac-VH80	Right Side	155	0	17.5	15.87	1.46	0.01	0.00108	0.00
5.8G WLAN		802.11ac-VH80	Right Side	155	1	17.5	15.64	1.53	0	0	0.00
5.8G WLAN		802.11ac-VH80	Right Side	155	0+1	17.5	15.90	1.45	0	0	0.00
5.8G WLAN		802.11ac-VH80	Top Side	155	0	17.5	15.87	1.46	0	0	0.00
5.8G WLAN		802.11ac-VH80	Top Side	155	0+1	17.5	15.90	1.45	0	0	0.00
5.8G WLAN		802.11ac-VH80	Bottom Side	155	1	17.5	15.64	1.53	0	0	0.00
5.8G WLAN		802.11ac-VH80	Bottom Side	155	0+1	17.5	15.90	1.45	0	0	0.00

## FCC SAR Test Report

---

### 4.7.5 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Since all the measured SAR are less than 0.8 W/kg, the repeated measurement is not required.

# FCC SAR Test Report

## 4.7.6 Simultaneous Multi-band Transmission Evaluation

### <SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR<sub>1g</sub> of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR<sub>1g</sub> is greater than the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
1	CDMA BC0 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.19	0.14	-	0.33	Σ SAR < 1.6, Not required
			Right Tilted	0.13	0.05	-	0.18	Σ SAR < 1.6, Not required
			Left Cheek	0.12	0.47	-	0.59	Σ SAR < 1.6, Not required
			Left Tilted	0.08	0.20	-	0.28	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.23	0.08	0.00	0.31	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.03	0.00	0.30	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.23	0.08	-	0.31	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.03	-	0.30	Σ SAR < 1.6, Not required
			Left Side	0.19	0.00	-	0.19	Σ SAR < 1.6, Not required
			Right Side	0.22	0.03	-	0.25	Σ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
			Bottom Side	0.06	0.03	-	0.09	Σ SAR < 1.6, Not required
		2	CDMA BC0 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.19	0.49	-
Right Tilted	0.13				0.39	-	0.52	Σ SAR < 1.6, Not required
Left Cheek	0.12				0.73	-	0.85	Σ SAR < 1.6, Not required
Left Tilted	0.08				0.63	-	0.71	Σ SAR < 1.6, Not required
Body-Worn	Front Face			0.23	0.02	0.00	0.25	Σ SAR < 1.6, Not required
	Rear Face			0.27	0.00	0.00	0.27	Σ SAR < 1.6, Not required
Hotspot	Front Face			0.23	0.02	-	0.25	Σ SAR < 1.6, Not required
	Rear Face			0.27	0.00	-	0.27	Σ SAR < 1.6, Not required
	Left Side			0.19	0.00	-	0.19	Σ SAR < 1.6, Not required
	Right Side			0.22	0.00	-	0.22	Σ SAR < 1.6, Not required
	Top Side			0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
	Bottom Side			0.06	0.00	-	0.06	Σ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
3	CDMA BC1 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.68	0.14	-	0.82	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.66	0.05	-	0.71	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.38	0.47	-	0.85	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.42	0.20	-	0.62	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.39	0.08	0.00	0.47	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.47	0.03	0.00	0.50	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.39	0.08	-	0.47	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.47	0.03	-	0.50	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.43	0.00	-	0.43	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.14	0.03	-	0.17	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.15	0.00	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.40	0.03	-	0.43	$\Sigma$ SAR < 1.6, Not required
4	CDMA BC1 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.68	0.49	-	1.17	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.66	0.39	-	1.05	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.38	0.73	-	1.11	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.42	0.63	-	1.05	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.39	0.02	0.00	0.41	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.47	0.00	0.00	0.47	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.39	0.02	-	0.41	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.47	0.00	-	0.47	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.43	0.00	-	0.43	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.14	0.00	-	0.14	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.15	0.00	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.40	0.00	-	0.40	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
5	CDMA BC10 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.18	0.14	-	0.32	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.12	0.05	-	0.17	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.12	0.47	-	0.59	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.08	0.20	-	0.28	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.22	0.08	0.00	0.30	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.26	0.03	0.00	0.29	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.22	0.08	-	0.30	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.26	0.03	-	0.29	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.19	0.00	-	0.19	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.21	0.03	-	0.24	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.06	0.03	-	0.09	$\Sigma$ SAR < 1.6, Not required
6	CDMA BC10 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.18	0.49	-	0.67	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.12	0.39	-	0.51	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.12	0.73	-	0.85	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.08	0.63	-	0.71	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.22	0.02	0.00	0.24	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.26	0.00	0.00	0.26	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.22	0.02	-	0.24	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.26	0.00	-	0.26	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.19	0.00	-	0.19	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.21	0.00	-	0.21	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.06	0.00	-	0.06	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
7	LTE 2 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.37	0.14	-	0.51	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.35	0.05	-	0.40	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.25	0.47	-	0.72	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.26	0.20	-	0.46	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.32	0.08	0.00	0.40	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.34	0.03	0.00	0.37	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.32	0.08	-	0.40	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.34	0.03	-	0.37	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.33	0.00	-	0.33	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.04	0.03	-	0.07	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.10	0.00	-	0.10	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.29	0.03	-	0.32	$\Sigma$ SAR < 1.6, Not required
8	LTE 2 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.37	0.49	-	0.86	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.35	0.39	-	0.74	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.25	0.73	-	0.98	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.26	0.63	-	0.89	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.32	0.02	0.00	0.34	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.34	0.00	0.00	0.34	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.32	0.02	-	0.34	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.34	0.00	-	0.34	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.33	0.00	-	0.33	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.04	0.00	-	0.04	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.10	0.00	-	0.10	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.29	0.00	-	0.29	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
9	LTE 4 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.66	0.14	-	0.80	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.51	0.05	-	0.56	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.43	0.47	-	0.90	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.38	0.20	-	0.58	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.41	0.08	0.00	0.49	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.55	0.03	0.00	0.58	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.41	0.08	-	0.49	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.55	0.03	-	0.58	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.24	0.00	-	0.24	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.13	0.03	-	0.16	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.15	0.00	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.59	0.03	-	0.62	$\Sigma$ SAR < 1.6, Not required
10	LTE 4 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.66	0.49	-	1.15	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.51	0.39	-	0.90	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.43	0.73	-	1.16	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.38	0.63	-	1.01	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.41	0.02	0.00	0.43	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.55	0.00	0.00	0.55	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.41	0.02	-	0.43	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.55	0.00	-	0.55	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.24	0.00	-	0.24	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.13	0.00	-	0.13	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.15	0.00	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.59	0.00	-	0.59	$\Sigma$ SAR < 1.6, Not required





# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
11	LTE 5 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.15	0.14	-	0.29	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.10	0.05	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.13	0.47	-	0.60	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.09	0.20	-	0.29	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.13	0.08	0.00	0.21	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.15	0.03	0.00	0.18	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.13	0.08	-	0.21	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.15	0.03	-	0.18	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.09	0.00	-	0.09	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.11	0.03	-	0.14	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.03	0.03	-	0.06	$\Sigma$ SAR < 1.6, Not required
12	LTE 5 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.15	0.49	-	0.64	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.10	0.39	-	0.49	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.13	0.73	-	0.86	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.09	0.63	-	0.72	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.13	0.02	0.00	0.15	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.15	0.00	0.00	0.15	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.13	0.02	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.15	0.00	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.09	0.00	-	0.09	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.11	0.00	-	0.11	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.03	0.00	-	0.03	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
13	LTE 7 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.24	0.14	-	0.38	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.10	0.05	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.39	0.47	-	0.86	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.08	0.20	-	0.28	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.33	0.08	0.00	0.41	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.36	0.03	0.00	0.39	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.33	0.08	-	0.41	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.36	0.03	-	0.39	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.34	0.00	-	0.34	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.02	0.03	-	0.05	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.01	0.00	-	0.01	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.17	0.03	-	0.20	$\Sigma$ SAR < 1.6, Not required
14	LTE 7 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.24	0.49	-	0.73	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.10	0.39	-	0.49	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.39	0.73	-	1.12	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.08	0.63	-	0.71	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.33	0.02	0.00	0.35	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.36	0.00	0.00	0.36	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.33	0.02	-	0.35	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.36	0.00	-	0.36	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.34	0.00	-	0.34	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.02	0.00	-	0.02	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.01	0.00	-	0.01	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.17	0.00	-	0.17	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
15	LTE 12 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.13	0.14	-	0.27	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.10	0.05	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.12	0.47	-	0.59	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.11	0.20	-	0.31	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.18	0.08	0.00	0.26	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.23	0.03	0.00	0.26	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.18	0.08	-	0.26	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.23	0.03	-	0.26	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.16	0.00	-	0.16	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.18	0.03	-	0.21	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.03	0.03	-	0.06	$\Sigma$ SAR < 1.6, Not required
16	LTE 12 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.13	0.49	-	0.62	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.10	0.39	-	0.49	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.12	0.73	-	0.85	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.11	0.63	-	0.74	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.18	0.02	0.00	0.20	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.23	0.00	0.00	0.23	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.18	0.02	-	0.20	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.23	0.00	-	0.23	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.16	0.00	-	0.16	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.18	0.00	-	0.18	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.03	0.00	-	0.03	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
17	LTE 13 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.07	0.14	-	0.21	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.04	0.05	-	0.09	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.06	0.47	-	0.53	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.04	0.20	-	0.24	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.11	0.08	0.00	0.19	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.14	0.03	0.00	0.17	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.11	0.08	-	0.19	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.14	0.03	-	0.17	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.08	0.00	-	0.08	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.10	0.03	-	0.13	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.05	0.03	-	0.08	$\Sigma$ SAR < 1.6, Not required
18	LTE 13 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.07	0.49	-	0.56	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.04	0.39	-	0.43	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.06	0.73	-	0.79	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.04	0.63	-	0.67	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.11	0.02	0.00	0.13	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.14	0.00	0.00	0.14	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.11	0.02	-	0.13	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.14	0.00	-	0.14	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.08	0.00	-	0.08	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.10	0.00	-	0.10	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.05	0.00	-	0.05	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
19	LTE 25 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.38	0.14	-	0.52	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.35	0.05	-	0.40	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.22	0.47	-	0.69	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.26	0.20	-	0.46	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.26	0.08	0.00	0.34	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.32	0.03	0.00	0.35	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.26	0.08	-	0.34	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.32	0.03	-	0.35	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.27	0.00	-	0.27	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.08	0.03	-	0.11	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.10	0.00	-	0.10	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.28	0.03	-	0.31	$\Sigma$ SAR < 1.6, Not required
20	LTE 25 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.38	0.49	-	0.87	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.35	0.39	-	0.74	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.22	0.73	-	0.95	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.26	0.63	-	0.89	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.26	0.02	0.00	0.28	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.32	0.00	0.00	0.32	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.26	0.02	-	0.28	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.32	0.00	-	0.32	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.27	0.00	-	0.27	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.08	0.00	-	0.08	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.10	0.00	-	0.10	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.28	0.00	-	0.28	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
21	LTE 26 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.13	0.14	-	0.27	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.06	0.05	-	0.11	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.08	0.47	-	0.55	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.04	0.20	-	0.24	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.07	0.08	0.00	0.15	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.05	0.03	0.00	0.08	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.07	0.08	-	0.15	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.05	0.03	-	0.08	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.03	0.00	-	0.03	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.02	0.03	-	0.05	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.05	0.03	-	0.08	$\Sigma$ SAR < 1.6, Not required
22	LTE 26 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.13	0.49	-	0.62	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.06	0.39	-	0.45	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.08	0.73	-	0.81	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.04	0.63	-	0.67	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.07	0.02	0.00	0.09	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.05	0.00	0.00	0.05	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.07	0.02	-	0.09	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.05	0.00	-	0.05	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.03	0.00	-	0.03	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.02	0.00	-	0.02	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.05	0.00	-	0.05	$\Sigma$ SAR < 1.6, Not required



# FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
23	LTE 41 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.20	0.14	-	0.34	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.14	0.05	-	0.19	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.22	0.47	-	0.69	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.09	0.20	-	0.29	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.18	0.08	0.00	0.26	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.21	0.03	0.00	0.24	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.18	0.08	-	0.26	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.21	0.03	-	0.24	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.20	0.00	-	0.20	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.00	0.03	-	0.03	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.10	0.03	-	0.13	$\Sigma$ SAR < 1.6, Not required
24	LTE 41 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.20	0.49	-	0.69	$\Sigma$ SAR < 1.6, Not required
			Right Tilted	0.14	0.39	-	0.53	$\Sigma$ SAR < 1.6, Not required
			Left Cheek	0.22	0.73	-	0.95	$\Sigma$ SAR < 1.6, Not required
			Left Tilted	0.09	0.63	-	0.72	$\Sigma$ SAR < 1.6, Not required
		Body-Worn	Front Face	0.18	0.02	0.00	0.20	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.21	0.00	0.00	0.21	$\Sigma$ SAR < 1.6, Not required
		Hotspot	Front Face	0.18	0.02	-	0.20	$\Sigma$ SAR < 1.6, Not required
			Rear Face	0.21	0.00	-	0.21	$\Sigma$ SAR < 1.6, Not required
			Left Side	0.20	0.00	-	0.20	$\Sigma$ SAR < 1.6, Not required
			Right Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	$\Sigma$ SAR < 1.6, Not required
			Bottom Side	0.10	0.00	-	0.10	$\Sigma$ SAR < 1.6, Not required

Test Engineer : Willy Chang, and Chiajui Fu



## 5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D750V3	1013	Aug. 24, 2015	1 Year
System Validation Dipole	SPEAG	D835V2	4d121	Aug. 24, 2015	1 Year
System Validation Dipole	SPEAG	D1750V2	1055	Aug. 20, 2015	1 Year
System Validation Dipole	SPEAG	D1900V2	5d036	Jan. 22, 2016	1 Year
System Validation Dipole	SPEAG	D2450V2	737	Aug. 20, 2015	1 Year
System Validation Dipole	SPEAG	D2600V2	1020	Aug. 19, 2015	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1019	Aug. 28, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3864	Jul. 23, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	7346	Sep. 02, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3650	Jul. 23, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	861	Apr. 28, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	916	Dec. 16, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1277	Jul. 22, 2015	1 Year
Wireless Communication Test Set	Agilent	E5515C	MY50266628	Nov. 05, 2015	2 Years
Radio Communication Analyzer	Anritsu	MT8820C	6201300638	Jul. 29, 2015	1 Year
ENA Series Network Analyzer	Agilent	E5071C	MY46214281	Jun. 23, 2015	1 Year
EXA Spectrum Analyzer	Agilent	N9010A	MY52220314	Oct. 23, 2015	1 Year
EXG-B MW Analog Signal Generator	Agilent	N5173B	MY53270724	Jan. 20, 2016	1 Year
Power Meter	Anritsu	ML2495A	1218009	Jul. 06, 2015	1 Year
Power Sensor	Anritsu	MA2411B	1207252	Jul. 06, 2015	1 Year
Thermometer	YFE	YF-160A	130504579	Aug. 20, 2015	1 Year



# FCC SAR Test Report

## 6. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
<b>Measurement System</b>								
Probe Calibration	6.0	Normal	1	1	1	6.0	6.0	∞
Axial Isotropy	4.7	Rectangular	√3	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.707	0.707	3.9	3.9	∞
Boundary Effect	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	2.0	Rectangular	√3	1	1	1.2	1.2	∞
<b>Test Sample Related</b>								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	∞
<b>Phantom and Tissue Parameters</b>								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.2	Rectangular	√3	1	1	4.2	4.2	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
<b>Combined Standard Uncertainty</b>						± 11.2 %	± 10.4 %	
<b>Expanded Uncertainty (K=2)</b>						± 22.4 %	± 20.8 %	

**Uncertainty budget for frequency range 300 MHz to 3 GHz**



# FCC SAR Test Report

A D T

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
<b>Measurement System</b>								
Probe Calibration	6.55	Normal	1	1	1	6.55	6.55	∞
Axial Isotropy	4.7	Rectangular	√3	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.707	0.707	3.9	3.9	∞
Boundary Effect	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	6.7	Rectangular	√3	1	1	3.9	3.9	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	4.0	Rectangular	√3	1	1	2.3	2.3	∞
<b>Test Sample Related</b>								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	∞
<b>Phantom and Tissue Parameters</b>								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.6	Rectangular	√3	1	1	4.4	4.4	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
<b>Combined Standard Uncertainty</b>						± 12.3 %	± 11.5 %	
<b>Expanded Uncertainty (K=2)</b>						± 24.6 %	± 23.0 %	

Uncertainty budget for frequency range 3 GHz to 6 GHz



## FCC SAR Test Report

---

### 7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Taiwan HwaYa EMC/RF/Safety/Telecom Lab:**

Add: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-318-3232

Fax: 886-3-327-0892

**Taiwan LinKo EMC/RF Lab:**

Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180

Fax: 886-2-2605-1924

**Taiwan HsinChu EMC/RF Lab:**

Add: No. 81-1, Lu Liao Keng, 9<sup>th</sup> Ling, Wu Lung Vil., Chiung Lin Township, Hsinchu County 307, Taiwan, R.O.C.

Tel: 886-3-593-5343

Fax: 886-3-593-5342

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The road map of all our labs can be found in our web site also.

---END---