



FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : Smartphone
MODEL NAME : 2PYR100
FCC ID : NM82PYR100
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Sep. 05, 2016 and testing was completed on Sep. 30, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION5

1.1 Applicant.....5

1.2 Manufacturer5

1.3 Product Feature of Equipment Under Test5

1.4 Product Specification of Equipment Under Test6

1.5 Modification of EUT6

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator7

1.7 Testing Location7

1.8 Applicable Standards8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST9

2.1 Test Mode.....9

2.2 Connection Diagram of Test System10

2.3 Support Unit used in test configuration10

2.4 Measurement Results Explanation Example10

3 CONDUCTED TEST RESULT11

3.1 Measuring Instruments.....11

3.2 Test Setup11

3.3 Test Result of Conducted Test.....11

3.4 Conducted Output Power12

3.5 Peak-to-Average Ratio13

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....14

3.7 Conducted Band Edge15

3.8 Conducted Spurious Emission16

3.9 Frequency Stability.....17

4 RADIATED TEST ITEMS18

4.1 Measuring Instruments.....18

4.2 Test Setup18

4.3 Test Result of Radiated Test.....18

4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement19

4.5 Field Strength of Spurious Radiation Measurement20

5 LIST OF MEASURING EQUIPMENT21

6 UNCERTAINTY OF EVALUATION22

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 25.23 dB at 15044.500 MHz



1 General Description

1.1 Applicant

HTC Corporation

No.23, Xinghua Rd., Taoyuan District, Taoyuan City, Taiwan 330

1.2 Manufacturer

HTC Corporation

No.23, Xinghua Rd., Taoyuan District, Taoyuan City, Taiwan 330

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Model Name	2PYR100
FCC ID	NM82PYR100
Sample 1	EUT with battery 1 and LCD panel 1
Sample 2	EUT with battery 2 and LCD panel 2
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE WLAN 11b/g/n HT20/HT40 Bluetooth BR/EDR/LE
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. All the radiated test cases were performance with adapter 1, Earphone, USB cable 1, and sample 1.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	GSM/GPRS/EDGE: 850: 33.89 dBm 1900: 30.53 dBm WCDMA: Band V: 24.99 dBm Band II: 24.59 dBm Band IV: 25.43 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: BPSK (Uplink) HSDPA: 64QAM (Downlink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.7762	0.0072 ppm	246KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.2427	0.0036 ppm	246KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	BPSK	0.1189	0.0215 ppm	4M18F9W
Part 24	GSM1900 GPRS class 8	GMSK	1.0257	0.0096 ppm	246KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.4305	0.0048 ppm	248KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	BPSK	0.2523	0.0154 ppm	4M18F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	BPSK	0.2312	0.0271 ppm	4M19F9W

1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd., Kwei-Shan District, Tao Yuan City, Taiwan R.O.C. TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. : 03CH11-HY



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.



3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band).

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform (0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz) in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.

	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100



4.5 Field Strength of Spurious Radiation Measurement

4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 27, 2016	Sep. 29, 2016~ Sep. 30, 2016	Jun. 26, 2017	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Nov. 20, 2015	Sep. 29, 2016~ Sep. 30, 2016	Nov. 19, 2016	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL883644	Voltage:0~20V;Current:0~5A	Nov. 26, 2015	Sep. 29, 2016~ Sep. 30, 2016	Nov. 25, 2016	Conducted (TH03-HY)
Base Station (Measure)	Rohde & Schwarz	CMU200	117995	GSM / GPRS / WCDMA / CDMA	Aug. 03, 2016	Sep. 29, 2016~ Sep. 30, 2016	Aug.04, 2017	Conducted (TH03-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 20, 2015	Sep. 22, 2016~ Sep. 26, 2016	Nov. 19, 2016	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D	35414	30MHz~1GHz	Nov. 17, 2015	Sep. 22, 2016~ Sep. 26, 2016	Nov. 16, 2016	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 08, 2015	Sep. 22, 2016~ Sep. 26, 2016	Oct. 07, 2016	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 19, 2015	Sep. 22, 2016~ Sep. 26, 2016	Nov. 18, 2016	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY52350276	10Hz ~ 44GHZ	Mar. 21, 2016	Sep. 22, 2016~ Sep. 26, 2016	Mar. 20, 2017	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Sep. 22, 2016~ Sep. 26, 2016	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Sep. 22, 2016~ Sep. 26, 2016	N/A	Radiation (03CH11-HY)
Preamplifier	MITEQ	TTA0204	1872107	2GHz~40GHz	Feb. 15, 2016	Sep. 22, 2016~ Sep. 26, 2016	Feb. 14, 2017	Radiation (03CH11-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May. 19, 2016	Sep. 22, 2016~ Sep. 26, 2016	May. 18, 2017	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 02, 2015	Sep. 22, 2016~ Sep. 26, 2016	Nov. 01, 2016	Radiation (03CH11-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.40
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	33.87	33.88	33.85	30.37	30.49	30.52
GPRS class 8	33.88	33.89	33.87	30.38	30.50	30.53
GPRS class 10	32.46	32.44	32.41	29.78	29.92	29.85
GPRS class 11	31.56	31.54	31.50	29.09	29.03	29.13
GPRS class 12	30.30	30.30	30.25	28.15	28.10	28.23
EGPRS class 8	28.25	28.24	28.24	26.72	26.53	26.56
EGPRS class 10	27.90	27.88	27.86	26.41	26.24	26.26
EGPRS class 11	27.31	27.32	27.27	24.94	24.83	24.87
EGPRS class 12	25.30	25.25	25.24	23.82	23.73	23.80

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	24.99	24.90	24.93	24.28	24.56	24.59	25.27	25.17	25.43
HSDPA Subtest-1	24.18	24.16	24.21	23.53	23.78	23.82	24.40	24.31	24.41
HSDPA Subtest-2	24.20	24.18	24.25	23.63	23.83	23.91	24.43	24.33	24.37
HSDPA Subtest-3	23.75	23.72	23.79	23.34	23.48	23.55	23.92	23.87	23.89
HSDPA Subtest-4	23.69	23.65	23.75	23.32	23.46	23.51	23.92	23.88	23.97
HSUPA Subtest-1	23.64	23.81	23.87	23.72	24.02	23.99	24.25	24.32	24.29
HSUPA Subtest-2	22.63	22.70	22.84	22.73	22.92	22.83	22.80	23.00	22.95
HSUPA Subtest-3	22.06	22.29	22.36	23.01	23.18	23.04	23.25	23.44	23.32
HSUPA Subtest-4	23.26	23.42	23.49	23.10	23.25	23.20	23.20	23.38	23.27
HSUPA Subtest-5	23.96	24.19	24.29	23.89	24.12	24.10	24.48	24.33	24.41



Radiated Spurious Emission

GSM850 (GPRS class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-59.47	-13	-46.47	-64.19	-61.23	0.98	4.89	H
	2472	-57.90	-13	-44.90	-67.28	-59.78	1.28	5.32	H
	3296	-62.44	-13	-49.44	-74.95	-65.85	1.54	7.10	H
	1648	-62.61	-13	-49.61	-65.87	-64.37	0.98	4.89	V
	2472	-56.02	-13	-43.02	-66.37	-57.9	1.28	5.32	V
	3296	-63.95	-13	-50.95	-75.47	-67.36	1.54	7.10	V
Middle	1672	-60.68	-13	-47.68	-65.27	-62.36	0.99	4.82	H
	2512	-55.39	-13	-42.39	-64.95	-57.36	1.29	5.41	H
	3344	-62.59	-13	-49.59	-74.76	-66.2	1.56	7.31	H
	1672	-63.33	-13	-50.33	-66.35	-65.01	0.99	4.82	V
	2512	-53.54	-13	-40.54	-63.77	-55.51	1.29	5.41	V
	3344	-65.25	-13	-52.25	-76.64	-68.86	1.56	7.31	V
Highest	1696	-58.46	-13	-45.46	-63.17	-60.06	1.00	4.75	H
	2544	-57.28	-13	-44.28	-66.87	-59.26	1.30	5.44	H
	3392	-60.86	-13	-47.86	-73.13	-64.66	1.57	7.52	H
	1696	-61.53	-13	-48.53	-65.3	-63.13	1.00	4.75	V
	2544	-55.17	-13	-42.17	-65.4	-57.15	1.30	5.44	V
	3392	-63.27	-13	-50.27	-75.07	-67.07	1.57	7.52	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-58.13	-13	-45.13	-62.85	-59.89	0.98	4.89	H
	2472	-67.19	-13	-54.19	-76.57	-69.07	1.28	5.32	H
	3296	-64.57	-13	-51.57	-77.08	-67.98	1.54	7.10	H
	1648	-63.45	-13	-50.45	-66.71	-65.21	0.98	4.89	V
	2472	-65.94	-13	-52.94	-76.3	-67.82	1.28	5.32	V
	3296	-65.09	-13	-52.09	-76.61	-68.5	1.54	7.10	V
Middle	1672	-57.59	-13	-44.59	-62.18	-59.27	0.99	4.82	H
	2512	-66.28	-13	-53.28	-75.84	-68.25	1.29	5.41	H
	3345	-64.70	-13	-51.70	-76.87	-68.31	1.56	7.32	H
	1672	-60.91	-13	-47.91	-63.93	-62.59	0.99	4.82	V
	2512	-66.01	-13	-53.01	-76.24	-67.98	1.29	5.41	V
	3345	-65.66	-13	-52.66	-77.05	-69.27	1.56	7.32	V
Highest	1696	-57.99	-13	-44.99	-62.7	-59.59	1.00	4.75	H
	2544	-64.92	-13	-51.92	-74.51	-66.9	1.30	5.44	H
	3393	-64.87	-13	-51.87	-77.14	-68.68	1.57	7.53	H
	1696	-63.79	-13	-50.79	-67.56	-65.39	1.00	4.75	V
	2544	-63.90	-13	-50.90	-74.13	-65.88	1.30	5.44	V
	3393	-65.15	-13	-52.15	-76.95	-68.96	1.57	7.53	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GPRS class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-58.51	-13	-45.51	-73	-65.08	1.67	8.24	H
	5548	-49.55	-13	-36.55	-69.67	-56.62	2.65	9.72	H
	7400	-53.60	-13	-40.60	-79.13	-62.74	2.46	11.60	H
	3700	-61.58	-13	-48.58	-75.98	-68.15	1.67	8.24	V
	5548	-47.68	-13	-34.68	-66.26	-54.75	2.65	9.72	V
	7400	-54.95	-13	-41.95	-79.22	-64.09	2.46	11.60	V
	9251	-51.51	-13	-38.51	-77.68	-61.57	2.54	12.60	V
	12954.5	-40.20	-13	-27.20	-73.83	-50.23	2.92	12.94	V
14797.5	-41.33	-13	-28.33	-77.2	-51.17	3.51	13.36	V	
Middle	3763	-53.62	-13	-40.62	-68.32	-60.25	1.69	8.32	H
	5639	-40.73	-13	-27.73	-60.63	-47.78	2.71	9.76	H
	7520	-54.08	-13	-41.08	-79.07	-63.47	2.42	11.81	H
	3763	-59.40	-13	-46.40	-73.67	-66.03	1.69	8.32	V
	5639	-44.43	-13	-31.43	-62.83	-51.48	2.71	9.76	V
	7520	-54.90	-13	-41.90	-78.99	-64.29	2.42	11.81	V
	9398	-51.91	-13	-38.91	-77.41	-61.88	2.57	12.54	V
	13163.5	-40.07	-13	-27.07	-74.59	-50.33	2.97	13.23	V
15044.5	-38.23	-13	-25.23	-74.18	-48.28	3.62	13.66	V	
Highest	3819	-61.95	-13	-48.95	-76.73	-68.63	1.70	8.38	H
	5730	-51.03	-13	-38.03	-71.18	-58.06	2.76	9.79	H
	7639	-54.63	-13	-41.63	-79.33	-64.13	2.38	11.88	H
	3819	-63.10	-13	-50.10	-77.23	-69.78	1.70	8.38	V
	5730	-50.73	-13	-37.73	-69.71	-57.76	2.76	9.79	V
	7639	-55.31	-13	-42.31	-79.31	-64.81	2.38	11.88	V
	13372.5	-39.15	-13	-26.15	-74.54	-49.65	3.02	13.52	V
	15282	-38.82	-13	-25.82	-75.15	-49.1	3.72	13.99	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-56.05	-13	-43.05	-70.54	-62.62	1.67	8.24	H
	5548	-48.82	-13	-35.82	-68.94	-55.89	2.65	9.72	H
	7400	-53.92	-13	-40.92	-79.45	-63.06	2.46	11.60	H
	12954.5	-39.82	-13	-26.82	-77.34	-49.85	2.92	12.94	H
	3700	-69.09	-13	-56.09	-75.66	-75.66	1.67	8.24	V
	5548	-57.44	-13	-44.44	-64.51	-64.51	2.65	9.72	V
	7400	-70.08	-13	-57.08	-79.22	-79.22	2.46	11.60	V
	12954.5	-44.36	-13	-31.36	-77.99	-54.39	2.92	12.94	V
Middle	3763	-57.89	-13	-44.89	-72.59	-64.52	1.69	8.32	H
	5639	-46.45	-13	-33.45	-66.35	-53.5	2.71	9.76	H
	7520	-53.99	-13	-40.99	-78.98	-63.38	2.42	11.81	H
	13163.5	-38.70	-13	-25.70	-76.42	-48.96	2.97	13.23	H
	3763	-59.67	-13	-46.67	-73.94	-66.3	1.69	8.32	V
	5639	-44.24	-13	-31.24	-62.64	-51.29	2.71	9.76	V
	7520	-54.95	-13	-41.95	-79.04	-64.34	2.42	11.81	V
	13163.5	-38.62	-13	-25.62	-73.14	-48.88	2.97	13.23	V
Highest	3819	-60.03	-13	-47.03	-74.81	-66.71	1.70	8.38	H
	5730	-45.83	-13	-32.83	-65.98	-52.86	2.76	9.79	H
	7639	-54.50	-13	-41.50	-79.2	-64	2.38	11.88	H
	13372.5	-39.15	-13	-26.15	-76.83	-49.65	3.02	13.52	H
	3819	-60.11	-13	-47.11	-74.24	-66.79	1.70	8.38	V
	5730	-49.20	-13	-36.20	-68.18	-56.23	2.76	9.79	V
	7639	-55.29	-13	-42.29	-79.29	-64.79	2.38	11.88	V
	13372.5	-38.40	-13	-25.40	-73.79	-48.9	3.02	13.52	V
	15282	-40.55	-13	-27.55	-76.88	-50.83	3.72	13.99	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-69.69	-13	-56.69	-74.41	-71.45	0.98	4.89	H
	2480	-67.05	-13	-54.05	-76.43	-68.96	1.28	5.34	H
	3305	-64.31	-13	-51.31	-76.7	-67.76	1.54	7.14	H
	1648	-71.86	-13	-58.86	-75.12	-73.62	0.98	4.89	V
	2480	-66.05	-13	-53.05	-76.41	-67.96	1.28	5.34	V
	3305	-65.53	-13	-52.53	-77.01	-68.98	1.54	7.14	V
Middle	1672	-70.35	-13	-57.35	-74.94	-72.03	0.99	4.82	H
	2509	-66.84	-13	-53.84	-76.4	-68.8	1.29	5.41	H
	3345	-64.88	-13	-51.88	-77.05	-68.49	1.56	7.32	H
	1672	-71.84	-13	-58.84	-74.86	-73.52	0.99	4.82	V
	2509	-66.34	-13	-53.34	-76.57	-68.3	1.29	5.41	V
	3345	-65.75	-13	-52.75	-77.14	-69.36	1.56	7.32	V
Highest	1688	-70.32	-13	-57.32	-74.91	-71.95	1.00	4.77	H
	2536	-67.21	-13	-54.21	-76.79	-69.19	1.30	5.43	H
	3386	-64.98	-13	-51.98	-77.22	-68.76	1.57	7.50	H
	1688	-71.85	-13	-58.85	-74.87	-73.48	1.00	4.77	V
	2536	-66.54	-13	-53.54	-76.77	-68.52	1.30	5.43	V
	3386	-65.60	-13	-52.60	-77.26	-69.38	1.57	7.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-63.78	-13	-50.78	-78.32	-70.35	1.67	8.24	H
	5555	-59.41	-13	-46.41	-79.59	-66.48	2.66	9.72	H
	7404	-54.10	-13	-41.10	-79.65	-63.25	2.46	11.61	H
	3700	-63.95	-13	-50.95	-78.39	-70.52	1.67	8.24	V
	5555	-60.45	-13	-47.45	-79.1	-67.52	2.66	9.72	V
	7404	-55.43	-13	-42.43	-79.82	-64.58	2.46	11.61	V
Middle	3764	-63.05	-13	-50.05	-77.78	-69.68	1.69	8.32	H
	5646	-58.95	-13	-45.95	-78.86	-66	2.71	9.76	H
	7528	-54.06	-13	-41.06	-79.09	-63.46	2.42	11.82	H
	3764	-63.52	-13	-50.52	-77.85	-70.15	1.69	8.32	V
	5646	-59.69	-13	-46.69	-78.12	-66.74	2.71	9.76	V
	7528	-55.05	-13	-42.05	-79.16	-64.45	2.42	11.82	V
Highest	3814	-63.67	-13	-50.67	-78.55	-70.34	1.70	8.38	H
	5723	-58.08	-13	-45.08	-78.25	-65.12	2.75	9.79	H
	7628	-54.90	-13	-41.90	-79.63	-64.39	2.39	11.88	H
	3814	-64.42	-13	-51.42	-78.57	-71.09	1.70	8.38	V
	5723	-60.70	-13	-47.70	-79.73	-67.74	2.75	9.79	V
	7628	-55.59	-13	-42.59	-79.59	-65.08	2.39	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band IV(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3427	-65.07	-13	-52.07	-77.68	-71.17	1.58	7.68	H
	5135	-61.00	-13	-48.00	-80.19	-68.29	2.41	9.70	H
	6850	-56.44	-13	-43.44	-79.68	-64.42	2.64	10.62	H
	3427	-65.50	-13	-52.50	-77.99	-71.6	1.58	7.68	V
	5135	-62.26	-13	-49.26	-80.32	-69.55	2.41	9.70	V
	6850	-56.99	-13	-43.99	-79.89	-64.97	2.64	10.62	V
Middle	3462	-64.81	-13	-51.81	-77.75	-71.05	1.59	7.83	H
	5198	-60.80	-13	-47.80	-80.12	-68.05	2.45	9.70	H
	6927	-56.86	-13	-43.86	-80.3	-64.96	2.61	10.71	H
	3462	-64.95	-13	-51.95	-78.13	-71.19	1.59	7.83	V
	5198	-61.94	-13	-48.94	-80.29	-69.19	2.45	9.70	V
	6927	-57.16	-13	-44.16	-80.36	-65.26	2.61	10.71	V
Highest	3504	-64.69	-13	-51.69	-77.97	-71.09	1.61	8.00	H
	5261	-61.24	-13	-48.24	-80.52	-68.45	2.49	9.70	H
	7011	-56.42	-13	-43.42	-80.13	-64.66	2.59	10.82	H
	3504	-64.11	-13	-51.11	-77.98	-70.51	1.61	8.00	V
	5261	-61.82	-13	-48.82	-80.45	-69.03	2.49	9.70	V
	7011	-56.83	-13	-43.83	-80.37	-65.07	2.59	10.82	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.