

May 3, 2017

## Declaration – MIF for HAC RF Interference Evaluation

To Whom It May Concern,


This device, with FCC ID: **NM82PZC500**, Hearing Aid Compatibility Requirement is going to be certified under **ANSI C63.19-2011 version per Part 20.19**.

The M rating was determined by measuring the maximum steady state average E-field values in dB (V/m) as documented in the HAC report and adding the MIF value in dB (V/m) using pre-determined values provided by Speag under UID 10021 DAB (06.02.2014)/ UID 10011 CAB (16.01.2014)/ UID 10295 AAB (16.01.2014)/ UID 10170 CAB (13.05.2013)/ UID 10172 CAC (16.11.2016)/ UID 10061 CAB (26.11.2014)/ UID 10077 CAB (26.11.2014)/ UID 10069 CAB (26.11.2014).

The Speag-reference documentation for supporting the pre-determined MIF value is Schmid & Partner Engineering AG, **UID SUMMARY (Communication Systems for Calibration, Issued Date 2016/07/08)**.

We confirm that the Speag simulation provided represents all the air interface modes applicable for a HAC rating for this handset.

Sincerely Yours,



**Susan Yang / Project Manager**

**HTC Corporation**

Tel: 886-2-8912-4138

Fax: 886-2-8912-6307

E-mail: [Susan\\_Yang@htc.com](mailto:Susan_Yang@htc.com)