



RF EXPOSURE REPORT

REPORT NO.: SA970430L01

MODEL NO.: DIAM500

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: HTC Corporation

ADDRESS: No. 23, Xinghua Rd., Taoyuan City, 330,
Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



1. Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.585
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	0.86	1.219
EIRP Power	1.86	1.535

***Note:** The antenna is PIFA antenna with 1dBi gain.

Threshold for no SAR evaluation is 24.585mW

Transmitter power is 0.998mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold