

EUT Specification

EUT	PDA phone
	WLAN: 2.412GHz ~ 2.462GHz
Frequency band	WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz
(Operating)	□ WLAN: 5.745GHz ~ 5.825GHz
	\bigcirc Others <u>Bluetooth: 2.402GHz ~ 2.480GHz</u>
	Portable (<20cm separation)
Device category	Mobile (>20cm separation)
	Others
	Occupational/Controlled exposure ($S = 5mW/cm^2$)
Exposure classification	General Population/Uncontrolled exposure
	$(S=1mW/cm^2)$
	Single antenna
	Multiple antennas
Antenna diversity	Tx diversity
	Rx diversity
	Tx/Rx diversity
Max. output power	0.74 dBm (1.19mW)
Antenna gain (Max)	1 dBi (Numeric gain: 1.26)
	MPE Evaluation
Evaluation applied	SAR Evaluation*
	□ N/A

Remark:

- 1. The maximum output power is <u>0.74dBm (1.19mW)</u> at <u>2441MHz</u> (with <u>1.26 numeric antenna</u> <u>gain.</u>)
- 2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
- 3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

TEST RESULTS

No non-compliance noted.

Remark: Please refer to the separated SAR report.