



FCC TEST REPORT (15.247)

REPORT NO.: RF140409C02A
MODEL NO.: HTL23
FCC ID: NM8HTL23
RECEIVED: Apr. 09, 2014
TESTED: Apr. 25, 2014 ~ Apr. 30, 2014
ISSUED: May 15, 2014

APPLICANT: HTC Corporation

ADDRESS: 1F, 6-3 Baoqiang Road, Xindian District, New Taipei City, Taiwan 231

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

- RELEASE CONTROL RECORD5
- 1. CERTIFICATION.....6
- 2. SUMMARY OF TEST RESULTS7
 - 2.1 MEASUREMENT UNCERTAINTY.....7
- 3. GENERAL INFORMATION8
 - 3.1 GENERAL DESCRIPTION OF EUT8
 - 3.2 DESCRIPTION OF TEST MODES9
 - 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 10
 - 3.3 DESCRIPTION OF SUPPORT UNITS 14
 - 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST 14
 - 3.4 DUTY CYCLE TEST SIGNAL 15
 - 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS 17
- 4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND) 18
 - 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 18
 - 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 18
 - 4.1.2 TEST INSTRUMENTS 19
 - 4.1.3 TEST PROCEDURES 20
 - 4.1.4 DEVIATION FROM TEST STANDARD 20
 - 4.1.5 TEST SETUP 21
 - 4.1.6 EUT OPERATING CONDITIONS 22
 - 4.1.7 TEST RESULTS..... 23
 - 4.2 CONDUCTED EMISSION MEASUREMENT 33
 - 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 33
 - 4.2.2 TEST INSTRUMENTS 33
 - 4.2.3 TEST PROCEDURES 34
 - 4.2.4 DEVIATION FROM TEST STANDARD 34
 - 4.2.5 TEST SETUP 35
 - 4.2.6 EUT OPERATING CONDITIONS 35
 - 4.2.7 TEST RESULTS..... 36
 - 4.3 6dB BANDWIDTH MEASUREMENT 38
 - 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT 38
 - 4.3.2 TEST SETUP 38
 - 4.3.3 TEST INSTRUMENTS 38
 - 4.3.4 TEST PROCEDURE 38
 - 4.3.5 DEVIATION FROM TEST STANDARD 38
 - 4.3.6 EUT OPERATING CONDITIONS 38
 - 4.3.7 TEST RESULTS..... 39
 - 4.4 CONDUCTED OUTPUT POWER 41
 - 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 41
 - 4.4.2 TEST SETUP 41
 - 4.4.3 TEST INSTRUMENTS 41
 - 4.4.4 TEST PROCEDURES 41
 - 4.4.5 DEVIATION FROM TEST STANDARD 41
 - 4.4.6 EUT OPERATING CONDITIONS 41
 - 4.4.7 TEST RESULTS..... 42
 - 4.5 POWER SPECTRAL DENSITY MEASUREMENT 43
 - 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 43
 - 4.5.2 TEST SETUP 43
 - 4.5.3 TEST INSTRUMENTS 43
 - 4.5.4 TEST PROCEDURE 43
 - 4.5.5 DEVIATION FROM TEST STANDARD 43



4.5.6	EUT OPERATING CONDITION.....	43
4.5.7	TEST RESULTS.....	44
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	46
4.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT	46
4.6.2	TEST SETUP	46
4.6.3	TEST INSTRUMENTS	46
4.6.4	TEST PROCEDURE	46
4.6.5	DEVIATION FROM TEST STANDARD	46
4.6.6	EUT OPERATING CONDITION.....	46
4.6.7	TEST RESULTS.....	47
5.	TEST TYPES AND RESULTS (FOR 5.0GHz BAND)	50
5.1	RADIATED EMISSION AND BANDEDGE MEASUREMENT	50
5.1.1	LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	50
5.1.2	TEST INSTRUMENTS.....	51
5.1.3	TEST PROCEDURES	51
5.1.4	DEVIATION FROM TEST STANDARD	51
5.1.5	TEST SETUP	51
5.1.6	EUT OPERATING CONDITIONS	51
5.1.7	TEST RESULTS.....	52
5.2	CONDUCTED EMISSION MEASUREMENT	62
5.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	62
5.2.2	TEST INSTRUMENTS	62
5.2.3	TEST PROCEDURES	62
5.2.4	DEVIATION FROM TEST STANDARD	62
5.2.5	TEST SETUP	62
5.2.6	EUT OPERATING CONDITIONS	62
5.2.7	TEST RESULTS.....	63
5.3	6dB BANDWIDTH MEASUREMENT	65
5.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	65
5.3.2	TEST SETUP	65
5.3.3	TEST INSTRUMENTS.....	65
5.3.4	TEST PROCEDURE	65
5.3.5	DEVIATION FROM TEST STANDARD	65
5.3.6	EUT OPERATING CONDITIONS	65
5.3.7	TEST RESULTS.....	66
5.4	MAXIMUM OUTPUT POWER	68
5.4.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	68
5.4.2	TEST SETUP	68
5.4.3	INSTRUMENTS	68
5.4.4	TEST PROCEDURES	68
5.4.5	DEVIATION FROM TEST STANDARD	68
5.4.6	EUT OPERATING CONDITIONS	68
5.4.7	TEST RESULTS.....	69
5.5	POWER SPECTRAL DENSITY MEASUREMENT.....	70
5.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	70
5.5.2	TEST SETUP	70
5.5.3	TEST INSTRUMENTS.....	70
5.5.4	TEST PROCEDURE	70
5.5.5	DEVIATION FROM TEST STANDARD	70
5.5.6	EUT OPERATING CONDITION.....	70
5.5.7	TEST RESULTS.....	71
5.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	73
5.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	73
5.6.2	TEST SETUP	73



A D T

5.6.3	TEST INSTRUMENTS	73
5.6.4	TEST PROCEDURE	73
5.6.5	DEVIATION FROM TEST STANDARD	73
5.6.6	EUT OPERATING CONDITION.....	73
5.6.7	TEST RESULTS.....	73
6.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	77
7.	INFORMATION ON THE TESTING LABORATORIES	78
8.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	79



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140409C02A	Original release	May 15, 2014



1. CERTIFICATION

PRODUCT: Smartphone
MODEL NO.: HTL23
BRAND: HTC
APPLICANT: HTC Corporation
TESTED: Apr. 25, 2014 ~ Apr. 30, 2014
TEST SAMPLE: Production Unit
STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.10-2009

The above equipment (model: HTL23) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Ivonne Wu , **DATE** : May 15, 2014
Ivonne Wu / Supervisor

APPROVED BY : Sam Chen , **DATE** : May 15, 2014
Sam Chen / Senior Project Engineer

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -8.65dB at 13.56250MHz.
15.205 & 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.09dB at 2484.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Smartphone
MODEL NO.	HTL23
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion battery)
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11a: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7 802.11ac: up to V9
OPERATING FREQUENCY	2.4GHz: 2412 ~ 2462MHz 5.0GHz: 5745 ~ 5805MHz
NUMBER OF CHANNEL	2.4GHz: 11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz) 5.0GHz: 4 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz) 1 for 802.11ac (80MHz)
OUTPUT POWER	226.99mW for 2412 ~ 2462MHz 252.93mW for 5745 ~ 5805MHz
ANTENNA TYPE	2.4GHz: PIFA antenna with -4dBi gain 5.0GHz: PIFA antenna with -4dBi gain
ANTENNA CONNECTOR	NA
DATA CABLE	Refer to Note as below
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Refer to Note as below

NOTE:

1. The EUT's accessories list refers to Ext. Pho.
2. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

FOR 2.4GHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

FOR 5.0GHz (5745 ~ 5805MHz):

5 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	161	5805MHz
153	5765MHz		
157	5785MHz		

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY
155	5775MHz



A D T

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

WLAN 2.4GHz:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

RADIATED EMISSION TEST (BELOW 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0

POWER LINE CONDUCTED EMISSION TEST:

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0



A D T

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

Test CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE \geq 1G	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
RE $<$ 1G	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
PLC	25deg. C, 65%RH	120Vac, 60Hz	Peter Weng
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao



A D T

WLAN 5.0GHz (5745 ~ 5805MHz):

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	149 to 161	149, 157, 161	OFDM	BPSK	6.0
-	802.11n (20MHz)	149 to 161	149, 157, 161	OFDM	BPSK	MCS0
-	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0
-	802.11ac (80MHz)	155	155	OFDM	BPSK	V0

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	149 to 161	161	OFDM	BPSK	MCS0

POWER LINE CONDUCTED EMISSION TEST:

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	149 to 161	161	OFDM	BPSK	MCS0



BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	149 to 161	149, 157, 161	OFDM	BPSK	6.0
-	802.11n (20MHz)	149 to 161	149, 157, 161	OFDM	BPSK	MCS0
-	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0
-	802.11ac (80MHz)	155	155	OFDM	BPSK	V0

ANTENNA PORT CONDUCTED MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	149 to 161	149, 157, 161	OFDM	BPSK	6.0
-	802.11n (20MHz)	149 to 161	149, 157, 161	OFDM	BPSK	MCS0
-	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	MCS0
-	802.11ac (80MHz)	155	155	OFDM	BPSK	V0


Test CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao
PLC	25deg. C, 65%RH	120Vac, 60Hz	Peter Weng
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST





A D T

3.4 DUTY CYCLE TEST SIGNAL


WLAN 2.4GHz

802.11b: Duty cycle of test signal is 100 %, duty factor is not required.

Duty cycle of test signal is > 98 %, duty factor is not required.

802.11g: Duty cycle = $1.347/1.371 = 0.982$

802.11n (20MHz): Duty cycle = $1.355/1.371 = 0.988$





A D T

5725MHz ~ 5825MHz

Duty cycle of test signal is > 98 %, duty factor is not required.


802.11a: Duty cycle = 1.354/1.370 = 0.988

802.11n (20MHz): Duty cycle = 1.275/1.290 = 0.988

If duty cycle is < 98%

802.11n (40MHz): Duty cycle = 593.27/641.35 = 0.925, Duty factor = 10 * log(1/0.925) = 0.34

802.11ac (80MHz): Duty cycle = 216.35/259.61 = 0.833, Duty factor = 10 * log(1/0.833) = 0.79





A D T

3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2009

558074 D01 DTS Meas Guidance v03r01

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver AGILENT	N9038A	MY51210203	Jan. 17, 2014	Jan. 16, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2013	Dec. 20, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 27, 2014	Feb. 26, 2015
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 19, 2014	Feb. 18, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 18, 2013	Dec. 17, 2014
Loop Antenna	HFH2-Z2	100070	Mar. 06, 2014	Mar. 05, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 26, 2013	Dec. 25, 2014
Preamplifier EMCI	EMC 184045	980116	Jan. 13, 2014	Jan. 12, 2015
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2013	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Power Meter	ML2495A	1232002	Aug. 23, 2013	Aug. 22, 2014
Power Sensor	MA2411B	1207325	Aug. 23, 2013	Aug. 22, 2014

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 10.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 690701.
 6. The IC Site Registration No. is IC 7450F-10.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP

Frequency Range 30MHz ~ 1GHz



Frequency Range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).



A D T

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



A D T

4.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	38.28	45.35	54	-15.72	26.91	3.54	37.52	120	349	Average
2390	56.81	63.88	74	-17.19	26.91	3.54	37.52	120	349	Peak
2412	103.89	110.91			26.96	3.54	37.52	120	349	Average
2412	108.82	115.84			26.96	3.54	37.52	120	349	Peak
2484	35.32	41.89	54	-18.68	27.15	3.6	37.32	120	349	Average
2484	55.51	62.08	74	-18.49	27.15	3.6	37.32	120	349	Peak
4824	46.49	62.81	54	-7.51	30.99	5.77	53.08	103	172	Average
4824	49.43	65.75	74	-24.57	30.99	5.77	53.08	103	172	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	37.9	44.97	54	-16.1	26.91	3.54	37.52	100	270	Average
2390	55.87	62.94	74	-18.13	26.91	3.54	37.52	100	270	Peak
2412	103.96	110.98			26.96	3.54	37.52	100	262	Average
2412	109.12	116.14			26.96	3.54	37.52	100	262	Peak
2484	35.88	42.45	54	-18.12	27.15	3.6	37.32	100	270	Average
2484	55.93	62.5	74	-18.07	27.15	3.6	37.32	100	270	Peak
4824	47.44	63.76	54	-6.56	30.99	5.77	53.08	122	12	Average
4824	48.84	65.16	74	-25.16	30.99	5.77	53.08	122	12	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.78	40.85	54	-20.22	26.91	3.54	37.52	143	329	Average
2390	56.09	63.16	74	-17.91	26.91	3.54	37.52	143	329	Peak
2437	103.86	110.7			27.06	3.56	37.46	143	329	Average
2437	108.94	115.78			27.06	3.56	37.46	143	329	Peak
2484	35.11	41.68	54	-18.89	27.15	3.6	37.32	143	329	Average
2484	55.69	62.26	74	-18.31	27.15	3.6	37.32	143	329	Peak
4874	48.67	64.86	54	-5.33	31.06	5.8	53.05	103	325	Average
4874	51.42	67.61	74	-22.58	31.06	5.8	53.05	103	325	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2356	33.65	40.83	54	-20.35	26.81	3.5	37.49	100	279	Average
2356	57.29	64.47	74	-16.71	26.81	3.5	37.49	100	279	Peak
2437	104.29	111.13			27.06	3.56	37.46	100	279	Average
2437	109.49	116.33			27.06	3.56	37.46	100	279	Peak
2484	36.5	43.07	54	-17.5	27.15	3.6	37.32	100	279	Average
2484	56.46	63.03	74	-17.54	27.15	3.6	37.32	100	279	Peak
4874	48.22	64.41	54	-5.78	31.06	5.8	53.05	100	17	Average
4874	50.94	67.13	74	-23.06	31.06	5.8	53.05	100	17	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2324	34.21	41.48	54	-19.79	26.72	3.48	37.47	118	341	Average
2324	56.6	63.87	74	-17.4	26.72	3.48	37.47	118	341	Peak
2462	103.43	110.14			27.1	3.58	37.39	118	341	Average
2462	108.57	115.28			27.1	3.58	37.39	118	341	Peak
2484	45.97	52.54	54	-8.03	27.15	3.6	37.32	118	341	Average
2484	58.17	64.74	74	-15.83	27.15	3.6	37.32	118	341	Peak
4924	47.4	63.48	54	-6.6	31.12	5.83	53.03	100	344	Average
4924	49.32	65.4	74	-24.68	31.12	5.83	53.03	100	344	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2356	34.82	42	54	-19.18	26.81	3.5	37.49	100	270	Average
2356	56.67	63.85	74	-17.33	26.81	3.5	37.49	100	270	Peak
2462	103.68	110.39			27.1	3.58	37.39	100	270	Average
2462	108.98	115.69			27.1	3.58	37.39	100	270	Peak
2484	46.23	52.8	54	-7.77	27.15	3.6	37.32	100	270	Average
2484	58.54	65.11	74	-15.46	27.15	3.6	37.32	100	270	Peak
4924	44.58	60.66	54	-9.42	31.12	5.83	53.03	102	246	Average
4924	47.16	63.24	74	-26.84	31.12	5.83	53.03	102	246	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.76	56.83	54	-4.24	26.91	3.54	37.52	122	346	Average
2390	70.04	77.11	74	-3.96	26.91	3.54	37.52	122	346	Peak
2412	97.23	104.25			26.96	3.54	37.52	122	346	Average
2412	107.27	114.29			26.96	3.54	37.52	122	346	Peak
2484	36.37	42.94	54	-17.63	27.15	3.6	37.32	122	346	Average
2484	56.37	62.94	74	-17.63	27.15	3.6	37.32	122	346	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	48.77	55.84	54	-5.23	26.91	3.54	37.52	100	263	Average
2390	68.14	75.21	74	-5.86	26.91	3.54	37.52	100	263	Peak
2412	98.77	105.79			26.96	3.54	37.52	100	263	Average
2412	108.29	115.31			26.96	3.54	37.52	100	263	Peak
2490	36.58	43.08	54	-17.42	27.2	3.62	37.32	100	263	Average
2490	57.85	64.35	74	-16.15	27.2	3.62	37.32	100	263	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2348	35.05	42.27	54	-18.95	26.77	3.5	37.49	121	350	Average
2348	56.94	64.16	74	-17.06	26.77	3.5	37.49	121	350	Peak
2437	97.54	104.38			27.06	3.56	37.46	121	350	Average
2437	107.9	114.74			27.06	3.56	37.46	121	350	Peak
2484	39.48	46.05	54	-14.52	27.15	3.6	37.32	121	350	Average
2484	57.23	63.8	74	-16.77	27.15	3.6	37.32	121	350	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2380	35.26	42.38	54	-18.74	26.86	3.52	37.5	102	272	Average
2380	57.2	64.32	74	-16.8	26.86	3.52	37.5	102	272	Peak
2437	98.19	105.03			27.06	3.56	37.46	102	272	Average
2437	108.59	115.43			27.06	3.56	37.46	102	272	Peak
2484	40.16	46.73	54	-13.84	27.15	3.6	37.32	102	272	Average
2484	56.57	63.14	74	-17.43	27.15	3.6	37.32	102	272	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2386	34.19	41.26	54	-19.81	26.91	3.52	37.5	118	341	Average
2386	56.59	63.66	74	-17.41	26.91	3.52	37.5	118	341	Peak
2462	98.14	104.85			27.1	3.58	37.39	118	341	Average
2462	107.6	114.31			27.1	3.58	37.39	118	341	Peak
2484	49.7	56.27	54	-4.3	27.15	3.6	37.32	118	341	Average
2484	67.18	73.75	74	-6.82	27.15	3.6	37.32	118	341	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2320	34.23	41.5	54	-19.77	26.72	3.48	37.47	100	271	Average
2320	57.89	65.16	74	-16.11	26.72	3.48	37.47	100	271	Peak
2462	99.13	105.84			27.1	3.58	37.39	100	271	Average
2462	108.59	115.3			27.1	3.58	37.39	100	271	Peak
2484	50.71	57.28	54	-3.29	27.15	3.6	37.32	100	271	Average
2484	68.91	75.48	74	-5.09	27.15	3.6	37.32	100	271	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.6	57.67	54	-3.4	26.91	3.54	37.52	119	350	Average
2390	69.77	76.84	74	-4.23	26.91	3.54	37.52	119	350	Peak
2412	97.01	104.03			26.96	3.54	37.52	119	350	Average
2412	107.46	114.48			26.96	3.54	37.52	119	350	Peak
2484	36.23	42.8	54	-17.77	27.15	3.6	37.32	119	350	Average
2484	57.55	64.12	74	-16.45	27.15	3.6	37.32	119	350	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.98	57.05	54	-4.02	26.91	3.54	37.52	102	270	Average
2390	70.57	77.64	74	-3.43	26.91	3.54	37.52	102	270	Peak
2412	97.75	104.77			26.96	3.54	37.52	102	270	Average
2412	108.27	115.29			26.96	3.54	37.52	102	270	Peak
2484	36.21	42.78	54	-17.79	27.15	3.6	37.32	102	270	Average
2484	55.92	62.49	74	-18.08	27.15	3.6	37.32	102	270	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2332	34.56	41.83	54	-19.44	26.72	3.48	37.47	123	346	Average
2332	55.8	63.07	74	-18.2	26.72	3.48	37.47	123	346	Peak
2437	98.06	104.9			27.06	3.56	37.46	123	346	Average
2437	107.75	114.59			27.06	3.56	37.46	123	346	Peak
2484	39.93	46.5	54	-14.07	27.15	3.6	37.32	123	346	Average
2484	56.94	63.51	74	-17.06	27.15	3.6	37.32	123	346	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.94	42.01	54	-19.06	26.91	3.54	37.52	100	266	Average
2390	55.32	62.39	74	-18.68	26.91	3.54	37.52	100	266	Peak
2437	98.56	105.4			27.06	3.56	37.46	100	266	Average
2437	108.82	115.66			27.06	3.56	37.46	100	266	Peak
2484	39.72	46.29	54	-14.28	27.15	3.6	37.32	100	266	Average
2484	57.28	63.85	74	-16.72	27.15	3.6	37.32	100	266	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2328	34.17	41.44	54	-19.83	26.72	3.48	37.47	120	345	Average
2328	56.91	64.18	74	-17.09	26.72	3.48	37.47	120	345	Peak
2462	97.89	104.6			27.1	3.58	37.39	120	345	Average
2462	107.49	114.2			27.1	3.58	37.39	120	345	Peak
2484	50.7	57.27	54	-3.3	27.15	3.6	37.32	120	345	Average
2484	70.91	77.48	74	-3.09	27.15	3.6	37.32	120	345	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.42	41.49	54	-19.58	26.91	3.54	37.52	101	272	Average
2390	55.44	62.51	74	-18.56	26.91	3.54	37.52	101	272	Peak
2462	98.79	105.5			27.1	3.58	37.39	101	272	Average
2462	108.64	115.35			27.1	3.58	37.39	101	272	Peak
2484	49.7	56.27	54	-4.3	27.15	3.6	37.32	101	272	Average
2484	70.08	76.65	74	-3.92	27.15	3.6	37.32	101	272	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

BELOW 1GHz WORST-CASE DATA:

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
71.85	18.58	39.14	40	-21.42	10.29	0.91	31.76	100	202	Peak
152.85	23.85	41.46	43.5	-19.65	12.72	1.36	31.69	100	324	Peak
220.89	22.78	42.54	46	-23.22	10.26	1.7	31.72	100	109	Peak
524	21.09	31.99	46	-24.91	17.86	2.86	31.62	100	118	Peak
738.9	26.25	32.83	46	-19.75	21.37	3.54	31.49	100	207	Peak
922.3	27.64	31.98	46	-18.36	23.64	4.02	32	100	194	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
30.54	35.35	53.76	40	-4.65	12.14	0.57	31.12	100	134	Peak
41.34	30.46	47.27	40	-9.54	13.56	0.68	31.05	100	286	Peak
69.96	26.2	46.35	40	-13.8	10.77	0.9	31.82	100	284	Peak
487.6	20.72	32.69	46	-25.28	17.08	2.74	31.79	100	173	Peak
696.2	24.66	32.28	46	-21.34	20.77	3.42	31.81	100	209	Peak
811	27.33	32.71	46	-18.67	22.37	3.72	31.47	100	241	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Apr. 24, 2014	Apr. 23, 2015
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 27, 2013	Dec. 26, 2014
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 23, 2013	Dec. 22, 2014
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 08, 2013	Jul. 07, 2014
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.

4.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA :

PHASE	Line 1	6dB BANDWIDTH	9kHz
--------------	--------	----------------------	------

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19297	0.28	38.18	28.62	38.46	28.90	63.91	53.91	-25.45	-25.01
2	0.49375	0.31	43.30	30.81	43.61	31.12	56.10	46.10	-12.50	-14.99
3	0.94297	0.34	39.02	30.45	39.36	30.79	56.00	46.00	-16.64	-15.21
4	2.35547	0.37	39.10	30.04	39.47	30.41	56.00	46.00	-16.53	-15.59
5	8.72266	0.49	35.33	26.50	35.82	26.99	60.00	50.00	-24.18	-23.01
6	13.56250	0.52	40.74	38.27	41.26	38.79	60.00	50.00	-18.74	-11.21

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.17344	0.27	31.51	16.21	31.78	16.48	64.79
2	0.39219	0.30	32.91	21.59	33.21	21.89	58.02	48.02	-24.81	-26.13
3	0.89219	0.33	39.00	29.54	39.33	29.87	56.00	46.00	-16.67	-16.13
4	2.15234	0.38	35.77	28.15	36.15	28.53	56.00	46.00	-19.85	-17.47
5	8.78906	0.50	34.68	26.73	35.18	27.23	60.00	50.00	-24.82	-22.77
6	13.55859	0.55	41.49	39.67	42.04	40.22	60.00	50.00	-17.96	-9.78

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.11	0.5	PASS
6	2437	8.10	0.5	PASS
11	2462	8.55	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.39	0.5	PASS
6	2437	16.42	0.5	PASS
11	2462	16.37	0.5	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.41	0.5	PASS
6	2437	16.42	0.5	PASS
11	2462	16.38	0.5	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11b



802.11g



802.11n (20MHz)




4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as section 4.3.6.



A D T

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
1	2412	119.40	20.77	30	PASS
6	2437	122.18	20.87	30	PASS
11	2462	120.78	20.82	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
1	2412	197.70	22.96	30	PASS
6	2437	216.27	23.35	30	PASS
11	2462	207.01	23.16	30	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
1	2412	196.34	22.93	30	PASS
6	2437	226.99	23.56	30	PASS
11	2462	206.06	23.14	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
- Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as section 4.3.6.



A D T

4.5.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
1	2412	-3.04	8	PASS
6	2437	-4.38	8	PASS
11	2462	-3.67	8	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
1	2412	-8.75	8	PASS
6	2437	-8.80	8	PASS
11	2462	-7.64	8	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
1	2412	-9.03	8	PASS
6	2437	-8.56	8	PASS
11	2462	-8.36	8	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11b



802.11g



802.11n (20MHz)




4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Ensure that the number of measurement points \geq span/RBW
4. According to measurement points to set differ measurement span.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Same as section 4.3.6.




A D T

4.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.


802.11b





A D T


802.11g





A D T

802.11n (20MHz)



5. TEST TYPES AND RESULTS (FOR 5.0GHz BAND)

5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

5.1.2 TEST INSTRUMENTS

Same as section 4.1.2.

5.1.3 TEST PROCEDURES

Same as section 4.1.3.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

5.1.5 TEST SETUP

Same as section 4.1.5.

5.1.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.



A D T

5.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA :

802.11a

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	50.29	50.17	79.47	-29.18	31.96	5.59	37.43	124	29	Average
5725	73.02	72.9	88.47	-15.45	31.96	5.59	37.43	124	29	Peak
5745	99.47	99.35			31.99	5.6	37.47	124	29	Average
5745	108.47	108.35			31.99	5.6	37.47	124	29	Peak
5825	38.78	38.55	79.47	-40.69	32.12	5.64	37.53	124	29	Average
5825	58.19	57.96	88.47	-30.28	32.12	5.64	37.53	124	29	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	47.3	47.18	74.75	-27.45	31.96	5.59	37.43	100	349	Average
5725	63.56	63.44	84.1	-20.54	31.96	5.59	37.43	100	349	Peak
5745	94.75	94.63			31.99	5.6	37.47	100	349	Average
5745	104.1	103.98			31.99	5.6	37.47	100	349	Peak
5825	38.67	38.44	74.75	-36.08	32.12	5.64	37.53	100	349	Average
5825	57.11	56.88	84.1	-26.99	32.12	5.64	37.53	100	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5745MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.65	38.53	79.53	-40.88	31.96	5.59	37.43	124	30	Average
5725	60.15	60.03	88.86	-28.71	31.96	5.59	37.43	124	30	Peak
5785	99.53	99.41			32.04	5.62	37.54	124	30	Average
5785	108.86	108.74			32.04	5.62	37.54	124	30	Peak
5825	38.83	38.6	79.53	-40.7	32.12	5.64	37.53	124	30	Average
5825	57.81	57.58	88.86	-31.05	32.12	5.64	37.53	124	30	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.42	38.3	74.9	-36.48	31.96	5.59	37.43	107	349	Average
5725	58.17	58.05	84.77	-26.6	31.96	5.59	37.43	107	349	Peak
5785	94.9	94.78			32.04	5.62	37.54	107	349	Average
5785	104.77	104.65			32.04	5.62	37.54	107	349	Peak
5825	38.7	38.47	74.9	-36.2	32.12	5.64	37.53	107	349	Average
5825	59.5	59.27	84.77	-25.27	32.12	5.64	37.53	107	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5785MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 161	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.38	38.26	80.44	-42.06	31.96	5.59	37.43	124	34	Average
5725	58.19	58.07	89.74	-31.55	31.96	5.59	37.43	124	34	Peak
5805	100.44	100.25			32.1	5.63	37.54	124	34	Average
5805	109.74	109.55			32.1	5.63	37.54	124	34	Peak
5825	51.33	51.1	80.44	-29.11	32.12	5.64	37.53	124	34	Average
5825	74.05	73.82	89.74	-15.69	32.12	5.64	37.53	124	34	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.42	38.3	76.02	-37.6	31.96	5.59	37.43	107	349	Average
5725	59.6	59.48	85.53	-25.93	31.96	5.59	37.43	107	349	Peak
5805	96.02	95.83			32.1	5.63	37.54	107	349	Average
5805	105.53	105.34			32.1	5.63	37.54	107	349	Peak
5825	47.94	47.71	76.02	-28.08	32.12	5.64	37.53	107	349	Average
5825	69.35	69.12	85.53	-16.18	32.12	5.64	37.53	107	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5805MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	52.36	52.24	79.45	-27.09	31.96	5.59	37.43	124	34	Average
5725	73.15	73.03	89.11	-15.96	31.96	5.59	37.43	124	34	Peak
5745	99.45	99.33			31.99	5.6	37.47	124	34	Average
5745	109.11	108.99			31.99	5.6	37.47	124	34	Peak
5825	38.7	38.47	79.45	-40.75	32.12	5.64	37.53	124	34	Average
5825	57.05	56.82	89.11	-32.06	32.12	5.64	37.53	124	34	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	48.64	48.52	75.33	-26.69	31.96	5.59	37.43	108	347	Average
5725	66.38	66.26	84.9	-18.52	31.96	5.59	37.43	108	347	Peak
5745	95.33	95.21			31.99	5.6	37.47	108	347	Average
5745	104.9	104.78			31.99	5.6	37.47	108	347	Peak
5825	38.7	38.47	75.33	-36.63	32.12	5.64	37.53	108	347	Average
5825	59.01	58.78	84.9	-25.89	32.12	5.64	37.53	108	347	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5745MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.34	38.22	79.24	-40.9	31.96	5.59	37.43	125	29	Average
5725	60.07	59.95	88.65	-28.58	31.96	5.59	37.43	125	29	Peak
5785	99.24	99.12			32.04	5.62	37.54	125	29	Average
5785	108.65	108.53			32.04	5.62	37.54	125	29	Peak
5825	38.64	38.41	79.24	-40.6	32.12	5.64	37.53	125	29	Average
5825	59.3	59.07	88.65	-29.35	32.12	5.64	37.53	125	29	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.44	38.32	75.35	-36.91	31.96	5.59	37.43	108	347	Average
5725	57.55	57.43	84.58	-27.03	31.96	5.59	37.43	108	347	Peak
5785	95.35	95.23			32.04	5.62	37.54	108	347	Average
5785	104.58	104.46			32.04	5.62	37.54	108	347	Peak
5825	38.73	38.5	75.35	-36.62	32.12	5.64	37.53	108	347	Average
5825	57.89	57.66	84.58	-26.69	32.12	5.64	37.53	108	347	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5785MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 161	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.56	38.44	79.54	-40.98	31.96	5.59	37.43	125	29	Average
5725	58.28	58.16	88.92	-30.64	31.96	5.59	37.43	125	29	Peak
5805	99.54	99.35			32.1	5.63	37.54	125	29	Average
5805	108.92	108.73			32.1	5.63	37.54	125	29	Peak
5825	52.47	52.24	79.54	-27.07	32.12	5.64	37.53	125	29	Average
5825	73.92	73.69	88.92	-15	32.12	5.64	37.53	125	29	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.41	38.29	75.65	-37.24	31.96	5.59	37.43	107	349	Average
5725	58.66	58.54	84.67	-26.01	31.96	5.59	37.43	107	349	Peak
5805	95.65	95.46			32.1	5.63	37.54	107	349	Average
5805	104.67	104.48			32.1	5.63	37.54	107	349	Peak
5825	45.3	45.07	75.65	-30.35	32.12	5.64	37.53	107	349	Average
5825	70.83	70.6	84.67	-13.84	32.12	5.64	37.53	107	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5805MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 151	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	45.77	45.65	73.72	-27.95	31.96	5.59	37.43	124	29	Average
5725	61.03	60.91	83.07	-22.04	31.96	5.59	37.43	124	29	Peak
5755	93.72	93.58			32.01	5.6	37.47	124	29	Average
5755	103.07	102.93			32.01	5.6	37.47	124	29	Peak
5825	38.7	38.47	73.72	-35.02	32.12	5.64	37.53	124	29	Average
5825	59.7	59.47	83.07	-23.37	32.12	5.64	37.53	124	29	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	40.18	40.06	69.87	-29.69	31.96	5.59	37.43	107	349	Average
5725	58.32	58.2	79.05	-20.73	31.96	5.59	37.43	107	349	Peak
5755	89.87	89.73			32.01	5.6	37.47	107	349	Average
5755	99.05	98.91			32.01	5.6	37.47	107	349	Peak
5825	38.18	37.99	69.87	-31.69	32.1	5.63	37.54	107	349	Average
5825	58.81	58.62	79.05	-20.24	32.1	5.63	37.54	107	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5755MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 159	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.29	38.17	73.97	-35.68	31.96	5.59	37.43	139	29	Average
5725	58.65	58.53	83.69	-25.04	31.96	5.59	37.43	139	29	Peak
5795	93.97	93.81			32.07	5.63	37.54	139	29	Average
5795	103.69	103.53			32.07	5.63	37.54	139	29	Peak
5825	44.57	44.34	73.97	-29.4	32.12	5.64	37.53	139	29	Average
5825	65.4	65.17	83.69	-18.29	32.12	5.64	37.53	139	29	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	38.48	38.36	70.29	-31.81	31.96	5.59	37.43	107	349	Average
5725	57.39	57.27	79.66	-22.27	31.96	5.59	37.43	107	349	Peak
5795	90.29	90.13			32.07	5.63	37.54	107	349	Average
5795	99.66	99.5			32.07	5.63	37.54	107	349	Peak
5825	41.54	41.31	70.29	-28.75	32.12	5.64	37.53	107	349	Average
5825	61.72	61.49	79.66	-17.94	32.12	5.64	37.53	107	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5795MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

802.11ac (80MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 155	FREQUENCY RANGE	1GHz ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	46.63	46.51	71.16	-24.53	31.96	5.59	37.43	140	29	Average
5725	62.5	62.38	82.03	-19.53	31.96	5.59	37.43	140	29	Peak
5775	91.16	91			32.04	5.62	37.5	140	29	Average
5775	102.03	101.87			32.04	5.62	37.5	140	29	Peak
5825	44.35	44.12	71.16	-26.81	32.12	5.64	37.53	140	29	Average
5825	64.91	64.68	82.03	-17.12	32.12	5.64	37.53	140	29	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	41.87	41.75	67	-25.13	31.96	5.59	37.43	108	352	Average
5725	60.94	60.82	78.06	-17.12	31.96	5.59	37.43	108	352	Peak
5775	87	86.84			32.04	5.62	37.5	108	352	Average
5775	98.06	97.9			32.04	5.62	37.5	108	352	Peak
5825	39.8	39.57	67	-27.2	32.12	5.64	37.53	108	352	Average
5825	59.3	59.07	78.06	-18.76	32.12	5.64	37.53	108	352	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 5775MHz: Fundamental frequency.
- 5725MHz & 5825MHz: Out of restricted band



A D T

BELOW 1GHz WORST-CASE DATA :

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 161	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Johnson Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
41.07	20.48	37.28	40	-19.52	13.55	0.67	31.02	100	302	Peak
160.41	26.21	43.97	43.5	-17.29	12.73	1.39	31.88	100	103	Peak
216.57	22.52	42.46	46	-23.48	10.05	1.67	31.66	100	55	Peak
432.3	19.29	32.77	46	-26.71	15.98	2.55	32.01	100	224	Peak
619.2	23.01	32.2	46	-22.99	19.83	3.14	32.16	100	186	Peak
773.2	26.27	32.13	46	-19.73	21.85	3.63	31.34	100	202	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
30.66	34.66	53.07	40	-5.34	12.14	0.57	31.12	100	134	Peak
42.42	30.9	47.7	40	-9.1	13.58	0.7	31.08	100	38	Peak
96.69	21.93	44.01	43.5	-21.57	8.83	1.05	31.96	100	331	Peak
484.1	21.25	33.34	46	-24.75	17	2.73	31.82	100	76	Peak
670.3	24.37	32.4	46	-21.63	20.46	3.32	31.81	100	213	Peak
892.9	28.94	33.57	46	-17.06	23.42	3.95	32	100	170	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

5.2 CONDUCTED EMISSION MEASUREMENT

5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

5.2.2 TEST INSTRUMENTS

Same as section 4.2.2.

5.2.3 TEST PROCEDURES

Same as section 4.2.3.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

5.2.5 TEST SETUP

Same as section 4.2.5.

5.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.

5.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA :

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.18125	0.27	36.51	25.57	36.78	25.84	64.43
2	0.49375	0.31	42.02	30.03	42.33	30.34	56.10	46.10	-13.78	-15.77
3	0.92344	0.33	41.35	31.03	41.68	31.36	56.00	46.00	-14.32	-14.64
4	2.29688	0.37	38.62	30.07	38.99	30.44	56.00	46.00	-17.01	-15.56
5	8.89453	0.49	37.10	28.13	37.59	28.62	60.00	50.00	-22.41	-21.38
6	13.55859	0.52	36.95	34.74	37.47	35.26	60.00	50.00	-22.53	-14.74

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






A D T

PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.19297	0.28	32.93	20.40	33.21	20.68	63.91
2	0.48203	0.31	33.29	18.76	33.60	19.07	56.30	46.30	-22.71	-27.24
3	0.91172	0.33	38.50	28.03	38.83	28.36	56.00	46.00	-17.17	-17.64
4	2.37891	0.38	35.96	27.69	36.34	28.07	56.00	46.00	-19.66	-17.93
5	9.14453	0.51	34.06	26.62	34.57	27.13	60.00	50.00	-25.43	-22.87
6	13.56250	0.55	42.67	40.80	43.22	41.35	60.00	50.00	-16.78	-8.65

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value





A D T

5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

5.3.2 TEST SETUP

Same as section 4.3.2.

5.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.3.4 TEST PROCEDURE

Same as section 4.3.4.

5.3.5 DEVIATION FROM TEST STANDARD

No deviation.

5.3.6 EUT OPERATING CONDITIONS

Same as section 4.3.6.



A D T

5.3.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	16.41	0.5	PASS
157	5785	16.41	0.5	PASS
161	5805	16.39	0.5	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	17.62	0.5	PASS
157	5785	17.64	0.5	PASS
161	5805	17.62	0.5	PASS

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
151	5755	35.40	0.5	PASS
159	5795	35.29	0.5	PASS

802.11ac (80MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
155	5775	75.35	0.5	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11a




802.11n (20MHz)



802.11n (40MHz)



802.11ac (80MHz)



5.4 MAXIMUM OUTPUT POWER

5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 5725–5850 MHz bands: 1 Watt (30dBm)

5.4.2 TEST SETUP

Same as section 4.4.2.

5.4.3 INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.4.4 TEST PROCEDURES

Same as section 4.4.4.

5.4.5 DEVIATION FROM TEST STANDARD

No deviation.

5.4.6 EUT OPERATING CONDITIONS

Same as section 4.3.6.

5.4.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
149	5745	252.93	24.03	30	PASS
157	5785	246.04	23.91	30	PASS
161	5805	240.44	23.81	30	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
149	5745	247.74	23.94	30	PASS
157	5785	231.74	23.65	30	PASS
161	5805	227.51	23.57	30	PASS

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
151	5755	177.01	22.48	30	PASS
159	5795	172.19	22.36	30	PASS

802.11ac (80MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
155	5775	119.67	20.78	30	PASS



A D T

5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST SETUP

Same as section 4.5.2.

5.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.5.4 TEST PROCEDURE.

Same as section 4.5.4.

5.5.5 DEVIATION FROM TEST STANDARD

No deviation.

5.5.6 EUT OPERATING CONDITION

Same as section 4.3.6.

5.5.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
149	5745	-9.69	8	PASS
157	5785	-9.28	8	PASS
161	5805	-9.02	8	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
149	5745	-9.75	8	PASS
157	5785	-9.57	8	PASS
161	5805	-10.00	8	PASS

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
151	5755	-15.79	8	PASS
159	5795	-14.98	8	PASS

802.11ac (80MHz)


CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
155	5775	-18.43	8	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11a




802.11n (20MHz)



802.11n (40MHz)



802.11ac (80MHz)





A D T

5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST SETUP

Same as section 4.6.2.

5.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.6.4 TEST PROCEDURE

Same as section 4.6.4

5.6.5 DEVIATION FROM TEST STANDARD

No deviation.

5.6.6 EUT OPERATING CONDITION

Same as section 4.3.6

5.6.7 TEST RESULTS



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T

802.11a



CH 149



CH 157




CH 161





A D T



802.11n (20MHz)






A D T

802.11n (40MHz)



802.11ac (80MHz)





A D T

6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---