



FCC TEST REPORT (PART 22)

REPORT NO.: RF150311C27
MODEL NAME: HTV31
FCC ID: NM8HTV31
RECEIVED: Mar. 11, 2015
TESTED: Mar. 12, 2015 ~ Apr. 01, 2015
ISSUED: Apr. 14, 2015

APPLICANT: HTC Corporation

ADDRESS: 1F, 6-3 Baoqiang Road, Xindian District, New Taipei City, Taiwan 231

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	3
1 CERTIFICATION	4
2 SUMMARY OF TEST RESULTS.....	5
2.1 MEASUREMENT UNCERTAINTY	5
2.2 TEST SITE AND INSTRUMENTS	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 CONFIGURATION OF SYSTEM UNDER TEST	9
3.3 DESCRIPTION OF SUPPORT UNITS	9
3.4 TEST ITEM AND TEST CONFIGURATION	10
3.5 EUT OPERATING CONDITIONS	14
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
4 TEST TYPES AND RESULTS.....	15
4.1 OUTPUT POWER MEASUREMENT	15
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	15
4.1.2 TEST PROCEDURES	15
4.1.3 TEST SETUP	16
4.1.4 TEST RESULTS	17
4.2 FREQUENCY STABILITY MEASUREMENT	29
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	29
4.2.2 TEST PROCEDURE	29
4.2.3 TEST SETUP	29
4.2.4 TEST RESULTS	30
4.3 OCCUPIED BANDWIDTH MEASUREMENT	32
4.3.1 TEST PROCEDURES	32
4.3.2 TEST SETUP	32
4.3.3 TEST RESULTS	33
4.4 BAND EDGE MEASUREMENT	39
4.4.1 LIMITS OF BAND EDGE MEASUREMENT	39
4.4.2 TEST SETUP	39
4.4.3 TEST PROCEDURES	39
4.4.4 TEST RESULTS	40
4.5 CONDUCTED SPURIOUS EMISSIONS.....	50
4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT.....	50
4.5.2 TEST PROCEDURE	50
4.5.3 TEST SETUP	50
4.5.4 TEST RESULTS	51
4.6 RADIATED EMISSION MEASUREMENT	54
4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	54
4.6.2 TEST PROCEDURES	54
4.6.3 DEVIATION FROM TEST STANDARD	54
4.6.4 TEST SETUP	55
4.6.5 TEST RESULTS	56
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	66
6 INFORMATION ON THE TESTING LABORATORIES	67
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	68



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150311C27	Original release	Apr. 14, 2015



1 CERTIFICATION

PRODUCT: Smartphone
MODEL: HTV31
BRAND: HTC
APPLICANT: HTC Corporation
TESTED: Mar. 12, 2015 ~ Apr. 01, 2015
TEST SAMPLE: Identical Prototype
STANDARDS: FCC PART 22, Subpart H

The above equipment (model: HTV31) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Ivonne Wu , **DATE** : Apr. 14, 2015
Ivonne Wu / Supervisor

APPROVED BY : Sam Chen , **DATE** : Apr. 14, 2015
Sam Chen / Senior Project Engineer

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 22.913 (a)	Effective Radiated Power	PASS	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	PASS	Meet the requirement of limit.
2.1049	Occupied Bandwidth	PASS	Meet the requirement of limit.
22.917	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -24.15dB at 2509.20MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2015	Jan. 21, 2016
Spectrum Analyzer Agilent	N9010A	MY52220314	Sep. 03, 2014	Sep. 02, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 09, 2015	Feb. 09, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 12, 2014	Dec. 11, 2015
Preamplifier EMCI	EMC 184045	980116	Jan. 09, 2015	Jan. 08, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2014	Dec. 26, 2015
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2014	Oct. 17, 2015
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Nov. 07, 2014	Nov. 06, 2015
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Radio Communication Analyzer	MT8820C	6201300640	Aug. 01, 2013	Jul. 31, 2015

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 10.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 690701.
 5. The IC Site Registration No. is IC 7450F-10.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Smartphone	
MODEL NAME	HTV31	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.83Vdc (battery)	
MODULATION TYPE	GSM/GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	BPSK
	LTE	QPSK, 16QAM
FREQUENCY RANGE	GSM/GPRS/EDGE	824.2MHz ~ 848.8MHz
	WCDMA	826.4MHz ~ 846.6MHz
	LTE 5 (Channel Bandwidth: 1.4MHz)	824.7MHz ~ 848.3MHz
	LTE 5 (Channel Bandwidth: 3MHz)	825.5MHz ~ 847.5MHz
	LTE 5 (Channel Bandwidth: 5MHz)	826.5MHz ~ 846.5MHz
	LTE 5 (Channel Bandwidth: 10MHz)	829MHz ~ 844MHz
	LTE 26 (Channel Bandwidth: 1.4MHz)	824.7MHz ~ 848.3MHz
	LTE 26 (Channel Bandwidth: 3MHz)	825.5MHz ~ 847.5MHz
	LTE 26 (Channel Bandwidth: 5MHz)	826.5MHz ~ 846.5MHz
	LTE 26 (Channel Bandwidth: 10MHz)	829MHz ~ 844MHz
	LTE 26 (Channel Bandwidth: 15MHz)	831.5MHz ~ 841.5MHz
MAX. ERP POWER	GSM	783.79mW
	EDGE	178.16mW
	WCDMA	72.31mW
	LTE 5 (Channel Bandwidth: 1.4MHz)	86.86mW
	LTE 5 (Channel Bandwidth: 3MHz)	96.34mW
	LTE 5 (Channel Bandwidth: 5MHz)	90.36mW
	LTE 5 (Channel Bandwidth: 10MHz)	95.06mW
	LTE 26 (Channel Bandwidth: 1.4MHz)	77.62mW
	LTE 26 (Channel Bandwidth: 3MHz)	78.31mW
	LTE 26 (Channel Bandwidth: 5MHz)	80.39mW
	LTE 26 (Channel Bandwidth: 10MHz)	76.07mW
LTE 26 (Channel Bandwidth: 15MHz)	80.69mW	


EMISSION DESIGNATOR	GSM	247KGXW
	EDGE	250KG7W
	WCDMA	4M15F9W
	LTE 5 (Channel Bandwidth: 1.4MHz)	1M09W7D
	LTE 5 (Channel Bandwidth: 3MHz)	2M70G7D
	LTE 5 (Channel Bandwidth: 5MHz)	4M50G7D
	LTE 5 (Channel Bandwidth: 10MHz)	8M98W7D
	LTE 26 (Channel Bandwidth: 1.4MHz)	1M09W7D
	LTE 26 (Channel Bandwidth: 3MHz)	2M70G7D
	LTE 26 (Channel Bandwidth: 5MHz)	4M50G7D
	LTE 26 (Channel Bandwidth: 15MHz)	8M96W7D
	LTE 26 (Channel Bandwidth: 10MHz)	13M5W7D
ANTENNA TYPE	Fixed Internal Antenna	
I/O PORTS	Refer to users' manual	
DATA CABLE	Refer to NOTE as below	
ACCESSORY DEVICES	Refer to NOTE as below	

NOTE:


1. The EUT's accessories list refers to Ext. Pho.
2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.R.P. TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y-plane for ERP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
-	ERP	128 to 251	128, 189, 251	GSM, EDGE
-	FREQUENCY STABILITY	128 to 251	189	GSM, EDGE
-	OCCUPIED BANDWIDTH	128 to 251	128, 189, 251	GSM, EDGE
-	BAND EDGE	128 to 251	128, 251	GSM, EDGE
-	CONDUCTED EMISSION	128 to 251	189	GSM, EDGE
-	RADIATED EMISSION	128 to 251	189	GSM, EDGE

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
-	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
-	FREQUENCY STABILITY	4132 to 4233	4182	WCDMA
-	OCCUPIED BANDWIDTH	4132 to 4233	4132, 4182, 4233	WCDMA
-	BAND EDGE	4132 to 4233	4132, 4233	WCDMA
-	CONDUCTED EMISSION	4132 to 4233	4182	WCDMA
-	RADIATED EMISSION	4132 to 4233	4182	WCDMA

LTE BAND 5 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
-	ERP	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	FREQUENCY STABILITY	20407 to 20643	20525	1.4MHz	QPSK	1 RB / 2 RB Offset
		20415 to 20635	20525	3MHz	QPSK	1 RB / 7 RB Offset
		20425 to 20625	20525	5MHz	QPSK	1 RB / 12 RB Offset
		20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset
-	OCCUPIED BANDWIDTH	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	BAND EDGE	20407 to 20643	20407	1.4MHz	QPSK	1 RB / 0 RB Offset
			20643	1.4MHz	QPSK	6 RB / 0 RB Offset
		20415 to 20635	20415	3MHz	QPSK	1 RB / 5 RB Offset
			20635	3MHz	QPSK	6 RB / 0 RB Offset
		20425 to 20626	20415	3MHz	QPSK	1 RB / 0 RB Offset
			20635	3MHz	QPSK	15 RB / 0 RB Offset
		20425 to 20626	20425	5MHz	QPSK	1 RB / 14 RB Offset
			20600	5MHz	QPSK	15 RB / 0 RB Offset
		20450 to 20600	20425	5MHz	QPSK	1 RB / 0 RB Offset
			20600	5MHz	QPSK	25 RB / 0 RB Offset
		20450 to 20600	20450	10MHz	QPSK	1 RB / 24 RB Offset
			20600	10MHz	QPSK	25 RB / 0 RB Offset
20450 to 20600	20450	10MHz	QPSK	1 RB / 0 RB Offset		
	20600	10MHz	QPSK	50 RB / 0 RB Offset		
-	CONDUCTED EMISSION	20407 to 20643	20525	1.4MHz	QPSK	1 RB / 49 RB Offset
		20415 to 20635	20525	3MHz	QPSK	50 RB / 0 RB Offset
		20425 to 20625	20525	5MHz	QPSK	1 RB / 2 RB Offset
		20450 to 20600	20525	10MHz	QPSK	1 RB / 7 RB Offset
-	RADIATED EMISSION	20450 to 20600	20525	10MHz	QPSK	1 RB / 12 RB Offset
-	RADIATED EMISSION	20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.



LTE BAND 26 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE		
-	ERP	26797 to 27033	26797, 26915, 27033	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		26805 to 27025	26805, 26915, 27025	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		26815 to 27015	26815, 26915, 27015	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		26840 to 26990	26840, 26915, 26990	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		26865 to 26965	26865, 26915, 26965	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
-	FREQUENCY STABILITY	26797 to 27033	26915	1.4MHz	QPSK	1 RB / 0 RB Offset		
		26805 to 27025	26915	3MHz	QPSK	1 RB / 0 RB Offset		
		26815 to 27015	26915	5MHz	QPSK	1 RB / 0 RB Offset		
		26840 to 26990	26915	10MHZ	QPSK	1 RB / 0 RB Offset		
		26865 to 26965	26915	15MHZ	QPSK	1 RB / 0 RB Offset		
-	OCCUPIED BANDWIDTH	26797 to 27033	26797, 26915, 27033	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset		
		26805 to 27025	26805, 26915, 27025	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset		
		26815 to 27015	26815, 26915, 27015	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset		
		26840 to 26990	26840, 26915, 26990	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset		
		26865 to 26965	26865, 26915, 26965	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset		
-	BAND EDGE	26797 to 27033	26797	1.4MHz	QPSK	1 RB / 0 RB Offset 6 RB / 0 RB Offset		
			27033	1.4MHz	QPSK	1 RB / 5 RB Offset 6 RB / 0 RB Offset		
		26805 to 27025	26805	3MHz	QPSK	1 RB / 0 RB Offset 15 RB / 0 RB Offset		
			27025	3MHz	QPSK	1 RB / 14 RB Offset 15 RB / 0 RB Offset		
		26815 to 27015	26815	5MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset		
			27015	5MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset		
		26840 to 26990	26840	10MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset		
			26990	10MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset		
		26865 to 26965	26865	15MHz	QPSK	1 RB / 0 RB Offset 75 RB / 0 RB Offset		
			26965	15MHz	QPSK	1 RB / 74 RB Offset 75 RB / 0 RB Offset		
		-	CONDUCTED EMISSION	26797 to 27033	26915	1.4MHz	QPSK	1 RB / 0 RB Offset
				26805 to 27025	26915	3MHz	QPSK	15 RB / 0 RB Offset
				26815 to 27015	26915	5MHz	QPSK	25 RB / 0 RB Offset
				26840 to 26990	26915	10MHZ	QPSK	1 RB / 0 RB Offset
26865 to 26965	26915			15MHZ	QPSK	1 RB / 37 RB Offset		
-	RADIATED EMISSION	26865 to 26965	26915	15MHZ	QPSK	1 RB / 0 RB Offset		

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.



A D T

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	26deg. C, 58%RH	3.83Vdc	Taylor Liu
FREQUENCY STABILITY	26deg. C, 58%RH	3.83Vdc	Taylor Liu
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.83Vdc	Taylor Liu
BAND EDGE	26deg. C, 58%RH	3.83Vdc	Taylor Liu
CONDUCTED EMISSION	26deg. C, 58%RH	3.83Vdc	Taylor Liu
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Hwa Chiang



A D T

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE, 5MHz for WCDMA, and 10MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15\text{dBi}$.

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA & LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



CONDUCTED POWER MEASUREMENT:



4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM850		
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
GSM (GMSK, 1Tx-slot)	33.15	33.11	33.13
GPRS (GMSK, 1Tx-slot)	33.09	33.14	33.08
GPRS (GMSK, 2Tx-slot)	31.80	31.94	31.99
GPRS (GMSK, 3Tx-slot)	30.06	30.32	30.01
GPRS (GMSK, 4Tx-slot)	29.50	29.43	29.44
EDGE (8PSK, 1Tx-slot)	26.64	26.69	26.74
EDGE (8PSK, 2Tx-slot)	26.49	26.54	26.59
EDGE (8PSK, 3Tx-slot)	26.31	26.38	26.33
EDGE (8PSK, 4Tx-slot)	24.56	24.52	24.51

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.12	23.07	22.95
HSDPA Subtest-1	21.77	21.79	21.70
HSDPA Subtest-2	21.85	21.76	21.76
HSDPA Subtest-3	21.28	21.27	21.24
HSDPA Subtest-4	21.28	21.30	21.22
HSUPA Subtest-1	22.06	22.09	21.40
HSUPA Subtest-2	20.98	20.85	20.32
HSUPA Subtest-3	20.88	20.87	20.61
HSUPA Subtest-4	20.94	20.99	20.12
HSUPA Subtest-5	22.10	22.11	22.10



A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	22.25	22.34	22.40	0	21.23	21.32	21.38	1
	1	2	22.66	22.75	22.81	0	21.64	21.73	21.79	1
	1	5	22.23	22.32	22.38	0	21.21	21.30	21.36	1
	3	0	21.24	21.33	21.39	0	20.22	20.31	20.37	1
	3	1	21.19	21.28	21.34	0	20.17	20.26	20.32	1
	3	3	21.13	21.22	21.28	0	20.11	20.20	20.26	1
	6	0	21.11	21.20	21.26	1	20.09	20.18	20.24	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	22.33	22.42	22.48	0	21.31	21.40	21.46	1
	1	7	22.74	22.83	22.89	0	21.72	21.81	21.87	1
	1	14	22.31	22.40	22.46	0	21.29	21.38	21.44	1
	8	0	21.32	21.41	21.47	1	20.30	20.39	20.45	2
	8	3	21.27	21.36	21.42	1	20.25	20.34	20.40	2
	8	7	21.21	21.30	21.36	1	20.19	20.28	20.34	2
	15	0	21.19	21.28	21.34	1	20.17	20.26	20.32	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	22.39	22.48	22.54	0	21.37	21.46	21.52	1
	1	12	22.80	22.89	22.95	0	21.78	21.87	21.93	1
	1	24	22.37	22.46	22.52	0	21.35	21.44	21.50	1
	12	0	21.38	21.47	21.53	1	20.36	20.45	20.51	2
	12	6	21.33	21.42	21.48	1	20.31	20.40	20.46	2
	12	13	21.27	21.36	21.42	1	20.25	20.34	20.40	2
	25	0	21.25	21.34	21.40	1	20.23	20.32	20.38	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	22.46	22.55	22.61	0	21.44	21.53	21.59	1
	1	24	22.87	22.96	23.02	0	21.85	21.94	22.00	1
	1	49	22.44	22.53	22.59	0	21.42	21.51	21.57	1
	25	0	21.45	21.54	21.60	1	20.43	20.52	20.58	2
	25	12	21.40	21.49	21.55	1	20.38	20.47	20.53	2
	25	25	21.34	21.43	21.49	1	20.32	20.41	20.47	2
	50	0	21.32	21.41	21.47	1	20.30	20.39	20.45	2



A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26797	Mid CH 26915	High CH 27033		Low CH 26797	Mid CH 26915	High CH 27033	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
26 / 1.4M	1	0	22.19	22.15	22.25	0	21.15	21.11	21.21	1
	1	2	21.89	21.85	21.95	0	20.85	20.81	20.91	1
	1	5	22.17	22.13	22.23	0	21.13	21.09	21.19	1
	3	0	21.11	21.07	21.17	0	20.07	20.03	20.13	1
	3	1	21.09	21.05	21.15	0	20.05	20.01	20.11	1
	3	3	21.04	21.00	21.10	0	20.00	19.96	20.06	1
	6	0	21.07	21.03	21.13	1	20.03	19.99	20.09	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26805	Mid CH 26915	High CH 27025		Low CH 26805	Mid CH 26915	High CH 27025	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
26 / 3M	1	0	22.27	22.23	22.35	0	21.23	21.19	21.31	1
	1	7	21.97	21.93	22.05	0	20.93	20.89	21.01	1
	1	14	22.25	22.21	22.33	0	21.21	21.17	21.29	1
	8	0	21.19	21.15	21.27	1	20.15	20.11	20.23	2
	8	3	21.17	21.13	21.25	1	20.13	20.09	20.21	2
	8	7	21.12	21.08	21.20	1	20.08	20.04	20.16	2
	15	0	21.15	21.11	21.23	1	20.11	20.07	20.19	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26815	Mid CH 26915	High CH 27015		Low CH 26815	Mid CH 26915	High CH 27015	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
26 / 5M	1	0	22.36	22.32	22.40	0	21.32	21.28	21.36	1
	1	12	22.06	22.02	22.10	0	21.02	20.98	21.06	1
	1	24	22.34	22.30	22.38	0	21.30	21.26	21.34	1
	12	0	21.28	21.24	21.32	1	20.24	20.20	20.28	2
	12	6	21.26	21.22	21.30	1	20.22	20.18	20.26	2
	12	13	21.21	21.17	21.25	1	20.17	20.13	20.21	2
	25	0	21.24	21.20	21.28	1	20.20	20.16	20.24	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26840	Mid CH 26915	High CH 26990		Low CH 26840	Mid CH 26915	High CH 26990	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
26 / 10M	1	0	22.46	22.27	22.52	0	21.42	21.23	21.48	1
	1	24	22.05	21.97	22.22	0	21.01	20.93	21.18	1
	1	49	22.36	22.25	22.50	0	21.32	21.21	21.46	1
	25	0	21.30	21.19	21.44	1	20.26	20.15	20.40	2
	25	12	21.30	21.17	21.42	1	20.26	20.13	20.38	2
	25	25	21.26	21.12	21.37	1	20.22	20.08	20.33	2
	50	0	21.34	21.15	21.40	1	20.30	20.11	20.36	2



A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26865	Mid CH 26915	High CH 26965		Low CH 26865	Mid CH 26915	High CH 26965	
			831.5 MHz	836.5 MHz	841.5 MHz		831.5 MHz	836.5 MHz	841.5 MHz	
26 / 15M	1	0	22.63	22.80	22.61	0	21.34	21.51	21.57	1
	1	37	22.33	22.39	22.31	0	21.04	21.21	21.27	1
	1	74	22.61	22.70	22.59	0	21.32	21.49	21.55	1
	36	0	21.55	21.64	21.53	1	20.26	20.43	20.49	2
	36	19	21.53	21.64	21.51	1	20.24	20.41	20.47	2
	36	39	21.48	21.60	21.46	1	20.19	20.36	20.42	2
	75	0	21.51	21.68	21.49	1	20.22	20.39	20.45	2



A D T

ERP POWER (dBm)

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	128	824.2	-0.58	31.208	28.48	704.37	H
	189	836.4	-0.42	31.3	28.73	746.45	H
	251	848.8	-0.13	31.222	28.94	783.79	H
	128	824.2	-9.37	31.504	19.98	99.63	V
	189	836.4	-9.07	31.117	19.90	97.66	V
	251	848.8	-9.35	31.922	20.42	110.20	V

EDGE							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	128	824.2	-6.55	31.208	22.51	178.16	H
	189	836.4	-7.02	31.3	22.13	163.31	H
	251	848.8	-6.62	31.222	22.45	175.87	H
	128	824.2	-15.32	31.504	14.03	25.32	V
	189	836.4	-14.74	31.117	14.23	26.47	V
	251	848.8	-15.63	31.922	14.14	25.95	V

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	4132	826.4	-10.66	31.208	18.40	69.15	H
	4182	836.4	-10.79	31.3	18.36	68.55	H
	4233	846.6	-10.48	31.222	18.59	72.31	H
	4132	826.4	-18.80	31.504	10.55	11.36	V
	4182	836.4	-18.03	31.117	10.94	12.41	V
	4233	846.6	-19.47	31.922	10.30	10.72	V



A D T

LTE Band 5							
Channel Bandwidth: 1.4MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20407	824.7	-9.67	31.208	19.39	86.86	H
	20525	836.5	-10.06	31.3	19.09	81.10	H
	20643	848.3	-9.75	31.222	19.32	85.55	H
	20407	824.7	-15.83	31.504	13.52	22.51	V
	20525	836.5	-15.24	31.117	13.73	23.59	V
	20643	848.3	-16.25	31.922	13.52	22.50	V

LTE Band 5							
Channel Bandwidth: 1.4MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20407	824.7	-10.31	31.208	18.75	74.95	H
	20525	836.5	-10.48	31.3	18.67	73.62	H
	20643	848.3	-10.27	31.222	18.80	75.89	H
	20407	824.7	-16.53	31.504	12.82	19.16	V
	20525	836.5	-16.06	31.117	12.91	19.53	V
	20643	848.3	-16.92	31.922	12.85	19.28	V

LTE Band 5							
Channel Bandwidth: 3MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20415	825.5	-9.22	31.208	19.84	96.34	H
	20525	836.5	-10.13	31.3	19.02	79.80	H
	20635	847.5	-9.41	31.222	19.66	92.51	H
	20415	825.5	-15.68	31.504	13.67	23.30	V
	20525	836.5	-15.96	31.117	13.01	19.98	V
	20635	847.5	-15.85	31.922	13.92	24.67	V



A D T

LTE Band 5							
Channel Bandwidth: 3MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20415	825.5	-10.26	31.208	18.80	75.82	H
	20525	836.5	-10.20	31.3	18.95	78.52	H
	20635	847.5	-10.22	31.222	18.85	76.77	H
	20415	825.5	-17.24	31.504	12.11	16.27	V
	20525	836.5	-16.63	31.117	12.34	17.13	V
	20635	847.5	-17.37	31.922	12.40	17.39	V

LTE Band 5							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20425	826.5	-9.75	31.208	19.31	85.27	H
	20525	836.5	-9.59	31.3	19.56	90.36	H
	20625	846.5	-9.69	31.222	19.38	86.74	H
	20425	826.5	-15.90	31.504	13.45	22.15	V
	20525	836.5	-15.43	31.117	13.54	22.58	V
	20625	846.5	-16.07	31.922	13.70	23.45	V

LTE Band 5							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20425	826.5	-10.15	31.208	18.91	77.77	H
	20525	836.5	-10.61	31.3	18.54	71.45	H
	20625	846.5	-10.14	31.222	18.93	78.20	H
	20425	826.5	-17.21	31.504	12.14	16.38	V
	20525	836.5	-16.62	31.117	12.35	17.17	V
	20625	846.5	-17.57	31.922	12.20	16.60	V



A D T

LTE Band 5							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829.0	-9.55	31.208	19.51	89.29	H
	20525	836.5	-9.37	31.3	19.78	95.06	H
	20600	844.0	-9.72	31.222	19.35	86.14	H
	20450	829.0	-15.53	31.504	13.82	24.12	V
	20525	836.5	-15.03	31.117	13.94	24.76	V
	20600	844.0	-16.26	31.922	13.51	22.45	V

LTE Band 5							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829.0	-10.94	31.208	18.12	64.83	H
	20525	836.5	-10.79	31.3	18.36	68.55	H
	20600	844.0	-10.41	31.222	18.66	73.49	H
	20450	829.0	-16.93	31.504	12.42	17.47	V
	20525	836.5	-16.78	31.117	12.19	16.55	V
	20600	844.0	-16.96	31.922	12.81	19.11	V



LTE Band 26							
Channel Bandwidth: 1.4MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26797	824.7	-10.36	31.208	18.70	74.10	H
	26915	836.5	-10.25	31.3	18.90	77.62	H
	27033	848.3	-10.63	31.222	18.44	69.86	H
	26797	824.7	-18.09	31.504	11.26	13.38	V
	26915	836.5	-17.20	31.117	11.77	15.02	V
	27033	848.3	-17.89	31.922	11.88	15.42	V

LTE Band 26							
Channel Bandwidth: 1.4MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26797	824.7	-11.34	31.208	17.72	59.13	H
	26915	836.5	-11.70	31.3	17.45	55.59	H
	27033	848.3	-11.76	31.222	17.31	53.85	H
	26797	824.7	-19.32	31.504	10.03	10.08	V
	26915	836.5	-18.68	31.117	10.29	10.68	V
	27033	848.3	-19.65	31.922	10.12	10.28	V

LTE Band 26							
Channel Bandwidth: 3MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26805	825.5	-10.12	31.208	18.94	78.31	H
	26915	836.5	-10.24	31.3	18.91	77.80	H
	27025	847.5	-10.85	31.222	18.22	66.40	H
	26805	825.5	-17.65	31.504	11.70	14.80	V
	26915	836.5	-17.85	31.117	11.12	12.93	V
	27025	847.5	-18.00	31.922	11.77	15.04	V



A D T

LTE Band 26							
Channel Bandwidth: 3MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26805	825.5	-11.89	31.208	17.17	52.10	H
	26915	836.5	-12.07	31.3	17.08	51.05	H
	27025	847.5	-11.39	31.222	17.68	58.64	H
	26805	825.5	-18.55	31.504	10.80	12.03	V
	26915	836.5	-18.73	31.117	10.24	10.56	V
	27025	847.5	-18.84	31.922	10.93	12.39	V

LTE Band 26							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26815	826.5	-10.29	31.208	18.77	75.30	H
	26915	836.5	-10.70	31.3	18.45	69.98	H
	27015	846.5	-10.02	31.222	19.05	80.39	H
	26815	826.5	-17.81	31.504	11.54	14.27	V
	26919	836.5	-17.15	31.117	11.82	15.19	V
	27015	846.5	-18.05	31.922	11.72	14.87	V

LTE Band 26							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26815	826.5	-11.65	31.208	17.41	55.06	H
	26915	836.5	-11.94	31.3	17.21	52.60	H
	27015	846.5	-11.60	31.222	17.47	55.87	H
	26815	826.5	-18.36	31.504	10.99	12.57	V
	26919	836.5	-18.86	31.117	10.11	10.25	V
	27015	846.5	-19.67	31.922	10.10	10.24	V



A D T

LTE Band 26							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26840	829.0	-10.43	31.208	18.63	72.91	H
	26915	836.5	-10.42	31.3	18.73	74.64	H
	26990	844.0	-10.26	31.222	18.81	76.07	H
	26840	829.0	-17.84	31.504	11.51	14.17	V
	26919	836.5	-17.09	31.117	11.88	15.41	V
	26990	844.0	-18.30	31.922	11.47	14.03	V

LTE Band 26							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26840	829.0	-11.52	31.208	17.54	56.73	H
	26915	836.5	-11.95	31.3	17.20	52.48	H
	26990	844.0	-11.85	31.222	17.22	52.75	H
	26840	829.0	-19.15	31.504	10.20	10.48	V
	26919	836.5	-18.65	31.117	10.32	10.76	V
	26990	844.0	-18.92	31.922	10.85	12.17	V



A D T

LTE Band 26							
Channel Bandwidth: 15MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26865	831.5	-9.99	31.208	19.07	80.69	H
	26915	836.5	-10.56	31.3	18.59	72.28	H
	26965	841.5	-10.30	31.222	18.77	75.37	H
	26865	831.5	-17.79	31.504	11.56	14.34	V
	26915	836.5	-17.00	31.117	11.97	15.73	V
	26965	841.5	-18.44	31.922	11.33	13.59	V

LTE Band 26							
Channel Bandwidth: 15MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	26865	831.5	-10.91	31.208	18.15	65.28	H
	26915	836.5	-11.06	31.3	18.09	64.42	H
	26965	841.5	-11.76	31.222	17.31	53.85	H
	26865	831.5	-18.26	31.504	11.09	12.86	V
	26915	836.5	-17.81	31.117	11.16	13.05	V
	26965	841.5	-19.08	31.922	10.69	11.73	V

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP



4.2.4 TEST RESULTS

FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)							LIMIT (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4MHz	3MHz	5MHz	10MHz	
3.83	0.003	0.004	0.002	0.004	0.003	0.003	0.002	2.5
3.5	0.002	0.002	0.004	0.002	0.005	0.004	0.004	2.5
4.4	0.004	0.005	0.003	0.003	0.002	0.002	0.003	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.4Vdc.

FREQUENCY ERROR vs. TEMPERATURE

TEMP. (°C)	FREQUENCY ERROR (ppm)							LIMIT (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4MHz	3MHz	5MHz	10MHz	
-30	0.001	0.003	0.003	0.004	0.003	0.005	0.003	2.5
-20	0.004	0.005	-0.004	0.002	0.002	0.002	-0.004	2.5
-10	0.003	-0.004	-0.002	-0.004	0.003	-0.003	-0.005	2.5
0	0.003	-0.002	-0.003	-0.002	0.002	-0.005	-0.002	2.5
10	-0.002	-0.003	-0.002	-0.003	0.004	-0.003	-0.003	2.5
20	-0.003	-0.004	-0.004	-0.005	-0.003	-0.004	-0.003	2.5
30	-0.004	-0.005	-0.003	-0.003	-0.002	-0.003	0.004	2.5
40	-0.005	-0.002	0.005	-0.001	-0.004	-0.002	0.005	2.5
50	-0.003	0.002	0.004	0.003	-0.003	0.004	0.002	2.5

FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)					LIMIT (ppm)
	LTE Band 26					
	1.4MHz	3MHz	5MHz	10MHz	15MHz	
3.83	0.004	0.003	0.004	0.003	0.003	2.5
3.5	0.003	0.004	0.002	0.002	0.002	2.5
4.4	0.001	0.002	0.003	0.004	0.005	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.55Vdc to 4.35Vdc.

FREQUENCY ERROR vs. TEMPERATURE


TEMP. (°C)	FREQUENCY ERROR (ppm)					LIMIT (ppm)
	LTE Band 26					
	1.4MHz	3MHz	5MHz	10MHz	15MHz	
-30	0.004	0.002	0.003	0.004	0.002	2.5
-20	0.002	0.006	-0.005	0.001	0.001	2.5
-10	0.001	0.004	-0.003	0.003	-0.003	2.5
0	-0.003	0.003	-0.004	-0.004	-0.004	2.5
10	-0.002	-0.003	-0.005	-0.003	-0.003	2.5
20	-0.003	-0.004	-0.002	-0.002	-0.005	2.5
30	-0.005	-0.003	-0.003	-0.005	-0.005	2.5
40	-0.004	-0.006	0.004	-0.003	0.002	2.5
50	0.002	-0.003	0.006	0.004	0.002	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 TEST SETUP






A D T

4.3.3 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)
		GSM	EDGE			WCDMA
128	824.2	246.04	249.54	4132	826.4	4.1524
189	836.4	246.07	250.25	4182	836.4	4.1503
251	848.8	246.83	251.35	4233	846.6	4.1523
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)
		GSM	EDGE			WCDMA
128	824.2	309.80	310.60	4132	826.4	4.730
189	836.4	312.80	319.10	4182	836.4	4.726
251	848.8	312.50	308.40	4233	846.6	4.724







A D T


LTE BAND 5							
CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.0862	1.0865	20415	825.5	2.6981	2.6944
20525	836.5	1.0862	1.0888	20525	836.5	2.6974	2.6965
20643	848.3	1.0875	1.0890	20635	847.5	2.6992	2.6966
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.212	1.213	20415	825.5	2.931	2.927
20525	836.5	1.207	1.214	20525	836.5	2.937	2.932
20643	848.3	1.206	1.210	20635	847.5	2.935	2.929

SPECTRUM PLOT OF WORST VALUE






LTE BAND 5							
CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.4995	4.4911	20450	829.0	8.9710	8.9773
20525	836.5	4.4949	4.4880	20525	836.5	8.9615	8.9607
20625	846.5	4.4907	4.4897	20600	844.0	8.9647	8.9647
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.815	4.801	20450	829.0	9.520	9.531
20525	836.5	4.816	4.802	20525	836.5	9.520	9.502
20625	846.5	4.796	4.794	20600	844.0	9.538	9.516





A D T


LTE BAND 26							
CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
26797	824.7	1.0866	1.0876	26805	825.5	2.7023	2.6953
26915	836.5	1.0860	1.0869	26915	836.5	2.7008	2.6958
27033	848.3	1.0862	1.0882	27025	847.5	2.6957	2.6964
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
26797	824.7	1.211	1.215	26805	825.5	2.923	2.926
26915	836.5	1.214	1.214	26915	836.5	2.925	2.913
27033	848.3	1.211	1.211	27025	847.5	2.923	2.921





A D T


LTE BAND 26							
CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
26815	826.5	4.4915	4.4878	26840	829.0	8.9631	8.9648
26915	836.5	4.4920	4.4876	26915	836.5	8.9589	8.9586
27015	846.5	4.4954	4.4878	26990	844.0	8.9640	8.9601
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
26815	826.5	4.809	4.791	26840	829.0	9.496	9.501
26915	836.5	4.813	4.791	26915	836.5	9.527	9.511
27015	846.5	4.796	4.793	26990	844.0	9.503	9.520





A D T

LTE BAND 26							
CHANNEL BANDWIDTH: 15MHz							
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
26865	831.5	13.451	13.456	26865	831.5	14.25	14.25
26915	836.5	13.442	13.442	26915	836.5	14.24	14.24
26965	841.5	13.450	13.448	26965	841.5	14.25	14.24




4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST SETUP




4.4.3 TEST PROCEDURES

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 3.9kHz and VB of the spectrum is 12kHz (GSM/GPRS/EDGE).
- The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 13kHz and VB of the spectrum is 51kHz (LTE Bandwidth 1.4MHz).
- The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz (LTE Bandwidth 3MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Bandwidth 5MHz/10MHz).
- The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 150kHz and VB of the spectrum is 470kHz (LTE Bandwidth 15MHz).
- Record the max trace plot into the test report.




A D T

4.4.4 TEST RESULTS






A D T






A D T






A D T






A D T






A D T






A D T






A D T






A D T





A D T



4.5 CONDUCTED SPURIOUS EMISSIONS


4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13dBm.

4.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30 MHz to 9GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.


4.5.3 TEST SETUP






A D T

4.5.4 TEST RESULTS






A D T





A D T



4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13dBm.

4.6.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15\text{dBi}$.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.3 DEVIATION FROM TEST STANDARD

No deviation

4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.6.5 TEST RESULTS


GSM:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
 Condition: PART 22/24 3m Horizontal
 Remark : GSM 850_LINK_CH189
 Tested by: Hwa Chiang
 Plane : X

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	59.43	-56.31	-42.25	-13.00	-43.31	-14.06 Peak
2	122.61	-44.27	-36.14	-13.00	-31.27	-8.13 Peak
3	193.62	-49.07	-43.16	-13.00	-36.07	-5.91 Peak
4	317.50	-63.44	-57.68	-13.00	-50.44	-5.76 Peak
5	652.10	-56.89	-56.75	-13.00	-43.89	-0.14 Peak
6	947.50	-51.42	-56.44	-13.00	-38.42	5.02 Peak
7	1672.80	-39.66	-47.57	-13.00	-26.66	7.91 Peak
8 pp	2509.20	-37.15	-48.43	-13.00	-24.15	11.28 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-04-01



Site : 966 chamber 1
 Condition: PART 22/24 3m Vertical
 Remark : GSM 850_LINK_CH189
 Tested by: Hwa Chiang
 Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	35.13	-45.71	-34.61	-13.00	-32.71	-11.10	Peak
2	96.42	-49.67	-39.33	-13.00	-36.67	-10.34	Peak
3	195.78	-56.04	-50.04	-13.00	-43.04	-6.00	Peak
4	392.40	-64.06	-60.96	-13.00	-51.06	-3.10	Peak
5	736.80	-54.90	-53.83	-13.00	-41.90	-1.07	Peak
6	948.20	-51.11	-56.17	-13.00	-38.11	5.06	Peak
7	1672.80	-44.23	-52.14	-13.00	-31.23	7.91	Peak
8 pp	2509.20	-39.33	-50.61	-13.00	-26.33	11.28	Peak
9	8364.00	-39.84	-63.97	-13.00	-26.84	24.13	Peak



A D T

EDGE:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2015-03-28



Site : 966 chamber 1
 Condition: PART 22/24 3m Horizontal
 Remark : EDGE 850_Link_CH189
 Tested by: Hwa Chiang
 Plane : X


	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-51.91	-59.82	-13.00	-38.91	7.91	Peak
2 pp	2509.20	-39.28	-50.56	-13.00	-26.28	11.28	Peak



A D T

Data: 6

Date: 2015-03-28



Site : 966 chamber 1
 Condition: PART 22/24 3m Vertical
 Remark : EDGE 850_Link_CH189
 Tested by: Hwa Chiang
 Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-53.94	-61.85	-13.00	-40.94	7.91	Peak
2 pp	2509.20	-39.93	-51.21	-13.00	-26.93	11.28	Peak

WCDMA:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2015-03-28



Site : 966 chamber 1
 Condition: PART 22/24 3m Horizontal
 Remark : Band V_Link_CH4182
 Tested by: Hwa Chiang
 Plane : X

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-56.59	-64.50	-13.00	-43.59	7.91 Peak
2 pp	2509.20	-50.88	-62.16	-13.00	-37.88	11.28 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2015-03-28



Site : 966 chamber 1
 Condition: PART 22/24 3m Vertical
 Remark : Band V_Link_CH4182
 Tested by: Hwa Chiang
 Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-56.67	-64.58	-13.00	-43.67	7.91	Peak
2 pp	2509.20	-50.43	-61.71	-13.00	-37.43	11.28	Peak

LTE BAND 5
CHANNEL BANDWIDTH: 10MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-03-28



Site : 966 chamber 1
 Condition: PART 22/24 3m Horizontal
 Remark : LTE_Band 5_QPSK(1,24)_10M_CH20525
 Tested by: Hwa Chiang
 Plane : X

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	96.69	-48.14	-37.85	-13.00	-35.14	-10.29	Peak
2	pp 124.77	-45.20	-37.25	-13.00	-32.20	-7.95	Peak
3	194.43	-47.26	-41.30	-13.00	-34.26	-5.96	Peak
4	314.70	-62.07	-56.29	-13.00	-49.07	-5.78	Peak
5	433.00	-67.81	-64.35	-13.00	-54.81	-3.46	Peak
6	695.50	-68.24	-67.89	-13.00	-55.24	-0.35	Peak
7	1673.00	-52.71	-60.62	-13.00	-39.71	7.91	Peak
8	2509.50	-47.86	-59.14	-13.00	-34.86	11.28	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-04-01



Site : 966 chamber 1
 Condition: PART 22/24 3m Vertical
 Remark : LTE_Band 5_QPSK(1,24)_10M_CH20525
 Tested by: Hwa Chiang
 Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	34.86	-47.87	-36.77	-13.00	-34.87	-11.10	Peak
2	125.31	-50.61	-42.66	-13.00	-37.61	-7.95	Peak
3	195.24	-55.47	-49.51	-13.00	-42.47	-5.96	Peak
4	390.30	-65.64	-62.38	-13.00	-52.64	-3.26	Peak
5	589.10	-67.46	-67.41	-13.00	-54.46	-0.05	Peak
6	986.70	-64.42	-69.64	-13.00	-51.42	5.22	Peak
7	2509.50	-41.05	-52.33	-13.00	-28.05	11.28	Peak
8 pp	8365.00	-40.53	-64.66	-13.00	-27.53	24.13	Peak

LTE BAND 26
CHANNEL BANDWIDTH: 15MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-03-28



Site : 966 chamber 1
 Condition: PART 22/24 3m Horizontal
 Remark : LTE_Band 26_QPSK(1,0)_15M_CH26915
 Tested by: Hwa Chiang
 Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	59.43	-55.28	-41.22	-13.00	-42.28	-14.06	Peak
2	pp 123.42	-42.64	-34.57	-13.00	-29.64	-8.07	Peak
3	197.67	-47.84	-41.75	-13.00	-34.84	-6.09	Peak
4	319.60	-61.90	-56.18	-13.00	-48.90	-5.72	Peak
5	659.10	-68.21	-68.03	-13.00	-55.21	-0.18	Peak
6	994.40	-63.62	-68.87	-13.00	-50.62	5.25	Peak
7	1673.00	-51.49	-59.40	-13.00	-38.49	7.91	Peak
8	2509.50	-43.01	-54.29	-13.00	-30.01	11.28	Peak



A D T




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-04-01



Site : 966 chamber 1
 Condition: PART 22/24 3m Vertical
 Remark : LTE_Band 26_QPSK(1,0)_15M_CH26915
 Tested by: Hwa Chiang
 Plane : X

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	49.17	-46.64	-32.90	-13.00	-33.64	-13.74	Peak
2	125.85	-48.79	-40.90	-13.00	-35.79	-7.89	Peak
3	193.08	-55.41	-49.54	-13.00	-42.41	-5.87	Peak
4	392.40	-64.07	-60.97	-13.00	-51.07	-3.10	Peak
5	687.80	-67.88	-67.56	-13.00	-54.88	-0.32	Peak
6	949.60	-63.19	-68.30	-13.00	-50.19	5.11	Peak
7	1673.00	-55.36	-63.27	-13.00	-42.36	7.91	Peak
8	2509.50	-45.95	-57.23	-13.00	-32.95	11.28	Peak
9 pp	8365.00	-40.28	-64.41	-13.00	-27.28	24.13	Peak



A D T

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab:

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab:

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---