

Antenna Specification

Project Name :	Phoebus	Date:	06/06/2007
Project Manager:	Kelven Ko	Rev.:	0.1

Countersign :

Lorentz Lu

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*



Revision History

Revision	Revision History	Date	Author(s)
0.1	Preliminary Release	06/06/2007	Lorentz Lu

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*





CONTENTS

Embedded GSM Antenna Engineering Specification	P.4
Embedded BT Antenna Engineering Specification	P.9
Embedded WiFi Antenna Engineering Specification	P.11

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*





Embedded Quad-Band Antenna

1. Overview

The following is the specification of the embedded Quad-band antenna for PHONE applications. Quad-band includes GSM850, GSM900, DCS1800 and PCS1900.

1.1.1 Denotations

dBi: Decibel relative isotropic antenna VSWR: Voltage Standing Wave Ratio Tx: Transmit frequency Rx: Receive frequency GSM: Global Service for Mobile communication DCS: Digital Communication System PCS: Personal Communication System SAR: Specific Absorption Rate Peak Gain: The peak value of the antenna gain Average Gain: The average value of the antenna gain EIRP: Effective Isotropic Radiation Power TRP: Total Radiation Power EIS: Effective Isotropic Sensitivity TIS: Total Isotropic Sensitivity dBm: Decibel of m-Watt

1.1.2 Frequency Allocation

GSM850: 824MHz~894MHz GSM900: 880MHz~960MHz DCS1800: 1710MHz~1880MHz PCS1900: 1850MHz~1990MHz

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. HTC CONFIDENTIAL



2. Measurement Parameters

2.1 Passive Parameters

2.1.1 VSWR

VSWR indicates the matching characteristics of the antenna. VSWR can be measured by a network analyzer.

2.1.2 Antenna Gain and Pattern

Antenna gain and far-field pattern can be determined by two measurement skills, depending on the own equipments. One is the far-field measurement; the other is the 3-D measurement system. Sometimes, the gain value is also needed to be measured under specified user conditions.

2.2 Active Parameters

2.2.1 Radiation Power

Antenna radiation power means the real radiated ability of an active system. Two most popular index values to specify the ability of radiation power is EIRP and TRP. EIRP means the peak radiation power, and TRP is the total radiation power. In some user conditions, the TRP value is also specified.

2.2.2 Receiving Sensitivity

Antenna radiation power means the real receiving ability of an active system. Two most popular index values to specify the ability of receiving ability is EIS and TIS. EIS means the peak receiving sensitivity, and TIS is the total receiving sensitivity. In some user conditions, the TIS value is also specified.

2.2.3 SAR (Specified Absorption Rate)

In order to protect the health of human, WHO has specified the SAR value (Specified Absorption Rate of human) to ensure the RF device has less damage to human health. The SAR value limitation is 1.6mW/g.

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*



3. Specification Requirements

3.1 Passive Specifications

3.1.1 VSWR (For US 850/1900 System only)

	GSM850	GSM900	DCS1800	PCS1900
Free space	4:1	4:1	3:1	3:1

Notably: The VSWR value will be degraded due to mechanical and space constrains.

3.1.2 Gain and Patterns (Total Field)

(1)Free Space (For US 850/1900 System only)

	GSM850	GSM900	DCS1800	PCS1900
Average gain	>-4.5dBi	>-6.5dBi	>-4.5dBi	>-2.5dBi

Notably: The target values (peak and average gains) will be degraded due to mechanical and space constrains.

3.2 Active Specifications

3.2.1 Radiation Power

(1)Free Space (For US 850/1900 System only)

	GSM850	GSM900	DCS1800	PCS1900
EIRP	>30.0dBm	>28.0dBm	>25.0dBm	>29.0dBm
TRP	>28.0dBm	>26.0dBm	>25.0dBm	>27.0dBm

Notably: The radiation power values will be degraded due to mechanical and space constrains.

3.2.2 Receiving Sensitivity

(1) Free Space (For US 850/1900 System only)

· · · ·				
	GSM850	GSM900	DCS1800	PCS1900
EIS	<-104.0dBm	<-100.0dBm	<-104.0dBm	<-104.0dBm
TIS	<-103.0dBm	<-100.0dBm	<-101.5dBm	<-103.0dBm

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*





Notably: The receiving sensitivity values will be degraded due to mechanical and space constrains.

4. Antenna Materials

The antenna can not have the materials of plumbum (Pb), halogen and mercury (Hg).

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*





Embedded BT Antenna

1. Overview

The following is the specification of the embedded BT antenna for PHONE applications.

1.1.1 Denotations

dBi: Decibel relative isotropic antenna VSWR: Voltage Standing Wave Ratio Peak Gain: The peak value of the antenna gain Average Gain: The average value of the antenna gain EIRP: Effective Isotropic Radiation Power EIS: Effective Isotropic Sensitivity dBm: Decibel of m-Watt

1.1.2 Frequency Allocation

BT: 2400MHz~2500MHz

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*





2. Specification Requirements

2.1 Passive Specifications

2.1.1 VSWR

	BT2400
Free space	2:1

Notably: The VSWR value will be degraded due to mechanical and space constrains.

2.1.2 Gain and Patterns (Total Field)

Free Space

	BT2400
Peak gain	>0.0dBi
Average gain	> -5.0dBi

Notably: The target values (peak and average gains) will be degraded due to mechanical and space constrains.

2.2 Active Specifications

2.2.1 Radiation Power

Free Space

	BT2400
EIRP	> -6 dBm

Notably: The radiation power values will be degraded due to mechanical and space constrains.

2.2.2 Receiving Sensitivity

Free Space

-	BT
EIS	< -73.0dBm

Notably: The receiving sensitivity values will be degraded due to mechanical and space constrains.

3. Antenna Materials

The antenna can not have the materials of plumbum (Pb), halogen and mercury (Hg).

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*





Embedded WiFi Antenna

4. Overview

The following is the specification of the embedded WiFi antenna for PHONE applications.

1.1.3 Denotations

dBi: Decibel relative isotropic antenna VSWR: Voltage Standing Wave Ratio Peak Gain: The peak value of the antenna gain Average Gain: The average value of the antenna gain EIRP: Effective Isotropic Radiation Power EIS: Effective Isotropic Sensitivity dBm: Decibel of m-Watt

1.1.4 Frequency Allocation

WiFi: 2400MHz~2500MHz

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*





5. Specification Requirements

2.1 Passive Specifications

2.1.3 VSWR

	WiFi2400
Free space	2:1

Notably: The VSWR value will be degraded due to mechanical and space constrains.

2.1.4 Gain and Patterns (Total Field)

Free Space

	WiFi2400
Peak gain	>0.0dBi
Average gain	> -4.0dBi

Notably: The target values (peak and average gains) will be degraded due to mechanical and space constrains.

2.2 Active Specifications

2.2.3 Radiation Power

Free Space

	WiFi2400
EIRP	>9dBm

Notably: The radiation power values will be degraded due to mechanical and space constrains.

2.2.4 Receiving Sensitivity

Free Space

	WiFi
EIS	< -76.0dBm

Notably: The receiving sensitivity values will be degraded due to mechanical and space constrains.

6. Antenna Materials

The antenna can not have the materials of plumbum (Pb), halogen and mercury (Hg).

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP. *HTC CONFIDENTIAL*