

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT****INTENTIONAL RADIATOR CERTIFICATION TO  
FCC PART 15 SUBPART C REQUIREMENT  
AND INDUSTRY CANADA RSS-210**

OF

**Product Name:** PDA Phone

**Brand Name:** HTC

**Model Name:** PB99100

**Model Difference:** N/A

**IC:** 4115B-PB99100

**FCC ID:** NM8PB99100


**Report No.:** EH/2009/90002

**Issue Date:** Oct. 02, 2009

**Rule Part:** §15.247, Cat: DSS  
RSS-210 issue 7:2007, Annex 8

**Prepared for:** HTC Corporation  
No. 23 Xinghua Rd., Taoyuan City, Taoyuan County  
330, Taiwan, ROC

**Prepared by:** SGS Taiwan Ltd.  
Electronics & Communication Laboratory  
No. 134, Wu Kung Rd., Wuku Industrial Zone,  
Taipei County, Taiwan.



*Note: This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.*

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service ([www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm)) and Terms and Conditions for Electronic Documents ([www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm)). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at [www.sgsonsite.com/authentication](http://www.sgsonsite.com/authentication). Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

## CERTIFICATION OF COMPLIANCE

**Applicant:** HTC Corporation  
No. 23 Xinghua Rd., Taoyuan City, Taoyuan County 330, Taiwan,  
ROC

**Product Name:** PDA Phone

**Brand Name:** HTC

**IC:** 4115B-PB99100

**FCC ID:** NM8PB99100

**Model No.:** PB99100

**Model Difference:** N/A

**File Number:** EH/2009/90002

**Date of test:** Aug. 17, 2009 ~ Sep. 03, 2009

**Date of EUT Received:** Aug. 17, 2009

**We hereby certify that:**

The above equipment was tested by SGS Taiwan Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and RSS-Gen. issue 2:2007, the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15C:2007, §15.247 and RSS-210 issue 7: 2007 Annex 8.

The test results of this report relate only to the tested sample identified in this report.

<b>Test By:</b>	<u>Jazz Huang</u>	<b>Date:</b>	<u>Oct. 02, 2009</u>
	<b>Jazz Huang / Engineer</b>		
<b>Prepared By:</b>	<u>Gigi yeh</u>	<b>Date:</b>	<u>Oct. 02, 2009</u>
	<b>Gigi Yeh / Clerk</b>		
<b>Approved By:</b>	<u>Vincent Su</u>	<b>Date:</b>	<u>Oct. 02, 2009</u>
	<b>Vincent Su / Manager</b>		

## Version

Version No.	Date	Description
00	Oct. 02, 2009	Initial creation of document

## Table of Contents

<b>1. GENERAL INFORMATION .....</b>	<b>7</b>
1.1. Product Description .....	7
1.2. Related Submittal(s) / Grant (s) .....	10
1.3. Test Methodology .....	10
1.4. Test Facility .....	10
1.5. Special Accessories .....	10
1.6. Equipment Modifications .....	10
<b>2. SYSTEM TEST CONFIGURATION .....</b>	<b>11</b>
2.1. EUT Configuration .....	11
2.2. EUT Exercise .....	11
2.3. Test Procedure .....	11
2.4. Configuration of Tested System .....	12
<b>3. SUMMARY OF TEST RESULTS .....</b>	<b>13</b>
<b>4. DESCRIPTION OF TEST MODES .....</b>	<b>13</b>
<b>5. AC POWER LINE CONDUCTED EMISSION TEST .....</b>	<b>14</b>
5.1. Standard Applicable: .....	14
5.2. Measurement Equipment Used: .....	14
5.3. EUT Setup: .....	14
5.4. Measurement Procedure: .....	15
5.5. Measurement Result: .....	15
<b>6. PEAK OUTPUT POWER MEASUREMENT .....</b>	<b>18</b>
6.1. Standard Applicable: .....	18
6.2. Measurement Equipment Used: .....	18
6.3. Test Set-up: .....	19
6.4. Measurement Procedure: .....	19
6.5. Measurement Result: .....	20
<b>7. 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT .....</b>	<b>25</b>
7.1. Standard Applicable: .....	25
7.2. Measurement Equipment Used: .....	26
7.3. Test SET-UP: .....	27
7.4. Measurement Procedure: .....	28
7.5. Field Strength Calculation .....	28
7.6. Measurement Result: .....	28

<b>8. SPURIOUS EMISSION TEST .....</b>	<b>37</b>
8.1. Standard Applicable: .....	37
8.2. Measurement Equipment Used: .....	37
8.3. Test SET-UP:.....	37
8.4. Measurement Procedure: .....	38
8.5. Field Strength Calculation .....	38
8.6. Measurement Result: .....	38
<b>9. FREQUENCY SEPARATION .....</b>	<b>63</b>
9.1. Standard Applicable: .....	63
9.2. Measurement Equipment Used: .....	63
9.3. Test Set-up: .....	63
9.4. Measurement Procedure: .....	63
9.5. Measurement Result: .....	63
<b>10. NUMBER OF HOPPING FREQUENCY .....</b>	<b>65</b>
10.1. Standard Applicable: .....	65
10.2. Measurement Equipment Used: .....	65
10.3. Test Set-up: .....	65
10.4. Measurement Procedure: .....	65
10.5. Measurement Result: .....	65
<b>11. TIME OF OCCUPANCY (DWELL TIME) .....</b>	<b>67</b>
11.1. Standard Applicable: .....	67
11.2. Measurement Equipment Used: .....	67
11.3. Test Set-up: .....	67
11.4. Measurement Procedure: .....	67
11.5. Measurement Result: .....	68
<b>12. Peak Power Spectral Density .....</b>	<b>74</b>
12.1. Standard Applicable: .....	74
12.2. Measurement Equipment Used: .....	74
12.3. Test Set-up: .....	74
12.4. Measurement Procedure: .....	74
12.5. Measurement Result: .....	75
<b>13. 20dB Bandwidth.....</b>	<b>78</b>
13.1. Standard Applicable: .....	78
13.2. Measurement Equipment Used: .....	78
13.3. Test Set-up: .....	78

13.4. Measurement Procedure: .....	78
13.5. Measurement Result: .....	79
<b>14. ANTENNA REQUIREMENT .....</b>	<b>84</b>
14.1. Standard Applicable: .....	84
14.2. Antenna Connected Construction: .....	84
<b>15. 99% Bandwidth Measurement .....</b>	<b>85</b>
15.1. Standard Applicable: .....	85
15.2. Measurement Equipment Used: .....	85
15.3. Test Set-up: .....	85
15.4. Measurement Procedure: .....	85
15.5. Measurement Result: .....	86

## 1. GENERAL INFORMATION

### 1.1. Product Description

General:

Product Name	PDA Phone	
Brand Name	HTC	
Model Name	PB99100	
Model Difference	N/A	
Data Cable (USB)	Model No.: DC M400, Supplier: MEC	
Simple Hands-free (SHF)	Model No.: RC E151, Supplier: Cotron / Merry	
Power Supply	3.7 Vdc re-chargeable battery or 5Vdc by AC/DC power adapter	
	Battery:	Model: BB99100, Supplier: Formasa / Welldone
	Adapter:	Model No.: PSAA05X-050(X=A,C,E,K or S), Supplier: Phihong

### Other Source

Camera	(1) 1ST :Model No.: 08PM15A ; Supplier: LiteOn (2) 2ND:Model No.: 50-70483HTT8 ; Supplier: Primax
--------	--

GSM and WCDMA:

	Operating Frequency		Rated Power
Cellular Phone Standards Frequency Range and Power	GSM/GPRS/EDGE 850 Class 12	824.2 MHz– 848.8 MHz	33 dBm
	GSM/GPRS/EDGE 900 Class 12	880.2MHz – 914.8MHz	33 dBm
	GSM/GPRS/EDGE 1800 Class 12	1710.2MHz – 1784.8MHz	30 dBm
	GSM/GPRS/EDGE 1900 Class 12	1850.2MHz – 1909.8MHz	30 dBm
	WCDMA/HSUPA/HSDPA Band I	1922.4MHz – 1977.6MHz	24 dBm
	WCDMA/HSUPA/HSDPA Band IV	1712.4MHz –1752.6MHz	24 dBm
	WCDMA/HSUPA/HSDPA Band VIII	815MHz – 880MHz	24dBm
	HSUPA data rate: uplink up to 2Mbps HSDPA data rate: downlink up to 7.2Mbps		
Type of Emission	GSM 850: 247KGXW, GSM 1900 :247KGXW EDGE 850: 247KG7W, EDGE 1900:246KG7W WCDMA Band IV: 4M16F9W		
IMEI	354957030014388		



WLAN:

Frequency Range:	2412 – 2462 MHz
Channel number:	11 channels
Max. Output Power:	802.11 b: 17.41 dBm (Peak) 802.11 g: 13.54dBm (Peak)
Modulation Technology:	DSSS, OFDM
Modulation type:	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Transition Rate:	802.11 b: 1/2/5.5/11 Mbps; 802.11 g: 6/9/12/18/24/36/48/54 Mbps
Antenna Designation:	PIFA Antenna / 1.1dBi.
Type of Emission	16M3G1D

The EUT is compliance with IEEE 802.11 b/g Standard.

Bluetooth:

Bluetooth Version	<input type="checkbox"/> V1.1 (GFSK) <input type="checkbox"/> V1.2 (GFSK) <input type="checkbox"/> V2.0 (GFSK) <input type="checkbox"/> V2.0 + EDR (GFSK + /4DQPSK + 8DPSK) <input checked="" type="checkbox"/> V2.1 + EDR (GFSK + /4DQPSK + 8DPSK)
Frequency Range	2402 – 2480MHz
Channel number	79 channels max.
Rated Power	1.85 dBm (Peak)
Modulation type	Frequency Hopping Spread Spectrum
Antenna Designation	PIFA Antenna / 1.1dBi.
Type of Emission	1M84F7D

This report applies for Bluetooth

## 1.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: NM8PB99100** filing to comply with Section 15.247 of the FCC Part 15C, Subpart C Rules. And **IC: 4115B-PB99100** filing to comply with Industry Canada RSS-210 issue 7: 2007 Annex 8.

## 1.3. Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003) and RSS-Gen: 2007. Radiated testing was performed at an antenna to EUT distance 3 meters.

## 1.4. Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC Registration Number are: 990257 and 236194, Canada Registration Number: 4620A-1.

The 10 m Open Area Test Sites located on the address of SGS Taiwan Ltd. No. 29, Pau-Tou-Tsuo Valley Chia-Pau Tsuen, Linkou Hsiang, Taipei county, which is constructed and calibrated to meet the CISPR 22/EN 55022 requirements. SGS Site No. 1(3 & 10 meters) and FCC Registration Number: 94644.

## 1.5. Special Accessories

Not available for this EUT intended for grant.

## 1.6. Equipment Modifications

Not available for this EUT intended for grant.

## 2. SYSTEM TEST CONFIGURATION

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT (Transmitter) was tested with a test program to fix the Tx/RX frequency that was for the purpose of the measurements. For more information please see test data and APPENDIX 1 for set-up photographs.

### 2.3. Test Procedure

#### 2.3.1 Conducted Emissions


The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 7, 13 of ANSI C63.4-2003 and RSS-Gen:2007, Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and Average detector mode.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna. according to the requirements in Section 8 and 13 of ANSI C63.4-2003.

## 2.4. Configuration of Tested System

**Fig. 2-1 Configuration of Tested System (Fixed channel)**



**Table 2-1 Equipment Used in Tested System**

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.
1.	AC Adaptor	Phihong:	PSAA05X-050(X=A,C,E,K or S)	79H00055-29M
2.	Bluetooth Software	Bluesuite 1.22	CSR	Version 1.22

### 3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207(a)/ RSS-Gen §7.2.2	AC Power line Conducted Emission	Compliant
§15.247(b)(1)/ RSS-210 issue 7, §A8.4(2)	Peak Output Power	Compliant
§15.247(d) RSS-210 issue 7, §A8.5	100 KHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(c) RSS-Gen §7.2.3 RSS-210 issue 7, §A2.9	TX/RX Spurious Emission	Compliant
§15.247(a)(1)/ RSS-210 issue 7, §A8.1(b)	Frequency Separation	Compliant
§15.247(a)(1)(iii)/ RSS-210 issue 7, §A8.1(d)	Number of hopping frequency	Compliant
§15.247(a)(1)(ii)/ RSS-210 issue 7, §A8.1(d)	Time of Occupancy	Compliant
§15.247/ RSS-210 issue 7, §A8.2(b)	Peak Power Density	Compliant
§15.247(a)(1)	20dB Bandwidth	No Limit
§15.203, §15.247(c)/ RSS-GEN 7.1.4, RSS-210 issue 7, §A8.4	Antenna Requirement	Compliant
RSS-Gen §4.4.1	99% Power Bandwidth	Compliant

### 4. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low (2402MHz) 、mid (2441MHz) and high (2480MHz) with highest data rate are chosen for full testing.

The field strength of radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for Bluetooth Transmitter for channel Low, Mid and High, the worst case H position was reported.

## 5. AC POWER LINE CONDUCTED EMISSION TEST

### 5.1. Standard Applicable:

According to §15.207 and RSS-Gen §7.2.2, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note		
1.The lower limit shall apply at the transition frequencies		
2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

### 5.2. Measurement Equipment Used:

AC Power Line Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	R&S	ESCS30	828985/004	09/16/2009	09/15/2010
LISN	Rolf-Heine	NNB-2/16Z	99012	02/02/2009	02/01/2010
LISN	FCC	FCC-LISN-50/250-25-2-01	04034	02/02/2009	02/01/2010
Coaxial Cables	N/A	WK CE Cable	N/A	10/30/2008	10/29/2009

### 5.3. EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4-2003.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

#### 5.4. Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

#### 5.5. Measurement Result:


The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Note: Refer to next page for measurement data and plots.



## AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	Bluetooth Mode			Test Date:	Sep. 04, 2009
Temperature:	23	Humidity:	60 %	Test By:	Jazz




Site: SGS CONDUCTED #1  
Limit: CISPR22 Class B Conduction(QP)  
EUT: PDA Phone  
MN: PB9910  
Note: BT LINK MODE

Phase: L1  
Power: AC 120V/60Hz  
Distance:

Temperature: 23 °C  
Humidity: 60 %  
Air Pressure: hpa

No.	Mk.	Freq. MHz	Reading Level dBuV	Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1850	39.00	0.14	39.14	64.26	-25.12	QP	
2		0.1850	28.40	0.14	28.54	54.26	-25.72	AVG	
3		0.3650	41.80	0.09	41.89	58.61	-16.72	QP	
4		0.3650	33.80	0.09	33.89	48.61	-14.72	AVG	
5		0.4600	44.30	0.07	44.37	56.69	-12.32	QP	
6	*	0.4600	35.40	0.07	35.47	46.69	-11.22	AVG	
7		0.6700	42.70	0.08	42.78	56.00	-13.22	QP	
8		0.6700	29.80	0.08	29.88	46.00	-16.12	AVG	
9		1.2100	40.50	0.10	40.60	56.00	-15.40	QP	
10		1.2100	28.10	0.10	28.20	46.00	-17.80	AVG	
11		2.3800	41.50	0.13	41.63	56.00	-14.37	QP	
12		2.3800	28.40	0.13	28.53	46.00	-17.47	AVG	





Site SGS CONDUCTED #1

Phase: **N**

Temperature: 23 °C

Limit: CISPR22 Class B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 60 %

EUT: PDA Phone

Distance:

Air Pressure: hpa

M/N: PB9910

Note: BT LINK MODE

No.	Mk.	Freq. MHz	Reading Level dBuV	Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.3300	42.50	0.12	42.62	59.45	-16.83	QP	
2		0.3300	34.30	0.12	34.42	49.45	-15.03	AVG	
3		0.3700	43.80	0.11	43.91	58.50	-14.59	QP	
4	*	0.3700	37.90	0.11	38.01	48.50	-10.49	AVG	
5		0.4600	43.40	0.10	43.50	56.69	-13.19	QP	
6		0.4600	35.50	0.10	35.60	46.69	-11.09	AVG	
7		1.0800	39.30	0.12	39.42	56.00	-16.58	QP	
8		1.0800	30.10	0.12	30.22	46.00	-15.78	AVG	
9		1.8800	39.40	0.15	39.55	56.00	-16.45	QP	
10		1.8800	28.00	0.15	28.15	46.00	-17.85	AVG	
11		3.0900	35.40	0.16	35.56	56.00	-20.44	QP	
12		3.0900	27.10	0.16	27.26	46.00	-18.74	AVG	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。 This document is issued by the Company subject to its General Conditions of Service ([www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm)) and Terms and Conditions for Electronic Documents ([www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm)). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at [www.sgs.com/site/authentication](http://www.sgs.com/site/authentication). Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

## 6. PEAK OUTPUT POWER MEASUREMENT

### 6.1. Standard Applicable:


According to §15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1Watt. For all other frequency hopping systems in the 2400 – 2483.5MHz band: 0.125 Watts.

According to RSS-210 issue 7, §A8.4(2), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, the maximum conducted output power shall not exceed 1 W. For all other frequency hopping systems, the maximum peak conducted output power shall not exceed 0.125 W.

### 6.2. Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	04/19/2008	04/18/2010
Spectrum Analyzer	Agilent	E4440A	MY45304525	01/23/2008	01/22/2010
DC Block	Agilent	BLK-18	155452	07/05/2009	07/04/2010
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	01/05/2009	01/04/2010
Attenuator	Mini-Circuit	BW-S6W5	001	07/05/2009	07/04/2010
Attenuator	Mini-Circuit	BW-S10W5	001	07/05/2009	07/04/2010
Attenuator	Mini-Circuit	BW-S20W5	001	07/05/2009	07/04/2010
Splitter	Agilent	11636B	N/A	07/05/2009	07/04/2010

### 6.3. .Test Set-up:



### 6.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum. (Channel power function, RBW, VBW = 1MHz)
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

**6.5. Measurement Result:****BDR mode:**

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	0.00	0.00	0.00	0.00100	1
2441.00	0.90	0.00	0.90	0.00123	1
2480.00	1.46	0.00	1.46	0.00140	1


*\*Note: offset 1dB***EDR mode:**

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	0.36	0.00	0.36	0.00109	1
2441.00	1.28	0.00	1.28	0.00134	1
2480.00	1.85	0.00	1.85	0.00153	1


*\*Note: offset 1dB*

Note: Refer to next page for plots.


## Peak Power Output Data Plot (CH Low) (BDR mode)




## Peak Power Output Data Plot (CH Mid) (BDR mode)




## Peak Power Output Data Plot (CH High) (BDR mode)




## Peak Power Output Data Plot (CH Low) (EDR mode)



## Peak Power Output Data Plot (CH Mid) (EDR mode)



## Peak Power Output Data Plot (CH High) (EDR mode)





## 7. 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

### 7.1. Standard Applicable:

According to §15.247(d), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

According to RSS-210 issue 7, §A8.5, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

**7.2. Measurement Equipment Used:****7.2.1. Conducted Emission at antenna port:**

Refer to section 6.2 for details.

**7.2.2. Radiated emission:**

966 Chamber					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	R&S	FSP 40	100034	02/12/2009	02/11/2010
Loop antenna	MESSTEC	FLA30	03/10086	07/08/2009	07/07/2011
Bilog Antenna	SCHWAZBECK	VULB9160	9160-3136	11/15/2008	11/14/2009
Horn antenna	SCHWAZBECK	BBHA 9120D	9120D-673	05/09/2008	05/08/2010
Pre-Amplifier	Agilent	8447D	1937A02834	11/30/2008	11/29/2009
Pre-Amplifier	Agilent	8449B	3008A01973	01/05/2009	01/04/2010
Turn Table	HD	DT420	N/A	N.C.R	N.C.R
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R
Controller	HD	HD100	N/A	N.C.R	N.C.R
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	01/05/2009	01/04/2010
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	01/05/2009	01/04/2010
3m Site	SGS	966 chamber	N/A	11/08/2008	11/09/2009


## 7.3. Test SET-UP:

### 7.3.1. Conducted Emission at antenna port:


Refer to section 6.3 for details.

### 7.3.2. Radiated emission:

#### (A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



#### (B) Radiated Emission Test Set-UP Frequency Over 1 GHz



#### 7.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=100KHz, Span=25MHz, Sweep = auto
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

#### 7.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:



$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	


#### 7.6. Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

## BDR Mode Band Edges Test Data CH-Low



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。 This document is issued by the Company subject to its General Conditions of Service ([www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm)) and Terms and Conditions for Electronic Documents ([www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm)). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at [www.sgs.com/authentication](http://www.sgs.com/authentication). Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

**Band Edges Test Data CH-High**

### Radiated Emission: (BDR mode)

Operation Mode TX CH Low  
Fundamental Frequency 2402 MHz  
Temperature 25 °C  
Humidity 65 %

Test Date Sep. 04, 2009  
Test By Jazz  
Pol Ver.

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2344.00	58.62	---	-15.94	42.68	---	74.00	54.00	-11.32	Peak
2378.37	58.46	---	-15.82	42.64	---	74.00	54.00	-11.36	Peak
2390.00	52.81	---	-10.66	42.15	---	74.00	54.00	-11.85	Peak

Operation Mode TX CH Low  
Fundamental Frequency 2402 MHz  
Temperature 25  
Humidity 65 %

Test Date Sep. 04, 2009  
Test By Jazz  
Pol Hor.

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2344.00	58.14	---	-15.94	42.20	---	74.00	54.00	-11.80	Peak
2378.37	58.73	---	-15.82	42.91	---	74.00	54.00	-11.09	Peak
2390.00	53.62	---	-10.66	42.96	---	74.00	54.00	-11.04	Peak

### Remark :

- (1) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- (3) Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (4) Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

## Radiated Emission:

Operation Mode	TX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25	Pol	Ver.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2483.56	57.01	---	-10.36	46.65	---	74.00	54.00	-7.35	Peak

Operation Mode	TX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25	Pol	Hor.
Humidity	65 %		



Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2483.56	61.60	---	-10.36	51.24	---	74.00	54.00	-2.76	Peak

## Remark :


- (1) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- (3) Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (4) Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



## EDR Mode Band Edges Test Data CH-Low



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。 This document is issued by the Company subject to its General Conditions of Service ([www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm)) and Terms and Conditions for Electronic Documents ([www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm)). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at [www.sgs.com/authentication](http://www.sgs.com/authentication). Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

**Band Edges Test Data CH-High**

### Radiated Emission:

Operation Mode TX CH Low  
Fundamental Frequency 2402 MHz  
Temperature 25 °C  
Humidity 65 %

Test Date Sep. 04, 2009  
Test By Jazz  
Pol Ver.

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2344.00	57.98	---	-15.94	42.04	---	74.00	54.00	-11.96	Peak
2380.00	58.36	---	-15.82	42.54	---	74.00	54.00	-11.46	Peak
2390.00	52.68	---	-10.66	42.02	---	74.00	54.00	-11.98	Peak

Operation Mode TX CH Low  
Fundamental Frequency 2402 MHz  
Temperature 25  
Humidity 65 %

Test Date Sep. 04, 2009  
Test By Jazz  
Pol Hor.

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2344.00	57.82	---	-15.94	41.88	---	74.00	54.00	-12.12	Peak
2380.00	58.27	---	-15.82	42.45	---	74.00	54.00	-11.55	Peak
2390.00	53.35	---	-10.66	42.69	---	74.00	54.00	-11.31	Peak

### Remark :

- (1) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- (3) Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (4) Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

## Radiated Emission:

Operation Mode	TX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25	Pol	Ver.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2483.56	55.68	---	-10.36	45.32	---	74.00	54.00	-8.68	Peak

Operation Mode	TX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25	Pol	Hor.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL C F(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2483.56	60.66	---	-10.36	50.30	---	74.00	54.00	-3.70	Peak

## Remark :

- (1) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- (3) Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (4) Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

## 8. SPURIOUS EMISSION TEST

### 8.1. Standard Applicable:

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

According to RSS-Gen §7.2.3 and RSS-210 issue 7, §A2.9, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

### 8.2. Measurement Equipment Used:

#### 8.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.

#### 8.2.2. Radiated emission:

Refer to section 7.2 for details.

### 8.3. Test SET-UP:

#### 8.3.1. Conducted Emission at antenna port:

Refer to section 6.3 for details.

#### 8.3.2. Radiated emission:

Refer to section 7.3 for details.

#### 8.4. Measurement Procedure:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measured were complete.

#### 8.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:


$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	


#### 8.6. Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.


## BDR Mode Conducted Spurious Emission Measurement Result Ch Low 30MHz – 3GHz




## Ch Low 3GHz – 26.5GHz



## Ch Mid 30MHz – 3GHz




## Ch Mid 3GHz – 26.5GHz







## Ch High 30MHz – 3GHz




## Ch High 3GHz – 26.5GHz




## Conducted Spurious Emission Measurement Result (EDR mode) Ch Low 30MHz – 3GHz




## Ch Low 3GHz – 26.5GHz




## Ch Mid 30MHz – 3GHz




## Ch Mid 3GHz – 26.5GHz



## Ch High 30MHz – 3GHz



## Ch High 3GHz – 26.5GHz



**Radiated Spurious Emission Measurement Result (below 1GHz) (EDR mode)**

Operation Mode	TX CH Low	Test Date	Sep. 04, 2009
Fundamental Frequency	2402MHz	Test By	Jazz
Temperature	25	Pol	Ver./Hor.
Humidity	65 %		

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
104.69	V	Peak	58.57	-29.76	28.81	43.50	-14.69
227.88	V	Peak	48.52	-30.26	18.26	46.00	-27.74
252.13	V	Peak	48.20	-29.79	18.41	46.00	-27.59
347.19	V	Peak	45.83	-27.30	18.53	46.00	-27.47
560.59	V	Peak	45.65	-23.54	22.11	46.00	-23.89
775.93	V	Peak	43.86	-20.20	23.66	46.00	-22.34
104.69	H	Peak	49.96	-29.76	20.20	43.50	-23.30
276.38	H	Peak	46.26	-29.14	17.12	46.00	-28.88
300.63	H	Peak	46.99	-28.46	18.53	46.00	-27.47
324.88	H	Peak	47.33	-27.77	19.56	46.00	-26.44
371.44	H	Peak	45.74	-26.67	19.07	46.00	-26.93
717.73	H	Peak	43.70	-20.92	22.78	46.00	-23.22

**Remark :**

- 1 Measuring frequencies from 30 MHz to the 1GHz.
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

**Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode	TX CH Mid	Test Date	Sep. 04, 2009
Fundamental Frequency	2441MHz	Test By	Jazz
Temperature	25	Pol	Ver./Hor.
Humidity	65 %		

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
104.69	V	Peak	58.79	-29.76	29.03	43.50	-14.47
252.13	V	Peak	49.21	-29.79	19.42	46.00	-26.58
324.88	V	Peak	46.51	-27.77	18.74	46.00	-27.26
439.34	V	Peak	44.27	-25.15	19.12	46.00	-26.88
647.89	V	Peak	43.75	-21.84	21.91	46.00	-24.09
837.04	V	Peak	44.04	-19.57	24.47	46.00	-21.53
104.69	H	Peak	49.59	-29.76	19.83	43.50	-23.67
158.04	H	Peak	44.55	-27.01	17.54	43.50	-25.96
276.38	H	Peak	46.96	-29.14	17.82	46.00	-28.18
324.88	H	Peak	46.26	-27.77	18.49	46.00	-27.51
465.53	H	Peak	43.01	-24.95	18.06	46.00	-27.94
662.44	H	Peak	43.56	-21.67	21.89	46.00	-24.11

**Remark :**

- 1 Measuring frequencies from 30 MHz to the 1GHz.
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

**Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode	TX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480MHz	Test By	Jazz
Temperature	25	Pol	Ver./Hor.
Humidity	65 %		

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
104.69	V	Peak	57.88	-29.76	28.12	43.50	-15.38
252.13	V	Peak	49.50	-29.79	19.71	46.00	-26.29
324.88	V	Peak	45.88	-27.77	18.11	46.00	-27.89
395.69	V	Peak	44.20	-26.08	18.12	46.00	-27.88
643.04	V	Peak	43.61	-21.96	21.65	46.00	-24.35
764.29	V	Peak	44.61	-20.32	24.29	46.00	-21.71
104.69	H	Peak	49.52	-29.76	19.76	43.50	-23.74
276.38	H	Peak	49.53	-29.14	20.39	46.00	-25.61
300.63	H	Peak	50.39	-28.46	21.93	46.00	-24.07
347.19	H	Peak	45.10	-27.30	17.80	46.00	-28.20
575.14	H	Peak	43.03	-23.23	19.80	46.00	-26.20
837.04	H	Peak	43.51	-19.57	23.94	46.00	-22.06

**Remark :**

- 1 Measuring frequencies from 30 MHz to the 1GHz.
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	TX CH Low	Test Date	Sep. 04, 2009
Fundamental Frequency	2402 MHz	Test By	Jazz
Temperature	25	Pol	Ver.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
4804.0	46.85	---	-5.92	40.93	---	74.00	54.00	-13.07	Peak
7206.0	----					74.00	54.00		
9608.0	----					74.00	54.00		
12010.0	----					74.00	54.00		
14412.0	----					74.00	54.00		
16814.0	----					74.00	54.00		
19216.0	----					74.00	54.00		
21618.0	----					74.00	54.00		
24020.0	----					74.00	54.00		

**Remark:**

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- 5 Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	TX CH Low	Test Date	Sep. 04, 2009
Fundamental Frequency	2402 MHz	Test By	Jazz
Temperature	25	Pol	Hor.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
4804.0	44.36	---	-5.92	38.44	---	74.00	54.00	-15.56	Peak
7206.0	----					74.00	54.00		
9608.0	----					74.00	54.00		
12010.0	----					74.00	54.00		
14412.0	----					74.00	54.00		
16814.0	----					74.00	54.00		
19216.0	----					74.00	54.00		
21618.0	----					74.00	54.00		
24020.0	----					74.00	54.00		

**Remark:**

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- 5 Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	TX CH Mid	Test Date	Sep. 04, 2009
Fundamental Frequency	2441 MHz	Test By	Jazz
Temperature	25	Pol	Ver.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
4882.0	47.86	---	-5.79	42.07	---	74.00	54.00	-11.93	Peak
7323.0	----					74.00	54.00		
9764.0	----					74.00	54.00		
12205.0	----					74.00	54.00		
14646.0	----					74.00	54.00		
17087.0	----					74.00	54.00		
19528.0	----					74.00	54.00		
21969.0	----					74.00	54.00		
24410.0	----					74.00	54.00		

**Remark:**

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- 5 Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	TX CH Mid	Test Date	Sep. 04, 2009
Fundamental Frequency	2441 MHz	Test By	Jazz
Temperature	25	Pol	Hor.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
4882.0	47.10	---	-5.79	41.31	---	74.00	54.00	-12.69	Peak
7323.0	----					74.00	54.00		
9764.0	----					74.00	54.00		
12205.0	----					74.00	54.00		
14646.0	----					74.00	54.00		
17087.0	----					74.00	54.00		
19528.0	----					74.00	54.00		
21969.0	----					74.00	54.00		
24410.0	----					74.00	54.00		

**Remark:**

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- 5 Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	TX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25	Pol	Ver.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
4960.0	49.07	---	-5.68	43.39	---	74.00	54.00	-10.61	Peak
7440.0	----					74.00	54.00		
9920.0	----					74.00	54.00		
12400.0	----					74.00	54.00		
14880.0	----					74.00	54.00		
17360.0	----					74.00	54.00		
19840.0	----					74.00	54.00		
22320.0	----					74.00	54.00		
24800.0	----					74.00	54.00		

**Remark:**

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- 5 Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

### Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	TX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25	Pol	Hor.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	Remark
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
4960.0	49.84	---	-5.67	44.17	---	74.00	54.00	-9.83	Peak
7440.0	----					74.00	54.00		
9920.0	----					74.00	54.00		
12400.0	----					74.00	54.00		
14880.0	----					74.00	54.00		
17360.0	----					74.00	54.00		
19840.0	----					74.00	54.00		
22320.0	----					74.00	54.00		
24800.0	----					74.00	54.00		

#### Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- 5 Spectrum AV Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode RX CH Low  
 Fundamental Frequency 2402MHz  
 Temperature 25 °C  
 Humidity 65 %

Test Date Sep. 04, 2009  
 Test By Jazz  
 Pol Ver./Hor

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
104.69	V	Peak	58.23	-29.76	28.47	43.50	-15.03
158.04	V	Peak	44.26	-27.01	17.25	43.50	-26.25
300.63	V	Peak	45.92	-28.46	17.46	46.00	-28.54
324.88	V	Peak	45.16	-27.77	17.39	46.00	-28.61
665.35	V	Peak	43.17	-21.62	21.55	46.00	-24.45
771.08	V	Peak	44.22	-20.24	23.98	46.00	-22.02
104.69	H	Peak	49.06	-29.76	19.30	43.50	-24.20
159.98	H	Peak	45.82	-27.01	18.81	43.50	-24.69
252.13	H	Peak	49.87	-29.79	20.08	46.00	-25.92
300.63	H	Peak	47.68	-28.46	19.22	46.00	-26.78
371.44	H	Peak	44.72	-26.67	18.05	46.00	-27.95
468.44	H	Peak	43.43	-24.93	18.50	46.00	-27.50

**Remark :**

- 1 Measuring frequencies from 30 MHz to the 1GHz.
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

**Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode	RX CH Mid	Test Date	Sep. 04, 2009
Fundamental Frequency	2441MHz	Test By	Jazz
Temperature	25°C	Pol	Ver./Hor
Humidity	65 %		

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
104.69	V	Peak	58.58	-29.76	28.82	43.50	-14.68
164.83	V	Peak	44.56	-27.39	17.17	43.50	-26.33
252.13	V	Peak	49.52	-29.79	19.73	46.00	-26.27
300.63	V	Peak	47.60	-28.46	19.14	46.00	-26.86
601.33	V	Peak	44.14	-22.66	21.48	46.00	-24.52
708.03	V	Peak	44.40	-21.05	23.35	46.00	-22.65
104.69	H	Peak	48.79	-29.76	19.03	43.50	-24.47
252.13	H	Peak	50.30	-29.70	20.60	46.00	-25.40
300.63	H	Peak	48.67	-28.46	20.21	46.00	-25.79
347.19	H	Peak	45.87	-27.30	18.57	46.00	-27.43
441.28	H	Peak	44.15	-25.10	19.05	46.00	-26.95
688.63	H	Peak	43.77	-21.28	22.49	46.00	-23.51

**Remark :**

- 1 Measuring frequencies from 30 MHz to the 1GHz.
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

**Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode	RX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480MHz	Test By	Jazz
Temperature	25 °C	Pol	Ver./Hor
Humidity	65%		

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
104.69	V	Peak	59.14	-29.76	29.38	43.50	-14.12
252.13	V	Peak	48.85	-29.79	19.06	46.00	-26.94
276.38	V	Peak	48.02	-29.14	18.88	46.00	-27.12
347.19	V	Peak	46.32	-27.30	19.02	46.00	-26.98
450.98	V	Peak	43.59	-24.88	18.71	46.00	-27.29
715.79	V	Peak	43.28	-20.95	22.33	46.00	-23.67
104.69	H	Peak	49.42	-29.76	19.66	43.50	-23.84
252.13	H	Peak	47.25	-29.79	17.46	46.00	-28.54
300.63	H	Peak	50.94	-28.46	22.48	46.00	-23.52
347.19	H	Peak	45.58	-27.30	18.28	46.00	-27.72
458.74	H	Peak	43.10	-24.81	18.29	46.00	-27.71
741.98	H	Peak	43.04	-20.61	22.43	46.00	-23.57

**Remark :**

- 1 Measuring frequencies from 30 MHz to the 1GHz.
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.



**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	RX CH Low	Test Date	Sep. 04, 2009
Fundamental Frequency	2402 MHz	Test By	Jazz
Temperature	25°C	Pol	Ver.
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2391.0	45.15	---	-10.66	34.49	---	74.00	54.00	-19.51	Peak
4804.0	43.47	---	-5.90	37.57	---	74.00	54.00	-16.43	Peak
7206.0	----					74.00	54.00		
9608.0	----					74.00	54.00		
12010.0	----					74.00	54.00		
14412.0	----					74.00	54.00		

**Remark:**

- (1) Measuring frequencies scanned from 1GHz to the 10th harmonic of highest fundamental frequency.
- (2) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column
- (4) Spectrum Peak Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (5) Spectrum AV Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	RX CH Low	Test Date	Sep. 04, 2009
Fundamental Frequency	2402 MHz	Test By	Jazz
Temperature	25 °C	Pol	Hor
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2391.0	48.04	---	-10.66	37.38	---	74.00	54.00	-16.62	Peak
4804.0	42.25	---	-5.90	36.35	---	74.00	54.00	-17.65	Peak
7206.0	----					74.00	54.00		
9608.0	----					74.00	54.00		
12010.0	----					74.00	54.00		
14412.0	----					74.00	54.00		

**Remark:**

- (1) Measuring frequencies scanned from 1GHz to the 10th harmonic of highest fundamental frequency.
- (2) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column
- (4) Spectrum Peak Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (5) Spectrum AV Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	RX CH Mid	Test Date	Sep. 04, 2009
Fundamental Frequency	2441 MHz	Test By	Jazz
Temperature	25 °C	Pol	Ver
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2443.0	44.99	---	-10.45	34.54	---	74.00	54.00	-19.46	Peak
4882.0	41.59	---	-5.79	35.80	---	74.00	54.00	-18.20	Peak
7323.0	----					74.00	54.00		
9764.0	----					74.00	54.00		
12205.0	----					74.00	54.00		
14646.0	----					74.00	54.00		

**Remark:**

- (1) Measuring frequencies scanned from 1GHz to the 10th harmonic of highest fundamental frequency.
- (2) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column
- (4) Spectrum Peak Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (5) Spectrum AV Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	RX CH Mid	Test Date	Sep. 04, 2009
Fundamental Frequency	2441 MHz	Test By	Jazz
Temperature	25 °C	Pol	Hor
Humidity	65%		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2443.0	46.96	---	-10.45	36.51	---	74.00	54.00	-17.49	Peak
4882.0	41.55	---	-5.79	35.76	---	74.00	54.00	-18.24	Peak
7323.0	----					74.00	54.00		
9764.0	----					74.00	54.00		
12205.0	----					74.00	54.00		
14646.0	----					74.00	54.00		

**Remark:**

- (1) Measuring frequencies scanned from 1GHz to the 10th harmonic of highest fundamental frequency.
- (2) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column
- (4) Spectrum Peak Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (5) Spectrum AV Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	RX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25 °C	Pol	Ver
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2475.5	47.35	---	-10.36	36.99	---	74.00	54.00	-17.01	Peak
4960.0	42.17	---	-5.68	36.49	---	74.00	54.00	-17.51	Peak
7440.0	----					74.00	54.00		
9920.0	----					74.00	54.00		
12400.0	----					74.00	54.00		
14880.0	----					74.00	54.00		

**Remark:**

- (1) Measuring frequencies scanned from 1GHz to the 10th harmonic of highest fundamental frequency.
- (2) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column
- (4) Spectrum Peak Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (5) Spectrum AV Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode	RX CH High	Test Date	Sep. 04, 2009
Fundamental Frequency	2480 MHz	Test By	Jazz
Temperature	25 °C	Pol	Hor
Humidity	65 %		

Freq. (MHz)	Peak Reading	AV Reading	Ant./CL CF(dB)	Actual FS		Peak Limit	AV Limit	Margin (dB)	
	(dBuV)	(dBuV)		Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)		
2475.5	48.81	---	-10.36	38.45	---	74.00	54.00	-15.55	Peak
4960.0	----					74.00	54.00		
7440.0	----					74.00	54.00		
9920.0	----					74.00	54.00		
12400.0	----					74.00	54.00		
14880.0	----					74.00	54.00		

**Remark:**

- (1) Measuring frequencies scanned from 1GHz to the 10th harmonic of highest fundamental frequency.
- (2) Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column
- (4) Spectrum Peak Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (5) Spectrum AV Setting : 1GHz- 40GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

## 9. FREQUENCY SEPARATION

### 9.1. Standard Applicable:

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 20dB bandwidth of the hopping channel, whichever is greater.

According to RSS 210 issue 6, A8.1(b), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 9.2. Measurement Equipment Used:

Refer to section 6.2 for details.

### 9.3. Test Set-up:

Refer to section 6.3 for details.

### 9.4. Measurement Procedure:


1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel .
4. Set the spectrum analyzer as RBW,VBW=3KHz, Adjust Span to 3.0 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

### 9.5. Measurement Result:

Channel separation (MHz)	Limit	Result
1	$\geq 25\text{KHz}$ or 2/3 times 20dB bandwidth	PASS

Note: Refer to next page for plots.

## Frequency Separation Test Data





## 10. NUMBER OF HOPPING FREQUENCY

### 10.1. Standard Applicable:

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

According to RSS-210 issue 7, §A8.1(d), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, the maximum conducted output power shall not exceed 1 W. For all other frequency hopping systems, the maximum peak conducted output power shall not exceed 0.125 W.

### 10.2. Measurement Equipment Used:

Refer to section 6.2 for details.

### 10.3. Test Set-up:

Refer to section 6.3 for details.


### 10.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW, VBW=100KHz,
5. Max hold, view and count how many channel in the band.


### 10.5. Measurement Result:

Note: Refer to next page for plots.

## Channel Number 2.4 GHz – 2.441GHz



## 2.441 GHz – 2.4835GHz



## 11. TIME OF OCCUPANCY (DWELL TIME)

### 11.1. Standard Applicable:

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

According to RSS-210 issue 7, §A8.1(d), Frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that a minimum of 15 hopping channels are used.

### 11.2. Measurement Equipment Used:

Refer to section 6.2 for details.

### 11.3. Test Set-up:

Refer to section 6.3 for details.

### 11.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW,VBW=100KHz, Span = 0Hz , Adjust Sweep = 30s.
5. Repeat above procedures until all frequency measured were complete.

### 11.5. Measurement Result:

A period time = 0.4 (ms) \* 79 = 31.6 (s)

CH Low: DH1 time slot = 0.417 (ms) \* (1600/(2\*79)) \* 31.6 = 133.44 (ms)

DH3 time slot = 1.667 (ms) \* (1600/(4\*79)) \* 31.6 = 266.72 (ms)

DH5 time slot = 2.925 (ms) \* (1600/(6\*79)) \* 31.6 = 312.00 (ms)

CH Mid: DH1 time slot = 0.417 (ms) \* (1600/(2\*79)) \* 31.6 = 133.44 (ms)

DH3 time slot = 1.667 (ms) \* (1600/(4\*79)) \* 31.6 = 266.72 (ms)

DH5 time slot = 2.925 (ms) \* (1600/(6\*79)) \* 31.6 = 312.00 (ms)


CH High: DH1 time slot = 0.417 (ms) \* (1600/(2\*79)) \* 31.6 = 133.44 (ms)

DH3 time slot = 1.667 (ms) \* (1600/(4\*79)) \* 31.6 = 266.72 (ms)


DH5 time slot = 2.925 (ms) \* (1600/(6\*79)) \* 31.6 = 312.00 (ms)

Note: Refer to next page for plots.


## CH-Low DH1



## DH3




## DH5




## CH-Mid


## DH1




## DH3




## DH5



## CH-High DH1




## DH3





## DH5



## 12. Peak Power Spectral Density

### 12.1. Standard Applicable:

According to §15.247(d), for direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3kHz band during any time interval of continuous transmission.

According to RSS-210 issue 7, §A8.2(b) and §A8.3(2), The transmitter power spectral density (into the antenna) shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0-second duration.

### 12.2. Measurement Equipment Used:

Refer to section 6.2 for details.

### 12.3. Test Set-up:

Refer to section 6.3 for details.

### 12.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3KHz, VBW = 10KHz, Span = 1.5MHz, Sweep=100s
4. Record the max. reading.
5. Repeat above procedures until all frequency measured were complete.

**12.5. Measurement Result:**


BDR Mode

CH	RF Power Density Reading (dBm)	Cable loss (dB)	RF Power Density Level (dBm)	Maximum Limit (dBm)
Low	-9.49	0.00	-9.49	8
Mid	-8.53	0.00	-8.53	8
High	-9.39	0.00	-9.39	8


Note: offset 6dB for path lose.

Note: Refer to next page for plots.

## Power Spectral Density Test Plot (CH-Low) (BDR)




## Power Spectral Density Test Plot (CH-Mid) (BDR)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。 This document is issued by the Company subject to its General Conditions of Service ([www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm)) and Terms and Conditions for Electronic Documents ([www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm)). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at [www.sgs.com/authentication](http://www.sgs.com/authentication). Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

## Power Spectral Density Test Plot (CH-High) (BDR)



### 13. 20dB Bandwidth

#### 13.1. Standard Applicable:

According to §15.247(a)(1), for frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

#### 13.2. Measurement Equipment Used:

Refer to section 6.2 for details.

#### 13.3. Test Set-up:

Refer to section 6.3 for details.

#### 13.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=10KHz (1 % of Bandwidth.), Span= 3MHz, Sweep=auto
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat above procedures until all frequency measured were complete.

**13.5. Measurement Result:**


BDR mode:

CH	Bandwidth (kHz)
Lower	792.163
Mid	792.919
Higher	793.511


EDR mode:

CH	Bandwidth (MHz)	2/3 Bandwidth (MHz)
Lower	1.219	0.813
Mid	1.228	0.819
Higher	1.225	0.817

## BDR Mode 20dB Bandwidth Test Data CH-Low




## 20dB Bandwidth Test Data CH-Mid







## 20dB Bandwidth Test Data CH-High




## EDR Mode 20dB Bandwidth Test Data CH-Low



## 20dB Bandwidth Test Data CH-Mid



## 20dB Bandwidth Test Data CH-High



## 14. ANTENNA REQUIREMENT

### 14.1. Standard Applicable:

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device.

And according to §15.246(1), if transmitting antennas of directional gain greater than 6dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to RSS-GEN 7.1.4, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest-gain antenna of each combination of transmitter and antenna type for which certification is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type and having equal or lesser gain as an antenna that had been successfully tested for certification with the transmitter, will also be considered certified with the transmitter, and may be used and marketed with the transmitter. The manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter.

When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. Any antenna gain in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power before using the power limits specified in RSS-210 or RSS-310 for devices of RF output powers of 10 milliwatts or less. For devices of output powers greater than 10 milliwatts, except devices subject to RSS-210 Annex 8 (Frequency Hopping and Digital Modulation Systems Operating in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz Bands) or RSS-210 Annex 9 (Local Area Network Devices), the total antenna gain shall be added to the measured RF output power before using the specified power limits. For devices subject to RSS-210 Annex 8 or Annex 9, the antenna gain shall not be added.

### 14.2. Antenna Connected Construction:

The directional gains of antenna used for transmitting is 1.1dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.

## 15. 99% Bandwidth Measurement

### 15.1. Standard Applicable:

RSS-Gen §4.4.1, the transmitter shall be operated at its maximum carrier power measured under normal test conditions. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual.

The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

The span between the two recorded frequencies is the occupied bandwidth.

### 15.2. Measurement Equipment Used:

Refer to section 6.2 for details.

### 15.3. Test Set-up:

Refer to section 6.3 for details.

### 15.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=1% of the approximate emission bandwidth, VBW = 3 times RBW, Span= approximately 20dB below the peak level. Sweep=auto
4. Turn on the 99% bandwidth function, max reading..
5. Repeat above procedures until all frequency measured were complete.

**15.5. Measurement Result:****BDR Mode**


CH	Bandwidth (kHz)
Lower	846.5897
Mid	844.1389
Higher	842.7513

**EDR Mode**


CH	Bandwidth (MHz)
Lower	1.1847
Mid	1.1808
Higher	1.1728

Note: Refer to next page for plots.


## BDR Mode 99% Band Width Test Data CH-Low



## 99% Band Width Test Data CH-Mid




## 99% Band Width Test Data CH-High






## EDR Mode

### 99% Band Width Test Data CH-Low



### 99% Band Width Test Data CH-Mid



## 99% Band Width Test Data CH-High

