



FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : Windows Phone
MODEL NAME : PC40210
FCC ID : NM8PC40210
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Spread Spectrum (DSS)

The product was received on Sep. 07, 2010 and completely tested on Mar. 08, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Anderson Chiu / Deputy Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : NM8PC40210

Page Number : 1 of 61

Report Issued Date : Mar. 18, 2011

Report Version : Rev. 01



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION..... 5

 1.1 Applicant..... 5

 1.2 Manufacturer..... 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Testing Site..... 6

 1.5 Applied Standards 6

 1.6 Ancillary Equipment List 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7

 2.1 RF Output Power..... 7

 2.2 Test Mode..... 8

 2.3 Connection Diagram of Test System..... 9

 2.4 RF Utility 10

3 TEST RESULT 11

 3.1 Number of Channel Measurement 11

 3.2 20dB Bandwidth Measurement 14

 3.3 Hopping Channel Separation Measurement 21

 3.4 Dwell Time Measurement..... 24

 3.5 Peak Output Power Measurement 26

 3.6 Band Edges Measurement..... 29

 3.7 Spurious Emission Measurement..... 41

 3.8 AC Conducted Emission Measurement..... 45

 3.9 Radiated Emission Measurement..... 49

 3.10 Antenna Requirements..... 58

4 LIST OF MEASURING EQUIPMENT..... 59

5 UNCERTAINTY OF EVALUATION..... 60

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.3	15.247(a)(1)	A8.1(b)	Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.4	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	≤ 1W	Pass	-
3.6	15.247(d)	A8.5	Frequency Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	A8.5	Spurious Emission	< 20 dBc	Pass	-
3.8	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 13.5 dB at 0.198 MHz
3.9	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.91 dB at 31.08 MHz
3.10	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

HTC Corporation

1F., No. 6-3, Baoqiang Rd., Xindian City, Taipei, Taiwan

1.2 Manufacturer

HTC Corporation

1F., No. 6-3, Baoqiang Rd., Xindian City, Taipei, Taiwan

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Windows Phone
Model Name	PC40210
FCC ID	NM8PC40210
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 2.54 dBm (0.002 W) Bluetooth EDR (2Mbps) : 5.27 dBm (0.003 W) Bluetooth EDR (3Mbps) : 3.14 dBm (0.002 W)
Antenna Type	PIFA Antenna with gain 0 dBi
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Production Unit

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DSS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07-HY	TW1022/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 7

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
5.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
7.	Earphone	Cotron	HS G400	N/A	N/A	N/A
8.	LCD Monitor	Lenovo	6135-AB1	FCC DoC	Shielded, 1.6 m	Unshielded, 1.8 m
9.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	π /4-DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	1.33 dBm	4.18 dBm	2.03 dBm
Ch39	2441MHz	2.27 dBm	5.09 dBm	3.06 dBm
Ch78	2480MHz	2.54 dBm	5.27 dBm	3.14 dBm

Remark:

1. The data rate was set in 2Mbps for all the test items due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Pre-scanned tests were conducted to determine the final configuration from all possible combinations.


The following tables are showing the test modes as the worst cases and recorded in this report.

Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth 1Mbps (GFSK) /
	Bluetooth EDR 2Mbps ($\pi/4$-DQPSK) /
	Bluetooth EDR 3Mbps (8-DPSK)
Conducted TCs	Mode 1: Bluetooth 1Mbps_CH00_2402 MHz
	Mode 2: Bluetooth 1Mbps_CH39_2441 MHz
	Mode 3: Bluetooth 1Mbps_CH78_2480 MHz
	Mode 4: Bluetooth EDR 2Mbps_CH00_2402 MHz
	Mode 5: Bluetooth EDR 2Mbps_CH39_2441 MHz
	Mode 6: Bluetooth EDR 2Mbps_CH78_2480 MHz
	Mode 7: Bluetooth EDR 3Mbps_CH00_2402 MHz
	Mode 8: Bluetooth EDR 3Mbps_CH39_2441 MHz
	Mode 9: Bluetooth EDR 3Mbps_CH78_2480 MHz
Radiated TCs	Mode 1: Bluetooth EDR 2Mbps_CH00_2402 MHz
	Mode 2: Bluetooth EDR 2Mbps_CH39_2441 MHz
	Mode 3: Bluetooth EDR 2Mbps_CH78_2480 MHz
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + GPS Rx + Earphone + USB Cable (Charging from Adapter)
	Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + MPEG4 + Earphone + USB Cable (Charging from Adapter)
	Mode 3: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + Camera + Earphone + USB Cable (Charging from Adapter)
	Mode 4: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + GPS Rx + Earphone + USB Cable (Link with Notebook)


Remark:

1. TC stands for Test Configuration, and consists of adapter, battery, USB cable, and earphone.
2. For radiated TCs, the data rate was set in 2Mbps due to the highest RF output power; only the data of these modes was reported.
3. For conducted emission, the worst case is mode 4; only the test data of this mode was reported.


2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>

<EUT with Adapter Mode>



<EUT with USB Cable (Link with Notebook) Mode>



2.4 RF Utility

For Bluetooth function, the RF utility, "Remote 432X controller" was installed in notebook which was programmed in order to make the EUT into the engineering modes to contact with Bluetooth base station for transmitting and receiving signals continuously.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; $RBW \geq 1\%$ of the span; $VBW \geq RBW$; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.

3.1.4 Test Setup






3.1.5 Test Result of Number of Hopping Frequency


Test Mode :	Mode 4~6	Temperature :	25~27°C
Test Engineer :	Andy Yeh	Relative Humidity :	50~53%
Number of Hopping Channels (Channel)	Limits (Channel)	Pass/Fail	
79	> 15	Pass	



Number of Hopping Channel Plot on Channel 00 - 78



Date: 24.SEP.2010 15:14:09



Date: 24.SEP.2010 15:08:40

3.2 20dB Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup






3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	25~27°C
Test Engineer :	Andy Yeh	Relative Humidity :	50~53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.908
39	2441	0.908
78	2480	0.936


20 dB Bandwidth Plot on Channel 00



Date: 24.SEP.2010 11:58:13




20 dB Bandwidth Plot on Channel 39



Date: 24.SEP.2010 11:58:46

20 dB Bandwidth Plot on Channel 78




Date: 24.SEP.2010 11:59:21



Test Mode :	Mode 4, 5, 6	Temperature :	25~27°C
Test Engineer :	Andy Yeh	Relative Humidity :	50~53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.320
39	2441	1.284
78	2480	1.308


20 dB Bandwidth Plot on Channel 00



Date: 24.SEP.2010 12:03:52




20 dB Bandwidth Plot on Channel 39



Date: 24.SEP.2010 12:02:55

20 dB Bandwidth Plot on Channel 78




Date: 24.SEP.2010 12:02:23



Test Mode :	Mode 7, 8, 9	Temperature :	25~27°C
Test Engineer :	Andy Yeh	Relative Humidity :	50~53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.272
39	2441	1.278
78	2480	1.278


20 dB Bandwidth Plot on Channel 00



Date: 24.SEP.2010 12:05:01




20 dB Bandwidth Plot on Channel 39



Date: 24.SEP.2010 12:05:37

20 dB Bandwidth Plot on Channel 78



Date: 24.SEP.2010 12:06:08

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup






3.3.5 Test Result of Hopping Channel Separation

Test Mode :	Mode 4~6	Temperature :	25~27°C
Test Engineer :	Andy Yeh	Relative Humidity :	50~53%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.880	Pass
39	2441	1.002	0.856	Pass
78	2480	1.002	0.872	Pass


Channel Separation Plot on Channel 00 - 01



Date: 24.SEP.2010 13:54:13




Channel Separation Plot on Channel 39 - 40



Date: 24.SEP.2010 13:54:58

Channel Separation Plot on Channel 77 - 78



Date: 24.SEP.2010 13:55:45

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup



3.4.5 Test Result of Dwell Time

Test Mode :	Mode 5	Temperature :	25~27°C
Test Engineer :	Andy Yeh	Relative Humidity :	50~53%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
2DH5	3.40	3018.00	0.32	0.4	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)




2DH5 Dwell Time (One Pulse) Plot on Channel 39



Date: 24.SEP.2010 14:19:45

2DH5 Dwell Time (Count Pulses) Plot on Channel 39



Date: 24.SEP.2010 14:30:07

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW (20.97dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power

Test Mode :	Mode 4~6	Temperature :	25~27°C	
Test Engineer :	Andy Yeh	Relative Humidity :	50~53%	

Channel	Frequency (MHz)	RF Power (dBm)		
		π /4-DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	4.18	20.97	Pass
39	2441	5.09	20.97	Pass
78	2480	5.27	20.97	Pass




Peak Output Power Plot on Channel 00



Date: 24.SEP.2010 11:22:41


Peak Output Power Plot on Channel 39



Date: 24.SEP.2010 11:22:22



Peak Output Power Plot on Channel 78



Date: 24.SEP.2010 11:22:03



3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW) \geq RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

3.6.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>





3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	22~24°C
Test Channel :	00	Relative Humidity :	50~51%
		Test Engineer :	Jason Wang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2374	46.98	-27.02	74	42.36	32.16	5.99	33.53	128	346	Peak
2374	34.55	-19.45	54	29.93	32.16	5.99	33.53	128	346	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2319	46.92	-27.08	74	42.42	32.09	5.92	33.51	173	320	Peak
2319	33.99	-20.01	54	29.49	32.09	5.92	33.51	173	320	Average



Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
		Test Engineer :	Jason Wang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	63.4	-10.6	74	58.5	32.28	6.18	33.56	106	324	Peak
2483.5	29.34	-24.66	54	24.44	32.28	6.18	33.56	106	324	Average

Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Average Result (dBµV/m)	Average Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	81.86	52.52	29.34	54	-24.66	Pass
Hopping Mode	81.86	54.92	26.94	54	-27.06	Pass

Note : Average result = Maximum field strength – Delta result

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	57.16	-16.84	74	52.26	32.28	6.18	33.56	156	116	Peak
2483.5	27.62	-26.38	54	22.72	32.28	6.18	33.56	156	116	Average


Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Average Result (dBµV/m)	Average Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	77.69	50.07	27.62	54	-26.38	Pass
Hopping Mode	77.69	52	25.69	54	-28.31	Pass

Note : Average result = Maximum field strength – Delta result



Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Horizontal




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC CLASS-B HF_ANT_100824 HORIZONTAL
 Project : FR 0N1023
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	98.38	24.38	74.00	93.49	32.28	6.18	33.56	106	331	Peak
2 @	2480.00	81.86	27.86	54.00	76.96	32.28	6.18	33.56	106	331	Average

* Maximum field strength of the fundamental emission



Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Horizontal




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC CLASS-B HF_ANT_100824 HORIZONTAL
 Project : FR 0N1023
 Mode : Mode 3

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	96.28	22.28	74.00	91.38	32.28	6.18	33.56	106	331	Peak
2	2483.56	43.76	-30.24	74.00	38.86	32.28	6.18	33.56	106	331	Peak

* Marker-Delta Method (RBW/VBW=100KHz): 52.52 dB , single carrier Mode




Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Horizontal






Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Vertical





Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Vertical




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC CLASS-B HF_ANT_100824 VERTICAL
 Project : FR 0N1023
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	90.33	16.33	74.00	85.43	32.28	6.18	33.56	154	129	Peak
2	2484.23	40.26	-33.74	74.00	35.36	32.28	6.18	33.56	154	129	Peak

* Marker-Delta Method (RBW/VBW=100KHz): 50.07 dB , single carrier Mode



Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Vertical



Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC CLASS-B HF_ANT_100824 VERTICAL
 Project : FR 0N1023
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	90.85	16.85	74.00	85.95	32.28	6.18	33.56	154	129	Peak
2	2483.82	38.85	-35.15	74.00	33.95	32.28	6.18	33.56	154	129	Peak


* Marker-Delta Method (RBW/VBW=100KHz): 52.00 dB , Hopping Mode



3.6.6 Test Result of Conducted Band Edges

Test Mode :	Mode 4 and 6	Temperature :	25~27°C
Test Channel :	00 and 78	Relative Humidity :	50~53%
		Test Engineer :	Andy Yeh


Low Band Edge Plot on Channel 00



Date: 24.SEP.2010 14:09:52



High Band Edge Plot on Channel 78



Date: 24.SEP.2010 14:04:34

3.7 Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) \geq RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

3.7.4 Test Setup






3.7.5 Test Result


Test Mode :	Mode 4	Temperature :	25~27°C
Test Channel :	00	Relative Humidity :	50~53%
		Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 24.SEP.2010 15:16:23

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 24.SEP.2010 15:19:07




Test Mode :	Mode 5	Temperature :	25~27°C
Test Channel :	39	Relative Humidity :	50~53%
		Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 24.SEP.2010 15:19:33

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 24.SEP.2010 15:19:58




Test Mode :	Mode 6	Temperature :	25~27°C
Test Channel :	78	Relative Humidity :	50~53%
		Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 24.SEP.2010 15:20:25

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz



Date: 24.SEP.2010 15:20:49

3.8 AC Conducted Emission Measurement

3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.8.4 Test Setup



3.8.5 Test Result of AC Conducted Emission

Test Mode :	Mode 4	Temperature :	20~22°C
Test Engineer :	Hayden Wu	Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + GPS Rx + Earphone + USB Cable (Link with Notebook)		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	49.5	Off	L1	19.4	16.5	66.0
0.166000	46.8	Off	L1	19.3	18.4	65.2
0.198000	43.6	Off	L1	19.3	20.1	63.7
0.238000	38.6	Off	L1	19.4	23.6	62.2
0.270000	42.2	Off	L1	19.3	18.9	61.1
0.334000	36.4	Off	L1	19.3	23.0	59.4

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	20.2	Off	L1	19.4	35.8	56.0
0.166000	19.3	Off	L1	19.3	35.9	55.2
0.198000	31.5	Off	L1	19.3	22.2	53.7
0.238000	11.5	Off	L1	19.4	40.7	52.2
0.270000	31.3	Off	L1	19.3	19.8	51.1
0.334000	25.0	Off	L1	19.3	24.4	49.4



Test Mode :	Mode 4	Temperature :	20~22°C
Test Engineer :	Hayden Wu	Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + GPS Rx + Earphone + USB Cable (Link with Notebook)		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	49.6	Off	N	19.4	16.4	66.0
0.198000	50.2	Off	N	19.3	13.5	63.7
0.270000	44.6	Off	N	19.3	16.5	61.1
0.334000	37.1	Off	N	19.3	22.3	59.4
1.822000	33.7	Off	N	19.5	22.3	56.0
2.966000	30.4	Off	N	19.5	25.6	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	21.0	Off	N	19.4	35.0	56.0
0.198000	39.0	Off	N	19.3	14.7	53.7
0.270000	34.0	Off	N	19.3	17.1	51.1
0.334000	26.6	Off	N	19.3	22.8	49.4
1.822000	31.7	Off	N	19.5	14.3	46.0
2.966000	24.2	Off	N	19.5	21.8	46.0



3.9 Radiated Emission Measurement

3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

3.9.3 Test Procedures


1. The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
2. Use the following spectrum analyzer settings:
 - (1) Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - (2) Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log(\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
3. Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.9.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz





3.9.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Jason Wang	Temperature :	22~24°C	
		Relative Humidity :	50~51%	
Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



3.9.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	22~24°C
Test Channel :	00	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Horizontal
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.81	31.87	-8.13	40	43.84	18.95	0.54	31.46	163	228	Peak
51.33	27.41	-12.59	40	50.47	7.77	0.71	31.54	-	-	Peak
187.14	25.23	-18.27	43.5	46.52	8.96	1.27	31.52	-	-	Peak
713	21.6	-24.4	46	28.41	21.01	2.97	30.79	-	-	Peak
868.4	23.91	-22.09	46	28.46	22.87	3.3	30.72	-	-	Peak
982.5	25.11	-28.89	54	27.77	24.43	3.49	30.58	-	-	Peak
2374	46.98	-27.02	74	42.36	32.16	5.99	33.53	128	346	Peak
2374	34.55	-19.45	54	29.93	32.16	5.99	33.53	128	346	Average
2402	82.33	-	-	77.65	32.18	6.03	33.53	128	346	Average
2402	98.06	-	-	93.38	32.18	6.03	33.53	128	346	Peak
2488	45.23	-28.77	74	40.32	32.3	6.18	33.57	128	346	Peak
2488	33.88	-20.12	54	28.97	32.3	6.18	33.57	128	346	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Channel :	00	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Vertical
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.08	35.09	-4.91	40	47.06	18.95	0.54	31.46	155	113	Peak
49.71	26.89	-13.11	40	49.26	8.47	0.69	31.53	-	-	Peak
190.11	25.72	-17.78	43.5	47.03	8.92	1.28	31.51	-	-	Peak
678	20.89	-25.11	46	28.16	20.67	2.9	30.84	-	-	Peak
886.6	23.51	-22.49	46	27.85	23.05	3.32	30.71	-	-	Peak
974.8	24.63	-29.37	54	27.41	24.31	3.49	30.58	-	-	Peak
2319	46.92	-27.08	74	42.42	32.09	5.92	33.51	173	320	Peak
2319	33.99	-20.01	54	29.49	32.09	5.92	33.51	173	320	Average
2402	78.97	-	-	74.29	32.18	6.03	33.53	173	320	Average
2402	94.02	-	-	89.34	32.18	6.03	33.53	173	320	Peak
2494	44.98	-29.02	74	40.07	32.3	6.18	33.57	173	320	Peak
2494	33.86	-20.14	54	28.95	32.3	6.18	33.57	173	320	Average



Test Mode :	Mode 2	Temperature :	22~24°C
Test Channel :	39	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Horizontal
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.16	31.44	-8.56	40	43.95	18.4	0.55	31.46	133	261	Peak
41.34	27.74	-12.26	40	45.82	12.8	0.63	31.51	-	-	Peak
193.08	24.05	-19.45	43.5	45.38	8.88	1.29	31.5	-	-	Peak
741.7	23.86	-22.14	46	30.12	21.42	3.04	30.72	-	-	Peak
825	24.17	-21.83	46	29.21	22.46	3.21	30.71	-	-	Peak
960.1	26.12	-27.88	54	29.13	24.09	3.47	30.57	-	-	Peak
2366	46.22	-27.78	74	41.62	32.13	5.99	33.52	106	2	Peak
2366	34.32	-19.68	54	29.72	32.13	5.99	33.52	106	2	Average
2441	82.62	-	-	77.82	32.24	6.11	33.55	106	2	Average
2441	98.52	-	-	93.72	32.24	6.11	33.55	106	2	Peak
2494	45.23	-28.77	74	40.32	32.3	6.18	33.57	106	2	Peak
2494	33.82	-20.18	54	28.91	32.3	6.18	33.57	106	2	Average



Test Mode :	Mode 2	Temperature :	22~24°C
Test Channel :	39	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Vertical
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.89	34.04	-5.96	40	46.55	18.4	0.55	31.46	127	141	Peak
48.9	27.05	-12.95	40	48.94	8.96	0.68	31.53	-	-	Peak
190.38	26.19	-17.31	43.5	47.5	8.92	1.28	31.51	-	-	Peak
741.7	24.19	-21.81	46	30.45	21.42	3.04	30.72	-	-	Peak
791.4	24.92	-21.08	46	30.37	22.1	3.13	30.68	-	-	Peak
956.6	26.46	-19.54	46	29.53	24.03	3.47	30.57	-	-	Peak
2344	45.22	-28.78	74	40.68	32.11	5.95	33.52	168	326	Peak
2344	33.89	-20.11	54	29.35	32.11	5.95	33.52	168	326	Average
2441	94.62	-	-	89.82	32.24	6.11	33.55	168	326	Peak
2441	79.28	-	-	74.48	32.24	6.11	33.55	168	326	Average
2484	45.2	-28.8	74	40.3	32.28	6.18	33.56	168	326	Peak
2484	33.61	-20.39	54	28.71	32.28	6.18	33.56	168	326	Average



Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Horizontal
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.32	33.52	-6.48	40	47.13	17.29	0.57	31.47	122	331	Peak
55.11	31.36	-8.64	40	55.23	6.95	0.73	31.55	-	-	Peak
188.49	26.73	-16.77	43.5	48.03	8.94	1.27	31.51	-	-	Peak
785.8	23.82	-22.18	46	29.37	22.02	3.12	30.69	-	-	Peak
926.5	25.85	-20.15	46	29.5	23.58	3.4	30.63	-	-	Peak
996.5	26.99	-27.01	54	29.43	24.63	3.51	30.58	-	-	Peak
2373	45.22	-28.78	74	40.6	32.16	5.99	33.53	106	324	Peak
2373	34.01	-19.99	54	29.39	32.16	5.99	33.53	106	324	Average
2480	81.88	-	-	76.98	32.28	6.18	33.56	106	324	Average
2480	98.29	-	-	93.39	32.28	6.18	33.56	106	324	Peak
2483.5	63.4	-10.6	74	58.5	32.28	6.18	33.56	106	324	Peak
2483.5	29.34	-24.66	54	24.44	32.28	6.18	33.56	106	324	Average



Test Mode :	Mode 3	Temperature :	22~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Jason Wang	Polarization :	Vertical
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.16	33.47	-6.53	40	45.98	18.4	0.55	31.46	130	213	Peak
88.05	25.88	-17.62	43.5	47.86	8.62	0.93	31.53	-	-	Peak
191.46	26.71	-16.79	43.5	48.03	8.91	1.28	31.51	-	-	Peak
727.7	23.48	-22.52	46	30	21.22	3.01	30.75	-	-	Peak
925.8	25.57	-20.43	46	29.22	23.58	3.4	30.63	-	-	Peak
995.8	28.05	-25.95	54	30.49	24.63	3.51	30.58	-	-	Peak
2344	33.98	-20.02	54	29.44	32.11	5.95	33.52	156	116	Average
2344	46.21	-27.79	74	41.67	32.11	5.95	33.52	156	116	Peak
2480	92.86	-	-	87.96	32.28	6.18	33.56	156	116	Peak
2480	76.81	-	-	71.91	32.28	6.18	33.56	156	116	Average
2483.5	27.62	-26.38	54	22.72	32.28	6.18	33.56	156	116	Average
2483.5	57.16	-16.84	74	52.26	32.28	6.18	33.56	156	116	Peak



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101329	9kHz~30GHz	Apr. 26, 2010	Apr. 25, 2011	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 13, 2010	Sep. 12, 2011	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 14, 2010	Sep. 13, 2011	Conducted (TH02-HY)
EMI Test Receive	R&S	ESCS 30	100356	9KHz – 2.75GHz	Aug. 16, 2010	Aug. 15, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9kHz~30MHz	Nov. 30, 2009	Nov. 29, 2010	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9kHz~30MHz	Nov. 23, 2009	Nov. 22, 2010	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
System Simulator	R&S	CMU200	105934	N/A	Nov. 11, 2008	Nov. 10, 2010	Conduction (CO05-HY)
GPS Station	T&E	GS-50	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2010	Oct. 30, 2011	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9KHz ~ 30GHz	Dec. 03, 2010	Dec. 02, 2011	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2010	Aug. 18, 2011	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec. 06, 2010	Dec. 05, 2011	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32 dB.GAIN	Mar. 27, 2010	Mar. 26, 2011	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH07-HY)
Bluetooth Base Station	R&S	CBT32	100519	N/A	May 12, 2009	May 11, 2011	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		



Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				