

# A Test Lab Techno Corp.

Changan Lab : No. 140 -1, Changan Street, Bade City, Taoyuan County, Taiwan R.O.C.

Tel : 886-3-271-0188 / Fax : 886-3-271-0190

## SAR EVALUATION REPORT



Test Report No.	:	1107FS23-01
Applicant	:	HTC Corporation
Product Type	:	Smartphone
Trade Name	:	HTC
Model Number	:	PG76210
Dates of Test	:	Jul. 08 ~ Jul. 19, 2011
Date of Issued	:	Jul. 21, 2011
Test Environment	:	Ambient Temperature : $22 \pm 2$ ° C Relative Humidity : 40 - 70 %
Standard	:	ANSI/IEEE C95.1-1999 IEEE Std. 1528-2003 47 CFR Part §2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]
Max. SAR	:	1.370 W/kg Head SAR 1.300 W/kg Body SAR
Test Lab Location	:	Chang-an Lab



1. The test operations have to be performed with cautious behavior, the test results are as attached.
2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. The test results in the report only apply to the tested sample.

Approved By :



(Sam Chuang)

Tested By :



(Alex Wu)



# Contents

1. Description of Equipment under Test (EUT) .....	3
2. Introduction .....	4
2.1 SAR Definition .....	4
3. SAR Measurement Setup .....	5
3.1 DASY5 E-Field Probe System .....	6
3.2 Data Acquisition Electronic (DAE) System.....	9
3.3 Robot.....	9
3.4 Measurement Server.....	9
3.5 Device Holder.....	10
3.6 Phantom - SAM v4.0 .....	10
3.7 Oval Flat Phantom - ELI 4.0.....	11
3.8 Data Storage and Evaluation .....	11
4. Tissue Simulating Liquids .....	14
4.1 Ingredients .....	15
4.2 Recipes .....	15
4.3 Liquid Confirmation .....	16
5. SAR Testing with RF Transmitters .....	19
5.1 SAR Testing with HSDPA Transmitters .....	19
5.2 SAR Testing with 802.11 Transmitters .....	21
5.2.1 General Device Setup .....	21
5.2.2 Frequency Channel Configurations .....	21
5.3 Conducted Power.....	23
5.4 Simultaneous Transmitting Evaluate.....	28
6. System Performance Check .....	32
6.1 Symmetric Dipoles for System Validation .....	32
6.2 Validation.....	33
7. Test Equipment List.....	40
8. Measurement Uncertainty .....	41
9. Measurement Procedure .....	43
9.1 Spatial Peak SAR Evaluation .....	43
9.2 Area & Zoom Scan Procedures .....	44
9.3 Volume Scan Procedures .....	44
9.4 SAR Averaged Methods.....	44
9.5 Power Drift Monitoring.....	44
10. SAR Test Results Summary.....	45
10.1 Head SAR .....	45
10.2 Body SAR.....	46
10.3 Std. C95.1-1999 RF Exposure Limit .....	48
11. Conclusion .....	49
12. References.....	49
Appendix A - System Performance Check.....	50
Appendix B - SAR Measurement Data.....	59
Appendix C - Calibration.....	119



## 1. Description of Equipment under Test (EUT)

Applicant	HTC Corporation		
Applicant Address	No. 23, Xinghua Rd., Taoyuan City, Taoyuan County 330, Taiwan		
Manufacture	HTC Corporation		
Manufacture Address	No. 23, Xinghua Rd., Taoyuan City, Taoyuan County 330, Taiwan		
Product Type	Smartphone		
Trade Name	HTC		
Model Number	PG76210		
FCC ID	NM8PG76210		
RF Function	CDMA / 1xRTT / 1xEVDO Rev.0 / 1xEVDO Rev.A Cellular Band CDMA / 1xRTT / 1xEVDO Rev.0 / 1xEVDO Rev.A PCS Band CDMA / 1xRTT / 1xEVDO Rev.0 / 1xEVDO Rev.A AWS Band IEEE 802.11b / 802.11g / draft 802.11n 2.4GHz Standard-20MHz with Wi-Fi Hot spot mode Bluetooth		
Tx Frequency	Band		
	CDMA / 1xRTT / 1xEVDO Rev.0 / 1xEVDO Rev.A	Operate Frequency (MHz)	
		Cellular Band	824.0 - 849.0
		PCS	1850.0 - 1910.0
	AWS Band	1710.0 - 1755.0	
	IEEE 802.11b/802.11g	2412 - 2462	
draft 802.11n 2.4GHz Standard-20MHz	2412 - 2462		
Bluetooth	2402 - 2480		
RF Conducted Power (Avg.)	Band		
	Power (W / dBm)		
	CDMA Cellular Band		0.256 / 24.08
	CDMA PCS Band		0.262 / 24.19
	AWS Band		0.272 / 24.35
	IEEE 802.11b		0.066 / 18.17
	IEEE 802.11g		0.021 / 13.26
	Draft 802.11n 2.4GHz Standard-20MHz		0.021 / 13.12
Bluetooth		0.00035 / -4.60	
Max. SAR Measurement	1.370 W/kg Head SAR 1.300 W/kg Body SAR		
Antenna Type	PIFA Type		
Device Category	Portable Device		
RF Exposure Environment	General Population / Uncontrolled		
Battery Option	Standard		
Application Type	Certification		

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment / general population exposure limits specified in Standard C95.1-1999 and had been tested in accordance with the measurement procedures specified in IEEE Std. 1528-2003.

## 2. Introduction

The A Test Lab Techno Corp. has performed measurements of the maximum potential exposure to the user of **HTC Corporation Trade Name : HTC Model(s) : PG76210**. The test procedures, as described in American National Standards, Institute C95.1-1999 [ 1 ] , FCC/OET Bulletin 65 Supplement C [July 2001] were employed and they specify the maximum exposure limit of 1.6mW/g as averaged over any 1 gram of tissue for portable devices being used within 20cm between user and EUT in the uncontrolled environment. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the equipment used are included within this test report.

### 2.1 SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dw) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Figure 2).

$$\text{SAR} = \frac{d}{dt} \left( \frac{dw}{dm} \right) = \frac{d}{dt} \left( \frac{dw}{\rho dv} \right)$$

Figure 2. SAR Mathematical Equation

SAR is expressed in units of Watts per kilogram (W/kg)

$$\text{SAR} = \frac{\sigma E^2}{\rho}$$

Where :

$\sigma$  = conductivity of the tissue (S/m)


$\rho$  = mass density of the tissue (kg/m<sup>3</sup>)

$E$  = RMS electric field strength (V/m)

\* Note :

The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane [ 2 ]

### 3. SAR Measurement Setup



The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli TX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
5. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
6. A computer operating Windows 2000 or Windows XP.
7. DASY5 software.
8. Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
9. The SAM twin phantom enabling testing left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. Validation dipole kits allowing validating the proper functioning of the system.




### 3.1 DASYS E-Field Probe System

The SAR measurements were conducted with the dosimetric probe ES3DV3 or EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration [3] and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASYS software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped when reaching the maximum.

### 3.1.1 E-Field Probe Specification

Construction	<p>Symmetrical design with triangular core</p> <p>Built-in optical fiber for surface detection System</p> <p>Built-in shielding against static charges</p> <p>PEEK enclosure material (resistant to organic solvents, e.q., glycol)</p>
Calibration	<p>In air from 10 MHz to 6 GHz</p> <p>In brain and muscle simulating tissue at frequencies of 2450MHz (accuracy <math>\pm 8\%</math>)</p> <p>Calibration for other liquids and frequencies upon request</p>
Frequency	<p><math>\pm 0.2</math> dB (30 MHz to 6 GHz) for EX3DV4</p> <p><math>\pm 0.2</math> dB (30 MHz to 4 GHz) for ES3DV3</p>
Directivity	<p><math>\pm 0.3</math> dB in brain tissue (rotation around probe axis)</p> <p><math>\pm 0.5</math> dB in brain tissue (rotation normal probe axis)</p>
Dynamic Range	<p>10 <math>\mu</math> W/g to &gt; 100mW/g; Linearity: <math>\pm 0.2</math>dB</p>
Dimensions	<p>Overall length: 337mm</p> <p>Tip length: 20mm</p> <p>Body diameter: 12mm</p> <p>Tip diameter: 2.5mm for EX3DV4, 3.9mm for ES3DV3</p> <p>Distance from probe tip to dipole centers: 1.0mm for EX3DV4, 2.0mm for ES3DV3</p>
Application	<p>General dosimetry up to 6GHz</p> <p>Compliance tests of mobile phones</p> <p>Fast automatic scanning in arbitrary phantoms</p>





### 3.1.2 E-Field Probe Calibration process

#### Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm<sup>2</sup>) using an RF Signal generator, TEM cell, and RF Power Meter.

#### Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm<sup>2</sup>.

#### Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where :

- $\Delta t$  = Exposure time (30 seconds),
- $C$  = Heat capacity of tissue (head or body),
- $\Delta T$  = Temperature increase due to RF exposure.

$$\text{Or } \text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where :

- $\sigma$  = Simulated tissue conductivity,
- $\rho$  = Tissue density (kg/m<sup>3</sup>).





### 3.2 Data Acquisition Electronic (DAE) System

#### Cell Controller

Processor : Intel Core(TM)2 CPU  
Clock Speed : @ 1.86GHz  
Operating System : Windows XP Professional

#### Data Converter

Features : Signal Amplifier, multiplexer, A/D converter, and control logic  
Software : DASY5 v5.0 (Build 125) & SEMCAD X Version 13.4 Build 125  
Connecting Lines : Optical downlink for data and status info  
Optical uplink for commands and clock

### 3.3 Robot


Positioner : Stäubli Unimation Corp. Robot Model: TX90XL  
Repeatability :  $\pm 0.02$  mm  
No. of Axis : 6

### 3.4 Measurement Server

Processor : PC/104 with a 400MHz intel ULV Celeron  
I/O-board : Link to DAE4 (or DAE3)  
16-bit A/D converter for surface detection system  
Digital I/O interface  
Serial link to robot  
Direct emergency stop output for robot

### 3.5 Device Holder

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon=3$  and loss tangent  $\delta=0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



**Figure 5. Device Holder**

### 3.6 Phantom - SAM v4.0

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness	2 ±0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	1000x500 mm (LxW)
<b>Table 1. Specification of SAM v4.0</b>	



**Figure 6. SAM Twin Phantom**

### 3.7 Oval Flat Phantom - ELI 4.0

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (Oval Flat) phantom defined in IEEE 1528-2003, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of wireless portable device usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

<b>Shell Thickness</b>	2 ±0.2 mm
<b>Filling Volume</b>	Approx. 30 liters
<b>Dimensions</b>	190x600x400 mm (HxLxW)
<b>Table 2. Specification of ELI 4.0</b>	




Figure 7. Oval Flat Phantom

### 3.8 Data Storage and Evaluation

#### 3.8.1 Data Storage

The DASY5 software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension DA5. The post processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.



### 3.8.2 Data Evaluation

The DASY5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software :

- Probe parameters :**
- Sensitivity Normi, ai0, ai1, ai2
  - Conversion factor ConvFi
  - Diode compression point dcp<sub>i</sub>
- Device parameters :**
- Frequency f
  - Crest factor cf
- Media parameters :**
- Conductivity  $\sigma$
  - Density  $\rho$

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

- with  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )
- $U_i$  = input signal of channel  $i$  ( $i = x, y, z$ )
- $cf$  = crest factor of exciting field (DASY parameter)
- $dcp_i$  = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated :

**E-field probes :** 
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

**H-field probes :**

with  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$Norm_i$  = sensor sensitivity of channel  $i$  ( $i = x, y, z$ )

$\mu V/(V/m)^2$  for E-field Probes

$ConvF$  = sensitivity enhancement in solution

$a_{ij}$  = sensor sensitivity factors for H-field probes

$f$  = carrier frequency [GHz]

$E_i$  = electric field strength of channel  $i$  in V/m

$Hi$  = magnetic field strength of channel  $i$  in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude) :

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with  $SAR$  = local specific absorption rate in mW/g

$E_{tot}$  = total field strength in V/m

$\sigma$  = conductivity in [mho/m] or [Siemens/m]

$\rho$  = equivalent tissue density in  $g/cm^3$

**\*Note :** That the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = \frac{H_{tot}^2}{37.7}$$

with  $P_{pwe}$  = equivalent power density of a plane wave in  $mW/cm^2$

$E_{tot}$  = total electric field strength in V/m

$H_{tot}$  = total magnetic field strength in A/m



#### 4. Tissue Simulating Liquids

The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue. The dielectric parameters of the liquids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an E5071B Network Analyzer.

##### IEEE SCC-34/SC-2 in 1528 recommended Tissue Dielectric Parameters

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in 1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in human head. Other head and body tissue parameters that have not been specified in 1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equation and extrapolated according to the head parameter specified in 1528.

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 - 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(  $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$  )

**Table 3. Tissue dielectric parameters for head and body phantoms**



## 4.1 Ingredients

The following ingredients are used:

- Water: deionized water (pure H<sub>2</sub>O), resistivity  $\geq 16 \text{ M } \Omega$  -as basis for the liquid
- Sugar: refined white sugar (typically 99.7 % sucrose, available as crystal sugar in food shops)  
-to reduce relative permittivity
- Salt: pure NaCl -to increase conductivity
- Cellulose: Hydroxyethyl-cellulose, medium viscosity (75-125 mPa.s, 2% in water, 20 °C), CAS # 54290 -to increase viscosity and to keep sugar in solution.
- Preservative: Preventol D-7 Bayer AG, D-51368 Leverkusen, CAS # 55965-84-9 -to prevent the spread of bacteria and molds
- DGBE: Diethylenglycol-monobutyl ether (DGBE), Fluka Chemie GmbH, CAS # 112-34-5 -to reduce relative permittivity

## 4.2 Recipes

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands.

Note: The goal dielectric parameters (at 22 °C) must be achieved within a tolerance of  $\pm 5\%$  for  $\epsilon$  and  $\pm 5\%$  for  $\sigma$ .

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Salt: 99+% Pure Sodium Chloride      Sugar: 98+% Pure Sucrose

Water: De-ionized,  $16 \text{ M } \Omega$  resistivity      HEC: Hydroxyethyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl]ether



### 4.3 Liquid Confirmation

#### 4.3.1 Parameters

Liquid Verify								
Ambient Temperature : 22 ± 2 °C ; Relative Humidity : 40 -70%								
Liquid Type	Frequency	Temp (°C)	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)	Measured Date
835MHz Head	820MHz	22.0	$\epsilon_r$	41.50	41.41	-0.22%	± 5	07/10/2011
			$\sigma$	0.900	0.890	-1.11%	± 5	
	835MHz	22.0	$\epsilon_r$	41.50	41.18	-0.77%	± 5	
			$\sigma$	0.900	0.904	0.44%	± 5	
	850MHz	22.0	$\epsilon_r$	41.50	40.99	-1.23%	± 5	
			$\sigma$	0.900	0.919	2.11%	± 5	
1750MHz Head	1700MHz	22.0	$\epsilon_r$	40.00	39.56	-1.30%	± 5	07/10/2011
			$\sigma$	1.400	1.359	-0.88%	± 5	
	1750MHz	22.0	$\epsilon_r$	40.00	39.51	-1.42%	± 5	
			$\sigma$	1.400	1.403	2.33%	± 5	
	1760MHz	22.0	$\epsilon_r$	40.00	39.48	-1.50%	± 5	
			$\sigma$	1.400	1.410	2.84%	± 5	
1900MHz Head	1850MHz	22.0	$\epsilon_r$	40.00	38.37	-4.08%	± 5	07/10/2011
			$\sigma$	1.400	1.346	-3.86%	± 5	
	1900MHz	22.0	$\epsilon_r$	40.00	38.15	-4.63%	± 5	
			$\sigma$	1.400	1.372	-2.00%	± 5	
	1930MHz	22.0	$\epsilon_r$	40.00	38.12	-4.70%	± 5	
			$\sigma$	1.400	1.398	-0.14%	± 5	
2450MHz Head	2400MHz	22.0	$\epsilon_r$	39.20	39.73	0.93%	± 5	07/19/2011
			$\sigma$	1.800	1.743	-42.97%	± 5	
	2450MHz	22.0	$\epsilon_r$	39.20	39.60	1.26%	± 5	
			$\sigma$	1.800	1.800	-44.78%	± 5	
	2500MHz	22.0	$\epsilon_r$	39.20	39.45	36.88%	± 5	
			$\sigma$	1.800	1.868	-43.79%	± 5	

Table 4. Measured Tissue dielectric parameters for head phantoms






Liquid Verify								
Ambient Temperature : 22 ± 2 °C ; Relative Humidity : 40 -70%								
Liquid Type	Frequency	Temp (°C)	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)	Measured Date
835MHz Body	820MHz	22.0	$\epsilon_r$	55.20	54.56	-1.16%	± 5	07/07/2011
			$\sigma$	0.970	0.965	-0.52%	± 5	
	835MHz	22.0	$\epsilon_r$	55.20	54.39	-1.47%	± 5	
			$\sigma$	0.970	0.980	1.03%	± 5	
	850MHz	22.0	$\epsilon_r$	55.20	54.31	-1.61%	± 5	
			$\sigma$	0.970	0.998	2.89%	± 5	
835MHz Body	820MHz	22.0	$\epsilon_r$	55.20	54.56	-1.16%	± 5	07/11/2011
			$\sigma$	0.970	0.965	-0.52%	± 5	
	835MHz	22.0	$\epsilon_r$	55.20	54.39	-1.47%	± 5	
			$\sigma$	0.970	0.980	1.03%	± 5	
	850MHz	22.0	$\epsilon_r$	55.20	54.31	-1.61%	± 5	
			$\sigma$	0.970	0.998	2.89%	± 5	
1750MHz Body	1700MHz	22.0	$\epsilon_r$	53.43	52.95	-0.90%	± 5	07/09/2011
			$\sigma$	1.488	1.470	-1.21%	± 5	
	1750MHz	22.0	$\epsilon_r$	53.43	53.00	-0.80%	± 5	
			$\sigma$	1.488	1.521	2.22%	± 5	
	1760MHz	22.0	$\epsilon_r$	53.43	52.98	-0.84%	± 5	
			$\sigma$	1.488	1.529	2.76%	± 5	
1900MHz Body	1850MHz	22.0	$\epsilon_r$	53.30	52.17	-2.12%	± 5	07/08/2011
			$\sigma$	1.520	1.545	1.64%	± 5	
	1900MHz	22.0	$\epsilon_r$	53.30	52.04	-2.36%	± 5	
			$\sigma$	1.520	1.503	-1.12%	± 5	
	1930MHz	22.0	$\epsilon_r$	53.30	52.01	-2.42%	± 5	
			$\sigma$	1.520	1.531	0.72%	± 5	
2450MHz Body	2400MHz	22.0	$\epsilon_r$	52.70	51.81	-1.69%	± 5	07/09/2011
			$\sigma$	1.950	1.880	-3.59%	± 5	
	2450MHz	22.0	$\epsilon_r$	52.70	51.67	-1.95%	± 5	
			$\sigma$	1.950	1.937	-0.67%	± 5	
	2500MHz	22.0	$\epsilon_r$	52.70	51.50	-2.28%	± 5	
			$\sigma$	1.950	2.001	2.62%	± 5	

Table 5. Measured Tissue dielectric parameters for body phantoms

### 4.3.2 Liquid Depth

The liquid level was during measurement 15cm  $\pm$ 0.5cm.



**Figure 8. Head-Tissue-Simulating-Liquid**



**Figure 9. Body-Tissue-Simulating-Liquid**



## 5. SAR Testing with RF Transmitters

### 5.1 SAR Testing with CDMA2000 Transmitters

The following procedures were performed according to FCC “SAR Measurement Procedures for 3G Devices” v02, October 2007.

#### 5.1.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by “SAR Measurement Procedures for 3G Devices” v02, October 2007. Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 6. parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 7 was applied.
5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

Table 6. Parameters for Max. Power for RC1		
Parameter	Units	Value
$I_{or}$	dBm/1.23MHz	-104
$\frac{\text{Pilot } E_c}{I_{or}}$	dB	-7
$\frac{\text{Traffic } E_c}{I_{or}}$	dB	-7.4

Table 7. Parameters for Max. Power for RC3		
Parameter	Units	Value
$I_{or}$	dBm/1.23MHz	-86
$\frac{\text{Pilot } E_c}{I_{or}}$	dB	-7
$\frac{\text{Traffic } E_c}{I_{or}}$	dB	-7.4

#### 5.1.2 Head SAR Measurements

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.



### 5.1.3 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCHn) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCHn) with FCH at full rate and SCH0 enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts. Body SAR was measured using TDSO / SO32 with power control bits in the “All Up” Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.

### 5.1.4 Handsets with EVDO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for EV-DO is not required. Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3. SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots would be configured in the downlink for both Rev. 0 and Rev. A.



## **5.2 SAR Testing with 802.11 Transmitters**

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

### **5.2.1 General Device Setup**

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined

for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate.

The same data pattern should be used for all measurements.

### **5.2.2 Frequency Channel Configurations**

802.11 a/b/g and 4.9 GHz operating modes are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz §15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. 4.9 GHz is tested on channels 1, 10 and 5 or 6, whichever has the higher output power, for 5 MHz channels; channels 11, 15 and 19 for 10 MHz channels; and channels 21 and 25 for 20 MHz channels. These are referred to as the “default test channels”. 802.11g mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.



**802.11 Test Channels per FCC Requirement**

Mode	GHz	Channel	Turbo Channel	Default Test "Channels"				
				§15.247		UNII		
				802.11b	802.11g			
802.11 b/g	2412	1		✓	▽			
	2437	6	6	✓	▽			
	2462	11		✓	▽			
802.11a	5.18	36				✓		
	5.20	40	42 (5.21 GHz)				*	
	5.22	44					*	
	5.24	48						
	5.26	52	50 (5.25 GHz)			✓		
	5.28	56					*	
	5.30	60	58 (5.29 GHz)				*	
	5.32	64				✓		
	5.500	100	Unknown					*
	5.520	104				✓		
	5.540	108						*
	5.560	112						*
	5.580	116				✓		
	5.600	120						*
	5.620	124				✓		
	5.640	128						*
	5.660	132						*
	5.680	136				✓		
	5.700	140						*
	UNII or §15.247	5.745	149		✓		✓	
5.765		153	152 (5.76 GHz)		*		*	
5.785		157		✓			*	
5.805		161	160 (5.80 GHz)		*	✓		
§15.247	5.825	165		✓				



### 5.3 Conducted Power

Band	RC/TAP (REV)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
CDMA Cellular Band	RC1/SO55	Lowest	824.70	23.66
		Middle	836.52	<b>24.08</b>
		Highest	848.31	23.75
	RC3/SO55	Lowest	824.70	23.61
		Middle	836.52	24.00
		Highest	848.31	23.77

Band	RC/TAP (REV)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
1xRTT Cellular Band	RC3/SO32	Lowest	824.70	23.62
		Middle	836.52	23.99
		Highest	848.31	23.69

Band	RTAP (kbps)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
1xEVDO Rev.0 Cellular Band	153.6	Lowest	824.70	23.22
		Middle	836.52	23.32
		Highest	848.31	23.29

Band	RETAP Payload size	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
1xEVDO Rev.A Cellular Band	4096 Bits	Lowest	824.70	23.46
		Middle	836.52	23.56
		Highest	848.31	23.27



Band	RC/TAP (REV)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
CDMA PCS Band	RC1/SO55	Lowest	1851.25	23.86
		Middle	1880.00	23.78
		Highest	1908.75	24.19
	RC3/SO55	Lowest	1851.25	23.77
		Middle	1880.00	23.67
		Highest	1908.75	<b>24.19</b>

Band	RC/TAP (REV)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
1xRTT PCS Band	RC3/SO32	Lowest	1851.25	23.85
		Middle	1880.00	23.67
		Highest	1908.75	24.13

Band	RTAP (kbps)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
1xEVDO Rev.0 PCS Band	153.6	Lowest	1851.25	23.61
		Middle	1880.00	23.59
		Highest	1908.75	23.59

Band	RETAP Payload size	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
1xEVDO Rev.A PCS Band	4096 Bits	Lowest	1851.25	23.01
		Middle	1880.00	23.02
		Highest	1908.75	23.01





Band	RC/TAP (REV)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
CDMA AWS Band	RC1/SO55	Lowest	1711.25	23.66
		Middle	1732.50	24.30
		Highest	1753.75	23.77
	RC3/SO55	Lowest	1711.25	23.82
		Middle	1732.50	<b>24.35</b>
		Highest	1753.75	23.70

Band	RC/TAP (REV)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
AWS 1xRTT Band	RC3/SO32	Lowest	1711.25	23.78
		Middle	1732.50	24.31
		Highest	1753.75	23.93

Band	RTAP (kbps)	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
AWS 1xEVDO Rev.0 Band	153.6	Lowest	1711.25	23.38
		Middle	1732.50	23.47
		Highest	1753.75	23.29

Band	RETAP Payload size	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
AWS 1xEVDO Rev.A Band	4096 Bits	Lowest	1711.25	23.49
		Middle	1732.50	23.64
		Highest	1753.75	23.39



Band	Data Rate	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
IEEE 802.11b	1M	1	2412.0	17.96
		6	2437.0	17.85
		11	2462.0	18.03
	2M	1	2412.0	17.98
		6	2437.0	18.06
		11	2462.0	18.13
	5.5M	1	2412.0	18.03
		6	2437.0	18.05
		11	2462.0	<b>18.17</b>
	11M	1	2412.0	17.65
		6	2437.0	17.69
		11	2462.0	17.91
IEEE 802.11g	6M	1	2412.0	12.87
		6	2437.0	12.76
		11	2462.0	<b>13.26</b>
	9M	1	2412.0	12.51
		6	2437.0	12.35
		11	2462.0	13.07
	12M	1	2412.0	12.36
		6	2437.0	12.26
		11	2462.0	12.68
	18M	1	2412.0	12.19
		6	2437.0	12.25
		11	2462.0	12.48
	24M	1	2412.0	12.28
		6	2437.0	12.25
		11	2462.0	12.31
	36M	1	2412.0	11.79
		6	2437.0	11.82
		11	2462.0	11.96
	48M	1	2412.0	11.52
		6	2437.0	11.73
		11	2462.0	11.69
	54M	1	2412.0	11.45
		6	2437.0	11.47
		11	2462.0	11.54



Band	Data Rate	CH	Frequency (MHz)	RF Conducted Output Power (dBm)
				Average
Draft 802.11n_HT20	7.20 M	1	2412.0	12.93
		6	2437.0	12.81
		11	2462.0	<b>13.12</b>
	14.40 M	1	2412.0	12.63
		6	2437.0	12.67
		11	2462.0	12.96
	21.70M	1	2412.0	12.48
		6	2437.0	12.45
		11	2462.0	12.61
	28.90 M	1	2412.0	12.36
		6	2437.0	12.38
		11	2462.0	12.36
	43.30 M	1	2412.0	11.98
		6	2437.0	12.03
		11	2462.0	12.21
	57.80 M	1	2412.0	11.76
		6	2437.0	11.63
		11	2462.0	11.92
	65.00 M	1	2412.0	11.64
		6	2437.0	11.53
		11	2462.0	11.61
	72.20 M	1	2412.0	11.53
		6	2437.0	11.53
		11	2462.0	11.62



## 5.4 Simultaneous Transmitting Evaluate

RF Conducted Power		
Band	dBm	W
CDMA Cellular Band	24.08	0.256
CDMA PCS Band	24.19	0.262
AWS Band	24.35	0.272
Wi-Fi 802.11b	18.17	0.066
Wi-Fi 802.11g	13.26	0.021
Wi-Fi 802.11n	13.12	0.021
Bluetooth	-4.60	0.00035

Antenna Distance	
Antenna Account	Distance (cm)
Bluetooth to WLAN	0
Bluetooth to CDMA(License)	7.5
WLAN to CDMA (License)	7.5

### BT and CDMA and WLAN simultaneously SAR Description

- (1) Antenna Distance
  - 1a. BT & CDMA 7.5 cm
  - 1b. BT & WLAN 0cm
- (2) CDMA/BT - with antenna separation distance greater than 5cm - BT power is less than 2Pref , then both stand alone for BT and simultaneous SAR of CDMA/BT is not required
- (3) WLAN/BT - with antenna separation is less than 2.5cm - WLAN SAR is less than 1.2W/kg , then simultaneous SAR is not required
- (4) Cellular/PCS/AWS Stand-alone SAR is required due to routine evaluation requirements.
- (5) CDMA/WLAN - Sum of SAR is less than 1.6W/kg  
 Body SAR :  $\sum \text{SAR} = 1.557 < \text{SAR limit: } 1.6\text{mW/g}$   
 Head SAR :  $\sum \text{SAR} = 1.546 < \text{SAR limit: } 1.6\text{mW/g}$   
 Therefore, the Simultaneous SAR is not required.
- (6) For WiFi hot spot mode, since the CDMA network will not support the DTM mode, therefore the 1xRTT(FCH+SCH) / 1xEVDO SAR of head is not required.
- (7) The WiFi protocol is not support VoIP function; therefore the SAR of head is not required.

Note:

1. Simultaneous Transmission Summation of SAR, please find the Table 8 as below.
  - 2a. For Edge Top mode, that license antenna to edge top >2.5cm, therefore the license Stand-alone SAR is not required.
  - 2b. For Edge Bottom mode, that Unlicensed antenna to edge Bottom >2.5cm, therefore the Unlicensed Stand-alone SAR is not required.



**Table 8.**

<b>Right-Cheek mode</b>					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Right-Cheek	1.110	0.148	1.258	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Right-Cheek	0.926	0.148	1.074	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Right-Cheek	0.778	0.148	0.926	<1.6

<b>Right-Tilted mode</b>					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Right-Tilted	0.593	0.178	0.771	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Right-Tilted	0.600	0.178	0.778	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Right-Tilted	0.481	0.178	0.659	<1.6

<b>Left-Cheek mode</b>					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Left-Cheek	1.370	0.176	1.546	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Left-Cheek	0.910	0.176	1.086	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Left-Cheek	1.360	0.176	1.536	<1.6



Left-Tilted mode					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Left-Tilted	0.560	0.199	0.759	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Left-Tilted	0.515	0.199	0.714	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Head SAR	Left-Tilted	0.414	0.199	0.613	<1.6

Back surface mode					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	1.110	0.257	1.367	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	1.300	0.257	1.557	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	1.020	0.257	1.277	<1.6

Front surface mode					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.698	0.054	0.752	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.634	0.054	0.688	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.737	0.054	0.791	<1.6



Edge Left mode					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.333	0.039	0.372	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.578	0.039	0.617	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.246	0.039	0.285	<1.6

Edge Right mode					
The sum of the 1-g SAR					
Simult Tx	Configuration	CDMA PCS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.221	0.042	0.263	<1.6
Simult Tx	Configuration	CDMA Cellular Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.530	0.042	0.572	<1.6
Simult Tx	Configuration	CDMA AWS Band SAR mW/g	WLAN SAR mW/g	$\Sigma$ SAR mW/g	$\Sigma$ SAR
Body SAR	Flat	0.192	0.042	0.234	<1.6

## 6. System Performance Check

### 6.1 Symmetric Dipoles for System Validation

Construction	Symmetrical dipole with 1/4 balun enables measurement of feed point impedance with NWA matched for use near flat phantoms filled with head simulating solutions Includes distance holder and tripod adaptor Calibration Calibrated SAR value for specified position and input power at the flat phantom in head simulating solutions.
Frequency	835, 1750, 1900, 2450 MHz
Return Loss	> 20 dB at specified validation position
Power Capability	> 100 W (f < 1GHz); > 40 W (f > 1GHz)
Options	Dipoles for other frequencies or solutions and other calibration conditions are available upon request
Dimensions	D835V2 : dipole length 150 mm; overall height 330 mm D1750V2 : dipole length 72 mm; overall height 300 mm D1900V2 : dipole length 62 mm; overall height 300 mm D2450V2 : dipole length 51.5 mm; overall height 300 mm




Figure 10. System Verification Setup Diagram

Figure 11. Validation Kit





## 6.2 Validation


Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm 7\%$ . The validation was performed at 835, 1750, 1900, 2450 MHz.

Validation kit		Mixture Type	SAR <sub>1g</sub> [mW/g]	SAR <sub>10g</sub> [mW/g]	Date of Calibration		
D835V2-SN4d082		Head	9.65	6.26	07/20/2010		
		Body	10.00	6.60			
D1750V2-SN1023		Head	36.20	19.20	05/24/2011		
		Body	41.90	22.50			
D1900V2-SN5d111		Head	39.90	21.00	07/16/2010		
		Body	41.90	22.50			
D2450V2-SN712		Head	52.90	24.50	02/23/2011		
Frequency (MHz)	Power (dBm)	SAR <sub>1g</sub> (mW/g)	SAR <sub>10g</sub> (mW/g)	Drift (dB)	Difference percentage		Date
					1g	10g	
835 (Head)	250mW	2.46	1.6	-0.003	2.0 %	2.2 %	07/10/2011
	Normalize to 1 Watt	9.84	6.4				
835 (Body)	250mW	2.44	1.58	0.012	-2.4 %	-4.2 %	07/07/2011
	Normalize to 1 Watt	9.76	6.32				
835 (Body)	250mW	2.44	1.59	0.012	-2.4 %	-3.6 %	07/11/2011
	Normalize to 1 Watt	9.76	6.36				
1750 (Head)	250mW	8.97	4.71	0.021	-0.9 %	-1.9 %	07/10/2011
	Normalize to 1 Watt	35.88	18.84				
1750 (Body)	250mW	9.26	4.93	-0.018	0.7 %	0.6 %	07/09/2011
	Normalize to 1 Watt	37.04	19.72				
1900 (Head)	250mW	10.3	5.44	-0.043	3.3 %	3.6 %	07/10/2011
	Normalize to 1 Watt	41.2	21.76				
1900 (Body)	250mW	10.4	5.44	0.013	-0.7 %	-3.3 %	07/08/2011
	Normalize to 1 Watt	41.6	21.76				
2450 (Head)	250mW	13.4	6.31	-0.046	1.3 %	3.0 %	07/19/2011
	Normalize to 1 Watt	53.6	25.24				




Validation kit		Mixture Type	SAR <sub>1g</sub> [mW/g]		SAR <sub>10g</sub> [mW/g]		Date of Calibration
D2450V2-SN712		Body	50.40		23.30		02/23/2011
Frequency (MHz)	Power (dBm)	SAR <sub>1g</sub> (mW/g)	SAR <sub>10g</sub> (mW/g)	Drift (dB)	Difference percentage		Date
					1g	10g	
2450 (Body)	250mW	12.4	5.85	-0.051	-1.6 %	0.4 %	07/09/2011
	Normalize to 1 Watt	49.6	23.4				

**Z-axis Plot of System Performance Check**




**Head-Tissue-Simulating-Liquid 835MHz**




**Body-Tissue-Simulating-Liquid 835MHz (07/07/2011)**

**Z-axis Plot of System Performance Check**




**Body-Tissue-Simulating-Liquid 835MHz (07/11/2011)**




**Head-Tissue-Simulating-Liquid 1750MHz**

**Z-axis Plot of System Performance Check**




**Body-Tissue-Simulating-Liquid 1750MHz**




**Head-Tissue-Simulating-Liquid 1900MHz**

**Z-axis Plot of System Performance Check**




**Body-Tissue-Simulating-Liquid 1900MHz**



**Head-Tissue-Simulating-Liquid 2450MHz**

Z-axis Plot of System Performance Check



Body-Tissue-Simulating-Liquid 2450MHz



## 7. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	Dosimetric E-Field Probe	ES3DV3	3150	01/19/2011	01/19/2012
SPEAG	Dosimetric E-Field Probe	EX3DV4	3632	01/19/2011	01/19/2012
SPEAG	835MHz System Validation Kit	D835V2	4d082	07/20/2010	07/20/2011
SPEAG	1750MHz System Validation Kit	D1750V2	1023	05/24/2011	05/24/2012
SPEAG	1900MHz System Validation Kit	D1900V2	5d111	07/16/2010	07/16/2011
SPEAG	2450MHz System Validation Kit	D2450V2	712	02/23/2011	02/23/2012
SPEAG	Data Acquisition Electronics	DAE4	779	01/31/2011	01/31/2012
SPEAG	Measurement Server	SE UMS 011 AA	1025	NCR	
SPEAG	Device Holder	N/A	N/A	NCR	
SPEAG	Phantom	SAM V4.0	TP-1150	NCR	
SPEAG	Robot	Staubli TX90XL	F07/564ZA1/C/01	NCR	
SPEAG	Software	DASY5 V5.0 Build 125	N/A	NCR	
SPEAG	Software	SEMCAD V13.4 Build 125	N/A	NCR	
Agilent	Dielectric Probe Kit	85070C	US99360094	NCR	
Agilent	ENA Series Network Analyzer	E5071B	MY42404655	04/14/2010	04/14/2012
R&S	Power Sensor	NRP-Z22	100179	05/27/2011	05/27/2012
Agilent	MXG Vector Signal Generator	N5182A	MY47420962	05/16/2011	05/16/2012
Agilent	Dual Directional Coupler	778D	50334	NCR	
Mini-Circuits	Power Amplifier	ZHL-42W-SMA	D111103#5	NCR	
Mini-Circuits	Power Amplifier	ZVE-8G-SMA	D042005 671800514	NCR	

**Table 9. Test Equipment List**





## 8. **Measurement Uncertainty**

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, we estimate the measurement uncertainties in SAR to be less than  $\pm 20.10\%$  [ 8 ] .

According to Std. C95.3 [ 9 ] , the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of  $\pm 1$  to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least  $\pm 2$ dB can be expected.

According to CENELEC [ 10 ] , typical worst-case uncertainty of field measurements is  $\pm 5$  dB. For well-defined modulation characteristics the uncertainty can be reduced to  $\pm 3$  dB.



Item	Uncertainty Component	Uncertainty Value	Prob. Dist	Div.	$c_i$ (1g)	$c_i$ (10g)	Std. Unc. (1-g)	Std. Unc. (10-g)	$v_i$ or $V_{eff}$
<b>Measurement System</b>									
u1	Probe Calibration ( $k=1$ )	±5.5%	Normal	1	1	1	±5.5%	±5.5%	∞
u2	Probe Isotropy	±7.6%	Rectangular	$\sqrt{3}$	0.7	0.7	±3.1%	±3.1%	∞
u3	Boundary Effect	±1.0%	Rectangular	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
u4	Linearity	±4.7%	Rectangular	$\sqrt{3}$	1	1	±2.7%	±2.7%	∞
u5	System Detection Limit	±1.0%	Rectangular	$\sqrt{3}$	1	1	±0.58%	±0.58%	∞
u6	Readout Electronics	±0.3%	Normal	1	1	1	±0.3%	±0.3%	∞
u7	Response Time	±0.8%	Rectangular	$\sqrt{3}$	1	1	±0.5%	±0.5%	∞
u8	Integration Time	±2.6%	Rectangular	$\sqrt{3}$	1	1	±1.5%	±1.5%	∞
u9	RF Ambient Conditions	±0%	Rectangular	$\sqrt{3}$	1	1	±0%	±0%	∞
u10	RF Ambient Reflections	±0%	Rectangular	$\sqrt{3}$	1	1	±0%	±0%	∞
u11	Probe Positioner Mechanical Tolerance	±0.4%	Rectangular	$\sqrt{3}$	1	1	±0.2%	±0.2%	∞
u12	Probe Positioning with respect to Phantom Shell	±2.9%	Rectangular	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
u13	Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	±1.0%	Rectangular	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
<b>Test sample Related</b>									
u14	Test sample Positioning	±3.6%	Normal	1	1	1	±3.6%	±3.6%	89
u15	Device Holder Uncertainty	±3.5%	Normal	1	1	1	±3.5%	±3.5%	5
u16	Output Power Variation - SAR drift measurement	±5.0%	Rectangular	$\sqrt{3}$	1	1	±2.9%	±2.9%	∞
<b>Phantom and Tissue Parameters</b>									
u17	Phantom Uncertainty ( shape and thickness tolerances)	±4.0%	Rectangular	$\sqrt{3}$	1	1	±2.3%	±2.3%	∞
u18	Liquid Conductivity - deviation from target values	±5.0%	Rectangular	$\sqrt{3}$	0.64	0.43	±1.8%	±1.2%	∞
u19	Liquid Conductivity - measurement uncertainty	±1.93%	Normal	1	0.64	0.43	±1.24%	±0.83%	69
u20	Liquid Permittivity - deviation from target values	±5.0%	Rectangular	$\sqrt{3}$	0.6	0.49	±1.7%	±1.4%	∞
u21	Liquid Permittivity - measurement uncertainty	±1.4%	Normal	1	0.6	0.49	±0.84%	±1.69%	69
<b>Combined standard uncertainty</b>			RSS				±10.05%	±9.98%	313
<b>Expanded uncertainty (95% CONFIDENCE LEVEL )</b>			$k=2$				±20.10%	±19.96%	

Table 10. Uncertainty Budget of DASY



## 9. Measurement Procedure

The measurement procedures are as follows:

1. For WLAN function, engineering testing software installed on Notebook can provide continuous transmitting signal.
2. Measure output power through RF cable and power meter
3. Set scan area, grid size and other setting on the DASY software
4. Find out the largest SAR result on these testing positions of each band
5. Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

1. Power reference measurement
2. Area scan
3. Zoom scan
4. Power drift measurement

### 9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages

1. Extraction of the measured data (grid and values) from the Zoom Scan
2. Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. Generation of a high-resolution mesh within the measured volume
4. Interpolation of all measured values from the measurement grid to the high-resolution grid
5. Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. Calculation of the averaged SAR within masses of 1g and 10g



## 9.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 7x7x9 points with step size 5, 5 and 3 mm for 300 MHz to 3 GHz, and 7x7x9 points with step size 5, 5 and 3 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

## 9.3 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the DUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

## 9.4 SAR Averaged Methods

In DASYS, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 9.5 Power Drift Monitoring

All SAR testing is under the DUT install full charged battery and transmit maximum output power. In DASYS measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of DUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.



## 10. SAR Test Results Summary

### 10.1 Head SAR

Measurement Results								
Band	Frequency		Power (dBm)	Phantom Position	Spacing (mm)	SAR <sub>1g</sub> [mW/g]	Power Drift (dB)	Remark
	CH	MHz						
CDMA Cellular Band	1013	824.70	23.66	Right-cheek	0	0.929	-0.107	---
	384	836.52	24.08	Right-cheek	0	0.843	0.074	---
	777	848.31	23.75	Right-cheek	0	0.918	-0.085	---
	384	836.52	24.08	Right-Tilted	0	0.600	-0.011	---
	1013	824.70	23.66	Left-cheek	0	0.910	-0.017	---
	384	836.52	24.08	Left-cheek	0	0.828	0.026	---
	777	848.31	23.75	Left-cheek	0	0.870	0.004	---
	384	836.52	24.08	Left-Tilted	0	0.515	-0.059	---
CDMA PCS Band	25	1851.25	23.86	Right-cheek	0	0.952	-0.001	---
	600	1880.00	23.78	Right-cheek	0	1.110	-0.131	---
	1175	1908.75	24.19	Right-cheek	0	0.988	-0.199	---
	1175	1908.75	24.19	Right-Tilted	0	0.593	-0.047	---
	25	1851.25	23.86	Left-cheek	0	1.270	-0.003	---
	600	1880.00	23.78	Left-cheek	0	<b>1.370</b>	-0.046	---
	1175	1908.75	24.19	Left-cheek	0	1.330	0.031	---
	1175	1908.75	24.19	Left-Tilted	0	0.560	0.063	---
CDMA AWS Band	450	1732.50	24.35	Right-cheek	0	0.778	-0.063	---
	450	1732.50	24.35	Right-Tilted	0	0.481	0.176	---
	25	1711.25	23.82	Left-cheek	0	1.360	0.172	---
	450	1732.50	24.35	Left-cheek	0	1.300	0.007	---
	875	1753.75	23.70	Left-cheek	0	1.320	0.128	---
	450	1732.50	24.35	Left-Tilted	0	0.414	0.016	---
IEEE 802.11b Rate 5.5M	11	2462	18.17	Right-cheek	0	0.148	-0.05	---
	11	2462	18.17	Right-Tilted	0	0.178	0.047	---
	11	2462	18.17	Left-cheek	0	0.176	0.043	---
	11	2462	18.17	Left-Tilted	0	0.199	0.095	---
Std. C95.1-1999 - Safety Limit Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1 gram			



## 10.2 Body SAR

Measurement Results									
Band	Frequency		Power (dBm)	Phantom Position	Spacing (mm)	Accessory	SAR <sub>1g</sub> [mW/g]	Power Drift (dB)	Remark
	CH	MHz							
CDMA Cellular Band	384	836.52	24.08	Flat	15	Headset	0.299	0.048	Front Surface to Phantom
	384	836.52	24.08	Flat	15	Headset	0.540	-0.096	Back Surface to Phantom
CDMA PCS Band	1175	1908.75	24.19	Flat	15	Headset	0.414	0.088	Front Surface to Phantom
	1175	1908.75	24.19	Flat	15	Headset	0.585	0.035	Back Surface to Phantom
CDMA AWS Band	450	1732.50	24.35	Flat	15	Headset	0.377	-0.053	Front Surface to Phantom
	450	1732.50	24.35	Flat	15	Headset	0.467	-0.115	Back Surface to Phantom
CDMA Cellular Band	1013	824.70	23.66	Flat	10	N/A	<b>1.300</b>	-0.031	Back Surface to Phantom
	384	836.52	24.08	Flat	10	N/A	0.634	-0.011	Front Surface to Phantom
	384	836.52	24.08	Flat	10	N/A	1.090	-0.060	Back Surface to Phantom
	384	836.52	24.08	Flat	10	N/A	0.578	-0.085	Edge Left to Phantom
	384	836.52	24.08	Flat	10	N/A	0.530	-0.148	Edge Right to Phantom
	384	836.52	24.08	Flat	10	N/A	0.085	0.080	Edge Bottom to Phantom
	777	848.31	23.75	Flat	10	N/A	0.885	0.030	Back Surface to Phantom
CDMA PCS Band	25	1851.25	23.86	Flat	10	N/A	1.020	-0.031	Back Surface to Phantom
	600	1880.00	23.78	Flat	10	N/A	1.110	0.010	Back Surface to Phantom
	1175	1908.75	24.19	Flat	10	N/A	0.698	0.090	Front Surface to Phantom
	1175	1908.75	24.19	Flat	10	N/A	1.090	-0.081	Back Surface to Phantom
	1175	1908.75	24.19	Flat	10	N/A	0.333	0.022	Edge Left to Phantom
	1175	1908.75	24.19	Flat	10	N/A	0.221	-0.047	Edge Right to Phantom
	1175	1908.75	24.19	Flat	10	N/A	0.635	0.099	Edge Bottom to Phantom
Std. C95.1-1999 - Safety Limit Spatial Peak Uncontrolled Exposure/General Population						1.6 W/kg (mW/g) Averaged over 1 gram			



Measurement Results									
Band	Frequency		Power (dBm)	Phantom Position	Spacing (mm)	Accessory	SAR <sub>1g</sub> [mW/g]	Power Drift (dB)	Remark
	CH	MHz							
CDMA AWS Band	25	1711.25	23.82	Flat	10	N/A	1.020	-0.139	Back Surface to Phantom
	450	1732.50	24.35	Flat	10	N/A	0.737	-0.080	Front Surface to Phantom
	450	1732.50	24.35	Flat	10	N/A	0.943	0.047	Back Surface to Phantom
	450	1732.50	24.35	Flat	10	N/A	0.246	-0.079	Edge Left to Phantom
	450	1732.50	24.35	Flat	10	N/A	0.192	0.028	Edge Right to Phantom
	450	1732.50	24.35	Flat	10	N/A	0.483	0.073	Edge Bottom to Phantom
	875	1753.75	23.70	Flat	10	N/A	0.851	0.125	Back Surface to Phantom
IEEE 802.11b Rate 5.5M	11	2462	18.17	Flat	10	N/A	0.054	-0.121	Front Surface to Phantom
	11	2462	18.17	Flat	10	N/A	0.257	-0.043	Back Surface to Phantom
	11	2462	18.17	Flat	10	N/A	0.039	-0.142	Edge Left to Phantom
	11	2462	18.17	Flat	10	N/A	0.042	0.077	Edge Right to Phantom
	11	2462	18.17	Flat	10	N/A	0.194	0.055	Edge Bottom to Phantom
Std. C95.1-1999 - Safety Limit Spatial Peak Uncontrolled Exposure/General Population						1.6 W/kg (mW/g) Averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001], IEEE1528-2003 and RSS-102.
2. All modes of operation were investigated, and worst-case results are reported.
3. Tissue parameters and temperatures are listed on the SAR plots.
4. Batteries are fully charged for all readings.
5. Base on power table (section 5.3), the worst case is 802.11b CH11 rate 5.5M and therefore the test sample was investigated on this configuration.
6. If the conducted power of 802.11g and 802.11n are higher 0.25dB than 802.11b, 802.11g and 802.11n are supposed to be tested. Base on power table (section 5.3), the 802.11g and 802.11n were not required.
7. If the Channel's SAR 1g of maximum conducted power is > 0.8 mW/g, low, middle and high channel are supposed to be tested.
8. In Hot-spot mode, the antenna location to edge >5 cm, therefore for WWAN antenna in edge top is not required.
9. In Hot-spot mode, the antenna location to edge >5 cm, therefore for WLAN antenna in edge bottom is not required.



### 10.3 Std. C95.1-1999 RF Exposure Limit

Human Exposure	Population Uncontrolled Exposure ( W/kg ) or (mW/g)	Occupational Controlled Exposure ( W/kg ) or (mW/g)
Spatial Peak SAR* (head)	1.60	8.00
Spatial Peak SAR** (Whole Body)	0.08	0.40
Spatial Peak SAR*** (Partial-Body)	1.60	8.00
Spatial Peak SAR**** (Hands / Feet / Ankle / Wrist )	4.00	20.00

**Table 11. Safety Limits for Partial Body Exposure**

**Notes :**

- \* The Spatial Peak value of the SAR averaged over any 1 gram of tissue.  
( defined as a tissue volume in the shape of a cube ) and over the appropriate averaging time.
- \*\* The Spatial Average value of the SAR averaged over the whole – body.
- \*\*\* The Spatial Average value of the SAR averaged over the partial – body.
- \*\*\*\* The Spatial Peak value of the SAR averaged over any 10 grams of tissue.  
( defined as a tissue volume in the shape of a cube ) and over the appropriate averaging time.

**Population / Uncontrolled Environments :** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Occupational / Controlled Environments :** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).





## 11. Conclusion

The SAR test values found for the portable mobile phone **HTC Corporation Trade Name : HTC Model(s) : PG76210** is below the maximum recommended level of 1.6 W/kg (mW/g).

## 12. References

- [1] Std. C95.1-1999, "American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300KHz to 100GHz", New York.
- [2] NCRP, National Council on Radiation Protection and Measurements, "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields", NCRP report NO. 86, 1986.
- [3] T. Schmid, O. Egger, and N. Kuster, "Automatic E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp, 105-113, Jan. 1996.
- [4] K. Poković, T. Schmid, and N. Kuster, "Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequency", in ICECOM'97, Dubrovnik, October 15-17, 1997, pp.120-124.
- [5] K. Poković, T. Schmid, and N. Kuster, "E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23-25 June, 1996, pp.172-175.
- [6] N. Kuster, and Q. Balzano, "Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz", IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [7] Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988 , pp. 139-148.
- [8] N. Kuster, R. Kastle, T. Schmid, "Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [9] Std. C95.3-1991, "IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave, New York: IEEE, Aug. 1992.
- [10] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), *Human Exposure to Electromagnetic Fields High-frequency: 10KHz-300GHz*, Jan. 1995.
- [11] KDB248227 D01 SAR meas for 802 11 a b g v01r02.
- [12] KDB 648474 D01 SAR Handsets Multi Xmitter and Ant v01r05
- [13] KDB 941225 D01 SAR Test for 3G Devices 3G-SAR
- [14] KDB 941225 D03 SAR Test Reduction GSM GPRS EDGE
- [15] KDB 941225 D04 SAR for GSM E GPRS Dual Xfer Mode v01
- [16] KDB 941225 D06 Hot Spot SAR v01



## Appendix A - System Performance Check

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 5:30:18 PM

### System Performance Check at 835MHz\_20110710\_Head

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d082**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.904 \text{ mho/m}$ ;  $\epsilon_r = 41.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

### System Performance Check at 835MHz/Area Scan (61x121x1):

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 2.87 mW/g

### System Performance Check at 835MHz/Zoom Scan (7x7x7)/Cube 0:


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 57.7 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 3.7 W/kg

**SAR(1 g) = 2.46 mW/g; SAR(10 g) = 1.6 mW/g**

Maximum value of SAR (measured) = 2.88 mW/g



0 dB = 2.88mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/7/2011 9:54:17 PM

**System Performance Check at 835MHz\_20110707\_Body**

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d082**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.98 \text{ mho/m}$ ;  $\epsilon_r = 54.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 835MHz/Area Scan (61x121x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 2.85 mW/g

**System Performance Check at 835MHz/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 55.1 V/m; Power Drift = 0.016 dB  
 Peak SAR (extrapolated) = 3.62 W/kg  
**SAR(1 g) = 2.44 mW/g; SAR(10 g) = 1.58 mW/g**  
 Maximum value of SAR (measured) = 2.85 mW/g



0 dB = 2.85mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/11/2011 1:27:14 AM

**System Performance Check at 835MHz\_20110711\_Body**

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d082**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.98 \text{ mho/m}$ ;  $\epsilon_r = 54.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 835MHz/Area Scan (61x121x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 2.86 mW/g

**System Performance Check at 835MHz/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 55.4 V/m; Power Drift = 0.012 dB  
 Peak SAR (extrapolated) = 3.63 W/kg  
**SAR(1 g) = 2.44 mW/g; SAR(10 g) = 1.59 mW/g**  
 Maximum value of SAR (measured) = 2.86 mW/g



0 dB = 2.86mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 1:37:56 AM

**System Performance Check at 1750MHz\_20110710\_Head**

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN:1023**

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1750 \text{ MHz}$ ;  $\sigma = 1.4 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.28, 5.28, 5.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 1750MHz/Area Scan (61x61x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 11.5 mW/g

**System Performance Check at 1750MHz/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 92.9 V/m; Power Drift = 0.021 dB  
 Peak SAR (extrapolated) = 16.3 W/kg  
**SAR(1 g) = 8.97 mW/g; SAR(10 g) = 4.71 mW/g**  
 Maximum value of SAR (measured) = 11.4 mW/g



0 dB = 11.4mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 7:42:10 AM

**System Performance Check at 1750MHz\_20110709\_Body**

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN:1023**

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1750 \text{ MHz}$ ;  $\sigma = 1.52 \text{ mho/m}$ ;  $\epsilon_r = 53$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 1750MHz/Area Scan (61x61x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 11.8 mW/g

**System Performance Check at 1750MHz/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 91.9 V/m; Power Drift = -0.018 dB  
 Peak SAR (extrapolated) = 16 W/kg  
**SAR(1 g) = 9.26 mW/g; SAR(10 g) = 4.93 mW/g**  
 Maximum value of SAR (measured) = 11.7 mW/g



0 dB = 11.7mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 10:12:17 AM

**System Performance Check at 1900MHz\_201107010\_Head**

**DUT: Dipole D1900V2\_SN5d111; Type: D1900V2; Serial: D1900V2 - SN:5d111**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.37 \text{ mho/m}$ ;  $\epsilon_r = 38.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 1900MHz/Area Scan (61x61x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 13.2 mW/g

**System Performance Check at 1900MHz/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 101.3 V/m; Power Drift = -0.043 dB  
 Peak SAR (extrapolated) = 18.5 W/kg  
**SAR(1 g) = 10.3 mW/g; SAR(10 g) = 5.44 mW/g**  
 Maximum value of SAR (measured) = 13.1 mW/g



0 dB = 13.1mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 6:46:10 AM

**System Performance Check at 1900MHz\_20110708\_Body**

**DUT: Dipole D1900V2\_SN5d111; Type: D1900V2; Serial: D1900V2 - SN:5d111**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.5 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 1900MHz/Area Scan (61x61x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 13.1 mW/g

**System Performance Check at 1900MHz/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 97.7 V/m; Power Drift = 0.013 dB  
 Peak SAR (extrapolated) = 18.2 W/kg  
**SAR(1 g) = 10.4 mW/g; SAR(10 g) = 5.44 mW/g**  
 Maximum value of SAR (measured) = 13.2 mW/g



0 dB = 13.2mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/19/2011 11:37:26 AM

**System Performance Check at 2450MHz\_20110719\_Head**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:712**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.8 \text{ mho/m}$ ;  $\epsilon_r = 39.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.28, 7.28, 7.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 2450MHz/Area Scan (61x61x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 17.9 mW/g

**System Performance Check at 2450MHz/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 99 V/m; Power Drift = -0.046 dB  
 Peak SAR (extrapolated) = 27.1 W/kg  
**SAR(1 g) = 13.4 mW/g; SAR(10 g) = 6.31 mW/g**  
 Maximum value of SAR (measured) = 17.7 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 9:24:30 AM

**System Performance Check at 2450MHz\_20110709\_Body**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:712**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.94 \text{ mho/m}$ ;  $\epsilon_r = 51.7$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.23, 7.23, 7.23); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**System Performance Check at 2450MHz/Area Scan (61x61x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 16.6 mW/g

**System Performance Check at 2450MHz/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 92.6 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 24.4 W/kg

**SAR(1 g) = 12.4 mW/g; SAR(10 g) = 5.85 mW/g**

Maximum value of SAR (measured) = 16.3 mW/g



0 dB = 16.3mW/g



## Appendix B - SAR Measurement Data

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 7:51:00 PM

**RC\_CDMA Cellular CH1013**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 824.7 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.895$  mho/m;  $\epsilon_r = 41.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Right Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (91x151x1):**

Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.976 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 15.4 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.929 mW/g; SAR(10 g) = 0.710 mW/g**

Maximum value of SAR (measured) = 1.02 mW/g



0 dB = 1.02mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 7:16:05 PM

**RC\_CDMA Cellular CH384**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.906 \text{ mho/m}$ ;  $\epsilon_r = 41.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (91x151x1):**

Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (interpolated) = 0.916 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 14.3 V/m; Power Drift = 0.074 dB  
 Peak SAR (extrapolated) = 1.04 W/kg  
**SAR(1 g) = 0.843 mW/g; SAR(10 g) = 0.641 mW/g**  
 Maximum value of SAR (measured) = 0.905 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 8:55:20 PM

**RC\_CDMA Cellular CH777**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 848.31 MHz;Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 848.31 \text{ MHz}$ ;  $\sigma = 0.917 \text{ mho/m}$ ;  $\epsilon_r = 41$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (91x151x1):**

Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (interpolated) = 1.01 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 15.1 V/m; Power Drift = -0.085 dB  
 Peak SAR (extrapolated) = 1.17 W/kg  
**SAR(1 g) = 0.918 mW/g; SAR(10 g) = 0.700 mW/g**  
 Maximum value of SAR (measured) = 1.02 mW/g



0 dB = 1.02mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 9:30:13 PM

**RT\_CDMA Cellular CH384**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.906 \text{ mho/m}$ ;  $\epsilon_r = 41.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Right Tilted/Area Scan (61x101x1):**


Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.659 mW/g

**Right Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 24.1 V/m; Power Drift = -0.011 dB  
 Peak SAR (extrapolated) = 0.772 W/kg  
**SAR(1 g) = 0.600 mW/g; SAR(10 g) = 0.453 mW/g**  
 Maximum value of SAR (measured) = 0.669 mW/g

**Right Tilted/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 24.1 V/m; Power Drift = -0.011 dB  
 Peak SAR (extrapolated) = 1.19 W/kg  
**SAR(1 g) = 0.514 mW/g; SAR(10 g) = 0.321 mW/g**  
 Maximum value of SAR (measured) = 0.630 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 11:10:47 PM

**LC\_CDMA Cellular CH1013**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 824.7 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 0.895 \text{ mho/m}$ ;  $\epsilon_r = 41.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.01 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$

Reference Value = 13.4 V/m; Power Drift = -0.017 dB

Peak SAR (extrapolated) = 1.12 W/kg

**SAR(1 g) = 0.910 mW/g; SAR(10 g) = 0.679 mW/g**

Maximum value of SAR (measured) = 1.04 mW/g



0 dB = 1.04mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 10:16:27 PM

**LC\_CDMA Cellular CH384**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.906 \text{ mho/m}$ ;  $\epsilon_r = 41.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.955 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 12.7 V/m; Power Drift = 0.026 dB  
 Peak SAR (extrapolated) = 1.08 W/kg  
**SAR(1 g) = 0.828 mW/g; SAR(10 g) = 0.616 mW/g**  
 Maximum value of SAR (measured) = 0.914 mW/g





Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 10:45:42 PM

**LC\_CDMA Cellular CH777**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 848.31 MHz;Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 848.31 \text{ MHz}$ ;  $\sigma = 0.917 \text{ mho/m}$ ;  $\epsilon_r = 41$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.944 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 12.9 V/m; Power Drift = 0.00352 dB  
 Peak SAR (extrapolated) = 1.14 W/kg  
**SAR(1 g) = 0.870 mW/g; SAR(10 g) = 0.669 mW/g**  
 Maximum value of SAR (measured) = 0.951 mW/g



0 dB = 0.951mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 11:42:20 PM

**LT\_CDMA Cellular CH384**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.906 \text{ mho/m}$ ;  $\epsilon_r = 41.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.15, 6.15, 6.15); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Left Tilted/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.570 mW/g

**Left Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 21.1 V/m; Power Drift = -0.059 dB  
 Peak SAR (extrapolated) = 0.680 W/kg  
**SAR(1 g) = 0.515 mW/g; SAR(10 g) = 0.389 mW/g**  
 Maximum value of SAR (measured) = 0.572 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 12:48:35 PM

**RC\_CDMA PCS CH 25**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1851.25 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1851.25 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (61x101x1):**


Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.14 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 14.7 V/m; Power Drift = -0.00128 dB  
 Peak SAR (extrapolated) = 1.3 W/kg  
**SAR(1 g) = 0.952 mW/g; SAR(10 g) = 0.629 mW/g**  
 Maximum value of SAR (measured) = 1.11 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 14.7 V/m; Power Drift = -0.00128 dB  
 Peak SAR (extrapolated) = 1.32 W/kg  
**SAR(1 g) = 0.915 mW/g; SAR(10 g) = 0.559 mW/g**  
 Maximum value of SAR (measured) = 1.07 mW/g



0 dB = 1.07mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 1:44:02 PM

**RC\_CDMA PCS CH 600**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1880 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.36 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (61x101x1):**


Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.37 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 15.5 V/m; Power Drift = -0.131 dB  
 Peak SAR (extrapolated) = 1.56 W/kg  
**SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.716 mW/g**  
 Maximum value of SAR (measured) = 1.32 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 15.5 V/m; Power Drift = -0.131 dB  
 Peak SAR (extrapolated) = 1.5 W/kg  
**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.614 mW/g**  
 Maximum value of SAR (measured) = 1.23 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 12:07:43 PM

**RC\_CDMA PCS CH 1175**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (61x101x1):**


Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 1.18 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 14.4 V/m; Power Drift = -0.199 dB  
 Peak SAR (extrapolated) = 1.45 W/kg  
**SAR(1 g) = 0.988 mW/g; SAR(10 g) = 0.637 mW/g**  
 Maximum value of SAR (measured) = 1.16 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 14.4 V/m; Power Drift = -0.199 dB  
 Peak SAR (extrapolated) = 1.44 W/kg  
**SAR(1 g) = 0.979 mW/g; SAR(10 g) = 0.572 mW/g**  
 Maximum value of SAR (measured) = 1.18 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 2:53:24 PM

**RT\_CDMA PCS CH 1175**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1909$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Right Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Tilted/Area Scan (61x101x1):**

Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.692 mW/g

**Right Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 22.7 V/m; Power Drift = -0.047 dB  
Peak SAR (extrapolated) = 1 W/kg  
**SAR(1 g) = 0.593 mW/g; SAR(10 g) = 0.322 mW/g**  
Maximum value of SAR (measured) = 0.732 mW/g





Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 11:10:15 AM

**LC\_CDMA PCS CH 25**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1851.25 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1851.25 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.5 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 13.5 V/m; Power Drift = -0.00321 dB  
 Peak SAR (extrapolated) = 1.93 W/kg  
**SAR(1 g) = 1.27 mW/g; SAR(10 g) = 0.768 mW/g**  
 Maximum value of SAR (measured) = 1.54 mW/g



0 dB = 1.54mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 4:07:34 PM

**LC\_CDMA PCS CH 600**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1880 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.36 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**


Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.67 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 16.4 V/m; Power Drift = -0.046 dB  
 Peak SAR (extrapolated) = 2 W/kg  
**SAR(1 g) = 1.37 mW/g; SAR(10 g) = 0.835 mW/g**  
 Maximum value of SAR (measured) = 1.62 mW/g







Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 10:43:33 AM

**LC\_CDMA PCS CH 1175**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 38.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.69 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 14.4 V/m; Power Drift = 0.031 dB  
 Peak SAR (extrapolated) = 2.05 W/kg  
**SAR(1 g) = 1.33 mW/g; SAR(10 g) = 0.794 mW/g**  
 Maximum value of SAR (measured) = 1.61 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 3:21:20 PM

**LT\_CDMA PCS CH 1175**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.18, 5.18, 5.18); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Tilted/Area Scan (61x101x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.677 mW/g

**Left Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 22.2 V/m; Power Drift = 0.063 dB  
 Peak SAR (extrapolated) = 0.934 W/kg  
**SAR(1 g) = 0.560 mW/g; SAR(10 g) = 0.305 mW/g**  
 Maximum value of SAR (measured) = 0.698 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 2:12:49 AM

**RC\_CDMA AWS CH 450**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.28, 5.28, 5.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (61x91x1):**


Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.927 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 14.4 V/m; Power Drift = -0.063 dB  
 Peak SAR (extrapolated) = 1.11 W/kg  
**SAR(1 g) = 0.778 mW/g; SAR(10 g) = 0.505 mW/g**  
 Maximum value of SAR (measured) = 0.903 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 14.4 V/m; Power Drift = -0.063 dB  
 Peak SAR (extrapolated) = 1.06 W/kg  
**SAR(1 g) = 0.723 mW/g; SAR(10 g) = 0.448 mW/g**  
 Maximum value of SAR (measured) = 0.868 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 7:22:53 AM

**RT\_CDMA AWS CH 450**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.39 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.28, 5.28, 5.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Tilted/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.569 mW/g

**Right Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 21.4 V/m; Power Drift = 0.176 dB  
 Peak SAR (extrapolated) = 0.789 W/kg  
**SAR(1 g) = 0.481 mW/g; SAR(10 g) = 0.264 mW/g**  
 Maximum value of SAR (measured) = 0.598 mW/g



0 dB = 0.598mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 8:21:12 AM

**LC\_CDMA AWS CH 25**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1711.25 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1711.25 \text{ MHz}$ ;  $\sigma = 1.37 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.28, 5.28, 5.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.63 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$

Reference Value = 11.9 V/m; Power Drift = 0.172 dB

Peak SAR (extrapolated) = 2.13 W/kg

**SAR(1 g) = 1.36 mW/g; SAR(10 g) = 0.793 mW/g**

Maximum value of SAR (measured) = 1.65 mW/g



0 dB = 1.65mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 7:50:17 AM

**LC\_CDMA AWS CH 450**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.39 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.28, 5.28, 5.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.54 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$

Reference Value = 12.9 V/m; Power Drift = 0.00683 dB

Peak SAR (extrapolated) = 2.09 W/kg

**SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.762 mW/g**

Maximum value of SAR (measured) = 1.57 mW/g



0 dB = 1.57mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 8:45:52 AM

**LC\_CDMA AWS CH 875**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1753.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1754 \text{ MHz}$ ;  $\sigma = 1.41 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.28, 5.28, 5.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.54 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$

Reference Value = 11.5 V/m; Power Drift = 0.128 dB

Peak SAR (extrapolated) = 2.15 W/kg

**SAR(1 g) = 1.32 mW/g; SAR(10 g) = 0.760 mW/g**

Maximum value of SAR (measured) = 1.62 mW/g



0 dB = 1.62mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/10/2011 9:14:13 AM

**LT\_CDMA AWS CH 450**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.39 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5.28, 5.28, 5.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Tilted/Area Scan (61x101x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.525 mW/g

**Left Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 20 V/m; Power Drift = 0.016 dB  
 Peak SAR (extrapolated) = 0.648 W/kg  
**SAR(1 g) = 0.414 mW/g; SAR(10 g) = 0.228 mW/g**  
 Maximum value of SAR (measured) = 0.513 mW/g



0 dB = 0.513mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/19/2011 12:00:39 PM

**RC\_802.11b CH11\_5.5M**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.82 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.28, 7.28, 7.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Cheek/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.179 mW/g

**Right Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 10.2 V/m; Power Drift = -0.050 dB  
 Peak SAR (extrapolated) = 0.310 W/kg  
**SAR(1 g) = 0.148 mW/g; SAR(10 g) = 0.073 mW/g**  
 Maximum value of SAR (measured) = 0.193 mW/g



0 dB = 0.193mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/19/2011 12:25:18 PM

**RT\_802.11b CH11\_5.5M**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.82 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section  
 Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.28, 7.28, 7.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Right Tilted/Area Scan (61x111x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.227 mW/g

**Right Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 10.7 V/m; Power Drift = 0.047 dB  
 Peak SAR (extrapolated) = 0.372 W/kg  
**SAR(1 g) = 0.178 mW/g; SAR(10 g) = 0.087 mW/g**  
 Maximum value of SAR (measured) = 0.225 mW/g



0 dB = 0.225mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/19/2011 1:03:16 PM

**LC\_802.11b CH11\_5.5M**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.82 \text{ mho/m}$ ;  $\epsilon_r = 39.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.28, 7.28, 7.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Cheek/Area Scan (61x111x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.246 mW/g

**Left Cheek/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
Reference Value = 9.72 V/m; Power Drift = 0.043 dB  
Peak SAR (extrapolated) = 0.374 W/kg  
**SAR(1 g) = 0.176 mW/g; SAR(10 g) = 0.087 mW/g**  
Maximum value of SAR (measured) = 0.226 mW/g





Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/19/2011 1:32:06 PM

**LT\_802.11b CH11\_5.5M**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.82$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.28, 7.28, 7.28); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Left Tilted/Area Scan (61x111x1):**

Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.280 mW/g

**Left Tilted/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 9.18 V/m; Power Drift = 0.095 dB  
Peak SAR (extrapolated) = 0.436 W/kg  
**SAR(1 g) = 0.199 mW/g; SAR(10 g) = 0.092 mW/g**  
Maximum value of SAR (measured) = 0.265 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/11/2011 2:37:23 AM

**Flat\_CDMA Cellular CH384\_Headset\_Front Surface to Phantom\_15mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 54.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.324 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 15.7 V/m; Power Drift = 0.048 dB  
 Peak SAR (extrapolated) = 0.384 W/kg  
**SAR(1 g) = 0.299 mW/g; SAR(10 g) = 0.220 mW/g**  
 Maximum value of SAR (measured) = 0.334 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/11/2011 3:05:39 AM

**Flat\_CDMA Cellular CH384\_Headset\_Back Surface to Phantom\_15mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 54.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.636 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 20.9 V/m; Power Drift = -0.096 dB  
 Peak SAR (extrapolated) = 0.791 W/kg  
**SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.365 mW/g**  
 Maximum value of SAR (measured) = 0.627 mW/g





Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 2:43:31 AM

**Flat\_CDMA PCS CH 1175\_Headset\_Front Surface to Phantom\_15mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.470 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 14.5 V/m; Power Drift = 0.088 dB  
 Peak SAR (extrapolated) = 0.591 W/kg  
**SAR(1 g) = 0.414 mW/g; SAR(10 g) = 0.253 mW/g**  
 Maximum value of SAR (measured) = 0.496 mW/g



0 dB = 0.496mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 3:12:27 AM

**Flat\_CDMA PCS CH 1175\_Headset\_Back Surface to Phantom\_15mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.703 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 14.4 V/m; Power Drift = 0.035 dB  
 Peak SAR (extrapolated) = 0.867 W/kg  
**SAR(1 g) = 0.585 mW/g; SAR(10 g) = 0.348 mW/g**  
 Maximum value of SAR (measured) = 0.717 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 6:54:24 PM

**Flat\_CDMA AWS CH450\_Headset\_Front Surface to Phantom\_15mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 53$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (91x161x1):**

Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (interpolated) = 0.442 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 16.5 V/m; Power Drift = -0.053 dB  
 Peak SAR (extrapolated) = 0.540 W/kg  
**SAR(1 g) = 0.377 mW/g; SAR(10 g) = 0.245 mW/g**  
 Maximum value of SAR (measured) = 0.449 mW/g



0 dB = 0.449mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 5:30:26 PM

**Flat\_CDMA AWS CH450\_Headset\_Back Surface to Phantom\_15mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**


Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.588 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 16.9 V/m; Power Drift = -0.115 dB  
 Peak SAR (extrapolated) = 0.694 W/kg  
**SAR(1 g) = 0.467 mW/g; SAR(10 g) = 0.288 mW/g**  
 Maximum value of SAR (measured) = 0.556 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 16.9 V/m; Power Drift = -0.115 dB  
 Peak SAR (extrapolated) = 0.646 W/kg  
**SAR(1 g) = 0.433 mW/g; SAR(10 g) = 0.273 mW/g**  
 Maximum value of SAR (measured) = 0.522 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 3:17:05 AM

**Flat\_CDMA Cell CH 1013\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA Cellular ; Frequency: 824.7 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 0.949 \text{ mho/m}$ ;  $\epsilon_r = 53.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125


**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.41 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 34.1 V/m; Power Drift = -0.031 dB  
 Peak SAR (extrapolated) = 1.93 W/kg  
**SAR(1 g) = 1.30 mW/g; SAR(10 g) = 0.832 mW/g**  
 Maximum value of SAR (measured) = 1.48 mW/g





Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 3:43:39 AM

**Flat\_CDMA Cell CH 384\_Front Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.692 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 24.9 V/m; Power Drift = -0.011 dB  
 Peak SAR (extrapolated) = 0.800 W/kg  
**SAR(1 g) = 0.634 mW/g; SAR(10 g) = 0.484 mW/g**  
 Maximum value of SAR (measured) = 0.701 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 2:23:42 AM

**Flat\_CDMA Cell CH 384\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.23 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 31.3 V/m; Power Drift = -0.060 dB  
 Peak SAR (extrapolated) = 1.73 W/kg  
**SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.729 mW/g**  
 Maximum value of SAR (measured) = 1.28 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 4:13:23 AM

**Flat\_CDMA Cell CH 384\_Edge Left to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.673 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 26.3 V/m; Power Drift = -0.085 dB  
 Peak SAR (extrapolated) = 0.849 W/kg  
**SAR(1 g) = 0.578 mW/g; SAR(10 g) = 0.381 mW/g**  
 Maximum value of SAR (measured) = 0.669 mW/g





Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 4:39:54 AM

**Flat\_CDMA Cell CH 384\_Edge Right to Phantom\_10mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.573 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 24.5 V/m; Power Drift = -0.148 dB  
 Peak SAR (extrapolated) = 0.801 W/kg  
**SAR(1 g) = 0.530 mW/g; SAR(10 g) = 0.357 mW/g**  
 Maximum value of SAR (measured) = 0.623 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 5:06:33 AM

**Flat\_CDMA Cell CH 384\_Edge Bottom to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 836.52 MHz;Duty Cycle: 1:1  
Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.96$  mho/m;  $\epsilon_r = 53.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.096 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 10.1 V/m; Power Drift = 0.080 dB  
Peak SAR (extrapolated) = 0.217 W/kg  
**SAR(1 g) = 0.085 mW/g; SAR(10 g) = 0.047 mW/g**  
Maximum value of SAR (measured) = 0.101 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 2:48:16 AM

**Flat\_CDMA Cell CH 777\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA Cellular ; Frequency: 848.31 MHz;Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 848.31 \text{ MHz}$ ;  $\sigma = 0.973 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(6.16, 6.16, 6.16); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.01 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 28.4 V/m; Power Drift = 0.030 dB  
 Peak SAR (extrapolated) = 1.44 W/kg  
**SAR(1 g) = 0.885 mW/g; SAR(10 g) = 0.586 mW/g**  
 Maximum value of SAR (measured) = 1.07 mW/g



0 dB = 1.07mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 11:17:03 PM

**Flat\_CDMA PCS CH 25\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type:** Smartphone; FCC ID: NM8PG76210

Communication System: CDMA PCS ; Frequency: 1851.25 MHz;Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1851.25 \text{ MHz}$ ;  $\sigma = 1.46 \text{ mho/m}$ ;  $\epsilon_r = 52.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.34 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 20.3 V/m; Power Drift = -0.031 dB  
 Peak SAR (extrapolated) = 1.66 W/kg  
**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.584 mW/g**  
 Maximum value of SAR (measured) = 1.27 mW/g



0 dB = 1.27mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 11:49:54 PM

**Flat\_CDMA PCS CH 600\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.48$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.43 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 19.8 V/m; Power Drift = 0.010 dB

Peak SAR (extrapolated) = 1.71 W/kg

**SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.635 mW/g**

Maximum value of SAR (measured) = 1.37 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 9:30:47 PM

**Flat\_CDMA PCS CH 1175\_Front Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**


Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.773 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 17.9 V/m; Power Drift = 0.090 dB  
 Peak SAR (extrapolated) = 1.03 W/kg  
**SAR(1 g) = 0.698 mW/g; SAR(10 g) = 0.419 mW/g**  
 Maximum value of SAR (measured) = 0.829 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 17.9 V/m; Power Drift = 0.090 dB  
 Peak SAR (extrapolated) = 1.01 W/kg  
**SAR(1 g) = 0.634 mW/g; SAR(10 g) = 0.384 mW/g**  
 Maximum value of SAR (measured) = 0.810 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/8/2011 10:14:18 PM

**Flat\_CDMA PCS CH 1175\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**


Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.38 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 18.4 V/m; Power Drift = -0.081 dB  
 Peak SAR (extrapolated) = 1.77 W/kg  
**SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.619 mW/g**  
 Maximum value of SAR (measured) = 1.33 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 1:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 18.4 V/m; Power Drift = -0.081 dB  
 Peak SAR (extrapolated) = 1.3 W/kg  
**SAR(1 g) = 0.826 mW/g; SAR(10 g) = 0.486 mW/g**  
 Maximum value of SAR (measured) = 1.05 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 1:01:32 AM

**Flat\_CDMA PCS CH1175\_Edge Left to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (91x131x1):**

Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (interpolated) = 0.378 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 16.4 V/m; Power Drift = 0.022 dB  
 Peak SAR (extrapolated) = 0.499 W/kg  
**SAR(1 g) = 0.333 mW/g; SAR(10 g) = 0.203 mW/g**  
 Maximum value of SAR (measured) = 0.403 mW/g



0 dB = 0.403mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 1:42:42 AM

**Flat\_CDMA PCS CH1175\_Edge Right to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.265 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 13.6 V/m; Power Drift = -0.047 dB  
 Peak SAR (extrapolated) = 0.335 W/kg  
**SAR(1 g) = 0.221 mW/g; SAR(10 g) = 0.134 mW/g**  
 Maximum value of SAR (measured) = 0.266 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 2:09:58 AM

**Flat\_CDMA PCS CH1175\_Edge Bottom to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA PCS ; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1909 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(4.71, 4.71, 4.71); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.710 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 22.8 V/m; Power Drift = 0.099 dB  
 Peak SAR (extrapolated) = 0.932 W/kg  
**SAR(1 g) = 0.635 mW/g; SAR(10 g) = 0.363 mW/g**  
 Maximum value of SAR (measured) = 0.764 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 2:20:14 PM

**Flat\_CDMA AWS CH25\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1711.25 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1711.25 \text{ MHz}$ ;  $\sigma = 1.48 \text{ mho/m}$ ;  $\epsilon_r = 52.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.29 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 21.2 V/m; Power Drift = -0.139 dB  
 Peak SAR (extrapolated) = 1.53 W/kg  
**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.621 mW/g**  
 Maximum value of SAR (measured) = 1.23 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 3:34:04 PM

**Flat\_CDMA AWS CH450\_Front Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.922 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 19.4 V/m; Power Drift = -0.080 dB  
 Peak SAR (extrapolated) = 1.07 W/kg  
**SAR(1 g) = 0.737 mW/g; SAR(10 g) = 0.456 mW/g**  
 Maximum value of SAR (measured) = 0.885 mW/g



0 dB = 0.885mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 1:54:19 PM

**Flat\_CDMA AWS CH450\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 1.27 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
 Reference Value = 21.5 V/m; Power Drift = 0.047 dB  
 Peak SAR (extrapolated) = 1.38 W/kg  
**SAR(1 g) = 0.943 mW/g; SAR(10 g) = 0.579 mW/g**  
 Maximum value of SAR (measured) = 1.14 mW/g



0 dB = 1.14mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 4:02:03 PM

**Flat\_CDMA AWS CH450\_Edge Left to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 53$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (51x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.309 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 13.7 V/m; Power Drift = -0.079 dB  
 Peak SAR (extrapolated) = 0.348 W/kg  
**SAR(1 g) = 0.246 mW/g; SAR(10 g) = 0.154 mW/g**  
 Maximum value of SAR (measured) = 0.293 mW/g



0 dB = 0.293mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 4:26:57 PM

**Flat\_CDMA AWS CH450\_Edge Right to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.51 \text{ mho/m}$ ;  $\epsilon_r = 53$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (51x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.235 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 12.3 V/m; Power Drift = 0.028 dB  
 Peak SAR (extrapolated) = 0.291 W/kg  
**SAR(1 g) = 0.192 mW/g; SAR(10 g) = 0.118 mW/g**  
 Maximum value of SAR (measured) = 0.233 mW/g



0 dB = 0.233mW/g

Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 4:52:59 PM

**Flat\_CDMA AWS CH450\_Edge Bottom to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1732.5$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (51x71x1):**

Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.556 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 19.6 V/m; Power Drift = 0.073 dB  
Peak SAR (extrapolated) = 0.698 W/kg  
**SAR(1 g) = 0.483 mW/g; SAR(10 g) = 0.282 mW/g**  
Maximum value of SAR (measured) = 0.586 mW/g





Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 2:45:59 PM

**Flat\_CDMA AWS CH875\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: CDMA AWS; Frequency: 1753.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1754 \text{ MHz}$ ;  $\sigma = 1.52 \text{ mho/m}$ ;  $\epsilon_r = 53$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: ES3DV3 - SN3150; ConvF(5, 5, 5); Calibrated: 4/14/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.12 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 20.2 V/m; Power Drift = 0.125 dB  
 Peak SAR (extrapolated) = 1.34 W/kg  
**SAR(1 g) = 0.851 mW/g; SAR(10 g) = 0.506 mW/g**  
 Maximum value of SAR (measured) = 1.03 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 10:24:47 AM

**Flat\_802.11b CH11\_5.5M\_Front Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.95 \text{ mho/m}$ ;  $\epsilon_r = 51.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.23, 7.23, 7.23); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x111x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.073 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 1.79 V/m; Power Drift = -0.121 dB  
 Peak SAR (extrapolated) = 0.112 W/kg  
**SAR(1 g) = 0.054 mW/g; SAR(10 g) = 0.026 mW/g**  
 Maximum value of SAR (measured) = 0.069 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 11:44:50 AM

**Flat\_802.11b CH11\_5.5M\_Back Surface to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within:2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.23, 7.23, 7.23); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (61x101x1):**

Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.328 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 5.76 V/m; Power Drift = -0.043 dB  
Peak SAR (extrapolated) = 0.481 W/kg  
**SAR(1 g) = 0.257 mW/g; SAR(10 g) = 0.131 mW/g**  
Maximum value of SAR (measured) = 0.319 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 12:12:23 PM

**Flat\_802.11b CH11\_5.5M\_Edge Left to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.95 \text{ mho/m}$ ;  $\epsilon_r = 51.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.23, 7.23, 7.23); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (51x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.047 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 2.83 V/m; Power Drift = -0.142 dB  
 Peak SAR (extrapolated) = 0.071 W/kg  
**SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.018 mW/g**  
 Maximum value of SAR (measured) = 0.050 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 12:36:24 PM

**Flat\_802.11b CH11\_5.5M\_Edge Right to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.95 \text{ mho/m}$ ;  $\epsilon_r = 51.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.23, 7.23, 7.23); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (51x91x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.059 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
 Reference Value = 4.99 V/m; Power Drift = 0.077 dB  
 Peak SAR (extrapolated) = 0.087 W/kg  
**SAR(1 g) = 0.042 mW/g; SAR(10 g) = 0.021 mW/g**  
 Maximum value of SAR (measured) = 0.054 mW/g



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 7/9/2011 1:01:14 PM

**Flat\_802.11b CH11\_5.5M\_Edge Top to Phantom\_10mm**

**DUT: PG76210; Type: Smartphone; FCC ID: NM8PG76210**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.95 \text{ mho/m}$ ;  $\epsilon_r = 51.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section  
Measurement Standard: DASYS (IEEE/IEC)

DASY5 Configuration:


- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3632; ConvF(7.23, 7.23, 7.23); Calibrated: 1/19/2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 1/31/2011
- Phantom: SAM with CRP; Type: SAM; Serial: TP-1150 and higher
- Measurement SW: DASYS, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Flat/Area Scan (51x71x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.237 mW/g

**Flat/Zoom Scan (7x7x9)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=3\text{mm}$   
Reference Value = 6.44 V/m; Power Drift = 0.055 dB  
Peak SAR (extrapolated) = 0.373 W/kg  
**SAR(1 g) = 0.194 mW/g; SAR(10 g) = 0.093 mW/g**  
Maximum value of SAR (measured) = 0.249 mW/g





## **Appendix C - Calibration**

All of the instruments Calibration information are listed below.

- Dipole \_ D835V2 SN:4d082 Calibration No.D835V2-4d082\_Jul10
- Dipole \_ D1750V2 SN:1023 Calibration No.D1750V2-1023\_May11
- Dipole \_ D1900V2 SN:5d111 Calibration No.D1900V2-5d111\_Jul10
- Dipole \_ D2450V2 SN:712 Calibration No.D2450V2-712\_Feb11
- Probe \_ ES3DV3 SN:3150 Calibration No.ES3-3150\_Jan11
- Probe \_ EX3DV4 SN:3632 Calibration No.EX3-3632\_Jan11
- DAE \_ DAE4 SN:779 Calibration No.DAE4-779\_Jan11



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **ATL (Auden)**

Certificate No: **D835V2-4d082\_Jul10**

## CALIBRATION CERTIFICATE

Object: **D835V2 - SN: 4d082**

Calibration procedure(s): **QA CAL-05.v7  
Calibration procedure for dipole validation kits**

Calibration date: **July 20, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	06-Oct-09 (No. 217-01086)	Oct-10
Power sensor HP 8481A	US37292783	06-Oct-09 (No. 217-01086)	Oct-10
Reference 20 dB Attenuator	SN: 5086 (20g)	30-Mar-10 (No. 217-01158)	Mar-11
Type-N mismatch combination	SN: 5047.2 / 06327	30-Mar-10 (No. 217-01162)	Mar-11
Reference Probe ES3DV3	SN: 3205	30-Apr-10 (No. ES3-3205_Apr10)	Apr-11
DAE4	SN: 601	10-Jun-10 (No. DAE4-601_Jun10)	Jun-11

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-09)	In house check: Oct-11
RF generator R&S SMT-06	100005	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-09)	In house check: Oct-10

	Name	Function	Signature
Calibrated by:	Dimce Iliev	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: July 20, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- d) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.



### Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V4.9	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

### Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	42.0 $\pm$ 6 %	0.90 mho/m $\pm$ 6 %
Head TSL temperature during test	(23.1 $\pm$ 0.2) °C	----	----

### SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.40 mW / g
SAR normalized	normalized to 1W	9.60 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>9.65 mW /g <math>\pm</math> 17.0 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.56 mW / g
SAR normalized	normalized to 1W	6.24 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>6.26 mW /g <math>\pm</math> 16.5 % (k=2)</b>



### Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	55.0 ± 6 %	1.01 mho/m ± 6 %
Body TSL temperature during test	(22.0 ± 0.2) °C	----	----

### SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.58 mW / g
SAR normalized	normalized to 1W	10.3 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>10.0 mW / g ± 17.0 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.69 mW / g
SAR normalized	normalized to 1W	6.76 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>6.60 mW / g ± 16.5 % (k=2)</b>



## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.7 $\Omega$ - 3.2 $j\Omega$
Return Loss	- 29.0 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.3 $\Omega$ - 4.6 $j\Omega$
Return Loss	- 26.0 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.389ns
----------------------------------	---------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	October 17, 2008

## DASY5 Validation Report for Head TSL

Date/Time: 20.07.2010 15:48:57

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d082**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL900

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.9$  mho/m;  $\epsilon_r = 42.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.03, 6.03, 6.03); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- Measurement SW: DASY52, V52.2 Build 0, Version 52.2.0 (163)
- Postprocessing SW: SEMCAD X, V14.2 Build 2, Version 14.2.2 (1685)


**Pin=250 mW /d=15mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.1 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 3.63 W/kg

**SAR(1 g) = 2.4 mW/g; SAR(10 g) = 1.56 mW/g**


Maximum value of SAR (measured) = 2.8 mW/g







### Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body

Date/Time: 20.07.2010 12:03:13

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d082**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL900

Medium parameters used:  $f = 835$  MHz;  $\sigma = 1.01$  mho/m;  $\epsilon_r = 55$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.86, 5.86, 5.86); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- Measurement SW: DASY52, V52.2 Build 0, Version 52.2.0 (163)
- Postprocessing SW: SEMCAD X, V14.2 Build 2, Version 14.2.2 (1685)


**Pin=250 mW /d=15mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.1 V/m; Power Drift = 0.017 dB

Peak SAR (extrapolated) = 3.81 W/kg


**SAR(1 g) = 2.58 mW/g; SAR(10 g) = 1.69 mW/g**

Maximum value of SAR (measured) = 2.98 mW/g





### Impedance Measurement Plot for Body TSL





**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **ATL (Auden)**

Certificate No: **D1900V2-5d111\_Jul10**

## CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d111**

Calibration procedure(s) **QA CAL-05.v7  
Calibration procedure for dipole validation kits**

Calibration date: **July 16, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	06-Oct-09 (No. 217-01086)	Oct-10
Power sensor HP 8481A	US37292783	06-Oct-09 (No. 217-01086)	Oct-10
Reference 20 dB Attenuator	SN: 5086 (20g)	30-Mar-10 (No. 217-01158)	Mar-11
Type-N mismatch combination	SN: 5047.2 / 06327	30-Mar-10 (No. 217-01162)	Mar-11
Reference Probe ES3DV3	SN: 3205	30-Apr-10 (No. ES3-3205_Apr10)	Apr-11
DAE4	SN: 601	10-Jun-10 (No. DAE4-601_Jun10)	Jun-11
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-09)	In house check: Oct-11
RF generator R&S SMT-06	100005	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-09)	In house check: Oct-10

	Name	Function	Signature
Calibrated by:	Dimce Iliev	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: July 19, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- d) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.



### Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz ± 1 MHz	

### Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	40.3 ± 6 %	1.43 mho/m ± 6 %
Head TSL temperature during test	(22.4 ± 0.2) °C	---	---

### SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	10.1 mW / g
SAR normalized	normalized to 1W	40.4 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>39.9 mW /g ± 17.0 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.28 mW / g
SAR normalized	normalized to 1W	21.1 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>21.0 mW /g ± 16.5 % (k=2)</b>



### Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	53.3 ± 6 %	1.55 mho/m ± 6 %
Body TSL temperature during test	(22.4 ± 0.2) °C	----	----

### SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.6 mW / g
SAR normalized	normalized to 1W	42.4 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>41.9 mW / g ± 17.0 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.66 mW / g
SAR normalized	normalized to 1W	22.6 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>22.5 mW / g ± 16.5 % (k=2)</b>





## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	$50.7 \Omega + 6.6 j\Omega$
Return Loss	- 23.6 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	$46.7 \Omega + 6.5 j\Omega$
Return Loss	- 22.5 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.202 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 28, 2008

## DASY5 Validation Report for Head TSL

Date/Time: 16.07.2010 13:15:00

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d111**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL U12 BB

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.09, 5.09, 5.09); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Measurement SW: DASY52, V52.2 Build 0, Version 52.2.0 (163)
- Postprocessing SW: SEMCAD X, V14.2 Build 2, Version 14.2.2 (1685)


**Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.6 V/m; Power Drift = 0.029 dB

Peak SAR (extrapolated) = 18.4 W/kg

**SAR(1 g) = 10.1 mW/g; SAR(10 g) = 5.28 mW/g**


Maximum value of SAR (measured) = 12.4 mW/g



0 dB = 12.4mW/g



### Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body

Date/Time: 13.07.2010 12:57:16

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d111**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL U11 BB

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.55$  mho/m;  $\epsilon_r = 53.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.59, 4.59, 4.59); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- Measurement SW: DASY52, V52.2 Build 0, Version 52.2.0 (163)
- Postprocessing SW: SEMCAD X, V14.2 Build 2, Version 14.2.2 (1685)

**Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0: Measurement**


grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.7 V/m; Power Drift = 0.00345 dB

Peak SAR (extrapolated) = 17.7 W/kg

**SAR(1 g) = 10.6 mW/g; SAR(10 g) = 5.66 mW/g**

Maximum value of SAR (measured) = 13.3 mW/g




0 dB = 13.3mW/g





### Impedance Measurement Plot for Body TSL



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **ATL (Auden)**

Certificate No: **D2450V2-712\_Feb11**

## CALIBRATION CERTIFICATE

Object	D2450V2 - SN: 712																																														
Calibration procedure(s)	QA CAL-05.v8 Calibration procedure for dipole validation kits																																														
Calibration date:	February 23, 2011																																														
<p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity &lt; 70%.</p> <p>Calibration Equipment used (M&amp;TE critical for calibration)</p> <table border="1"> <thead> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date (Certificate No.)</th> <th>Scheduled Calibration</th> </tr> </thead> <tbody> <tr> <td>Power meter EPM-442A</td> <td>GB37480704</td> <td>06-Oct-10 (No. 217-01266)</td> <td>Oct-11</td> </tr> <tr> <td>Power sensor HP 8481A</td> <td>US37292783</td> <td>06-Oct-10 (No. 217-01266)</td> <td>Oct-11</td> </tr> <tr> <td>Reference 20 dB Attenuator</td> <td>SN: 5086 (20g)</td> <td>30-Mar-10 (No. 217-01158)</td> <td>Mar-11</td> </tr> <tr> <td>Type-N mismatch combination</td> <td>SN: 5047.2 / 06327</td> <td>30-Mar-10 (No. 217-01162)</td> <td>Mar-11</td> </tr> <tr> <td>Reference Probe ES3DV3</td> <td>SN: 3205</td> <td>30-Apr-10 (No. ES3-3205_Apr10)</td> <td>Apr-11</td> </tr> <tr> <td>DAE4</td> <td>SN: 601</td> <td>10-Jun-10 (No. DAE4-601_Jun10)</td> <td>Jun-11</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Secondary Standards</th> <th>ID #</th> <th>Check Date (in house)</th> <th>Scheduled Check</th> </tr> </thead> <tbody> <tr> <td>Power sensor HP 8481A</td> <td>MY41092317</td> <td>18-Oct-02 (in house check Oct-09)</td> <td>In house check: Oct-11</td> </tr> <tr> <td>RF generator R&amp;S SMT-06</td> <td>100005</td> <td>4-Aug-99 (in house check Oct-09)</td> <td>In house check: Oct-11</td> </tr> <tr> <td>Network Analyzer HP 8753E</td> <td>US37390585 S4206</td> <td>18-Oct-01 (in house check Oct-10)</td> <td>In house check: Oct-11</td> </tr> </tbody> </table>				Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration	Power meter EPM-442A	GB37480704	06-Oct-10 (No. 217-01266)	Oct-11	Power sensor HP 8481A	US37292783	06-Oct-10 (No. 217-01266)	Oct-11	Reference 20 dB Attenuator	SN: 5086 (20g)	30-Mar-10 (No. 217-01158)	Mar-11	Type-N mismatch combination	SN: 5047.2 / 06327	30-Mar-10 (No. 217-01162)	Mar-11	Reference Probe ES3DV3	SN: 3205	30-Apr-10 (No. ES3-3205_Apr10)	Apr-11	DAE4	SN: 601	10-Jun-10 (No. DAE4-601_Jun10)	Jun-11	Secondary Standards	ID #	Check Date (in house)	Scheduled Check	Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-09)	In house check: Oct-11	RF generator R&S SMT-06	100005	4-Aug-99 (in house check Oct-09)	In house check: Oct-11	Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-10)	In house check: Oct-11
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration																																												
Power meter EPM-442A	GB37480704	06-Oct-10 (No. 217-01266)	Oct-11																																												
Power sensor HP 8481A	US37292783	06-Oct-10 (No. 217-01266)	Oct-11																																												
Reference 20 dB Attenuator	SN: 5086 (20g)	30-Mar-10 (No. 217-01158)	Mar-11																																												
Type-N mismatch combination	SN: 5047.2 / 06327	30-Mar-10 (No. 217-01162)	Mar-11																																												
Reference Probe ES3DV3	SN: 3205	30-Apr-10 (No. ES3-3205_Apr10)	Apr-11																																												
DAE4	SN: 601	10-Jun-10 (No. DAE4-601_Jun10)	Jun-11																																												
Secondary Standards	ID #	Check Date (in house)	Scheduled Check																																												
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-09)	In house check: Oct-11																																												
RF generator R&S SMT-06	100005	4-Aug-99 (in house check Oct-09)	In house check: Oct-11																																												
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-10)	In house check: Oct-11																																												
Calibrated by:	Name Dimce Iliev	Function Laboratory Technician	Signature 																																												
Approved by:	Katja Pokovic	Technical Manager																																													
Issued: February 24, 2011																																															
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.																																															

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- d) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.



### Measurement Conditions

DASY system configuration, as far as not given on page 1.

<b>DASY Version</b>	DASY5	V52.6
<b>Extrapolation</b>	Advanced Extrapolation	
<b>Phantom</b>	Modular Flat Phantom V5.0	
<b>Distance Dipole Center - TSL</b>	10 mm	with Spacer
<b>Zoom Scan Resolution</b>	dx, dy, dz = 5 mm	
<b>Frequency</b>	2450 MHz $\pm$ 1 MHz	

### Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
<b>Nominal Head TSL parameters</b>	22.0 °C	39.2	1.80 mho/m
<b>Measured Head TSL parameters</b>	(22.0 $\pm$ 0.2) °C	39.1 $\pm$ 6 %	1.73 mho/m $\pm$ 6 %
<b>Head TSL temperature during test</b>	(21.2 $\pm$ 0.2) °C	----	----

### SAR result with Head TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b>	Condition	
SAR measured	250 mW input power	13.0 mW / g
SAR normalized	normalized to 1W	52.0 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>52.9 mW /g <math>\pm</math> 17.0 % (k=2)</b>

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b>	condition	
SAR measured	250 mW input power	6.08 mW / g
SAR normalized	normalized to 1W	24.3 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>24.5 mW /g <math>\pm</math> 16.5 % (k=2)</b>





### Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.2 ± 6 %	1.94 mho/m ± 6 %
Body TSL temperature during test	(21.8 ± 0.2) °C	----	----

### SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.6 mW / g
SAR normalized	normalized to 1W	50.4 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>50.4 mW / g ± 17.0 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.83 mW / g
SAR normalized	normalized to 1W	23.3 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>23.3 mW / g ± 16.5 % (k=2)</b>



## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.3 $\Omega$ + 1.7 j $\Omega$
Return Loss	- 27.0 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.8 $\Omega$ + 5.5 j $\Omega$
Return Loss	- 25.1 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1,146 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 05, 2002

## DASY5 Validation Report for Head TSL

Date/Time: 23.02.2011 12:42:01

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:712**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL U12 BB

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.73$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- Measurement SW: DASY52, V52.6.1 Build (408)
- Postprocessing SW: SEMCAD X, V14.4.2 Build (2595)

**Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm**

Reference Value = 101.5 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 26.439 W/kg

**SAR(1 g) = 13 mW/g; SAR(10 g) = 6.08 mW/g**


Maximum value of SAR (measured) = 16.525 mW/g



0 dB = 16.530mW/g



### Impedance Measurement Plot for Head TSL





## DASY5 Validation Report for Body TSL

Date/Time: 18.02.2011 14:36:14

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:712**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL U12 BB

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.94$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.31, 4.31, 4.31); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- Measurement SW: DASY52, V52.6.1 Build (408)
- Postprocessing SW: SEMCAD X, V14.4.2 Build (2595)


**Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0: Measurement**  
grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.420 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 26.751 W/kg

**SAR(1 g) = 12.6 mW/g; SAR(10 g) = 5.83 mW/g**


Maximum value of SAR (measured) = 16.714 mW/g



0 dB = 16.710mW/g



### Impedance Measurement Plot for Body TSL



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **ATL (Auden)**

Certificate No: **ES3-3150\_Jan11**

## CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3150**

Calibration procedure(s) **QA CAL-01.v7, QA CAL-23.v4 and QA CAL-25.v3  
Calibration procedure for dosimetric E-field probes**

Calibration date: **January 19, 2011**


This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.


All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41498087	1-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5054 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5086 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	29-Dec-10 (No. ES3-3013_Dec10)	Dec-11
DAE4	SN: 660	20-Apr-10 (No. DAE4-660_Apr10)	Apr-11

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-10)	In house check: Oct-11

Calibrated by:	Name	Function	Signature
	Marcel Fehr	Laboratory Technician	

Approved by:	Name	Function	Signature
	Katja Pokovic	Technical Manager	

Issued: January 20, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

#### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization $\phi$	$\phi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.





ES3DV3 SN:3150

January 19, 2011

# Probe ES3DV3

## SN:3150

Manufactured:	June 12, 2007
Last calibrated:	January 27, 2010
Recalibrated:	January 19, 2011

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)



ES3DV3 SN:3150

January 19, 2011

### DASY/EASY - Parameters of Probe: ES3DV3 SN:3150

#### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V/m})^2$ ) <sup>A</sup>	1.25	1.24	1.23	± 10.1%
DCP (mV) <sup>B</sup>	102.3	100.4	101.1	

#### Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dBuV	C	VR mV	Unc <sup>E</sup> (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	149.9	± 2.4 %
			Y	0.00	0.00	1.00	149.5	
			Z	0.00	0.00	1.00	149.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



ES3DV3 SN:3150

January 19, 2011

## DASY/EASY - Parameters of Probe: ES3DV3 SN:3150

### Calibration Parameter Determined in Head Tissue Simulating Media


f [MHz]	Validity [MHz] <sup>C</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
835	± 50 / ± 100	41.5 ± 5%	0.90 ± 5%	6.15	6.15	6.15	0.77	1.14 ± 11.0%
1810	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.28	5.28	5.28	0.49	1.53 ± 11.0%
1900	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.18	5.18	5.18	0.42	1.65 ± 11.0%

<sup>C</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.





### Frequency Response of E-Field

(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

### Dynamic Range f(SAR<sub>head</sub>) (TEM cell, f = 900 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

### Conversion Factor Assessment



### Deviation from Isotropy in HSL

Error ( $\phi, \theta$ ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  (k=2)



ES3DV3 SN:3150

January 19, 2011

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **ATL (Auden)**

Certificate No: **ES3-3150\_Jan11**

## CALIBRATION CERTIFICATE

Object: **ES3DV3 - SN:3150**

Calibration procedure(s): **QA CAL-01.v7, QA CAL-23.v4 and QA CAL-25.v3  
Calibration procedure for dosimetric E-field probes**

Calibration date: **January 19, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41498087	1-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5054 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5086 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	29-Dec-10 (No. ES3-3013_Dec10)	Dec-11
DAE4	SN: 660	20-Apr-10 (No. DAE4-660_Apr10)	Apr-11

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3842U01700	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-10)	In house check: Oct-11

	Name	Function	Signature
Calibrated by:	Marcel Fehr	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 20, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

#### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.





ES3DV3 SN:3150

January 19, 2011

# Probe ES3DV3

## SN:3150

Manufactured:	June 12, 2007
Last calibrated:	January 27, 2010
Recalibrated:	January 19, 2011

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)



ES3DV3 SN:3150

January 19, 2011

**DASY/EASY - Parameters of Probe: ES3DV3 SN:3150**

**Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	1.25	1.24	1.23	± 10.1%
DCP (mV) <sup>B</sup>	102.3	100.4	101.1	

**Modulation Calibration Parameters**

UID	Communication System Name	PAR		A dB	B dBuV	C	VR mV	Unc <sup>E</sup> (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	149.9	± 2.4 %
			Y	0.00	0.00	1.00	149.5	
			Z	0.00	0.00	1.00	149.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



ES3DV3 SN:3150

January 19, 2011

## DASY/EASY - Parameters of Probe: ES3DV3 SN:3150


### Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz]	Validity [MHz] <sup>c</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
835	± 50 / ± 100	41.5 ± 5%	0.90 ± 5%	6.15	6.15	6.15	0.77	1.14 ± 11.0%
1810	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.28	5.28	5.28	0.49	1.53 ± 11.0%
1900	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.18	5.18	5.18	0.42	1.65 ± 11.0%

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



### Frequency Response of E-Field

(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)


### Dynamic Range f(SAR<sub>head</sub>) (TEM cell, f = 900 MHz)



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)




### Conversion Factor Assessment



### Deviation from Isotropy in HSL

Error ( $\phi, \theta$ ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  (k=2)





ES3DV3 SN:3150

January 19, 2011

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **ATL (Auden)**

Certificate No: **EX3-3632\_Jan11**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3632**

Calibration procedure(s) **QA CAL-01.v7, QA CAL-12.v6, QA CAL-23.v4 and QA CAL-25.v3  
Calibration procedure for dosimetric E-field probes**

Calibration date: **January 19, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41498087	1-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5054 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5086 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	29-Dec-10 (No. ES3-3013_Dec10)	Dec-11
DAE4	SN: 660	20-Apr-10 (No. DAE4-660_Apr10)	Apr-11
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-10)	In house check: Oct-11

Calibrated by: **Name: Jeton Kastrati, Function: Laboratory Technician, Signature: [Signature]**

Approved by: **Name: Katja Pokovic, Function: Technical Manager, Signature: [Signature]**

Issued: January 20, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

### Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- **NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- **NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* *frequency\_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- **DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- **A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- **ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- **Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- **Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.



EX3DV4 SN:3632

January 19, 2011

# Probe EX3DV4

## SN:3632

Manufactured:	November 1, 2007
Last calibrated:	January 26, 2010
Recalibrated:	January 19, 2011

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)



EX3DV4 SN:3632

January 19, 2011

## DASY/EASY - Parameters of Probe: EX3DV4 SN:3632

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	0.46	0.44	0.39	± 10.1%
DGP (mV) <sup>B</sup>	97.4	94.9	97.4	

### Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dBuV	C	VR mV	Unc <sup>E</sup> (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	133.3	± 3.4 %
			Y	0.00	0.00	1.00	110.0	
			Z	0.00	0.00	1.00	125.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.





EX3DV4 SN:3632

January 19, 2011

## DASY/EASY - Parameters of Probe: EX3DV4 SN:3632

### Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz]	Validity [MHz] <sup>c</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	43.5 ± 5%	0.87 ± 5%	9.40	9.40	9.40	0.12	2.85 ± 13.3%
750	± 50 / ± 100	41.9 ± 5%	0.89 ± 5%	9.51	9.51	9.51	0.67	0.64 ± 11.0%
835	± 50 / ± 100	41.5 ± 5%	0.90 ± 5%	9.09	9.09	9.09	0.66	0.64 ± 11.0%
1810	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	8.16	8.16	8.16	0.51	0.74 ± 11.0%
1900	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	8.02	8.02	8.02	0.58	0.68 ± 11.0%
2450	± 50 / ± 100	39.2 ± 5%	1.80 ± 5%	7.28	7.28	7.28	0.33	0.91 ± 11.0%

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



EX3DV4 SN:3632

January 19, 2011

## DASY/EASY - Parameters of Probe: EX3DV4 SN:3632

### Calibration Parameter Determined in Body Tissue Simulating Media


f [MHz]	Validity [MHz] <sup>c</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	56.7 ± 5%	0.94 ± 5%	10.05	10.05	10.05	0.05	1.80 ± 13.3%
750	± 50 / ± 100	55.5 ± 5%	0.96 ± 5%	9.33	9.33	9.33	0.78	0.63 ± 11.0%
835	± 50 / ± 100	55.2 ± 5%	0.97 ± 5%	9.28	9.28	9.28	0.73	0.66 ± 11.0%
1810	± 50 / ± 100	53.3 ± 5%	1.52 ± 5%	7.57	7.57	7.57	0.83	0.60 ± 11.0%
1900	± 50 / ± 100	53.3 ± 5%	1.52 ± 5%	7.39	7.39	7.39	0.67	0.65 ± 11.0%
2450	± 50 / ± 100	52.7 ± 5%	1.95 ± 5%	7.23	7.23	7.23	0.28	1.07 ± 11.0%

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.





### Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

### Dynamic Range $f(SAR_{head})$ (TEM cell, $f = 900$ MHz)




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

### Conversion Factor Assessment



### Deviation from Isotropy in HSL

Error ( $\phi, \theta$ ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  (k=2)



EX3DV4 SN:3632

January 19, 2011

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	2 mm



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **ATL (Auden)**

Certificate No: **DAE4-779\_Jan11**

## CALIBRATION CERTIFICATE

Object **DAE4 - SD 000 D04 BJ - SN: 779**

Calibration procedure(s) **QA CAL-06.v22  
Calibration procedure for the data acquisition electronics (DAE)**

Calibration date: **January 31, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	28-Sep-10 (No:10376)	Sep-11
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Calibrator Box V1,1	SE UMS 006 AB 1004	07-Jun-10 (in house check)	In house check: Jun-11

Calibrated by:	Name <b>Andrea Guntli</b>	Function <b>Technician</b>	Signature 
Approved by:	Name <b>Fin Bornholt</b>	Function <b>R&amp;D Director</b>	Signature 

Issued: January 31, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary

**DAE** data acquisition electronics  
**Connector angle** information used in DASY system to align probe sensor X to the robot coordinate system.

### Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement*: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - *DC Voltage Measurement Linearity*: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - *Common mode sensitivity*: Influence of a positive or negative common mode voltage on the differential measurement.
  - *Channel separation*: Influence of a voltage on the neighbor channels not subject to an input voltage.
  - *AD Converter Values with inputs shorted*: Values on the internal AD converter corresponding to zero input voltage
  - *Input Offset Measurement*: Output voltage and statistical results over a large number of zero voltage measurements.
  - *Input Offset Current*: Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - *Input resistance*: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - *Low Battery Alarm Voltage*: Typical value for information. Below this voltage, a battery alarm signal is generated.
  - *Power consumption*: Typical value for information. Supply currents in various operating modes.





### DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 $\mu$ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	404.517 $\pm$ 0.1% (k=2)	403.748 $\pm$ 0.1% (k=2)	403.972 $\pm$ 0.1% (k=2)
Low Range	3.96927 $\pm$ 0.7% (k=2)	3.98585 $\pm$ 0.7% (k=2)	3.99915 $\pm$ 0.7% (k=2)

### Connector Angle

Connector Angle to be used in DASY system	155.5 $^{\circ}$ $\pm$ 1 $^{\circ}$
---	-------------------------------------

## Appendix

### 1. DC Voltage Linearity

High Range	Reading ( $\mu\text{V}$ )	Difference ( $\mu\text{V}$ )	Error (%)
Channel X + Input	200001.8	6.19	0.00
Channel X + Input	20003.75	4.25	0.02
Channel X - Input	-19996.56	3.04	-0.02
Channel Y + Input	200005.0	0.90	0.00
Channel Y + Input	20000.78	1.38	0.01
Channel Y - Input	-19996.43	2.97	-0.01
Channel Z + Input	200002.2	-1.15	-0.00
Channel Z + Input	19999.59	0.19	0.00
Channel Z - Input	-19995.05	4.35	-0.02

Low Range	Reading ( $\mu\text{V}$ )	Difference ( $\mu\text{V}$ )	Error (%)
Channel X + Input	2000.4	0.25	0.01
Channel X + Input	200.27	0.37	0.18
Channel X - Input	-199.08	1.12	-0.56
Channel Y + Input	2000.1	0.19	0.01
Channel Y + Input	199.01	-0.89	-0.45
Channel Y - Input	-199.30	0.50	-0.25
Channel Z + Input	1999.6	-0.40	-0.02
Channel Z + Input	199.22	-0.88	-0.44
Channel Z - Input	-200.27	-0.37	0.19

### 2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading ( $\mu\text{V}$ )	Low Range Average Reading ( $\mu\text{V}$ )
Channel X	200	-3.66	-5.39
	- 200	5.82	4.90
Channel Y	200	13.39	13.58
	- 200	-14.98	-15.16
Channel Z	200	2.20	2.53
	- 200	-4.84	-4.61

### 3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X ( $\mu\text{V}$ )	Channel Y ( $\mu\text{V}$ )	Channel Z ( $\mu\text{V}$ )
Channel X	200	-	1.33	-0.57
Channel Y	200	1.97	-	3.29
Channel Z	200	1.19	-0.28	-

#### 4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	15613	15134
Channel Y	15831	16218
Channel Z	16150	17743

#### 5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10M $\Omega$

	Average ( $\mu$ V)	min. Offset ( $\mu$ V)	max. Offset ( $\mu$ V)	Std. Deviation ( $\mu$ V)
Channel X	-0.26	-1.03	0.79	0.42
Channel Y	0.52	-1.04	2.07	0.58
Channel Z	-2.22	-3.25	-0.85	0.44

#### 6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

#### 7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

#### 8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

#### 9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9