

## **System Check\_Head\_750MHz\_110602**

### **DUT: Dipole 750 MHz**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: HSL\_750\_110602 Medium parameters used:  $f = 750.076$  MHz;  $\sigma = 0.886$  mho/m;  $\epsilon_r = 40.28$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(9.16, 9.16, 9.16); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 2.25 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 52.9 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 3.18 W/kg

**SAR(1 g) = 2.08 mW/g; SAR(10 g) = 1.34 mW/g**

Maximum value of SAR (measured) = 2.24 mW/g



0 dB = 2.24mW/g

## **System Check\_Head\_750MHz\_110604**

### **DUT: Dipole 750 MHz**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: HSL\_750\_110604 Medium parameters used:  $f = 750.076$  MHz;  $\sigma = 0.89$  mho/m;  $\epsilon_r = 40.32$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(9.16, 9.16, 9.16); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Left; Type: SAM; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 2.23 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 52.9 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 3.15 W/kg

**SAR(1 g) = 2.06 mW/g; SAR(10 g) = 1.33 mW/g**

Maximum value of SAR (measured) = 2.22 mW/g



0 dB = 2.22mW/g

## **System Check\_Body\_750MHz\_110602**

### **DUT: Dipole 750 MHz**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1  
Medium: MSL\_750\_110602 Medium parameters used:  $f = 750.076$  MHz;  $\sigma = 0.958$  mho/m;  $\epsilon_r = 53.11$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 2.49 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 49.6 V/m; Power Drift = 0.641 dB

Peak SAR (extrapolated) = 3.42 W/kg

**SAR(1 g) = 2.28 mW/g; SAR(10 g) = 1.49 mW/g**

Maximum value of SAR (measured) = 2.46 mW/g



0 dB = 2.24mW/g

## **System Check\_Body\_750MHz\_110604**

### **DUT: Dipole 750 MHz**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1  
Medium: MSL\_750\_110604 Medium parameters used:  $f = 750.076$  MHz;  $\sigma = 0.964$  mho/m;  $\epsilon_r = 53.16$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(8.81, 8.81, 8.81); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 2.42 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 49.8 V/m; Power Drift = 0.141 dB

Peak SAR (extrapolated) = 3.32 W/kg

**SAR(1 g) = 2.21 mW/g; SAR(10 g) = 1.45 mW/g**

Maximum value of SAR (measured) = 2.39 mW/g



0 dB = 2.39mW/g



## System Check\_Head\_835MHz\_110529

### DUT: Dipole 835 MHz

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium: HSL\_850\_110529 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.902$   
 $\text{mho/m}$ ;  $\epsilon_r = 43.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

### DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 2.56 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=5mm

Reference Value = 53.2 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 3.63 W/kg

**SAR(1 g) = 2.4 mW/g; SAR(10 g) = 1.56 mW/g**

Maximum value of SAR (measured) = 2.59 mW/g



0 dB = 2.59mW/g

## **System Check\_Head\_850MHz\_110530**

### **DUT: Dipole 835 MHz**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium: HSL\_850\_110530 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.912$   
 $\text{mho/m}$ ;  $\epsilon_r = 43.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 2.64 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=5mm

Reference Value = 54.3 V/m; Power Drift = -0.190 dB

Peak SAR (extrapolated) = 3.61 W/kg

**SAR(1 g) = 2.35 mW/g; SAR(10 g) = 1.52 mW/g**

Maximum value of SAR (measured) = 2.53 mW/g



0 dB = 2.53mW/g

## **System Check\_Body\_850MHz\_110530**

### **DUT: Dipole 835 MHz**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.976$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 2.89 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=5mm

Reference Value = 54.4 V/m; Power Drift = -0.001 dB

Peak SAR (extrapolated) = 3.95 W/kg

**SAR(1 g) = 2.67 mW/g; SAR(10 g) = 1.78 mW/g**

Maximum value of SAR (measured) = 2.88 mW/g



0 dB = 2.88mW/g

## **System Check\_Body\_835MHz\_110606**

### **DUT: Dipole 835 MHz**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL\_850\_110606 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.979 \text{ mho/m}$ ;  $\epsilon_r = 52.7$ ;  $\rho = 1000$

$\text{kg/m}^3$

Ambient Temperature : 22.6 ; Liquid Temperature : 21.7

#### **DASY5 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.9 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.4 V/m; Power Drift = -0.000862 dB

Peak SAR (extrapolated) = 3.96 W/kg

**SAR(1 g) = 2.68 mW/g; SAR(10 g) = 1.78 mW/g**

Maximum value of SAR (measured) = 2.88 mW/g



0 dB = 2.88mW/g



## **System Check\_Head\_1800MHz\_110601**

### **DUT: Dipole 1800 MHz**

Communication System: CW; Frequency: 1800 MHz; Duty Cycle: 1:1  
Medium: HSL\_1800\_110601 Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.43$   
mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(7.47, 7.47, 7.47); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 9.96 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=5mm

Reference Value = 82.8 V/m; Power Drift = 0.137 dB

Peak SAR (extrapolated) = 17.3 W/kg

**SAR(1 g) = 9.57 mW/g; SAR(10 g) = 5.18 mW/g**

Maximum value of SAR (measured) = 10.7 mW/g



0 dB = 10.7mW/g

## **System Check\_Head\_1800MHz\_110605**

### **DUT: Dipole 1800 MHz**

Communication System: CW; Frequency: 1800 MHz; Duty Cycle: 1:1  
Medium: HSL\_1800\_110605 Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 39.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.2 °C; Liquid Temperature : 21.2 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(7.47, 7.47, 7.47); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Left; Type: SAM; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 9.93 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 82.8 V/m; Power Drift = 0.137 dB

Peak SAR (extrapolated) = 17.2 W/kg

**SAR(1 g) = 9.53 mW/g; SAR(10 g) = 5.16 mW/g**

Maximum value of SAR (measured) = 10.6 mW/g



0 dB = 10.6mW/g

## **System Check\_Body\_1800MHz\_110602**

### **DUT: Dipole 1800 MHz**

Communication System: CW; Frequency: 1800 MHz; Duty Cycle: 1:1  
Medium: MSL\_1800\_110602 Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.55$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.6 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(7.41, 7.41, 7.41); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 11.5 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 79.9 V/m; Power Drift = 0.097 dB

Peak SAR (extrapolated) = 17.0 W/kg

**SAR(1 g) = 9.37 mW/g; SAR(10 g) = 5.08 mW/g**

Maximum value of SAR (measured) = 10.4 mW/g



0 dB = 10.4mW/g

## **System Check\_Body\_1800MHz\_110605**

### **DUT: Dipole 1800 MHz**

Communication System: CW; Frequency: 1800 MHz; Duty Cycle: 1:1

Medium: MSL\_1800\_110605 Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.56$  mho/m;  $\epsilon_r = 52.8$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.41, 7.41, 7.41); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 11.6 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 79.8 V/m; Power Drift = 0.097 dB

Peak SAR (extrapolated) = 17 W/kg

**SAR(1 g) = 9.39 mW/g; SAR(10 g) = 5.09 mW/g**

Maximum value of SAR (measured) = 10.5 mW/g



0 dB = 10.5mW/g



## **System Check\_Head\_1900MHz\_110529**

### **DUT: Dipole 1900 MHz**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 11.1 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 83.9 V/m; Power Drift = 0.012 dB

Peak SAR (extrapolated) = 17.5 W/kg

**SAR(1 g) = 9.41 mW/g; SAR(10 g) = 4.95 mW/g**

Maximum value of SAR (measured) = 10.4 mW/g



0 dB = 10.4mW/g

## **System Check\_Head\_1900MHz\_110601**

### **DUT: Dipole 1900 MHz**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110601 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.46$  mho/m;  $\epsilon_r = 39$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 11.4 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 84.1 V/m; Power Drift = 0.012 dB

Peak SAR (extrapolated) = 17.9 W/kg

**SAR(1 g) = 9.6 mW/g; SAR(10 g) = 5.04 mW/g**

Maximum value of SAR (measured) = 10.6 mW/g



0 dB = 10.6mW/g

## **System Check\_Body\_1900MHz\_110530**

### **DUT: Dipole 1900 MHz**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110530 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(7.26, 7.26, 7.26); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 12.0 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 77.6 V/m; Power Drift = 0.151 dB

Peak SAR (extrapolated) = 17.8 W/kg

**SAR(1 g) = 9.72 mW/g; SAR(10 g) = 5.27 mW/g**

Maximum value of SAR (measured) = 10.8 mW/g



0 dB = 10.8mW/g

## **System Check\_Body\_1900MHz\_110601**

### **DUT: Dipole 1900 MHz**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 11.3 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 84.2 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 18.6 W/kg

**SAR(1 g) = 9.59 mW/g; SAR(10 g) = 4.8 mW/g**

Maximum value of SAR (measured) = 10.8 mW/g



0 dB = 10.8mW/g



## **System Check\_Head\_2450MHz\_110602**

### **DUT: Dipole 2450 MHz**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium: HSL\_2450\_110602 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.84$  mho/m;  $\epsilon_r = 39.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(6.77, 6.77, 6.77); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Left; Type: SAM; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 16.6 mW/g



**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.1 V/m; Power Drift = 0.000 dB

Peak SAR (extrapolated) = 31.1 W/kg

**SAR(1 g) = 13.6 mW/g; SAR(10 g) = 6.07 mW/g**

Maximum value of SAR (measured) = 15.2 mW/g



0 dB = 15.2mW/g

## **System Check\_Body\_2450MHz\_110602**

### **DUT: Dipole 2450 MHz**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium: MSL\_2450\_110602 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.02$  mho/m;  $\epsilon_r = 53.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.6 °C

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3697; ConvF(7.02, 7.02, 7.02); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 17.6 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.5 V/m; Power Drift = 0.000 dB

Peak SAR (extrapolated) = 33.0 W/kg

**SAR(1 g) = 14.4 mW/g; SAR(10 g) = 6.43 mW/g**

Maximum value of SAR (measured) = 16.1 mW/g



0 dB = 16.1mW/g

## #01 GSM850\_Right Cheek\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_850\_110529 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.903$   
mho/m;  $\epsilon_r = 43.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.214 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 4.75 V/m; Power Drift = 0.121 dB

Peak SAR (extrapolated) = 0.248 W/kg

**SAR(1 g) = 0.204 mW/g; SAR(10 g) = 0.156 mW/g**

Maximum value of SAR (measured) = 0.215 mW/g



0 dB = 0.215mW/g

## #02 GSM850\_Right Tilted\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.903$   
mho/m;  $\epsilon_r = 43.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.182 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = -0.113 dB

Peak SAR (extrapolated) = 0.217 W/kg

**SAR(1 g) = 0.175 mW/g; SAR(10 g) = 0.134 mW/g**

Maximum value of SAR (measured) = 0.181 mW/g



0 dB = 0.181mW/g



### #03 GSM850\_Left Cheek\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.903$   
mho/m;  $\epsilon_r = 43.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.258 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 6.48 V/m; Power Drift = -0.149 dB

Peak SAR (extrapolated) = 0.300 W/kg

**SAR(1 g) = 0.241 mW/g; SAR(10 g) = 0.181 mW/g**

Maximum value of SAR (measured) = 0.254 mW/g



0 dB = 0.254mW/g

## #03 GSM850\_Left Cheek\_Ch189\_2D

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.903$   
mho/m;  $\epsilon_r = 43.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.258 mW/g

**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 6.48 V/m; Power Drift = -0.149 dB


Peak SAR (extrapolated) = 0.300 W/kg

**SAR(1 g) = 0.241 mW/g; SAR(10 g) = 0.181 mW/g**

Maximum value of SAR (measured) = 0.254 mW/g

# 1g/10g Averaged SAR

SAR, Zoom Scan: Value Along Z, X=2, Y=2



## #04 GSM850\_Left Tilted\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_850\_110529 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.903$   
mho/m;  $\epsilon_r = 43.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.163 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 10.7 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 0.196 W/kg

**SAR(1 g) = 0.160 mW/g; SAR(10 g) = 0.124 mW/g**

Maximum value of SAR (measured) = 0.166 mW/g



0 dB = 0.166mW/g

## #11 GSM1900\_Right Cheek\_Ch810

**DUT: 142244-01**

Communication System: PCS; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.45$   
mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.644 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 8.47 V/m; Power Drift = 0.092 dB

Peak SAR (extrapolated) = 0.871 W/kg

**SAR(1 g) = 0.566 mW/g; SAR(10 g) = 0.352 mW/g**

Maximum value of SAR (measured) = 0.617 mW/g



0 dB = 0.617mW/g



## #11 GSM1900\_Right Cheek\_Ch810\_2D

**DUT: 142244-01**

Communication System: PCS; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.644 mW/g

**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.47 V/m; Power Drift = 0.092 dB


Peak SAR (extrapolated) = 0.871 W/kg

**SAR(1 g) = 0.566 mW/g; SAR(10 g) = 0.352 mW/g**

Maximum value of SAR (measured) = 0.617 mW/g

# 1g/10g Averaged SAR

SAR, Zoom Scan: Value Along Z, X=2, Y=2



## #12 GSM1900\_Right Tilted\_Ch810

**DUT: 142244-01**

Communication System: PCS; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.226 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.8 V/m; Power Drift = -0.106 dB

Peak SAR (extrapolated) = 0.310 W/kg

**SAR(1 g) = 0.191 mW/g; SAR(10 g) = 0.112 mW/g**

Maximum value of SAR (measured) = 0.211 mW/g



0 dB = 0.211mW/g

## #13 GSM1900\_Left Cheek\_Ch810

**DUT: 142244-01**

Communication System: PCS; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.300 mW/g

**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.53 V/m; Power Drift = 0.011 dB

Peak SAR (extrapolated) = 0.478 W/kg

**SAR(1 g) = 0.313 mW/g; SAR(10 g) = 0.200 mW/g**

Maximum value of SAR (measured) = 0.334 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.53 V/m; Power Drift = 0.011 dB

Peak SAR (extrapolated) = 0.378 W/kg

**SAR(1 g) = 0.253 mW/g; SAR(10 g) = 0.164 mW/g**

Maximum value of SAR (measured) = 0.272 mW/g



0 dB = 0.272mW/g

## #14 GSM1900\_Left Tilted\_Ch810

**DUT: 142244-01**

Communication System: PCS; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.270 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.0 V/m; Power Drift = -0.080 dB

Peak SAR (extrapolated) = 0.366 W/kg

**SAR(1 g) = 0.226 mW/g; SAR(10 g) = 0.131 mW/g**

Maximum value of SAR (measured) = 0.249 mW/g



0 dB = 0.249mW/g



## #06 WCDMA V\_RMC12.2K\_Right Cheek\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA Band 5; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL\_850\_110529 Medium parameters used :  $f = 826.4$  MHz;  $\sigma = 0.893$  mho/m;  $\epsilon_r = 43.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.311 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.24 V/m; Power Drift = 0.150 dB

Peak SAR (extrapolated) = 0.354 W/kg

**SAR(1 g) = 0.292 mW/g; SAR(10 g) = 0.227 mW/g**

Maximum value of SAR (measured) = 0.306 mW/g



0 dB = 0.306mW/g

## #07 WCDMA V\_RMC12.2K\_Right Tilted\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA Band 5; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL\_850\_110529 Medium parameters used :  $f = 826.4$  MHz;  $\sigma = 0.893$  mho/m;  $\epsilon_r = 43.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.237 mW/g

**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.3 V/m; Power Drift = 0.002 dB

Peak SAR (extrapolated) = 0.284 W/kg

**SAR(1 g) = 0.234 mW/g; SAR(10 g) = 0.181 mW/g**

Maximum value of SAR (measured) = 0.242 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.3 V/m; Power Drift = 0.002 dB

Peak SAR (extrapolated) = 0.277 W/kg

**SAR(1 g) = 0.208 mW/g; SAR(10 g) = 0.147 mW/g**

Maximum value of SAR (measured) = 0.235 mW/g



0 dB = 0.235mW/g

## #08 WCDMA V\_RMC12.2K\_Left Cheek\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA Band 5; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL\_850\_110529 Medium parameters used :  $f = 826.4$  MHz;  $\sigma = 0.893$  mho/m;  $\epsilon_r = 43.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.378 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.98 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.434 W/kg

**SAR(1 g) = 0.350 mW/g; SAR(10 g) = 0.269 mW/g**

Maximum value of SAR (measured) = 0.367 mW/g



0 dB = 0.367mW/g

## #08 WCDMA V\_RMC12.2K\_Left Cheek\_Ch4132\_2D

**DUT: 142244-01**

Communication System: WCDMA Band 5; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL\_850\_110529 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.893$  mho/m;  $\epsilon_r = 43.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.378 mW/g

**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.98 V/m; Power Drift = -0.116 dB


Peak SAR (extrapolated) = 0.434 W/kg

**SAR(1 g) = 0.350 mW/g; SAR(10 g) = 0.269 mW/g**

Maximum value of SAR (measured) = 0.367 mW/g

# 1g/10g Averaged SAR

SAR, Zoom Scan: Value Along Z, X=2, Y=2





## #09 WCDMA V\_RMC12.2K\_Left Tilted\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA Band 5; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL\_850\_110529 Medium parameters used :  $f = 826.4$  MHz;  $\sigma = 0.893$  mho/m;  $\epsilon_r = 43.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(8.85, 8.85, 8.85); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.250 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.0 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 0.303 W/kg

**SAR(1 g) = 0.247 mW/g; SAR(10 g) = 0.192 mW/g**

Maximum value of SAR (measured) = 0.256 mW/g



0 dB = 0.256mW/g

## #16 WCDMA II\_RMC12.2K\_Right Cheek\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$   
mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 1.47 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 12.1 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 1.95 W/kg

**SAR(1 g) = 1.28 mW/g; SAR(10 g) = 0.799 mW/g**

Maximum value of SAR (measured) = 1.39 mW/g



0 dB = 1.39mW/g

## #16 WCDMA II\_RMC12.2K\_Right Cheek\_Ch9400\_2D

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$   
mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 1.47 mW/g

**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 12.1 V/m; Power Drift = -0.050 dB


Peak SAR (extrapolated) = 1.95 W/kg

**SAR(1 g) = 1.28 mW/g; SAR(10 g) = 0.799 mW/g**

Maximum value of SAR (measured) = 1.39 mW/g

# 1g/10g Averaged SAR

SAR, Zoom Scan: Value Along Z, X=2, Y=2



## #17 WCDMA II\_RMC12.2K\_Right Tilted\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.431 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.5 V/m; Power Drift = -0.090 dB

Peak SAR (extrapolated) = 0.552 W/kg

**SAR(1 g) = 0.345 mW/g; SAR(10 g) = 0.211 mW/g**

Maximum value of SAR (measured) = 0.365 mW/g



0 dB = 0.365mW/g



## #18 WCDMA II\_RMC12.2K\_Left Cheek\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.546 mW/g

**Ch9400/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = -0.096 dB

Peak SAR (extrapolated) = 0.772 W/kg

**SAR(1 g) = 0.515 mW/g; SAR(10 g) = 0.338 mW/g**

Maximum value of SAR (measured) = 0.547 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = -0.096 dB

Peak SAR (extrapolated) = 0.760 W/kg

**SAR(1 g) = 0.509 mW/g; SAR(10 g) = 0.328 mW/g**

Maximum value of SAR (measured) = 0.546 mW/g



0 dB = 0.546mW/g

## #19 WCDMA II\_RMC12.2K\_Left Tilted\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$   
mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.451 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 17.0 V/m; Power Drift = 0.022 dB

Peak SAR (extrapolated) = 0.629 W/kg

**SAR(1 g) = 0.389 mW/g; SAR(10 g) = 0.225 mW/g**

Maximum value of SAR (measured) = 0.433 mW/g



0 dB = 0.433mW/g

## #20 WCDMA II\_RMC12.2K\_Right Cheek\_Ch9262

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 1.16 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = 0.009 dB

Peak SAR (extrapolated) = 1.57 W/kg

**SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.642 mW/g**

Maximum value of SAR (measured) = 1.11 mW/g



0 dB = 1.11mW/g

## #21 WCDMA II\_RMC12.2K\_Right Cheek\_Ch9538

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_110529 Medium parameters used :  $f = 1852.4$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 38.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.46, 7.46, 7.46); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9262/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 1.28 mW/g


**Ch9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.083 dB

Peak SAR (extrapolated) = 1.71 W/kg

**SAR(1 g) = 1.12 mW/g; SAR(10 g) = 0.707 mW/g**

Maximum value of SAR (measured) = 1.20 mW/g



0 dB = 1.20mW/g



## #23 GSM850\_GPRS10\_Front Face\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.610 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 23.8 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 0.717 W/kg

**SAR(1 g) = 0.577 mW/g; SAR(10 g) = 0.444 mW/g**

Maximum value of SAR (measured) = 0.603 mW/g



0 dB = 0.603mW/g

## #24 GSM850\_GPRS10\_Rear Face\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.824 mW/g



**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 27.2 V/m; Power Drift = 0.147 dB

Peak SAR (extrapolated) = 1.05 W/kg

**SAR(1 g) = 0.837 mW/g; SAR(10 g) = 0.634 mW/g**

Maximum value of SAR (measured) = 0.872 mW/g



0 dB = 0.872mW/g

## #24 GSM850\_GPRS10\_Rear Face\_Ch189\_2D

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.824 mW/g

**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 27.2 V/m; Power Drift = 0.147 dB


Peak SAR (extrapolated) = 1.05 W/kg

**SAR(1 g) = 0.837 mW/g; SAR(10 g) = 0.634 mW/g**

Maximum value of SAR (measured) = 0.872 mW/g

# 1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=3, Y=3



## #25 GSM850\_GPRS10\_Top Side\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.020 mW/g

**Ch189/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.87 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.027 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.014 mW/g**

Maximum value of SAR (measured) = 0.021 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.87 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.023 W/kg

**SAR(1 g) = 0.017 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.019 mW/g



0 dB = 0.019mW/g



## #26 GSM850\_GPRS10\_Down Side\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.144 mW/g



**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 9.27 V/m; Power Drift = -0.167 dB

Peak SAR (extrapolated) = 0.175 W/kg

**SAR(1 g) = 0.092 mW/g; SAR(10 g) = 0.056 mW/g**

Maximum value of SAR (measured) = 0.111 mW/g



0 dB = 0.111mW/g

## #27 GSM850\_GPRS10\_Left Side\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.546 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 23.7 V/m; Power Drift = 0.136 dB

Peak SAR (extrapolated) = 0.731 W/kg

**SAR(1 g) = 0.521 mW/g; SAR(10 g) = 0.363 mW/g**

Maximum value of SAR (measured) = 0.552 mW/g



0 dB = 0.552mW/g

## #28 GSM850\_GPRS10\_Right Side\_Ch189

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.417 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 21.0 V/m; Power Drift = 0.192 dB

Peak SAR (extrapolated) = 0.593 W/kg

**SAR(1 g) = 0.423 mW/g; SAR(10 g) = 0.292 mW/g**

Maximum value of SAR (measured) = 0.449 mW/g



0 dB = 0.449mW/g

## #29 GSM850\_GPRS10\_Rear Face\_Ch128

**DUT: 142244-01**

Communication System: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 824.2$  MHz;  $\sigma = 0.964$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch128/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.651 mW/g


**Ch128/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.9 V/m; Power Drift = -0.017 dB

Peak SAR (extrapolated) = 0.793 W/kg

**SAR(1 g) = 0.636 mW/g; SAR(10 g) = 0.485 mW/g**

Maximum value of SAR (measured) = 0.669 mW/g



0 dB = 0.669mW/g



## #30 GSM850\_GPRS10\_Rear Face\_Ch251

**DUT: 142244-01**

Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.99$   
mho/m;  $\epsilon_r = 52.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch251/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.625 mW/g


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 24.6 V/m; Power Drift = 0.061 dB

Peak SAR (extrapolated) = 0.770 W/kg

**SAR(1 g) = 0.604 mW/g; SAR(10 g) = 0.458 mW/g**

Maximum value of SAR (measured) = 0.634 mW/g



0 dB = 0.634mW/g

## #32 GSM850\_GPRS10\_Rear Face\_Ch189\_Earphone

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.977$   
mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch189/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.561 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.8 V/m; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 0.833 W/kg

**SAR(1 g) = 0.514 mW/g; SAR(10 g) = 0.349 mW/g**

Maximum value of SAR (measured) = 0.544 mW/g



0 dB = 0.544mW/g

**#197 GSM850\_EDGE10\_Rear Face\_1cm\_Ch189**

**DUT: 142244-01**

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:4

Medium: MSL\_850\_110606 Medium parameters used :  $f = 836.4$  MHz;  $\sigma = 0.98$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch189/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.868 mW/g


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.9 V/m; Power Drift = -0.178 dB

Peak SAR (extrapolated) = 1.04 W/kg

**SAR(1 g) = 0.830 mW/g; SAR(10 g) = 0.629 mW/g**

Maximum value of SAR (measured) = 0.867 mW/g



**#198 GSM850\_EDGE10\_Rear Face\_1cm\_Ch128**

**DUT: 142244-01**

Communication System: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium: MSL\_850\_110606 Medium parameters used :  $f = 824.2$  MHz;  $\sigma = 0.967$  mho/m;  $\epsilon_r = 52.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch128/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.873 mW/g



**Ch128/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.1 V/m; Power Drift = 0.00257 dB

Peak SAR (extrapolated) = 1.06 W/kg

**SAR(1 g) = 0.836 mW/g; SAR(10 g) = 0.632 mW/g**

Maximum value of SAR (measured) = 0.877 mW/g



0 dB = 0.877mW/g



**#199 GSM850\_EDGE10\_Rear Face\_1cm\_Ch251**

**DUT: 142244-01**

Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:4

Medium: MSL\_850\_110606 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.993$  mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1249; Calibrated: 2011/2/21
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch251/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.746 mW/g



**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.7 V/m; Power Drift = -0.131 dB

Peak SAR (extrapolated) = 0.872 W/kg

**SAR(1 g) = 0.691 mW/g; SAR(10 g) = 0.520 mW/g**

Maximum value of SAR (measured) = 0.726 mW/g



0 dB = 0.726mW/g

## #41 GSM1900\_GPRS10\_Front Face\_Ch810

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.896 mW/g



**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 10.7 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 1.14 W/kg

**SAR(1 g) = 0.791 mW/g; SAR(10 g) = 0.533 mW/g**

Maximum value of SAR (measured) = 0.841 mW/g



0 dB = 0.841mW/g

## #41 GSM1900\_GPRS10\_Front Face\_Ch810\_2D

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.896 mW/g

**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 10.7 V/m; Power Drift = -0.127 dB


Peak SAR (extrapolated) = 1.14 W/kg

**SAR(1 g) = 0.791 mW/g; SAR(10 g) = 0.533 mW/g**

Maximum value of SAR (measured) = 0.841 mW/g

# 1g/10g Averaged SAR

SAR, Zoom Scan: Value Along Z, X=1, Y=2



## #42 GSM1900\_GPRS10\_Rear Face\_Ch810

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.688 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 9.22 V/m; Power Drift = -0.133 dB

Peak SAR (extrapolated) = 0.986 W/kg

**SAR(1 g) = 0.638 mW/g; SAR(10 g) = 0.408 mW/g**

Maximum value of SAR (measured) = 0.693 mW/g



0 dB = 0.693mW/g



## #43 GSM1900\_GPRS10\_Top Side\_Ch810

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110530 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.26, 7.26, 7.26); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.087 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 7.39 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 0.134 W/kg

**SAR(1 g) = 0.083 mW/g; SAR(10 g) = 0.049 mW/g**

Maximum value of SAR (measured) = 0.089 mW/g



0 dB = 0.089mW/g

## #44 GSM1900\_GPRS10\_Down Side\_Ch810

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110530 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.26, 7.26, 7.26); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.274 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 13.6 V/m; Power Drift = 0.043 dB

Peak SAR (extrapolated) = 0.505 W/kg

**SAR(1 g) = 0.287 mW/g; SAR(10 g) = 0.161 mW/g**

Maximum value of SAR (measured) = 0.319 mW/g



0 dB = 0.319mW/g

## #45 GSM1900\_GPRS10\_Left Side\_Ch810

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.224 mW/g

**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 8.50 V/m; Power Drift = -0.131 dB

Peak SAR (extrapolated) = 0.356 W/kg

**SAR(1 g) = 0.235 mW/g; SAR(10 g) = 0.148 mW/g**

Maximum value of SAR (measured) = 0.255 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 8.50 V/m; Power Drift = -0.131 dB

Peak SAR (extrapolated) = 0.301 W/kg

**SAR(1 g) = 0.200 mW/g; SAR(10 g) = 0.124 mW/g**

Maximum value of SAR (measured) = 0.214 mW/g



0 dB = 0.214mW/g

## #46 GSM1900\_GPRS10\_Right Side\_Ch810

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.551 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 13.6 V/m; Power Drift = 0.188 dB

Peak SAR (extrapolated) = 0.811 W/kg

**SAR(1 g) = 0.520 mW/g; SAR(10 g) = 0.311 mW/g**

Maximum value of SAR (measured) = 0.572 mW/g



0 dB = 0.572mW/g



## #48 GSM1900\_GPRS10\_Front Face\_Ch810\_Earphone

**DUT: 142244-01**

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.54$   
mho/m;  $\epsilon_r = 52.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.820 mW/g


**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 8.51 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 1.11 W/kg

**SAR(1 g) = 0.773 mW/g; SAR(10 g) = 0.521 mW/g**

Maximum value of SAR (measured) = 0.821 mW/g



0 dB = 0.821mW/g

## #33 WCDMA V\_RMC12.2K\_Front Face\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.422 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 20.1 V/m; Power Drift = 0.043 dB

Peak SAR (extrapolated) = 0.495 W/kg

**SAR(1 g) = 0.401 mW/g; SAR(10 g) = 0.311 mW/g**

Maximum value of SAR (measured) = 0.420 mW/g



0 dB = 0.420mW/g

## #34 WCDMA V\_RMC12.2K\_Rear Face\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.568 mW/g



**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 23.4 V/m; Power Drift = -0.064 dB

Peak SAR (extrapolated) = 0.661 W/kg

**SAR(1 g) = 0.534 mW/g; SAR(10 g) = 0.408 mW/g**

Maximum value of SAR (measured) = 0.561 mW/g



0 dB = 0.561mW/g

## #34 WCDMA V\_RMC12.2K\_Rear Face\_Ch4132\_2D

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.568 mW/g



**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 23.4 V/m; Power Drift = -0.064 dB

Peak SAR (extrapolated) = 0.661 W/kg

**SAR(1 g) = 0.534 mW/g; SAR(10 g) = 0.408 mW/g**

Maximum value of SAR (measured) = 0.561 mW/g





## #35 WCDMA V\_RMC12.2K\_Top Side\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.022 mW/g

**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.99 V/m; Power Drift = 0.167 dB

Peak SAR (extrapolated) = 0.025 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.015 mW/g**

Maximum value of SAR (measured) = 0.021 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.99 V/m; Power Drift = 0.167 dB

Peak SAR (extrapolated) = 0.020 W/kg

**SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.012 mW/g**

Maximum value of SAR (measured) = 0.016 mW/g



0 dB = 0.016mW/g

## #36 WCDMA V\_RMC12.2K\_Down Side\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.087 mW/g



**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 8.46 V/m; Power Drift = 0.146 dB

Peak SAR (extrapolated) = 0.122 W/kg

**SAR(1 g) = 0.076 mW/g; SAR(10 g) = 0.050 mW/g**

Maximum value of SAR (measured) = 0.080 mW/g



0 dB = 0.080mW/g

## #37 WCDMA V\_RMC12.2K\_Left Side\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.456 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 21.8 V/m; Power Drift = -0.130 dB

Peak SAR (extrapolated) = 0.605 W/kg

**SAR(1 g) = 0.431 mW/g; SAR(10 g) = 0.300 mW/g**

Maximum value of SAR (measured) = 0.459 mW/g



0 dB = 0.459mW/g

## #38 WCDMA V\_RMC12.2K\_Right Side\_Ch4132

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.347 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.8 V/m; Power Drift = 0.004 dB

Peak SAR (extrapolated) = 0.459 W/kg

**SAR(1 g) = 0.329 mW/g; SAR(10 g) = 0.230 mW/g**

Maximum value of SAR (measured) = 0.352 mW/g



0 dB = 0.352mW/g



## #40 WCDMA V\_RMC12.2K\_Rear Face\_Ch4132\_Earphone

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_850\_110530 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.966$   
mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2010/10/22
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch4132/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.437 mW/g


**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 16.9 V/m; Power Drift = 0.105 dB

Peak SAR (extrapolated) = 0.568 W/kg

**SAR(1 g) = 0.365 mW/g; SAR(10 g) = 0.256 mW/g**

. Maximum value of SAR (measured) = 0.388 mW/g



0 dB = 0.388mW/g

## #49 WCDMA II\_RMC12.2K\_Front Face\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$   
mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 1.23 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 10.8 V/m; Power Drift = 0.067 dB

Peak SAR (extrapolated) = 1.62 W/kg

**SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.722 mW/g**

Maximum value of SAR (measured) = 1.17 mW/g



0 dB = 1.17mW/g

## #49 WCDMA II\_RMC12.2K\_Front Face\_Ch9400\_2D

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$   
mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 1.23 mW/g

**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 10.8 V/m; Power Drift = 0.067 dB


Peak SAR (extrapolated) = 1.62 W/kg

**SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.722 mW/g**

Maximum value of SAR (measured) = 1.17 mW/g

# 1g/10g Averaged SAR

SAR, Zoom Scan: Value Along Z, X=2, Y=2



## #50 WCDMA II\_RMC12.2K\_Rear Face\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (51x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.903 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.72 V/m; Power Drift = -0.095 dB

Peak SAR (extrapolated) = 1.26 W/kg

**SAR(1 g) = 0.833 mW/g; SAR(10 g) = 0.537 mW/g**

Maximum value of SAR (measured) = 0.893 mW/g



0 dB = 0.893mW/g



## #51 WCDMA II\_RMC12.2K\_Top Side\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$   
mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.224 mW/g



**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,  
dz=5mm

Reference Value = 11.9 V/m; Power Drift = -0.010 dB

Peak SAR (extrapolated) = 0.320 W/kg

**SAR(1 g) = 0.216 mW/g; SAR(10 g) = 0.136 mW/g**

Maximum value of SAR (measured) = 0.231 mW/g



0 dB = 0.231mW/g

## #52 WCDMA II\_RMC12.2K\_Down Side\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (31x51x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.454 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.4 V/m; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 0.760 W/kg

**SAR(1 g) = 0.474 mW/g; SAR(10 g) = 0.296 mW/g**

Maximum value of SAR (measured) = 0.503 mW/g



0 dB = 0.503mW/g

## #53 WCDMA II\_RMC12.2K\_Left Side\_Ch9400

**DUT: 142244-01**

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900\_110601 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3731; ConvF(7.13, 7.13, 7.13); Calibrated: 2010/9/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch9400/Area Scan (31x81x1):** Measurement grid: dx=20mm, dy=20mm  
Maximum value of SAR (interpolated) = 0.297 mW/g

**Ch9400/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.98 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 0.441 W/kg

**SAR(1 g) = 0.294 mW/g; SAR(10 g) = 0.186 mW/g**

Maximum value of SAR (measured) = 0.321 mW/g


**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.98 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 0.398 W/kg

**SAR(1 g) = 0.267 mW/g; SAR(10 g) = 0.167 mW/g**

Maximum value of SAR (measured) = 0.286 mW/g



0 dB = 0.286mW/g