



FCC TEST REPORT (PART 22)

REPORT NO.: RF110727C21B

MODEL NO.: PI39110

FCC ID: NM8PI39110

RECEIVED: Sep. 09, 2011

TESTED: Sep. 15 ~ Sep. 16, 2011

ISSUED: Sep. 19, 2011

APPLICANT: HTC Corporation

ADDRESS: 23, Xinghua Rd., Taoyuan 330, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 47 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agency. The test results in the report only apply to the tested sample.





A D T

TABLE OF CONTENTS

| | |
|---|----|
| RELEASE CONTROL RECORD..... | 4 |
| 1 CERTIFICATION | 5 |
| 2 SUMMARY OF TEST RESULTS | 6 |
| 2.1 MEASUREMENT UNCERTAINTY | 6 |
| 3 GENERAL INFORMATION..... | 7 |
| 3.1 GENERAL DESCRIPTION OF EUT | 7 |
| 3.2 DESCRIPTION OF TEST MODES..... | 8 |
| 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST | 8 |
| 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL | 9 |
| 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS | 11 |
| 3.4 DESCRIPTION OF SUPPORT UNITS | 11 |
| 4 TEST TYPES AND RESULTS | 12 |
| 4.1 OUTPUT POWER MEASUREMENT | 12 |
| 4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT | 12 |
| 4.1.2 TEST INSTRUMENTS..... | 13 |
| 4.1.3 TEST PROCEDURES | 14 |
| 4.1.4 TEST SETUP..... | 15 |
| 4.1.5 EUT OPERATING CONDITIONS | 15 |
| 4.1.6 TEST RESULTS | 16 |
| 4.2 FREQUENCY STABILITY MEASUREMENT..... | 17 |
| 4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT | 17 |
| 4.2.2 TEST INSTRUMENTS..... | 17 |
| 4.2.3 TEST PROCEDURE..... | 18 |
| 4.2.4 TEST SETUP..... | 18 |
| 4.2.5 TEST RESULTS | 19 |
| 4.3 OCCUPIED BANDWIDTH MEASUREMENT | 20 |
| 4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT | 20 |
| 4.3.2 TEST INSTRUMENTS..... | 20 |
| 4.3.3 TEST SETUP..... | 20 |
| 4.3.4 TEST PROCEDURES | 21 |
| 4.3.5 EUT OPERATING CONDITION | 21 |
| 4.3.6 TEST RESULTS | 22 |
| 4.4 BAND EDGE MEASUREMENT..... | 25 |
| 4.4.1 LIMITS OF BAND EDGE MEASUREMENT | 25 |
| 4.4.2 TEST INSTRUMENTS..... | 25 |
| 4.4.3 TEST SETUP..... | 25 |
| 4.4.4 TEST PROCEDURES | 26 |
| 4.4.5 EUT OPERATING CONDITION | 26 |
| 4.4.6 TEST RESULTS | 27 |



A D T

| | | |
|-------|--|----|
| 4.5 | CONDUCTED SPURIOUS EMISSIONS | 30 |
| 4.5.1 | LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT | 30 |
| 4.5.2 | TEST INSTRUMENTS..... | 30 |
| 4.5.3 | TEST PROCEDURE..... | 31 |
| 4.5.4 | TEST SETUP..... | 31 |
| 4.5.5 | EUT OPERATING CONDITIONS | 31 |
| 4.5.6 | TEST RESULTS | 32 |
| 4.6 | RADIATED EMISSION MEASUREMENT | 38 |
| 4.6.1 | LIMITS OF RADIATED EMISSION MEASUREMENT | 38 |
| 4.6.2 | TEST INSTRUMENTS..... | 38 |
| 4.6.3 | TEST PROCEDURES | 39 |
| 4.6.4 | DEVIATION FROM TEST STANDARD | 39 |
| 4.6.5 | TEST SETUP..... | 40 |
| 4.6.6 | EUT OPERATING CONDITIONS | 40 |
| 4.6.7 | TEST RESULTS (FREQUENCY RANGE BELOW 1GHz) | 41 |
| 4.6.8 | TEST RESULTS (FREQUENCY RANGE ABOVE 1GHz) | 42 |
| 5 | PHOTOGRAPHS OF THE TEST CONFIGURATION..... | 45 |
| 6 | INFORMATION ON THE TESTING LABORATORIES | 46 |
| 7 | APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB..... | 47 |



A D T

RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|------------------|-------------------|---------------|
| Original release | N/A | Sep. 16, 2011 |



1 CERTIFICATION

PRODUCT: Windows Phone

MODEL: PI39110

BRAND: HTC

APPLICANT: HTC Corporation

TEST SAMPLE: Production Unit

TESTED : Sep. 15 ~ Sep. 16, 2011

STANDARDS : FCC Part 22, Subpart H
ANSI C63.4-2003

This report is issued as a supplementary report of **RF110727C21-2**. This report shall be used combined together with its original report.

PREPARED BY :  , DATE : Sep. 16, 2011
Pettie Chen / Specialist

APPROVED BY :  , DATE : Sep. 16, 2011
Gary Chang / Technical Manager

NOTE: The only the testing for WCDMA band V was performed for this addendum. Refer to original report for the other test data.

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 22 & Part 2 | | | |
|--|--|--------|--|
| STANDARD SECTION | TEST TYPE AND LIMIT | RESULT | REMARK |
| 2.1046 22.913 (a) | Maximum Peak Output Power Limit: max. 7 watts e.r.p peak power | PASS | Meet the requirement of limit. Max. e.r.p is 14.0dBm at 846.6MHz. |
| 2.1055 | Frequency Stability AFC Freq. Error vs. Voltage AFC Freq. Error vs. Temperature Limit: max. ± 2.5 ppm | PASS | Meet the requirement of limit. |
| 2.1049 (h) | Occupied Bandwidth | PASS | Meet the requirement of limit. |
| 22.917 | Band Edge Measurements | PASS | Meet the requirement of limit. |
| 2.1051 22.917 | Conducted Spurious Emissions | PASS | Meet the requirement of limit. |
| 2.1053 22.917 | Radiated Spurious Emissions | PASS | Meet the requirement of limit. Minimum passing margin is -27.8dB at 2509.2MHz. |

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT | FREQUENCY | UNCERTAINTY |
|---------------------|-----------------|-------------|
| Conducted emissions | 9kHz~30MHz | 2.44 dB |
| Radiated emissions | 30MHz ~ 200MHz | 3.34 dB |
| | 200MHz ~1000MHz | 3.35 dB |
| | 1GHz ~ 18GHz | 2.26 dB |
| | 18GHz ~ 40GHz | 1.94 dB |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | | |
|-----------------------|--|---------------------|
| EUT | Windows Phone | |
| MODEL NO. | PI39110 | |
| FCC ID | NM8PI39110 | |
| POWER SUPPLY | 5.0Vdc (adapter or host equipment) 3.8Vdc (battery) | |
| MODULATION TYPE | WCDMA | BPSK |
| FREQUENCY RANGE | WCDMA | 826.4MHz ~ 846.6MHz |
| MAX. ERP POWER | WCDMA | 0.0251 Watts |
| WCDMA RELEASE VERSION | 6 | |
| ANTENNA TYPE | Fixed antenna with 0dBi gain | |
| I/O PORTS | Refer to users' manual | |
| DATA CABLE | Refer to Note as below | |
| ACCESSORY DEVICES | Refer to Note as below | |

NOTE:

1. This is a supplementary report of RF110727C21-2. This report shall be combined together with its original report.
2. This report is prepared for FCC class II permissive change. Difference compared with the original report is adding WCDMA Band V by software enabled. Therefore, only the testing for WCDMA band V was performed for this addendum.
3. The EUT's accessories list refers to Ext Pho_NM8PI39110.pdf.
** Main Sample + Items of 1, 4, 5 and 7 are the worst combination for final test.
4. IMEI Code: 35803504*****.
5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

FOR WCDMA:


102 channels are provided to this EUT. Therefore, the low, middle and high channels are chosen for testing.

| | CHANNEL | FREQUENCY | TX MODE |
|--------|---------|-----------|---------------------|
| LOW | 4132 | 826.4 MHz | WCDMA, HSDPA, HSUPA |
| MIDDLE | 4182 | 836.4 MHz | WCDMA, HSDPA, HSUPA |
| HIGH | 4233 | 846.6 MHz | WCDMA, HSDPA, HSUPA |

NOTE:

1. Below 1 GHz, the channel 4132, 4182 and 4233 were pre-tested in chamber. The channel 4233 was chosen for final test.
2. Above 1 GHz, the channel 4132, 4182 and 4233 were tested individually.
3. The channel space is 0.2MHz.
4. After pretest of output power and spurious emission under WCDMA-RMC, HSDPA & HSUPA mode, find the worst mode is WCDMA-RMC. Therefore, select WCDMA-RMC mode to do final test

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

FOR WCDMA:

| EUT CONFIGURE MODE | APPLICABLE TO | | | | | | | DESCRIPTION |
|--------------------|---------------|----|----|----|----|-------|-------|-------------|
| | OP | FS | OB | BE | CE | RE<1G | RE≥1G | |
| - | √ | √ | √ | √ | √ | √ | √ | - |

Where **OP**: Output power **FS**: Frequency stability
OB: Occupied bandwidth **BE**: Band edge
CE: Conducted spurious emissions **RE<1G**: Radiated emission below 1GHz
RE≥1G: Radiated emission above 1GHz

OUTPUT POWER MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | AXIS |
|-------------------|------------------|-----------------------|------|
| 4132 to 4233 | 4132, 4182, 4233 | WCDMA | Z |

FREQUENCY STABILITY MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY |
|-------------------|----------------|-----------------------|
| 4132 to 4233 | 4182 | WCDMA |

OCCUPIED BANDWIDTH MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY |
|-------------------|------------------|-----------------------|
| 4132 to 4233 | 4132, 4182, 4233 | WCDMA, HSDPA, HSUPA |

BAND EDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY |
|-------------------|----------------|-----------------------|
| 4132 to 4233 | 4132, 4233 | WCDMA |

CONDUCTED SPURIOUS EMISSIONS MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY |
|-------------------|------------------|-----------------------|
| 4132 to 4233 | 4132, 4182, 4233 | WCDMA |

RADIATED EMISSION MEASUREMENT (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | AXIS |
|-------------------|----------------|-----------------------|------|
| 4132 to 4233 | 4233 | WCDMA | Z |

RADIATED EMISSION MEASUREMENT (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | AXIS |
|-------------------|------------------|-----------------------|------|
| 4132 to 4233 | 4132, 4182, 4233 | WCDMA | Z |

TEST CONDITION:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER | TESTED BY |
|---------------|--------------------------|--------------|-----------|
| OP | 25deg. C, 65%RH | 3.8Vdc | Kay Wu |
| FS | 25deg. C, 65%RH | 3.8Vdc | Kay Wu |
| OB | 25deg. C, 65%RH | 3.8Vdc | Kay Wu |
| EM | 25deg. C, 65%RH | 3.8Vdc | Kay Wu |
| BE | 25deg. C, 65%RH | 3.8Vdc | Kay Wu |
| CE | 25deg. C, 65%RH | 3.8Vdc | Kay Wu |
| RE < 1G | 25deg. C, 65%RH | 120Vac, 60Hz | Kay Wu |
| RE ≥ 1G | 25deg. C, 65%RH | 120Vac, 60Hz | Kay Wu |

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

ANSI C63.4-2003

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO. | FCC ID |
|-----|--------------------------------------|-------|-----------|------------|--------|
| 1 | UNIVERSAL RADIO COMMUNICATION TESTER | R&S | CMU200 | 104484 | NA |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|---|
| 1 | NA |

NOTE 1: All power cords of the above support units are non shielded (1.8m).

NOTE 2: Item 1 acted as a communication partner to transfer data.

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

The radiated peak output power shall be according to the specific rule Part 22.913 (a) that "Mobile / Portable station are limited to 7 watts e.r.p".

4.1.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|---|------------------------------|-------------|---------------------|-------------------------|
| Test Receiver ROHDE & SCHWARZ | ESIB7 | 100212 | Aug. 02, 2011 | Aug. 01, 2012 |
| Spectrum Analyzer ROHDE & SCHWARZ | FSP 40 | 100041 | Jul. 21, 2011 | Jul. 20, 2012 |
| BILOG Antenna SCHWARZBECK | VULB9168 | 9168-160 | Apr. 13, 2011 | Apr. 12, 2012 |
| HORN Antenna SCHWARZBECK | 9120D | 209 | Aug. 25, 2011 | Aug. 24, 2012 |
| HORN Antenna SCHWARZBECK | BBHA 9170 | BBHA9170243 | Dec. 27, 2010 | Dec. 26, 2011 |
| Preamplifier Agilent | 8447D | 2944A10633 | Nov. 02, 2010 | Nov. 01, 2011 |
| Preamplifier Agilent | 8449B | 3008A01964 | Nov. 02, 2010 | Nov. 01, 2011 |
| RF signal cable HUBER+SUHNNER | SUCOFLEX 104 | 295014/4 | Aug. 19, 2011 | Aug. 18, 2012 |
| RF signal cable HUBER+SUHNNER | SUCOFLEX 104 | 12738/6 | Aug. 19, 2011 | Aug. 18, 2012 |
| Software ADT. | ADT_Radiated_ V7.6.15.9.2 | NA | NA | NA |
| Antenna Tower inn-co GmbH | MA 4000 | 013303 | NA | NA |
| Antenna Tower Controller inn-co GmbH | CO2000 | 017303 | NA | NA |
| Turn Table ADT. | TT100. | TT93021703 | NA | NA |
| Turn Table Controller ADT. | SC100. | SC93021703 | NA | NA |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 3.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 988962.
 5. The IC Site Registration No. is IC 7450F-3.

4.1.3 TEST PROCEDURES

EIRP / ERP MEASUREMENT:


- a. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels, 4132, 4182 and 4233. RWB and VBW are 5MHz.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step c. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$
- e. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,
 $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi.}$

CONDUCTED POWER MEASUREMENT:

- a. The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.4 TEST SETUP

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.5 EUT OPERATING CONDITIONS

- a. The EUT makes a call to the communication simulator.
- b. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

4.1.6 TEST RESULTS

CONDUCTED POWER

| Band | WCDMA V | | |
|-----------------|---------|-------|-------|
| | Channel | 4132 | 4182 |
| Rx Channel | 4357 | 4407 | 4458 |
| Frequency | 826.4 | 836.4 | 846.6 |
| RMC 12.2K | 23.35 | 23.54 | 23.45 |
| HSDPA Subtest-1 | 23.26 | 23.45 | 23.42 |
| HSDPA Subtest-2 | 21.47 | 21.62 | 21.61 |
| HSDPA Subtest-3 | 20.23 | 20.44 | 20.45 |
| HSDPA Subtest-4 | 20.02 | 20.21 | 20.19 |
| HSUPA Subtest-1 | 23.04 | 22.68 | 23.05 |
| HSUPA Subtest-2 | 21.45 | 21.95 | 21.84 |
| HSUPA Subtest-3 | 22.11 | 22.09 | 22.27 |
| HSUPA Subtest-4 | 22.31 | 22.35 | 22.41 |
| HSUPA Subtest-5 | 23.33 | 23.46 | 23.45 |

ERP POWER

WCDMA-RMC MODE

| ERP POWER | | | | | |
|-------------|-----------------|-----------------|------------------------|--------------|--------|
| CHANNEL NO. | FREQUENCY (MHz) | S.G VALUE (dBm) | CORRECTION FACTOR (dB) | OUTPUT POWER | |
| | | | | dBm | Watt |
| 4132 | 826.4 | 22.0 | -8.6 | 13.4 | 0.0219 |
| 4182 | 836.4 | 22.1 | -8.6 | 13.5 | 0.0224 |
| 4233 | 846.6 | 22.7 | -8.7 | 14.0 | 0.0251 |

REMARKS: 1. Output Power (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

According to the FCC part 22.863 shall be tested the frequency stability. The rule is defined that "The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block." The frequency error rate is according to the JTC standard that the frequency error rate shall be accurate to within 2.5ppm of the received frequency from the base station. The test extreme voltage is according to the 2.1055(d)(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment and the extreme temperature rule is comply with the 2.1055(a)(1) $-30^{\circ}\text{C} \sim 55^{\circ}\text{C}$.

4.2.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|---|--------------|------------|---------------------|-------------------------|
| Spectrum Analyzer Agilent | E4446A | MY43360128 | Feb. 22, 2011 | Feb. 21, 2012 |
| Hewlett Packard RF cable | 8120-6192 | 01428251 | NA | NA |
| RF cable | SUCOFLEX 104 | 257029 | Sep. 11, 2011 | Sep. 10, 2012 |
| WIT Standard Temperature & Humidity Chamber | MHU-225AU | 920842 | Jun. 15, 2011 | Jun. 14, 2012 |


NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.2.3 TEST PROCEDURE

- a. Because of the measure the carrier frequency under the condition of the AFC lock, it shall be used the mobile station in the WCDMA link mode. This is accomplished with the use of the R&S CMU200. The oven room could control the temperatures and humidity. The WCDMA link channel is the 4182.
- b. Power must be removed when changing from one temperature to another or one voltage to another voltage. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- c. EUT is connected the external power supply to control the DC input power. The various Volts from the minimum 3.6Volts to 4.35Volts. Each step shall be record the frequency error rate.
- d. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing.
- e. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.4 TEST SETUP



4.2.5 TEST RESULTS

FOR WCDMA:

| AFC FREQUENCY ERROR vs. VOLTAGE | | | |
|---------------------------------|----------------------|-----------------------|-------------|
| VOLTAGE (Volts) | FREQUENCY ERROR (Hz) | FREQUENCY ERROR (ppm) | LIMIT (ppm) |
| 4.35 | -6 | -0.007 | 2.5 |
| 3.6 | -8 | -0.010 | 2.5 |

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.35Vdc.

| AFC FREQUENCY ERROR vs. TEMP. | | | |
|-------------------------------|----------------------|-----------------------|-------------|
| TEMP. (°C) | FREQUENCY ERROR (Hz) | FREQUENCY ERROR (ppm) | LIMIT (ppm) |
| 55 | -28 | -0.033 | 2.5 |
| 50 | -23 | -0.027 | 2.5 |
| 40 | -17 | -0.020 | 2.5 |
| 30 | -15 | -0.018 | 2.5 |
| 20 | -9 | -0.011 | 2.5 |
| 10 | -5 | -0.006 | 2.5 |
| 0 | -3 | -0.004 | 2.5 |
| -10 | -1 | -0.001 | 2.5 |
| -20 | 0 | 0.000 | 2.5 |
| -30 | 4 | 0.005 | 2.5 |

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT


The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the totalmean power of a given emission.

4.3.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|------------------------------|--------------|------------|---------------------|-------------------------|
| SPECTRUM ANALYZER R&S | FSP40 | 100039 | Jan. 11, 2011 | Jan. 10, 2012 |
| Mini-Circuits Power Splitter | ZN2PD-9G | NA | Mar. 24, 2011 | Mar. 23, 2012 |
| RF cable | SUCOFLEX 104 | 274403/4 | Aug. 20, 2011 | Aug. 19, 2012 |
| RF cable | SUCOFLEX 104 | 250729/4 | Aug. 19, 2011 | Aug. 18, 2012 |
| RF cable | SUCOFLEX 104 | 214377/4 | Aug. 19, 2011 | Aug. 18, 2012 |
| JFW 20dB attenuation | 50HF-020-SMA | NA | NA | NA |

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST SETUP



4.3.4 TEST PROCEDURES

- a. The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels, 4132, 4182 and 4233 (WCDMA) (low, middle and high operational frequency range.)
- b. The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- c. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.5 EUT OPERATING CONDITION

- a. The EUT makes a call to the communication simulator.
- b. The communication simulator station system controlled a EUT to export maximum and minimum output power under transmission mode and specific channel frequency.


4.3.6 TEST RESULTS

FOR WCDMA:

FOR WCDMA-RMC:

| CHANNEL | FREQUENCY (MHz) | 99% OCCUPIED BANDWIDTH (MHz) |
|---------|-----------------|------------------------------|
| 4132 | 826.4 | 4.14 |
| 4182 | 836.4 | 4.16 |
| 4233 | 846.6 | 4.14 |

CH 4182






A D T

FOR HSDPA:

| CHANNEL | FREQUENCY (MHz) | 99% OCCUPIED BANDWIDTH (MHz) |
|---------|-----------------|------------------------------|
| 4132 | 826.4 | 4.14 |
| 4182 | 836.4 | 4.16 |
| 4233 | 846.6 | 4.14 |


CH 4182



FOR HSUPA:

| CHANNEL | FREQUENCY (MHz) | 99% OCCUPIED BANDWIDTH (MHz) |
|---------|-----------------|------------------------------|
| 4132 | 826.4 | 4.16 |
| 4182 | 836.4 | 4.16 |
| 4233 | 846.6 | 4.14 |

CH 4132



4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT


According to FCC 22.917 specified that power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|------------------------------|--------------|------------|---------------------|-------------------------|
| SPECTRUM ANALYZER R&S | FSP40 | 100039 | Jan. 11, 2011 | Jan. 10, 2012 |
| Mini-Circuits Power Splitter | ZN2PD-9G | NA | Mar. 24, 2011 | Mar. 23, 2012 |
| RF cable | SUCOFLEX 104 | 274403/4 | Aug. 20, 2011 | Aug. 19, 2012 |
| RF cable | SUCOFLEX 104 | 250729/4 | Aug. 19, 2011 | Aug. 18, 2012 |
| RF cable | SUCOFLEX 104 | 214377/4 | Aug. 19, 2011 | Aug. 18, 2012 |
| JFW 20dB attenuation | 50HF-020-SMA | NA | NA | NA |

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST SETUP



4.4.4 TEST PROCEDURES

- a. The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels, 4132 and 4233.
- b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz.
- d. Record the max trace plot into the test report.

4.4.5 EUT OPERATING CONDITION


- a. The EUT makes a phone call to the communication simulator.
- b. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

4.4.6 TEST RESULTS


FOR WCDMA:

WCDMA-RMC MODE

LOWER BAND EDGE



HIGHER BAND EDGE







A D T

HSDPA MODE

LOWER BAND EDGE



HIGHER BAND EDGE







A D T

HSUPA MODE

LOWER BAND EDGE



HIGHER BAND EDGE





4.5 CONDUCTED SPURIOUS EMISSIONS

4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

In the FCC 22.917, On any frequency outside a licensee's frequency block within GPRS spectrum, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. The emission limit equal to -13dBm .

4.5.2 TEST INSTRUMENTS


| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|------------------------------|--------------|------------|---------------------|-------------------------|
| SPECTRUM ANALYZER R&S | FSP40 | 100039 | Feb. 23, 2011 | Feb. 22, 2012 |
| Mini-Circuits Power Splitter | ZN2PD-9G | NA | Mar. 24, 2011 | Mar. 23, 2012 |
| RF cable | SUCOFLEX 104 | 274403/4 | Aug. 20, 2011 | Aug. 19, 2012 |
| RF cable | SUCOFLEX 104 | 250729/4 | Aug. 19, 2011 | Aug. 18, 2012 |
| RF cable | SUCOFLEX 104 | 214377/4 | Aug. 19, 2011 | Aug. 18, 2012 |
| JFW 20dB attenuation | 50HF-020-SMA | NA | NA | NA |

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels, 4132, 4182 and 4233 (low, middle and high operational frequency range.)
- b. The conducted spurious emission used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- c. Measuring frequency range is from 9 kHz to 9GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.5.4 TEST SETUP




4.5.5 EUT OPERATING CONDITIONS

- a. The EUT makes a call to the communication simulator.
- b. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.


4.5.6 TEST RESULTS

FOR WCDMA-RMC:

CH 4132: 9kHz ~ 1GHz




1GHz ~ 4GHz






A D T

4GHz ~ 7GHz




7GHz ~ 9GHz






A D T

CH 4182: 9kHz ~ 1GHz




1GHz ~ 4GHz






A D T


4GHz ~ 7GHz




7GHz ~ 9GHz



CH 4233: 9kHz ~ 1GHz




1GHz ~ 4GHz






A D T

4GHz ~ 7GHz



7GHz ~ 9GHz



4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

In the FCC 22.917 (a), On any frequency outside a licensee's frequency block within GPRS spectrum, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. The emission limit equal to -13dBm .

4.6.2 TEST INSTRUMENTS

Same as 4.1.2.

4.6.3 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step c. Record the power level of S.G
- c. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,
 $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi.}$

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.6.6 EUT OPERATING CONDITIONS

- a. The EUT makes a call to the communication simulator.
- b. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.



4.6.7 TEST RESULTS (Frequency range below 1GHz)

| | | | |
|---------------------------------|-----------------|------------------------|---------------|
| MODE | TX channel 4233 | FREQUENCY RANGE | Below 1000MHz |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | INPUT POWER | 120Vac, 60 Hz |
| TESTED BY | Kay Wu | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | |
|---|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBUV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 82.48 | 37.0 | -13.0 | -59.5 | -7.7 | -67.2 |
| 2 | 121.36 | 44.2 | -13.0 | -58.0 | -7.7 | -65.7 |
| 3 | 142.75 | 45.2 | -13.0 | -63.0 | -7.7 | -70.7 |
| 4 | 206.89 | 43.0 | -13.0 | -60.7 | -7.7 | -68.4 |
| 5 | 271.04 | 42.0 | -13.0 | -54.2 | -7.7 | -61.9 |
| 6 | 414.89 | 36.6 | -13.0 | -50.7 | -7.8 | -58.5 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | |
| No. | Freq. (MHz) | Emission Level (dBUV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 43.61 | 40.1 | -13.0 | -50.4 | -7.7 | -58.1 |
| 2 | 82.48 | 36.7 | -13.0 | -54.7 | -7.7 | -62.4 |
| 3 | 123.31 | 42.6 | -13.0 | -59.4 | -7.7 | -67.1 |
| 4 | 169.96 | 39.9 | -13.0 | -59.7 | -7.7 | -67.4 |
| 5 | 214.67 | 43.4 | -13.0 | -58.7 | -7.7 | -66.4 |
| 6 | 329.36 | 35.9 | -13.0 | -49.5 | -7.8 | -57.3 |

NOTE: Power Value (dBum) = S.G Power Value (dBm) + Correction Factor (dB).

4.6.8 TEST RESULTS (Frequency range above 1GHz)

| | | | |
|---------------------------------|-----------------|------------------------|---------------|
| MODE | TX channel 4132 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | INPUT POWER | 120Vac, 60 Hz |
| TESTED BY | Mark Liao | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | |
|---|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBUV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 1652.8 | 39.0 | -13.0 | -62.9 | 7.6 | -55.3 |
| 2 | 2479.2 | 42.7 | -13.0 | -60.1 | 8.4 | -51.7 |
| 3 | 3305.6 | 40.8 | -13.0 | -63.3 | 9.9 | -53.4 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | |
| No. | Freq. (MHz) | Emission Level (dBUV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 1652.8 | 44.4 | -13.0 | -57.5 | 7.6 | -49.9 |
| 2 | 2479.2 | 41.7 | -13.0 | -61.1 | 8.4 | -52.7 |
| 3 | 3305.6 | 41.0 | -13.0 | -63.1 | 9.9 | -53.2 |

REMARKS: 1. Output Power (dBm) = S.G Value (dBm) + Correction Factor (dB).

2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



A D T

| | | | |
|---------------------------------|-----------------|------------------------|---------------|
| MODE | TX channel 4182 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | INPUT POWER | 120Vac, 60 Hz |
| TESTED BY | Mark Liao | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | |
|--|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 1672.8 | 40.8 | -13.0 | -61.3 | 7.7 | -53.6 |
| 2 | 2509.2 | 44.8 | -13.0 | -57.9 | 8.4 | -49.5 |
| 3 | 3345.6 | 40.9 | -13.0 | -63.5 | 9.9 | -53.6 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | |
| No. | Freq. (MHz) | Emission Level (dBuV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 1672.8 | 48.1 | -13.0 | -54.0 | 7.7 | -46.3 |
| 2 | 2509.2 | 53.5 | -13.0 | -49.2 | 8.4 | -40.8 |
| 3 | 3345.6 | 39.4 | -13.0 | -65.0 | 9.9 | -55.1 |

REMARKS: 1. Output Power (dBm) = S.G Value (dBm) + Correction Factor (dB).

2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



A D T

| | | | |
|---------------------------------|-----------------|------------------------|---------------|
| MODE | TX channel 4233 | FREQUENCY RANGE | Above 1000MHz |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | INPUT POWER | 120Vac, 60 Hz |
| TESTED BY | Mark Liao | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | |
|--|-------------|-----------------------|-------------|-----------------------|------------------------|-------------------|
| No. | Freq. (MHz) | Emission Level (dBUV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 1693.2 | 38.0 | -13.0 | -64.1 | 7.9 | -56.2 |
| 2 | 2539.8 | 41.0 | -13.0 | -61.9 | 8.5 | -53.4 |
| 3 | 3386.4 | 41.6 | -13.0 | -62.6 | 9.9 | -52.7 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | |
| No. | Freq. (MHz) | Emission Level (dBUV) | Limit (dBm) | S.G Power Value (dBm) | Correction Factor (dB) | Power Value (dBm) |
| 1 | 1693.2 | 42.6 | -13.0 | -59.5 | 7.9 | -51.6 |
| 2 | 2539.8 | 41.5 | -13.0 | -61.4 | 8.5 | -52.9 |
| 3 | 3386.4 | 41.3 | -13.0 | -62.9 | 9.9 | -53.0 |

REMARKS: 1. Output Power (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5.phtml.
If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050
Email: service.adt@tw.bureauveritas.com
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---