



A D T

FCC TEST REPORT (BLUETOOTH)

REPORT NO.: RF121129C09-3

MODEL NO.: PN07130

FCC ID: NM8PN07130

RECEIVED: Nov. 29, 2012

TESTED: Dec. 24, 2012 ~ Jan. 21, 2013

ISSUED: Jan. 31, 2013

APPLICANT: HTC Corporation

ADDRESS: 23, Xinghua Rd., Taoyuan 330, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

Table of Contents

RELEASE CONTROL RECORD.....	6
1. CERTIFICATION.....	7
2. SUMMARY OF TEST RESULTS.....	8
2.1 MEASUREMENT UNCERTAINTY	9
3. GENERAL INFORMATION.....	10
3.1 GENERAL DESCRIPTION OF EUT.....	10
3.2 DESCRIPTION OF TEST MODES.....	11
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	12
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
3.4 DESCRIPTION OF SUPPORT UNITS	16
3.4.1 CONFIGURATION OF SYSTEM UNDER TEST.....	16
4. TEST TYPES AND RESULTS (FOR Bluetooth EDR)	17
4.1 Radiated Emission AND BANDEdge Measurement	17
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT ...	17
4.1.2 TEST INSTRUMENTS.....	18
4.1.3 TEST PROCEDURES	19
4.1.4 DEVIATION FROM TEST STANDARD.....	19
4.1.5 TEST SETUP	20
4.1.6 EUT OPERATING CONDITIONS	20
4.1.7 TEST RESULTS	21
4.2 CONDUCTED EMISSION MEASUREMENT	31
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	31
4.2.2 TEST INSTRUMENTS.....	31
4.2.3 TEST PROCEDURES	32
4.2.4 DEVIATION FROM TEST STANDARD.....	32
4.2.5 TEST SETUP	33
4.2.6 EUT OPERATING CONDITIONS	33
4.2.7 TEST RESULTS	34
4.3 NUMBER OF HOPPING FREQUENCY USED	36
4.3.1 LIMIT OF HOPPING FREQUENCY USED	36
4.3.2 TEST SETUP	36
4.3.3 TEST INSTRUMENTS.....	36
4.3.4 TEST PROCEDURES	36
4.3.5 DEVIATION FROM TEST STANDARD.....	36
4.3.6 TEST RESULTS	36
4.4 DWELL TIME ON EACH CHANNEL	38
4.4.1 LIMIT OF DWELL TIME USED	38



A D T

4.4.2 TEST SETUP	38
4.4.3 TEST INSTRUMENTS.....	38
4.4.4 TEST PROCEDURES	38
4.4.5 DEVIATION FROM TEST STANDARD.....	38
4.4.6 TEST RESULTS	39
4.5 CHANNEL BANDWIDTH.....	42
4.5.1 LIMITS OF CHANNEL BANDWIDTH.....	42
4.5.2 TEST SETUP	42
4.5.3 TEST INSTRUMENTS.....	42
4.5.4 TEST PROCEDURE	42
4.5.5 DEVIATION FROM TEST STANDARD.....	42
4.5.6 EUT OPERATING CONDITION.....	42
4.5.7 TEST RESULTS	43
4.6 HOPPING CHANNEL SEPARATION	44
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION.....	44
4.6.2 TEST SETUP	44
4.6.3 TEST INSTRUMENTS.....	44
4.6.4 TEST PROCEDURES	44
4.6.5 DEVIATION FROM TEST STANDARD.....	44
4.6.6 TEST RESULTS	45
4.7 MAXIMUM OUTPUT POWER	46
4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	46
4.7.2 TEST SETUP	46
4.7.3 TEST INSTRUMENTS.....	46
4.7.4 TEST PROCEDURES	46
4.7.5 DEVIATION FROM TEST STANDARD.....	46
4.7.6 EUT OPERATING CONDITION.....	46
4.7.7 TEST RESULTS	47
4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	48
4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT ..	48
4.8.2 TEST INSTRUMENTS.....	48
4.8.3 TEST PROCEDURE	48
4.8.4 DEVIATION FROM TEST STANDARD.....	48
4.8.5 EUT OPERATING CONDITION.....	48
4.8.6 TEST RESULTS	48
5. TEST TYPES AND RESULTS (FOR Bluetooth LE 4.0)	52
5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT	52
5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT ...	52



A D T

5.1.2 TEST INSTRUMENTS	52
5.1.3 TEST PROCEDURES	53
5.1.4 DEVIATION FROM TEST STANDARD	53
5.1.5 TEST SETUP	54
5.1.6 EUT OPERATING CONDITIONS	54
5.1.7 TEST RESULTS	55
5.2 CONDUCTED EMISSION MEASUREMENT	65
5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	65
5.2.2 TEST INSTRUMENTS	65
5.2.3 TEST PROCEDURES	65
5.2.4 DEVIATION FROM TEST STANDARD	65
5.2.5 TEST SETUP	65
5.2.6 EUT OPERATING CONDITIONS	65
5.2.7 TEST RESULTS	66
5.3 6dB BANDWIDTH MEASUREMENT	68
5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	68
5.3.2 TEST SETUP	68
5.3.3 TEST INSTRUMENTS	68
5.3.4 TEST PROCEDURE	68
5.3.5 DEVIATION FROM TEST STANDARD	68
5.3.6 EUT OPERATING CONDITIONS	68
5.3.7 TEST RESULTS	69
5.4 CONDUCTED OUTPUT POWER	70
5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	70
5.4.2 TEST SETUP	70
5.4.3 TEST INSTRUMENTS	70
5.4.4 TEST PROCEDURES	70
5.4.5 DEVIATION FROM TEST STANDARD	70
5.4.6 EUT OPERATING CONDITIONS	70
5.4.7 TEST RESULTS	70
5.5 POWER SPECTRAL DENSITY MEASUREMENT	71
5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	71
5.5.2 TEST SETUP	71
5.5.3 TEST INSTRUMENTS	71
5.5.4 TEST PROCEDURE	71
5.5.5 DEVIATION FROM TEST STANDARD	71
5.5.6 EUT OPERATING CONDITION	71
5.5.7 TEST RESULTS	71



A D T

5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	72
5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT.....	72
5.6.2 TEST SETUP	72
5.6.3 TEST INSTRUMENTS.....	72
5.6.4 TEST PROCEDURE	72
5.6.5 DEVIATION FROM TEST STANDARD.....	73
5.6.6 EUT OPERATING CONDITION.....	73
5.6.7 TEST RESULTS	73
5.6.8 TEST RESULTS	74
6. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	75
7. INFORMATION ON THE TESTING LABORATORIES	76
8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	77



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF121129C09-3	Original release	Jan. 31, 2013



1. CERTIFICATION

PRODUCT: Smartphone

MODEL NO.: PN07130

BRAND: HTC

APPLICANT: HTC Corporation

TESTED: Dec. 24, 2012 ~ Jan. 21, 2013

TEST SAMPLE: Production Unit

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment (model: PN07130) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Vera Huang, **DATE :** Jan. 31, 2013

Vera Huang / Specialist

APPROVED BY : Anderson Chiu, **DATE :** Jan. 31, 2013

Anderson Chiu / Senior Engineer



A D T

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Bluetooth EDR)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.74dB at 0.51719MHz.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -8.13dB at 42.69MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) (Bluetooth LE 4.0)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.40dB at 0.51328MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -8.13dB at 42.69MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.



A D T

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Smartphone	
MODEL NO.	PN07130	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion battery)	
MODULATION TYPE	Bluetooth EDR	GFSK, $\pi/4$ -DQPSK, 8DPSK
	Bluetooth LE 4.0	GFSK
TRANSFER RATE	Bluetooth EDR	1/2/3Mbps
	Bluetooth LE 4.0	1Mbps
OPERATING FREQUENCY	2402 ~ 2480MHz	
NUMBER OF CHANNEL	Bluetooth EDR	79
	Bluetooth LE 4.0	40
CHANNEL SPACING	Bluetooth EDR	1MHz
	Bluetooth LE 4.0	2MHz
OUTPUT POWER	Bluetooth EDR	3.459mW
	Bluetooth LE 4.0	0.984mW
ANTENNA TYPE	PIFA antenna with -1dBi gain	
ANTENNA CONNECTOR	NA	
DATA CABLE	Refer to Note as below	
I/O PORTS	Refer to user's manual	
ACCESSORY DEVICES	Refer to Note as below	

NOTE:

1. The EUT's accessories list refers to Ext. Pho.
2. The device has 2 configurations as below.
 - Main Sample (A): Battery 1 + LCD Panel 1 + Front Camera 1
 - 2nd Sample (B): Battery 2 + LCD Panel 2 + Front Camera 2
3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 DESCRIPTION OF TEST MODES

For Bluetooth EDR:

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

For Bluetooth LE 4.0:

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

For Bluetooth EDR:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	Main Sample
B	√	-	-	-	2nd Sample

Where RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

APCM: Antenna Port Conducted Measurement

NOTE: 1. For Radiated emission test, pre-tested GFSK, π/4-DQPSK, 8DPSK modulation type and found GFSK was

the worst, therefore chosen for the final test and presented in the test report.

2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	GFSK	DH5
B	0 to 78	78	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	39	GFSK	DH5

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	39	GFSK	DH5



A D T

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	GFSK	DH5
A	0 to 78	0, 39, 78	$\pi/4$ -DQPSK	DH5
A	0 to 78	0, 39, 78	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
PLC	25deg. C, 65%RH	120Vac, 60Hz	David Huang
APCM	25deg. C, 65%RH	120Vac, 60Hz	Phoenix Chen



A D T

FOR Bluetooth LE 4.0:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE $<$ 1G	PLC	APCM	
A	✓	✓	✓	✓	Main Sample
B	✓	-	-	-	2nd Sample

Where RE \geq 1G: Radiated Emission above 1GHzRE $<$ 1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.**RADIATED EMISSION TEST (ABOVE 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	ATA RATE (Mbps)
A	0 to 39	0, 19, 39	GFSK	1.0
B	0 to 39	0	GFSK	1.0

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	ATA RATE (Mbps)
A	0 to 39	0	GFSK	1.0

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	ATA RATE (Mbps)
A	0 to 39	0	GFSK	1.0



A D T

ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A	0 to 39	0, 19, 39	GFSK	1.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
PLC	25deg. C, 65%RH	120Vac, 60Hz	David Huang
APCM	25deg. C, 62%RH	120Vac, 60Hz	Phoenix Chen

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2009

558074 D01 DTS Meas Guidance v01

FCC Public Notice DA 00-705


All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B. The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.4.1 CONFIGURATION OF SYSTEM UNDER TEST





A D T

4. TEST TYPES AND RESULTS (FOR Bluetooth EDR)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_BV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUe DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 19, 2012	Apr. 18, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2012	Dec. 16, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Apr. 03, 2012	Apr. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9120 D	209	Sep. 03, 2012	Sep. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170153	Jan. 17, 2012	Jan. 16, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 25, 2012	Dec. 24, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier EMCI	EMC 012645	980115	Dec. 30, 2011	Dec. 29, 2012
Preamplifier EMCI	EMC 012645	980115	Dec. 28, 2012	Dec. 27, 2013
Preamplifier EMCI	EMC 330H	980112	Dec. 30, 2011	Dec. 29, 2012
Preamplifier EMCI	EMC 330H	980112	Dec. 28, 2012	Dec. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable Worken	RG-213	NA	Jan. 02, 2012	Jan. 01, 2013
Software	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Bluetooth Tester	CBT	100870	Jan. 26, 2012	Jan. 25, 2013
Power Meter	ML2495A	1232002	Aug. 10, 2012	Aug. 09, 2013
Power Sensor	MA2411B	1207325	Aug. 15, 2012	Aug. 14, 2013

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 9.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 460141.
6. The IC Site Registration No. is IC 7450F-4.



4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The DH5 packet was the worst case duty cycle for a transmit dwell time on a channel, based upon Bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$.
Average value = peak reading + duty cycle correlation factor.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



A D T

4.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA : GFSK


MODE A



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT TX CH00
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Read Level	Limit Line	OverAntenna Limit Factor	Cable Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark		
								MHz	dB _{UV/m}	
1	2376.00	38.32	42.86	54.00	-15.68	28.11	4.85	37.50	107	24 Average
2	2376.00	50.46	55.00	74.00	-23.54	28.11	4.85	37.50	107	24 Peak
3	2398.00	38.28	42.76	54.00	-15.72	28.17	4.87	37.52	107	24 Average
4	2398.00	50.57	55.05	74.00	-23.43	28.17	4.87	37.52	107	24 Peak
5	2400.00	8.56	13.04	54.00	-45.44	28.17	4.87	37.52	107	24 Average
6	2400.00	38.66	43.14	74.00	-35.34	28.17	4.87	37.52	107	24 Peak
7 av	2402.00	65.87	70.35			28.17	4.87	37.52	107	24 Average
8 pp	2402.00	95.97	100.45			28.17	4.87	37.52	107	24 Peak
9	2492.00	38.88	42.69	54.00	-15.12	28.50	4.94	37.25	107	24 Average
10	2492.00	50.77	54.58	74.00	-23.23	28.50	4.94	37.25	107	24 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT TX CH00
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Read Level	Limit Line	OverAntenna Limit Factor	Cable Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark			
								MHz	dBuV/m	dBuV	dBuV/m
1	2324.00	38.33	43.06	54.00	-15.67	27.95	4.79	37.47	120	331	Average
2	2324.00	51.57	56.30	74.00	-22.43	27.95	4.79	37.47	120	331	Peak
3	2398.00	38.10	42.58	54.00	-15.90	28.17	4.87	37.52	120	331	Average
4	2398.00	51.41	55.89	74.00	-22.59	28.17	4.87	37.52	120	331	Peak
5	2400.00	8.35	12.83	54.00	-45.65	28.17	4.87	37.52	120	331	Average
6	2400.00	38.45	42.93	74.00	-35.55	28.17	4.87	37.52	120	331	Peak
7 av	2402.00	58.21	62.69			28.17	4.87	37.52	120	331	Average
8 pp	2402.00	88.31	92.79			28.17	4.87	37.52	120	331	Peak
9	2486.00	38.67	42.63	54.00	-15.33	28.44	4.92	37.32	120	331	Average
10	2486.00	51.45	55.41	74.00	-22.55	28.44	4.92	37.32	120	331	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT TX CH39
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Level	Read	Limit	Over	Antenna	Cable	Preampl	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
1	2368.00	38.37	42.96	54.00	-15.63	28.06	4.85	37.50	105	23 Average
2	2368.00	51.11	55.70	74.00	-22.89	28.06	4.85	37.50	105	23 Peak
3 av	2441.00	65.16	69.31			28.33	4.91	37.39	105	23 Average
4 pp	2441.00	95.26	99.41			28.33	4.91	37.39	105	23 Peak
5	2486.00	38.76	42.72	54.00	-15.24	28.44	4.92	37.32	105	23 Average
6	2486.00	51.60	55.56	74.00	-22.40	28.44	4.92	37.32	105	23 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT TX CH39
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor			
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2390.00	38.37	42.85	54.00	-15.63	28.17	4.87	37.52	120	311 Average
2	2390.00	50.73	55.21	74.00	-23.27	28.17	4.87	37.52	120	311 Peak
3 av	2441.00	58.44	62.59			28.33	4.91	37.39	120	311 Average
4 pp	2441.00	88.54	92.69			28.33	4.91	37.39	120	311 Peak
5	2496.00	38.79	42.60	54.00	-15.21	28.50	4.94	37.25	120	311 Average
6	2496.00	50.57	54.38	74.00	-23.43	28.50	4.94	37.25	120	311 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT TX CH78
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2322.00	38.07	42.80	54.00	-15.93	27.95	4.79	37.47	100	22 Average
2	2322.00	51.24	55.97	74.00	-22.76	27.95	4.79	37.47	100	22 Peak
3 av	2480.00	64.47	68.43			28.44	4.92	37.32	100	22 Average
4 pp	2480.00	94.57	98.53			28.44	4.92	37.32	100	22 Peak
5	2483.50	8.62	12.58	54.00	-45.38	28.44	4.92	37.32	100	22 Average
6	2483.50	38.72	42.68	74.00	-35.28	28.44	4.92	37.32	100	22 Peak
7	2485.50	38.92	42.88	54.00	-15.08	28.44	4.92	37.32	100	22 Average
8	2485.50	49.92	53.88	74.00	-24.08	28.44	4.92	37.32	100	22 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT TX CH78
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamplifier	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2370.00	38.32	42.86	54.00	-15.68	28.11	4.85	37.50	108	250 Average
2	2370.00	50.95	55.49	74.00	-23.05	28.11	4.85	37.50	108	250 Peak
3 av	2480.00	57.40	61.36			28.44	4.92	37.32	108	250 Average
4 pp	2480.00	87.50	91.46			28.44	4.92	37.32	108	250 Peak
5	2483.50	7.80	11.76	54.00	-46.20	28.44	4.92	37.32	108	250 Average
6	2483.50	37.90	41.86	74.00	-36.10	28.44	4.92	37.32	108	250 Peak
7	2485.50	38.68	42.64	54.00	-15.32	28.44	4.92	37.32	108	250 Average
8	2485.50	50.79	54.75	74.00	-23.21	28.44	4.92	37.32	108	250 Peak



A D T


MODE B



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 23



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT TX CH78
Tested by : Kay Wu
Temperature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Level	Read	Limit	OverAntenna	Cable	Preampl	A/Pos	T/Pos	Remark
		Freq	Level	Line	Limit Factor	Loss Factor	cm	deg	
1	2376.00	35.88	41.67	54.00	-18.12	26.86	4.85	37.50	100 32 Average
2	2376.00	50.60	56.39	74.00	-23.40	26.86	4.85	37.50	100 32 Peak
3 av	2480.00	69.23	74.48			27.15	4.92	37.32	100 32 Average
4 pp	2480.00	99.33	104.58			27.15	4.92	37.32	100 32 Peak
5	2483.50	7.06	12.31	54.00	-46.94	27.15	4.92	37.32	100 32 Average
6	2483.50	37.16	42.41	74.00	-36.84	27.15	4.92	37.32	100 32 Peak
7	2485.50	36.79	42.04	54.00	-17.21	27.15	4.92	37.32	100 32 Average
8	2485.50	50.64	55.89	74.00	-23.36	27.15	4.92	37.32	100 32 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 24



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT TX CH78
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : DH5

Freq	Level	Read	Limit	Over	Antenna	Cable	Preampl	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor			
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2368.00	35.98	41.82	54.00	-18.02	26.81	4.85	37.50	100	344 Average
2	2368.00	49.46	55.30	74.00	-24.54	26.81	4.85	37.50	100	344 Peak
3 av	2480.00	60.60	65.85			27.15	4.92	37.32	100	344 Average
4 pp	2480.00	90.70	95.95			27.15	4.92	37.32	100	344 Peak
5	2483.50	6.49	11.74	54.00	-47.51	27.15	4.92	37.32	100	344 Average
6	2483.50	36.60	41.85	74.00	-37.40	27.15	4.92	37.32	100	344 Peak
7	2485.50	36.42	41.67	54.00	-17.58	27.15	4.92	37.32	100	344 Average
8	2485.50	48.26	53.51	74.00	-25.74	27.15	4.92	37.32	100	344 Peak



A D T


BELOW 1GHz WORST-CASE DATA : GFSK



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT LF
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X

Freq	Level	Read	Limit	Over	Antenna	Cable	Preampl	A/Pos	T/Pos	Remark
		MHz	dBuV/m	dBuV	Line	Limit Factor	Loss	Factor	cm	
1	42.96	23.20	40.00	40.00	-16.80	13.58	0.70	31.08	100	255 Peak
2	106.95	28.69	49.75	43.50	-14.81	9.71	1.11	31.88	100	228 Peak
3 pp	150.42	32.18	49.74	43.50	-11.32	12.71	1.34	31.61	100	198 Peak
4	428.80	21.16	34.73	46.00	-24.84	15.91	2.53	32.01	100	188 Peak
5	686.40	25.82	33.62	46.00	-20.18	20.66	3.38	31.84	100	133 Peak
6	814.50	27.58	32.96	46.00	-18.42	22.42	3.73	31.53	100	187 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT LF
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X

Freq	Level	Read	Limit	Over	Antenna	Cable	Preampl	A/Pos	T/Pos	Remark
		MHz	dB _{UV} /m	dB _{UV}	Line	Limit Factor	dB/m	dB	cm	
1	30.00	30.89	49.48	40.00	-9.11	11.98	0.57	31.14	115	214 QP
2 pp	42.69	31.87	48.67	40.00	-8.13	13.58	0.70	31.08	121	254 QP
3 pk	156.09	31.95	49.63	43.50	-11.55	12.72	1.37	31.77	133	252 Peak
4	609.40	24.78	34.04	46.00	-21.22	19.72	3.12	32.10	100	133 Peak
5	716.50	26.21	33.36	46.00	-19.79	21.05	3.48	31.68	105	225 Peak
6	851.60	28.40	33.57	46.00	-17.60	22.89	3.82	31.88	187	74 Peak



A D T

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 09, 2012	Nov. 08, 2013
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 28, 2012	Dec. 27, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 21, 2012	Dec. 20, 2013
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 06, 2012	Jul. 05, 2013
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.



4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).


4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS

CONDUCTED WORST CASE DATA: GFSK

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------



	Frequency	Corr. Factor	Reading dBuV		Emission dBuV		Limit dBuV		Margins dB		Notes
No.	MHz	dB	QP	AV	QP	AV	QP	AV	QP	AV	Notes
1	0.15000	0.18	48.44	34.28	48.62	34.46	66.00	56.00	-17.38	-21.54	
+2	0.51719	0.22	48.04	37.51	48.26	37.73	56.00	46.00	-7.74	-8.27	
3	0.97422	0.26	46.44	36.88	46.70	37.14	56.00	46.00	-9.30	-8.86	
4	2.19531	0.30	44.65	36.42	44.95	36.72	56.00	46.00	-11.05	-9.28	
5	3.14453	0.34	43.74	35.04	44.08	35.38	56.00	46.00	-11.92	-10.62	
6	13.56250	0.53	42.78	39.99	43.31	40.52	60.00	50.00	-16.69	-9.48	


REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



A D T

PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------



No.	Frequency MHz	Corr. Factor	Reading dBuV		Emission dBuV		Limit dBuV		Margins dB		Notes
			dB	QP	AV	QP	AV	QP	AV	QP	
1	0.15781	0.16	47.83	33.87	47.99	34.03	65.58	55.58	-17.59	-21.55	
+2	0.38438	0.20	47.25	39.82	47.45	40.02	58.18	48.18	-10.74	-8.17	
3	0.97031	0.26	46.90	36.38	47.16	36.64	56.00	46.00	-8.84	-9.36	
4	2.23828	0.30	44.53	36.32	44.83	36.62	56.00	46.00	-11.17	-9.38	
5	3.09375	0.34	43.52	35.22	43.86	35.56	56.00	46.00	-12.14	-10.44	
6	13.55859	0.59	42.17	39.69	42.76	40.28	60.00	50.00	-17.24	-9.72	

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.


4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plot, it shows that the hopping frequencies are equally spaced.



A D T

GFSK






4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.



A D T


4.4.6 TEST RESULTS

GFSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	8.80	429.49	0.12	0.4
DH3	4.40	1698.72	0.24	0.4
DH5	3.10	2945.51	0.29	0.4

NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.





A D T


π/4-DQPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	8.60	432.69	0.12	0.4
DH3	4.50	1698.72	0.24	0.4
DH5	3.00	2964.74	0.28	0.4


NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.


DH1



DH3



DH5





A D T


8DPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	8.80	432.69	0.12	0.4
DH3	5.00	1690.71	0.27	0.4
DH5	3.90	2972.76	0.37	0.4


NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.


DH1



DH3



DH5






A D T

4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD


No deviation.

4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)		
		GFSK	$\pi/4$ -DQPSK	8DPSK
0	2402	0.989	1.35	1.31
39	2441	1.02	1.35	1.31
78	2480	1.02	1.35	1.30






4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.




A D T

4.6.6 TEST RESULTS

CHAN.	FREQ. (MHz)	ADJACENT CHANNEL SEPARATION (MHz)			20dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)			PASS / FAIL
		GFSK	$\pi/4$ -DQPSK	8DPSK	GFSK	$\pi/4$ -DQPSK	8DPSK	GFSK	$\pi/4$ -DQPSK	8DPSK	
0	2402	1.00	1.00	1.00	0.989	1.35	1.31	0.659	0.900	0.873	PASS
39	2441	1.01	1.01	1.01	1.02	1.35	1.31	0.680	0.900	0.873	PASS
78	2480	1.01	1.01	1.00	1.02	1.35	1.30	0.680	0.900	0.867	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.






4.7 MAXIMUM OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.7.2 TEST SETUP



4.7.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.7.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

4.7.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



A D T

4.7.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	OUTPUT POWER (mW)			OUTPUT POWER (dBm)			POWER LIMIT (mW)	PASS / FAIL
		GFSK	$\pi/4$ -DQPSK	8DPSK	GFSK	$\pi/4$ -DQPSK	8DPSK		
0	2402	2.972	2.523	2.851	4.73	4.02	4.55	125	PASS
39	2441	3.459	2.559	2.564	5.39	4.08	4.09	125	PASS
78	2480	3.206	2.259	2.249	5.06	3.54	3.52	125	PASS





4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.8.3 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set VBW =300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit continuously.

4.8.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

GFSK


Hopping disabled_ Low Channel




Hopping disabled_ High Channel



Hopping enabled_ Low Channel



Hopping enabled_ High Channel







A D T

π/4-DQPSK


Hopping disabled_Low Channel



Hopping disabled_High Channel



Hopping enabled_Low Channel







A D T

8DPSK


Hopping disabled_ Low Channel




Hopping disabled_ High Channel



Hopping enabled_ Low Channel



Hopping enabled_ High Channel





5. TEST TYPES AND RESULTS (FOR Bluetooth LE 4.0)

5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{UV}/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

5.1.2 TEST INSTRUMENTS

Same as 4.1.2.



A D T

5.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

5.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

5.1.6 EUT OPERATING CONDITIONS

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.



A D T

5.1.7 TEST RESULTS

ABOVE 1GHz DATA

MODE A




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19

Date: 2012-12-27



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT LE TX CH00
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Read Level	Limit Line	OverAntenna Limit Factor	Cable Loss	Preamplifier Factor	A/Pos		T/Pos		Remark
						dB	dB/m	dB	cm	
1	2324.00	38.10	42.83	54.00	-15.90	27.95	4.79	37.47	100	34 Average
2	2324.00	51.51	56.24	74.00	-22.49	27.95	4.79	37.47	100	34 Peak
3 pp	2402.00	88.20	92.68			28.17	4.87	37.52	100	34 Average
4 pk	2402.00	89.45	93.93			28.17	4.87	37.52	100	34 Peak
5	2488.00	38.75	42.65	54.00	-15.25	28.50	4.92	37.32	100	34 Average
6	2488.00	51.32	55.22	74.00	-22.68	28.50	4.92	37.32	100	34 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT LE TX CH00
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Line	Limit	Factor	Loss	Factor	cm	deg		
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2374.00	39.13	43.67	54.00	-14.87	28.11	4.85	37.50	122	312 Average
2	2374.00	51.42	55.96	74.00	-22.58	28.11	4.85	37.50	122	312 Peak
3 pp	2402.00	85.28	89.76			28.17	4.87	37.52	122	312 Average
4 pk	2402.00	86.20	90.68			28.17	4.87	37.52	122	312 Peak
5	2488.00	39.83	43.73	54.00	-14.17	28.50	4.92	37.32	122	312 Average
6	2488.00	51.55	55.45	74.00	-22.45	28.50	4.92	37.32	122	312 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT LE TX CH19
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit Factor	dB	dB/m	dB	dB	cm	
	MHz	dBuV/m	dBuV	dBuV/m						
1	2340.00	38.97	43.64	54.00	-15.03	28.00	4.82	37.49	100	32 Average
2	2340.00	51.81	56.48	74.00	-22.19	28.00	4.82	37.49	100	32 Peak
3 pp	2440.00	88.76	93.00			28.33	4.89	37.46	100	32 Average
4 pk	2440.00	89.78	94.02			28.33	4.89	37.46	100	32 Peak
5	2494.00	39.60	43.41	54.00	-14.40	28.50	4.94	37.25	100	32 Average
6	2494.00	51.31	55.12	74.00	-22.69	28.50	4.94	37.25	100	32 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT LE TX CH19
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2320.00	38.99	43.72	54.00	-15.01	27.95	4.79	37.47	121	314 Average
2	2320.00	51.16	55.89	74.00	-22.84	27.95	4.79	37.47	121	314 Peak
3 pp	2440.00	82.13	86.37			28.33	4.89	37.46	121	314 Average
4 pk	2440.00	83.25	87.49			28.33	4.89	37.46	121	314 Peak
5	2498.00	39.61	43.42	54.00	-14.39	28.50	4.94	37.25	121	314 Average
6	2498.00	50.71	54.52	74.00	-23.29	28.50	4.94	37.25	121	314 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT LE TX CH39
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		MHz	dBuV/m	dBuV	Line	Limit Factor	Loss Factor	dB	cm	
1	2376.00	39.06	43.60	54.00	-14.94	28.11	4.85	37.50	100	26 Average
2	2376.00	51.26	55.80	74.00	-22.74	28.11	4.85	37.50	100	26 Peak
3 pp	2480.00	84.70	88.66			28.44	4.92	37.32	100	26 Average
4 pk	2480.00	85.77	89.73			28.44	4.92	37.32	100	26 Peak
5	2492.00	39.64	43.45	54.00	-14.36	28.50	4.94	37.25	100	26 Average
6	2492.00	51.57	55.38	74.00	-22.43	28.50	4.94	37.25	100	26 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT LE TX CH39
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit Factor	Factor	Loss	Factor			
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2360.00	39.22	43.83	54.00	-14.78	28.06	4.82	37.49	118	315 Average
2	2360.00	51.36	55.97	74.00	-22.64	28.06	4.82	37.49	118	315 Peak
3 pp	2480.00	80.05	84.01			28.44	4.92	37.32	118	315 Average
4 pk	2480.00	81.15	85.11			28.44	4.92	37.32	118	315 Peak
5	2496.00	39.75	43.56	54.00	-14.25	28.50	4.94	37.25	118	315 Average
6	2496.00	50.85	54.66	74.00	-23.15	28.50	4.94	37.25	118	315 Peak



A D T

MODE B




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 23

Level (dBuV/m)

Date: 2013-01-21



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT LE TX CH00
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Level	Read	Limit	OverAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
		MHz	dBuV/m	dBuV	dBuV/m	Line	Limit Factor	Loss Factor	
1	2386.00	36.67	42.41	54.00	-17.33	26.91	4.85	37.50	104 35 Average
2	2386.00	49.72	55.46	74.00	-24.28	26.91	4.85	37.50	104 35 Peak
3 pp	2402.00	90.00	95.74			26.91	4.87	37.52	104 35 Average
4 pk	2402.00	91.00	96.74			26.91	4.87	37.52	104 35 Peak
5	2486.00	37.01	42.26	54.00	-16.99	27.15	4.92	37.32	104 35 Average
6	2486.00	49.52	54.77	74.00	-24.48	27.15	4.92	37.32	104 35 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 24



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT LE TX CH00
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X
Date : PRBS9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preampl	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2370.00	36.60	42.39	54.00	-17.40	26.86	4.85	37.50	100	315 Average
2	2370.00	49.41	55.20	74.00	-24.59	26.86	4.85	37.50	100	315 Peak
3 pp	2402.00	84.55	90.29			26.91	4.87	37.52	100	315 Average
4 pk	2402.00	85.62	91.36			26.91	4.87	37.52	100	315 Peak
5	2498.00	37.14	42.25	54.00	-16.86	27.20	4.94	37.25	100	315 Average
6	2498.00	49.17	54.28	74.00	-24.83	27.20	4.94	37.25	100	315 Peak



A D T


BELOW 1GHz WORST-CASE DATA



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m HORIZONTAL
Brand/Model: 121129C09
Remark : BT LE LF
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		MHz	dBuV/m	dBuV	Line	Limit Factor	dB/m	dB	cm	
1	42.15	24.69	41.49	40.00	-15.31	13.58	0.70	31.08	100	125 Peak
2	106.95	30.00	51.06	43.50	-13.50	9.71	1.11	31.88	100	155 Peak
3 pp	152.85	32.90	50.51	43.50	-10.60	12.72	1.36	31.69	100	225 Peak
4	470.10	21.14	33.62	46.00	-24.86	16.73	2.68	31.89	312	25 Peak
5	622.70	25.04	34.16	46.00	-20.96	19.88	3.16	32.16	152	28 Peak
6	787.90	27.59	33.29	46.00	-18.41	22.05	3.66	31.41	175	44 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5
Condition : FCC CLASS-B 3m VERTICAL
Brand/Model: 121129C09
Remark : BT LE LF
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X

Freq	Read	Limit	Over	Antenna	Cable	Preampl	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dBuV	Line	Limit Factor	Loss Factor	dB	cm	
1	30.54	31.18	49.59	40.00	-8.82	12.14	0.57	31.12	112 213 QP
2 pp	42.69	31.87	48.67	40.00	-8.13	13.58	0.70	31.08	102 352 QP
3 pk	157.98	31.88	49.60	43.50	-11.62	12.73	1.38	31.83	211 111 Peak
4	374.90	20.47	35.33	46.00	-25.53	14.75	2.33	31.94	122 25 Peak
5	615.70	24.25	33.44	46.00	-21.75	19.80	3.14	32.13	107 44 Peak
6	817.30	27.88	33.26	46.00	-18.12	22.45	3.74	31.57	155 89 Peak



A D T

5.2 CONDUCTED EMISSION MEASUREMENT

5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

Same as 4.2.1.

5.2.2 TEST INSTRUMENTS

Same as 4.2.2.

5.2.3 TEST PROCEDURES

Same as 4.2.3.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

5.2.5 TEST SETUP

Same as 4.2.5.

5.2.6 EUT OPERATING CONDITIONS

Same as 4.2.6.




A D T

5.2.7 TEST RESULTS

CONDUCTED WORST CASE DATA:

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------



	Frequency	Corr. Factor	Reading dBuV		Emission dBuV		Limit dBuV		Margins dB		Notes
No.	MHz	dB	QP	AV	QP	AV	QP	AV	QP	AV	Notes
1	0.37266	0.20	47.03	37.16	47.23	37.36	58.44	48.44	-11.21	-11.08	
+2	0.51328	0.22	48.38	37.21	48.60	37.43	56.00	46.00	-7.40	-8.57	
3	0.81797	0.24	46.65	36.55	46.89	36.79	56.00	46.00	-9.11	-9.21	
4	2.08984	0.29	44.37	36.51	44.66	36.80	56.00	46.00	-11.34	-9.20	
5	3.20313	0.34	44.05	35.24	44.39	35.58	56.00	46.00	-11.61	-10.42	
6	13.56250	0.53	42.39	39.59	42.92	40.12	60.00	50.00	-17.08	-9.88	


REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



A D T

PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------



V7.3.7.3

	Frequency	Corr. Factor	Reading dBuV		Emission dBuV		Limit dBuV		Margins dB		Notes
No.	MHz	dB	QP	AV	QP	AV	QP	AV	QP	AV	Notes
1	0.15000	0.15	45.33	32.48	45.48	32.63	66.00	56.00	-20.52	-23.37	
2	0.38047	0.20	47.98	39.86	48.18	40.06	58.27	48.27	-10.09	-8.21	
+3	0.50547	0.21	47.59	34.16	47.80	34.37	56.00	46.00	-8.20	-11.63	
4	0.95859	0.26	47.50	36.33	47.76	36.59	56.00	46.00	-8.24	-9.41	
5	2.18750	0.30	44.34	36.30	44.64	36.60	56.00	46.00	-11.36	-9.40	
6	13.55859	0.59	42.56	39.43	43.15	40.02	60.00	50.00	-16.85	-9.98	

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

5.3.2 TEST SETUP



5.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.3.4 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.5 DEVIATION FROM TEST STANDARD

No deviation.

5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

5.3.7 TEST RESULTS


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (KHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	708.650	0.5	PASS
19	2440	705.280	0.5	PASS
39	2480	705.330	0.5	PASS

5.4 CONDUCTED OUTPUT POWER

5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz: 1 Watt (30dBm)

5.4.2 TEST SETUP



5.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

5.4.5 DEVIATION FROM TEST STANDARD

No deviation.

5.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

5.4.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	0.984	-0.07	30	PASS
19	2440	0.951	-0.22	30	PASS
39	2480	0.733	-1.35	30	PASS




5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST SETUP



5.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.5.4 TEST PROCEDURE

- a. Set the RBW = 100 kHz, VBW =300 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
- d. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3 \text{ kHz}/100\text{kHz})$

5.5.5 DEVIATION FROM TEST STANDARD

No deviation.

5.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.5.7 TEST RESULTS


Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	2.77	-12.43	8	PASS
19	2440	2.64	-12.56	8	PASS
39	2480	2.04	-13.16	8	PASS

5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST SETUP



5.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

5.6.5 DEVIATION FROM TEST STANDARD

No deviation.

5.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6




5.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



A D T

5.6.8 TEST RESULTS

CH 0**CH 19****CH 39**



A D T

6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---