

## RF EXPOSURE REPORT

**REPORT NO.:** SA 980106L05A-2

MODEL NO.: RHOD400

**ACCORDING:** FCC Guidelines for Human Exposure

**IEEE C95.1** 

**APPLICANT: HTC Corporation** 

ADDRESS: No. 23, Xinghua Rd., Taoyuan City, 330, Taiwan,

R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,

Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Report No: SA980116L05A-2 Reference No.: 980303L12



## 1. Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW	
Low	2.402	24.585	
High	2.480	24.303	

Maximum measured transmitter power:

Pout (dBr	Pout (mW)	
<b>Conducted Power</b>	-0.03	0.933
EIRP Power	0.97	0.028

<sup>\*</sup>Note: The antenna is PIFA antenna with 1dBi gain.

Threshold for no SAR evaluation is 24.585mW Transmitter power is 0.028mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

Report No: SA980116L05A-2 Reference No.: 980303L12