

DAIRY LABEL/DL-50/40# FS

FACESTOCK

FM Litho: A medium gloss bleached hardwood and softwood kraft stock that is super-calendered and coated one side for high internal strength.

Basis Weight: 60# per ream $\pm 10\%$
{500 sheets 25" x 38"}

Tensile: MD 27# per inch width
CD 13# per inch width

Caliper: 0.0034 inches $\pm 10\%$

Tear: MD 45 grams per sheet
CD 50 grams per sheet

ADHESIVE

DL-50 is a permanent adhesive specifically formulated and designed for adhesion to HDPE (high density polyethylene) milk jugs and other applications with similar surfaces.

Minimum Application Temperature: +25°F
Service Temperature Range: -65°F to +160°F

Type: Hot Melt Rubber

LINER

40# FS: A bleached supercalendered kraft stock featuring high internal strength, toughness and tear resistance.

Basis Weight: 41# per ream $\pm 10\%$
{500 sheets 24" x 36"}

Tensile: MD 35# per inch width
CD 16# per inch width

Caliper: 0.0025 inches $\pm 10\%$

Tear: MD 35 grams per sheet
CD 45 grams per sheet

TOTAL CONSTRUCTION CALIPER: 0.0066 inches $\pm 10\%$

SHELF LIFE: One year when stored at 72°F/50% R.H.

As with all pressure-sensitive materials, this product should be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.



MODEL:
WM09STDB-0001

This device complies with Part 15 of FCC Rules. Operation is subject to the following conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: NMAWM09STDB0001

Canada ID: XXXXXXXX SN: