

Report No.: SZEM140700368401

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 60

# **FCC REPORT**

Application No.: SZEM1407003684RF

Applicant: IDT Technology Limited

**Product Name:** 2nd generation activity and sleep monitor wrist device

Model No.(EUT): PE289

Add Model No.: PE280, PE281, PE288

FCC ID: NMTPE289

**Standards:** 47 CFR Part 15, Subpart C (2013)

**Date of Receipt:** 2014-07-16

**Date of Test:** 2014-07-21 to 2014-08-06

**Date of Issue:** 2014-08-14

Test Result: PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM140700368401

Page: 2 of 60

# 2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2014-08-14		Original	

Authorized for issue by:		
Tested By	(Owen Zhou) /Project Engineer	2014-07-21  Date
Prepared By	(Molinda Li) /Clerk	2014-08-06  Date
Checked By	Emen _ L <sub>1</sub>	2014-08-15  Date



Report No.: SZEM140700368401

Page: 3 of 60

# 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	KDB558074 D01 v03r01	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	KDB558074 D01 v03r01	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	KDB558074 D01 v03r01	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r01	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r01	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

Remark:

Model No.: PE280, PE281, PE288, PE289

The model PE289 was tested fully, and the model PE280, PE281 and PE288 was performed the Radiated Emission, Conducted Emission, Conducted Peak Output Power and Transmitter Spurious Emission test for discrepancy, since the electrical circuit design, layout, RF Module used and internal wiring were identical for all above models. Only the PE288 indicate is OLED without ECG function and with a key, PE289 indicate is OLED with ECG function and a key, the plastic housing has little difference and metal color is different.



Report No.: SZEM140700368401

Page: 4 of 60

## 4 Contents

		Page
1 C	COVER PAGE	1
2 V	/ERSION	
	TEST SUMMARY	
	CONTENTS	
	GENERAL INFORMATION	
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF EUT	
5.3	TEST ENVIRONMENT	
5.4	DESCRIPTION OF SUPPORT UNITS	7
5.5	TEST LOCATION	
5.6	TEST FACILITY	8
5.7	DEVIATION FROM STANDARDS	8
5.8	ABNORMALITIES FROM STANDARD CONDITIONS	8
5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
5.10	EQUIPMENT LIST	9
6 T	TEST RESULTS AND MEASUREMENT DATA	
6.1	Antenna Requirement	
6.2	CONDUCTED EMISSIONS	
6.3	CONDUCTED PEAK OUTPUT POWER	
6.4	6DB OCCUPY BANDWIDTH	
6.5	POWER SPECTRAL DENSITY	28
6.6	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
6.7	Spurious RF Conducted Emissions	
6.8	RADIATED SPURIOUS EMISSION	
6	S.8.1 Spurious Emissions	



Report No.: SZEM140700368401

Page: 5 of 60

# 5 General Information

# 5.1 Client Information

Applicant:	IDT Technology Limited
Address of Applicant:	Block C, 9/F., Kaiser Estate, Phase 1, 41 Man Yue Street, Hunghom, Kowloon, Hong Kong.

# 5.2 General Description of EUT

ist device
5)
ole Battery)
tion test signal at the
8)



Report No.: SZEM140700368401

Page: 6 of 60

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
4	2408MHz	14	2428MHz	24	2448MHz	34	2468MHz
5	2410MHz	15	2430MHz	25	2450MHz	35	2470MHz
6	2412MHz	16	2432MHz	26	2452MHz	36	2472MHz
7	2414MHz	17	2434MHz	27	2454MHz	37	2474MHz
8	2416MHz	18	2436MHz	28	2456MHz	38	2476MHz
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency		
The Lowest channel	2402MHz		
The Middle channel	2440MHz		
The Highest channel	2480MHz		



Report No.: SZEM140700368401

Page: 7 of 60

#### 5.3 Test Environment

Operating Environment:		
Temperature:	20.0 °C	
Humidity:	55 % RH	
Atmospheric Pressure:	1005mbar	

# 5.4 Description of Support Units

The EUT has been tested with associated equipment below.

PC	IBM	8172
LCD-displaying	Lenovo	L1711pC
KEYBOARD	IBM	SK-8115
MOUSE	Lenovo	MO28UOA

#### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM140700368401

Page: 8 of 60

# 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

#### FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### • Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

#### 5.7 Deviation from Standards

None.

# 5.8 Abnormalities from Standard Conditions

None.

# 5.9 Other Information Requested by the Customer

None.





Report No.: SZEM140700368401

Page: 9 of 60

# 5.10 Equipment List

	Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)		
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-06-10		
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2014-10-24		
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-16		
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T8-02	SEL0162	2014-11-10		
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T4-02	SEL0163	2014-11-10		
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T2-02	SEL0164	2014-11-10		
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-16		
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-29		
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24		
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24		
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16		



Report No.: SZEM140700368401

Page: 10 of 60

	RE in Chamber				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2015-05-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2014-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2014-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
13	Band filter	Amindeon	82346	SEL0094	2015-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2014-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04



Report No.: SZEM140700368401

Page: 11 of 60

	RF connected test				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2014-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2014-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R&S	NRVS	SEL0144	2014-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2014-10-24

Note: The calibration interval is one year, all the instruments are valid.



Report No.: SZEM140700368401

Page: 12 of 60

# 6 Test results and Measurement Data

# 6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna:**



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -0.6dBi.



Report No.: SZEM140700368401

Page: 13 of 60


#### 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207				
Test Method:	ANSI C63.10: 2009				
Test Frequency Range:	150kHz to 30MHz				
Limit:	Fraguena, ranga (MIII-)	Limit (c	lBuV)		
	Frequency range (MHz)	Quasi-peak	Average		
	0.15-0.5	66 to 56*	56 to 46*		
	0.5-5	56	46		
	5-30	60	50		
	* Decreases with the logarithn	n of the frequency.		•	
Test Procedure:	The mains terminal distur room.	bance voltage test was	s conducted in a shie	elded	
	<ol> <li>The mains terminal disturbance voltage test was conducted in a shie room.</li> <li>The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω lin impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>The tabletop EUT was placed upon a non-metallic table 0.8m above th ground reference plane. And for floor-standing arrangement, the EUT placed on the horizontal ground reference plane,</li> <li>The test was performed with a vertical ground reference plane. The rea of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to the equipment and all of the interface cables must be changed according to the equipment and all of the interface cables must be changed according to the equipment and all of the interface cables must be changed according to the equipment and all of the equipment and all of</li></ol>		ne was ear ne he of 2.		



Report No.: SZEM140700368401

Page: 14 of 60





Report No.: SZEM140700368401

Page: 15 of 60


#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

#### For model PE289, PE288, PE280 and PE281





Site : Shielding Room

Condition : 47 CFR PART 15 B QP CE LINE

Job No. : 3684RF Mode : Charge


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.18152	0.02	9.70	32.22	41.94	64.42	-22.48	QP
2	0.18152	0.02	9.70	22.28	32.00	54.42	-22.41	Average
3	0.30188	0.01	9.70	18.39	28.10	50.19	-22.09	Average
4	0.30188	0.01	9.70	26.80	36.51	60.19	-23.68	QP
5	0.36338	0.01	9.77	17.56	27.33	48.65	-21.32	Average
6	0.36338	0.01	9.77	25.56	35.34	58.65	-23.31	QP
7	0.54355	0.01	9.80	25.71	35.52	56.00	-20.48	QP
8 @	0.54355	0.01	9.80	15.77	25.58	46.00	-20.42	Average
9	0.72744	0.02	9.80	13.54	23.36	46.00	-22.64	Average
10	0.72744	0.02	9.80	21.09	30.91	56.00	-25.09	QP
11	4.848	0.01	9.90	11.32	21.23	46.00	-24.77	Average
12	4.848	0.01	9.90	19.95	29.86	56.00	-26.14	QP



Report No.: SZEM140700368401

Page: 16 of 60

#### Neutral line:



Site : Shielding Room

Condition : 47 CFR PART 15 B QP CE NEUTRAL

Job No. : 3684RF Mode : Charge

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17961	0.02	9.70	22.64	32.36	54.50	-22.15	Average
2	0.17961	0.02	9.70	31.71	41.43	64.50	-23.07	QP
3	0.30348	0.01	9.71	26.92	36.64	60.15	-23.51	QP
4	0.30348	0.01	9.71	16.50	26.22	50.15	-23.93	Average
5	0.54355	0.01	9.80	24.43	34.24	56.00	-21.76	QP
6	0.54355	0.01	9.80	13.80	23.61	46.00	-22.39	Average
7	0.78761	0.02	9.80	11.83	21.65	46.00	-24.35	Average
8	0.78761	0.02	9.80	17.26	27.08	56.00	-28.92	QP
9	1.456	0.02	9.80	11.13	20.95	46.00	-25.05	Average
10	1.456	0.02	9.80	19.94	29.76	56.00	-26.24	QP
11	5.713	0.01	9.94	16.47	26.42	50.00	-23.58	Average
12	5.713	0.01	9.94	23.52	33.47	60.00	-26.53	QP

#### Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM140700368401

Page: 17 of 60

# 6.3 Conducted Peak Output Power





Report No.: SZEM140700368401

Page: 18 of 60

#### **Measurement Data**

#### For model PE289

. 0			
	GFSK mod	е	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	1.26	30.00	Pass
Middle	1.75	30.00	Pass
Highest	1.93	30.00	Pass

#### For model PE288

	GFSK mod	le	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	1.22	30.00	Pass
Middle	1.65	30.00	Pass
Highest	1.75	30.00	Pass

#### For model PE280

	GFSK mod	е	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	0.18	30.00	Pass
Middle	0.76	30.00	Pass
Highest	1.15	30.00	Pass

#### For model PE281

	GFSK mod	le	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-0.14	30.00	Pass
Middle	0.56	30.00	Pass
Highest	1.04	30.00	Pass






Report No.: SZEM140700368401

Page: 19 of 60


#### Test plot as follows:

#### For model PE289

Test mode: GFSK Test channel: Lowest










Report No.: SZEM140700368401


Page: 20 of 60

Test mode: GFSK Test channel: Highest



#### For model PE288

Test mode: GFSK Test channel: Lowest







Report No.: SZEM140700368401

Page: 21 of 60

Test mode: GFSK Test channel: Middle










Report No.: SZEM140700368401


Page: 22 of 60

#### For model PE280

Test mode: GFSK Test channel: Lowest










Report No.: SZEM140700368401


Page: 23 of 60

Test mode: GFSK Test channel: Highest



#### For model PE281

Test mode: GFSK Test channel: Lowest







Report No.: SZEM140700368401

Page: 24 of 60

Test mode: GFSK Test channel: Middle










Report No.: SZEM140700368401

Page: 25 of 60

# 6.4 6dB Occupy Bandwidth



#### **Measurement Data**

Test channel	6dB Occupy Bandwidth (kHz)	Limit (kHz)	Result
Lowest	673.077	≥500	Pass
Middle	658.654	≥500	Pass
Highest	668.269	≥500	Pass



Report No.: SZEM140700368401


Page: 26 of 60

## Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM140700368401

Page: 27 of 60

Test mode: GFSK Test channel: Highest






Report No.: SZEM140700368401

Page: 28 of 60

# 6.5 Power Spectral Density



#### **Measurement Data**

	GFSK mode		
Test channel	Power Spectral Density (dBm)	Limit (dBm)	Result
Lowest	0.93	≤8.00	Pass
Middle	1.44	≤8.00	Pass
Highest	1.61	≤8.00	Pass






Report No.: SZEM140700368401


Page: 29 of 60

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Middle






Report No.: SZEM140700368401

Page: 30 of 60

Test mode: GFSK Test channel: Highest






Report No.: SZEM140700368401

Page: 31 of 60

# 6.6 Band-edge for RF Conducted Emissions






Report No.: SZEM140700368401


Page: 32 of 60

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM140700368401

Page: 33 of 60

# 6.7 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	KDB558074 D01 v03r01	
Test Setup:	Spectrum Analyzer  E.U.T	
	Ground Reference Plane	
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test Mode:	Non-hopping transmitting with GFSK modulation	
Instruments Used:	Refer to section 4.10 for details	
Test Results:	Pass	




Report No.: SZEM140700368401

Page: 34 of 60

Test mode: GFSK Test channel: Lowest









Report No.: SZEM140700368401

Page: 35 of 60










Report No.: SZEM140700368401

Page: 36 of 60











Report No.: SZEM140700368401

Page: 37 of 60







<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140700368401

Page: 38 of 60











Report No.: SZEM140700368401

Page: 39 of 60

Test mode: GFSK Test channel: Highest









Report No.: SZEM140700368401

Page: 40 of 60








Report No.: SZEM140700368401

Page: 41 of 60



#### Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report.



Report No.: SZEM140700368401

Page: 42 of 60


# 6.8 Radiated Spurious Emission

6.8.1 Spurious Emiss	ions									
Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205									
Test Method:	ANSI C63.10 2009	ANSI C63.10 2009								
Test Site:	Measurement Distance	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Receiver Setup:	Frequency		Detector	RBW		VBW	Remark			
	0.009MHz-0.090MH	Z	Peak	10kHz	<u>z</u>	30kHz	Peak	9		
	0.009MHz-0.090MH	Z	Average	10kHz	<u>z</u>	30kHz	Average			
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	Z	30kHz	Quasi-peak			
	0.110MHz-0.490MH	Z	Peak	10kHz	Z	30kHz	Peak			
	0.110MHz-0.490MH	Z	Average	10kHz	Z	30kHz	Average			
	0.490MHz -30MHz		Quasi-peak	10kHz	Z	30kHz	Quasi-peak			
	30MHz-1GHz		Quasi-peak	100 kH	lz	300kHz	Quasi-peak			
	Above 1GHz		Peak	1MHz	<u>-</u>	3MHz	Peak			
	Above IGHZ		Peak	1MHz	-	10Hz	Average			
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)		Remark	Measureme distance (n			
	0.009MHz-0.490MHz	2	400/F(kHz)	-			300			
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-		30			
	1.705MHz-30MHz		30	-		-	30			
	30MHz-88MHz		100	40.0	Q	uasi-peak	3			
	88MHz-216MHz		150	43.5	Q	uasi-peak	3			
	216MHz-960MHz		200	46.0	Q	uasi-peak	3			
	960MHz-1GHz		500	54.0	Q	uasi-peak	3			
	Above 1GHz	ove 1GHz 5		54.0		Average	3			
	Note: 15.35(b), frequency emissions is limit applicable to the epeak emission level race	20c quip	IB above the in the ment under to	maximum est. This p	pe	rmitted ave	erage emissio	n		
Test Setup:										



Report No.: SZEM140700368401

Page: 43 of 60






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

#### Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz)
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse



Report No.: SZEM140700368401

Page: 44 of 60


	case.
	i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Charge mode.
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass



Report No.: SZEM140700368401

Page: 45 of 60

Radiated Emission below 1GHz(For PE289)					
30MHz~1GHz (QP)					
Test mode:	TX mode	Vertical			



Condition: 47 CFR PART 15B 3m 3142C VERTICAL

Job No. : 3684RF Test Mode: TX mode : PE281


	Freq	CableA		Preamp Factor	Read Level		Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	dB
1 2 3 4 5 6	163. 18 253. 84 375. 94 578. 67 793. 40 965. 54	1.34 1.69 2.13 2.68 3.18 3.67	9.50 8.77 11.49 15.10 18.48 21.13	26. 85 26. 53 26. 97 27. 57 27. 31 26. 47		7. 97 7. 17 10. 51 14. 14 19. 38 21. 55	46.00 46.00 46.00 46.00	-35.53 -38.83 -35.49 -31.86 -26.62 -32.45



Report No.: SZEM140700368401

Page: 46 of 60

Test mode:	TX mode	Horizontal
------------	---------	------------



Condition: 47 CFR PART 15B 3m 3142C HORIZONTAL

Job No. : 3684RF Test Mode: TX mode : PE281


F	Cabl req Los	eAntenna s Factor					Over Limit
	MHz d	B dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	dB
2 236 3 373 4 522 5 760	5.64 1.6 3.31 2.1 2.72 2.6 5.70 3.0		26.58 26.95 27.66 27.34	24. 03 25. 01 25. 00 25. 86	11.60 14.08 19.71	46.00 46.00 46.00 46.00	-38.61 -34.40 -31.92



Report No.: SZEM140700368401

Page: 47 of 60

Radiated Emission below 1GHz(For PE288)					
30MHz~1GHz (QP)					
Test mode:	TX mode	Vertical			



Condition: 47 CFR PART 15B 3m 3142C VERTICAL

Job No. : 3684RF Test Mode: TX mode : PE280


	Freq			Preamp Factor		Level		Over Limit
	MHz	d₿	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5	157. 56 214. 51 308. 91 443. 29 651. 94 948. 76	1.33 1.49 1.93 2.38 2.81 3.65	9.55 7.50 9.88 12.59 15.80 21.40	26. 87 26. 65 26. 46 27. 40 27. 47 26. 54	25. 16 22. 56 24. 44 25. 01 25. 95 23. 20	9. 17 4. 90 9. 79 12. 58 17. 09 21. 71	43.50 46.00 46.00 46.00	-34. 33 -38. 60 -36. 21 -33. 42 -28. 91 -24. 29



Report No.: SZEM140700368401

Page: 48 of 60

Test mode: TX mode	Horizontal
--------------------	------------



Condition: 47 CFR PART 15B 3m 3142C HORIZONTAL

Job No. : 3684RF Test Mode: TX mode : PE280

	Freq			Preamp Factor	Read Level		Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	dBuV/m	dB
1 2 3 4 5 6	86. 20 104. 90 143. 83 167. 82 443. 29 958. 79	1.10 1.21 1.31 1.35 2.38 3.66	5. 95 6. 90 8. 88 9. 25 12. 59 21. 10	27. 22 27. 17 26. 94 26. 82 27. 40 26. 51	24. 46 23. 50 22. 56 21. 50 24. 53 23. 98	4. 29 4. 44 5. 81 5. 28 12. 10 22. 23	43.50 43.50 43.50 46.00	-35. 71 -39. 06 -37. 69 -38. 22 -33. 90 -23. 77






Report No.: SZEM140700368401

Page: 49 of 60

Radiated Emission below 1GHz(For PE280)					
30MHz~1GHz (QP)					
Test mode:	TX mode	Vertical			



Condition: 47 CFR PART 15B 3m 3142C VERTICAL

Job No. : 3684RF Test Mode: TX mode : PE288


	Freq			Preamp Factor	Read Level		Limit Line	Over Limit
	MHz	d₿	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	dBuV/m	dB
1 2 3 4 5	32. 41 165. 49 317. 70 468. 88 603. 54 821. 71	0.60 1.35 1.96 2.49 2.71 3.29	16.10 9.50 9.82 13.20 15.27 19.13	27. 35 26. 83 26. 54 27. 54 27. 54 27. 16	23. 62 22. 92 23. 97 23. 95 24. 29 24. 26	12. 97 6. 94 9. 21 12. 10 14. 73 19. 52	43.50 46.00 46.00 46.00	-27. 03 -36. 56 -36. 79 -33. 90 -31. 27 -26. 48



Report No.: SZEM140700368401

Page: 50 of 60

Test mode:	TX mode	Horizontal
------------	---------	------------



Condition: 47 CFR PART 15B 3m 3142C HORIZONTAL

Job No. : 3684RF Test Mode: TX mode : PE288


	Freq	CableAntenna H Loss Factor H					Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	dB
2 3 4 5	121.55 156.46 245.09 443.29 603.54 912.86	1. 26 1. 33 1. 65 2. 38 2. 71 3. 61	7. 77 9. 58 8. 00 12. 59 15. 27 20. 47	27. 06 26. 87 26. 55 27. 40 27. 54 26. 71	24. 95 23. 71 25. 20 23. 28 26. 07 22. 88	6. 92 7. 75 8. 30 10. 85 16. 51 20. 25	43.50 46.00 46.00 46.00	-36.58 -35.75 -37.70 -35.15 -29.49 -25.75



Report No.: SZEM140700368401

Page: 51 of 60

Radiated Emission below 1GHz(For PE281)							
30MHz~1GHz (QP)							
Test mode: TX mode Vertical							



Condition: 47 CFR PART 15B 3m 3142C VERTICAL

Job No. : 3684RF Test Mode: TX mode : PE289


	Freq	CableA		Preamp Factor			Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
3 4 5	102.00 158.67 389.35 499.42 739.66 869.13	1.21 1.33 2.17 2.60 3.03	6.84 9.52 11.77 13.40 17.80 19.60	27. 07 27. 70 27. 37	24. 24 25. 69 24. 32	4. 11 7. 97 11. 11 13. 99 17. 78 20. 62	43.50 46.00 46.00 46.00	-39. 39 -35. 53 -34. 89 -32. 01 -28. 22 -25. 38



Report No.: SZEM140700368401

Page: 52 of 60

Test mode: TX mode	Horizontal
--------------------	------------



Condition: 47 CFR PART 15B 3m 3142C HORIZONTAL

Job No. : 3684RF Test Mode: TX mode : PE289

	Freq	CableAntenna Loss Factor			Read Level		Limit Line	Over Limit
•	MHz	dB	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	dB
1 2 3 4 5	162.04 231.72 338.40 541.37 675.21 839.18	1.34 1.58 2.02 2.64 2.85 3.36	9.50 8.26 10.46 14.72 16.40 19.22	26.85 26.59 26.70 27.63 27.44 27.09	24. 07 23. 48 23. 97 25. 96 25. 49 24. 82	8. 06 6. 73 9. 75 15. 69 17. 30 20. 31	46.00 46.00 46.00 46.00	-35. 44 -39. 27 -36. 25 -30. 31 -28. 70 -25. 69



Report No.: SZEM140700368401

Page: 53 of 60

#### For model PE289

Transmitte	r Emiss	ion above	1GHz					
Test mode:	Test mode:		GFSK Test		channel: Lowest		ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3738.129	4.99	33.10	38.84	42.01	41.26	74	-32.74	Vertical
4804.000	5.63	34.70	39.24	43.22	44.31	74	-29.69	Vertical
5940.967	6.36	36.19	39.19	43.00	46.36	74	-27.64	Vertical
7206.000	6.80	35.63	39.07	43.72	47.08	74	-26.92	Vertical
9608.000	8.94	37.33	37.93	41.81	50.15	74	-23.85	Vertical
12210.020	8.96	38.96	38.88	42.14	51.18	74	-22.82	Vertical
3776.385	4.95	33.13	38.86	43.11	42.33	74	-31.67	Horizontal
4804.000	5.63	34.70	39.24	43.27	44.36	74	-29.64	Horizontal
5971.290	6.54	36.24	39.19	43.47	47.06	74	-26.94	Horizontal
7206.000	6.80	35.63	39.07	42.85	46.21	74	-27.79	Horizontal
9608.000	8.94	37.33	37.93	41.31	49.65	74	-24.35	Horizontal
12055.600	9.22	38.77	38.75	42.73	51.97	74	-22.03	Horizontal

Test mode:		GFSK	Tes	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3786.010	4.94	33.14	38.86	42.19	41.41	74	-32.59	Vertical
4880.000	5.61	34.78	39.26	43.24	44.37	74	-29.63	Vertical
6219.512	6.37	36.06	39.16	43.60	46.87	74	-27.13	Vertical
7320.000	6.73	35.51	39.06	43.56	46.74	74	-27.26	Vertical
9760.000	8.84	37.80	37.84	40.14	48.94	74	-25.06	Vertical
11457.210	9.88	38.19	38.45	41.33	50.95	74	-23.05	Vertical
3824.757	4.97	33.19	38.88	41.67	40.95	74	-33.05	Horizontal
4880.000	5.61	34.78	39.26	43.59	44.72	74	-29.28	Horizontal
5880.782	6.01	36.07	39.20	43.64	46.52	74	-27.48	Horizontal
7320.000	6.73	35.51	39.06	43.33	46.51	74	-27.49	Horizontal
9760.000	8.84	37.80	37.84	40.88	49.68	74	-24.32	Horizontal
11903.140	9.35	38.60	38.66	41.83	51.12	74	-22.88	Horizontal



Report No.: SZEM140700368401

Page: 54 of 60

Test mode:		GFSK	Tes	t channel:	Highest	Ren	nark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3700.260	5.03	33.08	38.83	42.01	41.29	74	-32.71	Vertical
4960.000	5.60	34.86	39.29	43.45	44.62	74	-29.38	Vertical
6172.197	6.39	36.11	39.17	43.71	47.04	74	-26.96	Vertical
7440.000	6.72	35.43	39.05	43.28	46.38	74	-27.62	Vertical
9920.000	9.19	38.27	37.75	39.69	49.40	74	-24.60	Vertical
11399.030	10.04	38.15	38.42	41.51	51.28	74	-22.72	Vertical
3747.656	4.98	33.11	38.85	41.80	41.04	74	-32.96	Horizontal
4960.000	5.60	34.86	39.29	43.25	44.42	74	-29.58	Horizontal
6412.427	6.64	35.82	39.14	41.56	44.88	74	-29.12	Horizontal
7440.000	6.72	35.43	39.05	43.48	46.58	74	-27.42	Horizontal
9920.000	9.19	38.27	37.75	39.90	49.61	74	-24.39	Horizontal
11603.960	9.48	38.30	38.52	41.78	51.04	74	-22.96	Horizontal



Report No.: SZEM140700368401

Page: 55 of 60

#### For model PE288

Transmitte	r Emissi	on above	1GHz					
Test mode:	(	GFSK	Test	channel:	Lowest	Lowest Remai		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3700.260	5.03	33.08	38.83	42.13	41.41	74	-32.59	Vertical
4804.000	5.63	34.70	39.24	42.77	43.86	74	-30.14	Vertical
6283.164	6.48	35.98	39.15	42.79	46.10	74	-27.90	Vertical
7206.000	6.80	35.63	39.07	42.33	45.69	74	-28.31	Vertical
9608.000	8.94	37.33	37.93	40.44	48.78	74	-25.22	Vertical
11399.030	10.04	38.15	38.42	41.38	51.15	74	-22.85	Vertical
3923.367	5.10	33.37	38.92	41.59	41.14	74	-32.86	Horizontal
4804.000	5.63	34.70	39.24	42.84	43.93	74	-30.07	Horizontal
6478.053	6.46	35.79	39.13	43.50	46.62	74	-27.38	Horizontal
7206.000	6.80	35.63	39.07	41.20	44.56	74	-29.44	Horizontal
9608.000	8.94	37.33	37.93	40.46	48.80	74	-25.20	Horizontal
11399.030	10.04	38.15	38.42	41.38	51.15	74	-22.85	Horizontal

Test mode:		GFSK	Tes	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3824.757	4.97	33.19	38.88	41.63	40.91	74	-33.09	Vertical
4880.000	5.61	34.78	39.26	42.69	43.82	74	-30.18	Vertical
6561.030	6.23	35.74	39.13	42.60	45.44	74	-28.56	Vertical
7320.000	6.73	35.51	39.06	42.12	45.30	74	-28.70	Vertical
9760.000	8.84	37.80	37.84	39.58	48.38	74	-25.62	Vertical
12178.980	9.01	38.93	38.85	41.92	51.01	74	-22.99	Vertical
3579.815	5.08	32.98	38.78	41.95	41.23	74	-32.77	Horizontal
4880.000	5.61	34.78	39.26	42.96	44.09	74	-29.91	Horizontal
6235.364	6.40	36.04	39.16	43.05	46.33	74	-27.67	Horizontal
7320.000	6.73	35.51	39.06	42.78	45.96	74	-28.04	Horizontal
9760.000	8.84	37.80	37.84	39.35	48.15	74	-25.85	Horizontal
12524.820	8.84	39.23	39.14	42.96	51.89	74	-22.11	Horizontal



Report No.: SZEM140700368401

Page: 56 of 60

Test mode:		GFSK	Tes	t channel:	Highest	Re	mark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3943.392	5.13	33.40	38.93	41.88	41.48	74	-32.52	Vertical
4960.000	5.60	34.86	39.29	42.87	44.04	74	-29.96	Vertical
6478.053	6.46	35.79	39.13	42.45	45.57	74	-28.43	Vertical
7440.000	6.72	35.43	39.05	42.76	45.86	74	-28.14	Vertical
9920.000	9.19	38.27	37.75	38.28	47.99	74	-26.01	Vertical
11872.880	9.36	38.57	38.64	42.57	51.86	74	-22.14	Vertical
4065.707	5.20	33.66	38.98	41.12	41.00	74	-33.00	Horizontal
4960.000	5.60	34.86	39.29	42.66	43.83	74	-30.17	Horizontal
6267.190	6.46	36.00	39.16	42.77	46.07	74	-27.93	Horizontal
7440.000	6.72	35.43	39.05	42.23	45.33	74	-28.67	Horizontal
9920.000	9.19	38.27	37.75	38.12	47.83	74	-26.17	Horizontal
12366.420	8.70	39.16	39.01	41.68	50.53	74	-23.47	Horizontal



Report No.: SZEM140700368401

Page: 57 of 60

#### For model PE280

Transmitter Emission above 1GHz								
Test mode:		GFSK Test		channel: Lowest		Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3747.656	4.98	33.11	38.85	43.95	43.19	74	-30.81	Vertical
4804.000	5.63	34.70	39.24	45.60	46.69	74	-27.31	Vertical
6283.164	6.48	35.98	39.15	44.79	48.10	74	-25.90	Vertical
7206.000	6.80	35.63	39.07	45.23	48.59	74	-25.41	Vertical
9608.000	8.94	37.33	37.93	42.51	50.85	74	-23.15	Vertical
11752.600	9.41	38.45	38.59	42.62	51.89	74	-22.11	Vertical
3923.367	5.10	33.37	38.92	43.59	43.14	74	-30.86	Horizontal
4804.000	5.63	34.70	39.24	45.59	46.68	74	-27.32	Horizontal
6494.564	6.41	35.78	39.13	45.61	48.67	74	-25.33	Horizontal
7206.000	6.80	35.63	39.07	44.32	47.68	74	-26.32	Horizontal
9608.000	8.94	37.33	37.93	43.73	52.07	74	-21.93	Horizontal
11633.540	9.47	38.33	38.53	43.10	52.37	74	-21.63	Horizontal

Test mode:		GFSK	Tes	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3824.757	4.97	33.19	38.88	43.63	42.91	74	-31.09	Vertical
4880.000	5.61	34.78	39.26	45.58	46.71	74	-27.29	Vertical
5971.290	6.54	36.24	39.19	45.20	48.79	74	-25.21	Vertical
7320.000	6.73	35.51	39.06	45.71	48.89	74	-25.11	Vertical
9760.000	8.84	37.80	37.84	42.31	51.11	74	-22.89	Vertical
12241.140	8.91	39.00	38.91	43.21	52.21	74	-21.79	Vertical
3480.968	4.84	32.87	38.73	43.40	42.38	74	-31.62	Horizontal
4880.000	5.61	34.78	39.26	45.03	46.16	74	-27.84	Horizontal
6267.190	6.46	36.00	39.16	44.90	48.20	74	-25.80	Horizontal
7320.000	6.73	35.51	39.06	45.76	48.94	74	-25.06	Horizontal
9760.000	8.84	37.80	37.84	42.25	51.05	74	-22.95	Horizontal
11428.080	9.96	38.17	38.43	42.70	52.40	74	-21.60	Horizontal



Report No.: SZEM140700368401

Page: 58 of 60

Test mode:		GFSK		t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3795.660	4.93	33.15	38.87	43.74	42.95	74	-31.05	Vertical
4960.000	5.60	34.86	39.29	45.69	46.86	74	-27.14	Vertical
6527.712	6.32	35.76	39.13	44.19	47.14	74	-26.86	Vertical
7440.000	6.72	35.43	39.05	45.85	48.95	74	-25.05	Vertical
9920.000	9.19	38.27	37.75	40.97	50.68	74	-23.32	Vertical
12334.980	8.76	39.12	38.98	42.98	51.88	74	-22.12	Vertical
3863.900	5.02	33.26	38.90	42.97	42.35	74	-31.65	Horizontal
4960.000	5.60	34.86	39.29	45.68	46.85	74	-27.15	Horizontal
6140.854	6.45	36.14	39.17	44.35	47.77	74	-26.23	Horizontal
7440.000	6.72	35.43	39.05	45.81	48.91	74	-25.09	Horizontal
9920.000	9.19	38.27	37.75	41.19	50.90	74	-23.10	Horizontal
12366.420	8.70	39.16	39.01	42.68	51.53	74	-22.47	Horizontal





Report No.: SZEM140700368401

Page: 59 of 60

#### For model PE281

Transmitter Emission above 1GHz									
Test mode:		GFSK Test		channel: Lowest		Rema	ırk:	Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3766.785	4.96	33.13	38.86	44.34	43.57	74	-30.43	Vertical	
4804.000	5.63	34.70	39.24	44.42	45.51	74	-28.49	Vertical	
6001.768	6.71	36.30	39.18	43.83	47.66	74	-26.34	Vertical	
7206.000	6.80	35.63	39.07	44.58	47.94	74	-26.06	Vertical	
9608.000	8.94	37.33	37.93	42.61	50.95	74	-23.05	Vertical	
11994.380	9.31	38.69	38.70	43.48	52.78	74	-21.22	Vertical	
3815.033	4.95	33.18	38.88	44.19	43.44	74	-30.56	Horizontal	
4804.000	5.63	34.70	39.24	44.21	45.30	74	-28.70	Horizontal	
6094.137	6.53	36.20	39.17	44.98	48.54	74	-25.46	Horizontal	
7206.000	6.80	35.63	39.07	43.59	46.95	74	-27.05	Horizontal	
9608.000	8.94	37.33	37.93	42.86	51.20	74	-22.80	Horizontal	
11782.550	9.40	38.48	38.60	42.77	52.05	74	-21.95	Horizontal	

Test mode:		GFSK	Tes	t channel:	Middle	e Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3588.939	5.10	32.99	38.78	44.70	44.01	74	-29.99	Vertical
4880.000	5.61	34.78	39.26	44.12	45.25	74	-28.75	Vertical
6125.242	6.48	36.16	39.17	45.50	48.97	74	-25.03	Vertical
7320.000	6.73	35.51	39.06	44.77	47.95	74	-26.05	Vertical
9760.000	8.84	37.80	37.84	41.94	50.74	74	-23.26	Vertical
11312.310	9.82	38.14	38.38	42.05	51.63	74	-22.37	Vertical
3923.367	5.10	33.37	38.92	43.80	43.35	74	-30.65	Horizontal
4880.000	5.61	34.78	39.26	44.52	45.65	74	-28.35	Horizontal
5940.967	6.36	36.19	39.19	44.83	48.19	74	-25.81	Horizontal
7320.000	6.73	35.51	39.06	44.41	47.59	74	-26.41	Horizontal
9760.000	8.84	37.80	37.84	41.66	50.46	74	-23.54	Horizontal
11428.080	9.96	38.17	38.43	42.70	52.40	74	-21.60	Horizontal



Report No.: SZEM140700368401

Page: 60 of 60

Test mode:		GFSK	Tes	t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3738.129	4.99	33.10	38.84	44.17	43.42	74	-30.58	Vertical
4960.000	5.60	34.86	39.29	44.52	45.69	74	-28.31	Vertical
6001.768	6.71	36.30	39.18	43.68	47.51	74	-26.49	Vertical
7440.000	6.72	35.43	39.05	44.70	47.80	74	-26.20	Vertical
9920.000	9.19	38.27	37.75	40.86	50.57	74	-23.43	Vertical
11399.030	10.04	38.15	38.42	42.51	52.28	74	-21.72	Vertical
3766.785	4.96	33.13	38.86	44.46	43.69	74	-30.31	Horizontal
4960.000	5.60	34.86	39.29	44.28	45.45	74	-28.55	Horizontal
6001.768	6.71	36.30	39.18	44.44	48.27	74	-25.73	Horizontal
7440.000	6.72	35.43	39.05	44.76	47.86	74	-26.14	Horizontal
9920.000	9.19	38.27	37.75	40.48	50.19	74	-23.81	Horizontal
11457.210	9.88	38.19	38.45	42.68	52.30	74	-21.70	Horizontal

#### Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
  - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.