



<b>Prüfbericht - Nr.:</b> Test Report No.	<b>14009434 001</b>	<b>Seite 1 von 12</b> Page 1 of 12			
<b>Auftraggeber:</b> Applicant	<b>IDT Technology Ltd.</b> <b>Block C, 9/F., Kaiser Estate, Phase 1</b> <b>41 Man Yue Street</b> <b>Hunghom, Kowloon</b> <b>Hong Kong</b>				
<b>Gegenstand der Prüfung:</b> Test item	<b>Low Power Transmitter</b>				
<b>Bezeichnung:</b> Identification	<b>THGR123N, THGN123N</b> <b>THR123N, THN123N</b>	<b>Serien-Nr.:</b> Serial No.	<b>Engineering sample</b>		
<b>Wareneingangs-Nr.:</b> Receipt No.	<b>050524026</b>	<b>Eingangsdatum:</b> Date of receipt	<b>24.05.2005</b>		
<b>Prüfört:</b> Testing location	<b>TÜV Rheinland Hong Kong Ltd.</b> Unit 8, 25 <sup>th</sup> Floor, Skyline Tower, 39 Wang Kwong Road, Kowloon Bay Kowloon, Hong Kong  <b>Hong Kong Productivity Council</b> HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong				
<b>Prüfgrundlage:</b> Test specification	<b>FCC Part 15, Subpart C</b>				
<b>Prüfergebnis:</b> Test Result	<b>Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.</b> The above mentioned product was tested and <b>passed</b> .				
<b>geprüft / tested by:</b>	<b>kontrolliert / reviewed by:</b>				
05.10.2005 Hugo Wan 	05.10.2005 Thomas Berns 				
<b>Datum</b> Date	<b>Name</b> Name	<b>Unterschrift</b> Signature	<b>Datum</b> Date	<b>Name</b> Name	<b>Unterschrift</b> Signature
<b>Sonstiges: FCC ID NMTTHGN123N-01</b> Other Aspects					
<b>Abkürzungen:</b> OK, Pass, P = entspricht Prüfgrundlage Fail, F = entspricht nicht Prüfgrundlage N/A = nicht anwendbar NT = nicht getestet			<b>Abbreviations:</b> OK, Pass, P = passed Fail, F = failed N/A = not applicable NT = not tested		
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products.					

# Test Summary

## **Radiated Emission of Carrier Frequency**

*Result: Pass*

## **Spurious Radiated Emissions**

*Result: Pass*

## **Bandwidth Measurement**

*Result: Pass*

# Contents

- List of Test and Measurement Instruments.....4
- General Product Information .....5
  - Product Function and Intended Use.....5
  - Circuit Description .....5
  - Ratings and System Details .....5
  - Independent Operation Modes.....6
  - Submitted Documents .....6
  - Related Submittal(s) Grants .....6
- Test Set-up and Operation Mode.....7
  - Principle of Configuration Selection .....7
  - Test Operation and Test Software.....7
  - Special Accessories and Auxiliary Equipment .....7
  - Countermeasures to achieve EMC Compliance.....7
- Test Methodology .....8
  - Radiated Emission .....8
  - Field Strength Calculation.....8
- Test Results .....9
  - Radiated Emission of Carrier Frequency Section 15.231(b).....9
  - Spurious Radiated Emissions Section 15.231(b).....10
  - Bandwidth Measurement Section 15.231(c).....12
- Appendix 1: Test Results
- Appendix 2: Test Setup
- Appendix 3: EUT External Photo
- Appendix 4: EUT Internal Photo
- Appendix 5: FCCID Label, Block Diagram, Schematics and User manual.

## List of Test and Measurement Instruments

Kind of Equipment	Manufacturer	Type	S/N
Test Receiver	Rohde & Schwarz	ESVS30	842807/009
Biconical Antenna	Rohde & Schwarz	HK116	841489/015
Log.-Periodic Antenna	Rohde & Schwarz	HL223	841516/017
Double Ridge Horn Antenna	EMCO	3115	9002-3351
Double Ridge Horn Antenna	EMCO	3115	9002-3347
Signal Generator	Rohde & Schwarz	SMY 01	844146/024
Signal Generator	Rohde & Schwarz	SMY 01	844146/023
Spectrum Analyzer	Rohde & Schwarz	FSP30	1093.4495K30

## General Product Information

### Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a weather station operating at 433.92 MHz. The EUT senses the temperature and humidity level and then transmit this information to the associated weather station.

A transmitter transmits signal for every 39 seconds, and the signal on period is about 0.39s. It activated automatically shall cease transmission within 2 seconds after activation. Hence it operates around 92 times per hour.

### FCC ID NMTTHGN123N-01

Model	Product description
THGR123N	Remote Thermo-Hygrometer Sensor
THGN123N	
THR123N	
THN123N	

For the above multiple models, THGR123N contains the most integrated circuit and hence this model was chosen to be representative for testing.

The above models differ by the availability of Humidity sensor and LCD display. Every model has a basic temperature sensor and the test model THGR123N contains the temperature and humidity sensor and the LCD display.

### Circuit Description

The main unit of THGR123N is a multi-channel transmitter, after reset the unit, the MCU will turn on the super-regenerative transmit module and to send out the thermo-hygrometer signal. The transmit centre frequency is 433.92MHz. The micro-band is matched with the antenna 50ohm. The transmitter is turned on every 39, 41, 43 seconds for channels 1, 2, 3 respectively.

### Ratings and System Details

	Transmitter
Operated Frequency	: 433.92 MHz
Number of channels	: 3
Type of antenna	: Integral antenna
Power supply	: Battery operated 3.0V
Ports	: none
Protection Class	: III
Equipment Class	: B

## **Independent Operation Modes**

The basic operation modes are:

- Reset Button: Press to reset all value to default values.
- Channel selection.
- °C/F display format selection.

For further information refer to User Manual

## **Submitted Documents**

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- FCC ID label

## **Related Submittal(s) Grants**

This is a single application for certification of the transmitter.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- The EUT was set in a continuous transmission test mode.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

### Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Circuit Diagram or the Technical Construction File. No additional measures were employed to achieve compliance.

## Test Methodology

### Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in section 7.1.1 and 7.1.2 of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

$$\text{System Factor} = CF + FA - PA.$$

Where FS = Peak Value of Field Strength in dBuV/m at 3 meters.

R = Peak Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Average value of FS = FS –Average factor.

Average Factor = 20 log duty cycle.



## Test Results

### Radiated Emission of Carrier Frequency

### Section 15.231(b)

**RESULT:**
**Pass**

Test Specification : FCC Part 15 Section 15.231(b1 and b2)  
 Test Method : ANSI 63.4-2003  
 Measurement Location : Semi Anechoic Chamber  
 Measurement Distance : 3m  
 Detector Function : Peak  
 Measurement BW : 100 kHz  
 Supply Voltage : DC 3.0V  
 Channel under test : Channel 1 with worst case emission.

Polarization: Vertical

Value	Frequency (MHz)	System Factor (dB)	Measured Field strength (pk) (dBuV/m)	Average Factor (dB)	Net Field strength (dBuV/m)	Limit (dBuV/m)	Delta to Limit (dB)
Peak	433.90	18.3	73.7	-	73.7	100.8	-27.1
Average	433.90	18.3	73.7	-7.4	66.3	80.8	-14.5

Polarization: Horizontal

Value	Frequency (MHz)	System Factor (dB)	Measured Field strength (pk) (dBuV/m)	Average Factor (dB)	Net Field strength (dBuV/m)	Limit (dBuV/m)	Delta to Limit (dB)
Peak	433.90	18.3	69.5	-	69.5	100.8	-31.3
Average	433.90	18.3	69.5	-7.4	62.1	80.8	-18.7

Remark; The calculation of average factor is shown in appendix 1 page 5.

**Limit**
**Section 15.231(b2)**

Frequency within the band (MHz)	Peak Emission		Average Emission	
	(microvolt/meter)	dB $\mu$ V/m	(microvolt/meter)	dB $\mu$ V/m
433.90	109,958	100.8	10,996	80.8

According to section 15.35(b), when average radiated emission measurements are specified, including emission measurement below 1000MHz, there also is limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated.

**Spurious Radiated Emissions****Section 15.231(b)****RESULT:****Pass**

Test Specification : FCC Part 15 Section 15.231(b1 and b3)  
 Test Method : ANSI 63.4-2003  
 Measurement Location : Semi Anechoic Chamber  
 Measurement Distance : 3m  
 Detector Function : Peak  
 Measurement BW : 100 kHz  
 Supply Voltage : DC 3.0V  
 Measuring Frequency Range : 30-4500MHz

Polarization: Vertical

Frequency (MHz)	Reading (PK) (dBuV/m)	Antenna Factor (dBuV/m)	System Factor (dB)	Field strength (PK) (dBuV/m)	Average Factor (dB)	Field strength (AV) (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
867.802	4.74	22.20	2.67	29.90	-7.44	22.46	60.80	-38.34
*1301.692	41.63	24.90	-33.70	32.83	-7.44	25.39	54.00	-28.61
1735.553	40.29	26.50	-33.30	33.49	-7.44	26.05	60.80	-34.75
2169.514	38.64	27.80	-32.56	33.88	-7.44	26.44	60.80	-34.36
2603.555	38.89	28.88	-31.18	36.59	-7.44	29.15	60.80	-31.65
3036.996	46.30	30.00	-29.73	46.57	-7.44	39.13	60.80	-21.67
3471.377	45.07	31.20	-31.09	45.18	-7.44	37.74	60.80	-23.06
*3905.178	43.77	32.50	-30.35	45.92	-7.44	38.48	54.00	-15.52
4338.879	45.27	32.45	-29.91	47.81	-7.44	40.37	60.80	-20.43

Polarization: Horizontal

Frequency (MHz)	Reading (PK) (dBuV/m)	Antenna Factor (dBuV/m)	System Factor (dB)	Field strength (PK) (dBuV/m)	Average Factor (dB)	Field strength (AV) (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
867.802	4.83	22.20	2.67	29.70	-7.44	22.26	60.80	-38.54
*1301.712	40.81	24.90	-33.70	32.01	-7.44	24.57	54.00	-29.43
1735.373	39.70	26.50	-33.30	32.90	-7.44	25.46	60.80	-35.34
2169.514	44.53	27.80	-32.56	39.77	-7.44	32.33	60.80	-28.47
2603.395	40.15	28.88	-31.18	37.85	-7.44	30.41	60.80	-30.39
3037.176	48.93	30.00	-29.73	49.20	-7.44	41.76	60.80	-19.04
3471.257	48.04	31.20	-31.09	48.15	-7.44	40.71	60.80	-20.09
*3904.958	45.66	32.50	-30.35	47.81	-7.44	40.37	54.00	-13.63
4339.119	50.73	32.45	-29.91	53.27	-7.44	45.83	60.80	-14.97

Remark: ' \* ' indicates the frequency of the emissions fall into the restricted band.

There is no spurious emission found between lowest oscillating frequency 32.768kHz to 30 MHz.

**Limit****Section 15.231(b3)**

Frequency (MHz)	Field strength (microvolt/meter)	Field strength (dB $\mu$ V/m)	Measurement distance (meters)
433.900	1,099	$20 \cdot \log(1099) = 60.8$	3

## Section 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

## Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (microvolt/meter)	Field strength (dB $\mu$ V/m)	Measurement distance (meters)
30-88	100	$20 \cdot \log(100) = 40.0$	3
88-216	150	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
960-2500	500	$20 \cdot \log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

## Bandwidth Measurement

## Section 15.231(c)

### RESULT:

Pass

Test Specification : FCC Part 15 section 15.231(c)  
Port of Testing : Antenna port  
Detector Function : Peak  
Supply Voltage : DC 3.0V

Refer to the data graph, the 20dB points at lower edge and at higher edge are 8.6KHz and 10.8KHz respectively apart from the centre modulated carrier, the bandwidth of the emission is 0.0045 % of the centre frequency. Therefore, the EUT meets the requirement of section 15.231(c).

For test results refer to Appendix 1, page 2.

### Limit

### Section 15.231(c)

The bandwidth of the emission shall be no wider than 0.25% if the center frequency for devices operating above 70MHz and below 900MHz.