



RF EXPOSURE REPORT

REPORT NO.: SA981014H03

MODEL NO.: W121, LCS-8131N2

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT : NETRONIX , INC.

ADDRESS : No. 945, Boai St., Jubei City,
Hsin-Chu,302,Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

TEST LOCATION: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan



No SAR Evaluation Required if power is below the following threshold:

Tunable Range		Center of Tunable Band (GHz)	60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High		
2.412	2.462	2.437	24.37

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
13.8	24.0	-0.35	22.1

Threshold for no SAR evaluation is 24.37 mW

Maximum TX Power is 24.0 mW Conducted and 22.1 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold