



RF EXPOSURE REPORT

REPORT NO.: SA961101H03

MODEL NO.: W463, LCS-8531N, WFN-41

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT : NETRONIX, INC.

ADDRESS : No. 945, Boai St., Jubei City, Hsin-Chu, 302,
Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.

TEST LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.



No SAR Evaluation Required if power is below the following threshold:

Tunable Range		Center of Tunable Band (GHz)	60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High		
2.412	2.462	2.437	24.37

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
11.75	14.962	2.0	23.71

Threshold for no SAR evaluation is 24.37 mW

Maximum TX Power is 14.962 mW Conducted and 23.71 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold