

FCC Test Report (WLAN)

Report No.: RF180903E03

FCC ID: NOIDS-S97407

Test Model: S97407

Received Date: Sep. 03, 2018

Test Date: Nov. 20 to Dec. 12, 2018

Issued Date: May 24, 2019

Applicant: NETRONIX, INC.

Address: No. 945, Boai St., Jubei City, Hsin-Chu, 302, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT (WLAN)	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	14
3.5 General Description of Applied Standards	15
4 Test Types and Results	16
4.1 Radiated Emission and Bandedge Measurement	16
4.1.1 Limits of Radiated Emission and Bandedge Measurement	16
4.1.2 Test Instruments	17
4.1.3 Test Procedures	18
4.1.4 Deviation from Test Standard	18
4.1.5 Test Setup	19
4.1.6 EUT Operating Conditions	20
4.1.7 Test Results	21
4.2 Conducted Emission Measurement	37
4.2.1 Limits of Conducted Emission Measurement	37
4.2.2 Test Instruments	37
4.2.3 Test Procedures	38
4.2.4 Deviation from Test Standard	38
4.2.5 Test Setup	38
4.2.6 EUT Operating Conditions	38
4.2.7 Test Results	39
4.3 6dB Bandwidth Measurement	41
4.3.1 Limits of 6dB Bandwidth Measurement	41
4.3.2 Test Setup	41
4.3.3 Test Instruments	41
4.3.4 Test Procedure	41
4.3.5 Deviation from Test Standard	41
4.3.6 EUT Operating Conditions	41
4.3.7 Test Result	42
4.4 Conducted Output Power Measurement	44
4.4.1 Limits of Conducted Output Power Measurement	44
4.4.2 Test Setup	44
4.4.3 Test Instruments	44
4.4.4 Test Procedures	44
4.4.5 Deviation from Test Standard	44
4.4.6 EUT Operating Conditions	44
4.4.7 Test Results	45
4.5 Power Spectral Density Measurement	47
4.5.1 Limits of Power Spectral Density Measurement	47
4.5.2 Test Setup	47
4.5.3 Test Instruments	47
4.5.4 Test Procedure	47
4.5.5 Deviation from Test Standard	47
4.5.6 EUT Operating Condition	47

4.5.7 Test Results	48
4.6 Conducted Out of Band Emission Measurement.....	50
4.6.1 Limits of Conducted Out of Band Emission Measurement	50
4.6.2 Test Setup.....	50
4.6.3 Test Instruments	50
4.6.4 Test Procedure	50
4.6.5 Deviation from Test Standard	50
4.6.6 EUT Operating Condition	50
4.6.7 Test Results	50
5 Pictures of Test Arrangements.....	55
Appendix – Information on the Testing Laboratories	56

Release Control Record

Issue No.	Description	Date Issued
RF180903E03	Original release.	May 24, 2019

1 Certificate of Conformity

Product: 9.7" Digital Signage

Brand: SABLE

Test Model: S97407

Sample Status: ENGINEERING SAMPLE

Applicant: NETRONIX, INC.

Test Date: Nov. 20 to Dec. 12, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Phoenix Huang, **Date:** May 24, 2019
Phoenix Huang / Specialist

Approved by : May Chen, **Date:** May 24, 2019
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.86dB at 0.20078MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 7356.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex(MHF) not a standard connector.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.53 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.08 dB
	6GHz ~ 18GHz	4.98 dB
	18GHz ~ 40GHz	5.19 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (WLAN)

Product	9.7" Digital Signage
Brand	SABLE
Test Model	S97407
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	3.8Vdc form battery or 5Vdc from USB interface
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11Mbps 802.11g: up to 54Mbps 802.11n: up to 150Mbps
Operating Frequency	2.412 ~ 2.462GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7
Output Power	362.243 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	USB Cable × 1 (Shielded, 1m)

Note:

1. Simultaneously transmission condition.

Condition	Technology		
1	WLAN	Bluetooth	NFC
2	Zigbee	Bluetooth	NFC

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

2. The antennas provided to the EUT, please refer to the following table:

Technology	Brand	Model Name	Ant. Net Gain (dBi)	Frequency Range	Ant. Type	Connector Type	Cable Length (cm)
WLAN	Walsin	RFPCA410603EMAB302	3.74	2.4~2.4835 GHz	PCB	i-pex(MHF)	3
Bluetooth	Walsin	RFPCA221126EMAB301	3.09	2.4~2.4835 GHz	PCB	i-pex(MHF)	26
Zigbee	Walsin	RFPCA410604EMAB301	3.7	2.4~2.4835 GHz	PCB	i-pex(MHF)	4.5
NFC	NA	NA	-	13.56 MHz	PCB Loop	NA	NA

3. The EUT must be supplied with a battery as following table:

Brand	Model No.	Spec.
TCL	PR-248899G	3.8Vdc, 3035mAh, 11.53Wh

4. The EUT incorporates a SISO function.

MODULATION MODE	TX & RX CONFIGURATION	
802.11b	1TX	1RX
802.11g	1TX	1RX
802.11n (HT20)	1TX	1RX
802.11n (HT40)	1TX	1RX

5. The EUT was pre-tested under the following modes:

For Radiated Emission test

Pre-test Mode	Description
Mode A	Power from USB adapter
Mode B	Power from Battery

From the above modes, the worst case was found in **Mode A**. Therefore only the test data of the mode was recorded in this report.

For AC Power Conducted Emission test

Pre-test Mode	Description
Mode C	Power from USB adapter
Mode D	Power from Laptop

From the above modes, the worst case was found in **Mode D**. Therefore only the test data of the mode was recorded in this report.

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

7 channels are provided for 802.11n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	PLC: Power from Laptop Other: Power from USB adapter

Where **RE≥1G**: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane (below 1GHz) and X-plane (above 1GHz)**.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 2, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 2, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	1	OFDM	BPSK	6

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	1	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 2, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 2, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5


Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (System)	TESTED BY
RE $\geq$ 1G	23deg. C, 68%RH	120Vac, 60Hz	Steven Chiang
RE<1G	23deg. C, 68%RH	120Vac, 60Hz	Frank Chuang
PLC	25deg. C, 75%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Anderson Chen


3.3 Duty Cycle of Test Signal

Duty cycle of test signal is 100 %, duty factor is not required.


802.11b




802.11g



802.11n (HT20)



802.11n (HT40)



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	USB Adapter	ASUS	EXA1205UA	NA	NA	Provided by Lab
B.	Laptop	DELL	E6420	B92T3R1	FCC DoC	Provided by Lab


Note:

1. All power cords of the above support units are non-shielded (1.8m).


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Micro USB to USB Cable	1	1	Yes	0	Supplied by client

3.4.1 Configuration of System under Test

For Laptop Mode:



For USB Adapter Mode:



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	July 12, 2018	July 11, 2019
Pre-Amplifier EMCI	EMC001340	980142	Feb. 09, 2018	Feb. 08, 2019
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019
RF Cable	NA	LOOPCAB-001	Jan. 15, 2018	Jan. 14, 2019
RF Cable	NA	LOOPCAB-002	Jan. 15, 2018	Jan. 14, 2019
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 05, 2018	May 04, 2019
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Nov. 22, 2018	Nov. 21, 2019
RF Cable	8D	966-3-1	Mar. 20, 2018	Mar. 19, 2019
RF Cable	8D	966-3-2	Mar. 20, 2018	Mar. 19, 2019
RF Cable	8D	966-3-3	Mar. 20, 2018	Mar. 19, 2019
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Sep. 27, 2018	Sep. 26, 2019
Horn Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Nov. 25, 2018	Nov. 24, 2019
Pre-Amplifier EMCI	EMC12630SE	980384	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-1200	160922	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-2000	150317	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-5000	150322	Jan. 29, 2018	Jan. 28, 2019
Spectrum Analyzer Keysight	N9030A	MY54490679	July 23, 2018	July 22, 2019
Pre-Amplifier EMCI	EMC184045SE	980386	Jan. 29, 2018	Jan. 28, 2019
Horn Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Nov. 25, 2018	Nov. 24, 2019
RF Cable	EMC102-KM-KM-1200	160924	Jan. 29, 2018	Jan. 28, 2019
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019
Power meter Anritsu	ML2495A	1014008	May 09, 2018	May 08, 2019
Power sensor Anritsu	MA2411B	0917122	May 09, 2018	May 08, 2019

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. The CANADA Site Registration No. is 20331-1
4. Loop antenna was used for all emissions below 30 MHz.
5. Tested Date: Dec. 11 to 12, 2018

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (HyperTerminal paste S97407_RTL8711AM_1Tx_WiFi_Mp Command.txt command) has been activated to set the EUT on specific status.

4.1.7 Test Results

Above 1GHz Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.3 PK	74.0	-19.7	1.23 H	92	56.7	-2.4
2	2390.00	41.4 AV	54.0	-12.6	1.23 H	92	43.8	-2.4
3	*2412.00	98.6 PK			1.23 H	91	100.9	-2.3
4	*2412.00	96.1 AV			1.23 H	91	98.4	-2.3
5	4824.00	54.7 PK	74.0	-19.3	1.14 H	96	52.8	1.9
6	4824.00	53.7 AV	54.0	-0.3	1.14 H	96	51.8	1.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.4 PK	74.0	-19.6	3.39 V	295	56.8	-2.4
2	2390.00	41.1 AV	54.0	-12.9	3.39 V	295	43.5	-2.4
3	*2412.00	91.4 PK			3.39 V	295	93.7	-2.3
4	*2412.00	88.8 AV			3.39 V	295	91.1	-2.3
5	4824.00	49.0 PK	74.0	-25.0	2.76 V	321	47.1	1.9
6	4824.00	47.3 AV	54.0	-6.7	2.76 V	321	45.4	1.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.1 PK	74.0	-19.9	1.17 H	81	56.5	-2.4
2	2390.00	41.2 AV	54.0	-12.8	1.17 H	81	43.6	-2.4
3	*2437.00	99.0 PK			1.17 H	81	101.5	-2.5
4	*2437.00	96.6 AV			1.17 H	81	99.1	-2.5
5	2483.50	54.4 PK	74.0	-19.6	1.17 H	81	57.0	-2.6
6	2483.50	41.4 AV	54.0	-12.6	1.17 H	81	44.0	-2.6
7	4874.00	54.7 PK	74.0	-19.3	1.24 H	92	52.8	1.9
8	4874.00	53.6 AV	54.0	-0.4	1.24 H	92	51.7	1.9
9	7311.00	55.7 PK	74.0	-18.3	1.08 H	84	47.9	7.8
10	7311.00	51.4 AV	54.0	-2.6	1.08 H	84	43.6	7.8

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.2 PK	74.0	-19.8	3.38 V	293	56.6	-2.4
2	2390.00	41.1 AV	54.0	-12.9	3.38 V	293	43.5	-2.4
3	*2437.00	91.8 PK			3.38 V	293	94.3	-2.5
4	*2437.00	89.2 AV			3.38 V	293	91.7	-2.5
5	2483.50	54.5 PK	74.0	-19.5	3.38 V	293	57.1	-2.6
6	2483.50	41.3 AV	54.0	-12.7	3.38 V	293	43.9	-2.6
7	4874.00	48.5 PK	74.0	-25.5	2.81 V	335	46.6	1.9
8	4874.00	46.8 AV	54.0	-7.2	2.81 V	335	44.9	1.9
9	7311.00	52.6 PK	74.0	-21.4	2.57 V	344	44.8	7.8
10	7311.00	48.2 AV	54.0	-5.8	2.57 V	344	40.4	7.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.4 PK			1.16 H	92	100.9	-2.5
2	*2462.00	96.0 AV			1.16 H	92	98.5	-2.5
3	2483.50	54.3 PK	74.0	-19.7	1.16 H	92	56.9	-2.6
4	2483.50	41.3 AV	54.0	-12.7	1.16 H	92	43.9	-2.6
5	4924.00	54.6 PK	74.0	-19.4	1.10 H	94	52.6	2.0
6	4924.00	53.5 AV	54.0	-0.5	1.10 H	94	51.5	2.0
7	7386.00	54.0 PK	74.0	-20.0	1.01 H	83	46.1	7.9
8	7386.00	49.5 AV	54.0	-4.5	1.01 H	83	41.6	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	91.2 PK			3.44 V	294	93.7	-2.5
2	*2462.00	88.6 AV			3.44 V	294	91.1	-2.5
3	2483.50	54.1 PK	74.0	-19.9	3.44 V	294	56.7	-2.6
4	2483.50	41.1 AV	54.0	-12.9	3.44 V	294	43.7	-2.6
5	4924.00	49.1 PK	74.0	-24.9	2.85 V	340	47.1	2.0
6	4924.00	47.2 AV	54.0	-6.8	2.85 V	340	45.2	2.0
7	7386.00	52.0 PK	74.0	-22.0	2.52 V	336	44.1	7.9
8	7386.00	47.7 AV	54.0	-6.3	2.52 V	336	39.8	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.0 PK	74.0	-8.0	1.17 H	93	68.4	-2.4
2	2390.00	50.4 AV	54.0	-3.6	1.17 H	93	52.8	-2.4
3	*2412.00	108.0 PK			1.17 H	93	110.3	-2.3
4	*2412.00	98.7 AV			1.17 H	93	101.0	-2.3
5	4824.00	66.3 PK	74.0	-7.7	1.22 H	95	64.4	1.9
6	4824.00	53.8 AV	54.0	-0.2	1.22 H	95	51.9	1.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.2 PK	74.0	-13.8	3.38 V	311	62.6	-2.4
2	2390.00	44.3 AV	54.0	-9.7	3.38 V	311	46.7	-2.4
3	*2412.00	100.3 PK			3.38 V	311	102.6	-2.3
4	*2412.00	91.4 AV			3.38 V	311	93.7	-2.3
5	4824.00	48.8 PK	74.0	-25.2	1.00 V	329	46.9	1.9
6	4824.00	46.9 AV	54.0	-7.1	1.00 V	329	45.0	1.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 2	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	1.18 H	95	59.0	-2.4
2	2390.00	43.9 AV	54.0	-10.1	1.18 H	95	46.3	-2.4
3	*2417.00	103.0 PK			1.18 H	95	105.4	-2.4
4	*2417.00	93.7 AV			1.18 H	95	96.1	-2.4
5	4834.00	59.4 PK	74.0	-14.6	1.25 H	103	57.5	1.9
6	4834.00	46.7 AV	54.0	-7.3	1.25 H	103	44.8	1.9
7	7251.00	68.4 PK	74.0	-5.6	1.02 H	86	60.3	8.1
8	7251.00	53.5 AV	54.0	-0.5	1.02 H	86	45.4	8.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.2 PK	74.0	-19.8	3.35 V	278	56.6	-2.4
2	2390.00	41.5 AV	54.0	-12.5	3.35 V	278	43.9	-2.4
3	*2417.00	96.0 PK			3.35 V	278	98.4	-2.4
4	*2417.00	86.8 AV			3.35 V	278	89.2	-2.4
5	4834.00	52.1 PK	74.0	-21.9	3.40 V	357	50.2	1.9
6	4834.00	39.2 AV	54.0	-14.8	3.40 V	357	37.3	1.9
7	7251.00	65.5 PK	74.0	-8.5	2.61 V	343	57.4	8.1
8	7251.00	50.1 AV	54.0	-3.9	2.61 V	343	42.0	8.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	102.5 PK			1.15 H	84	105.0	-2.5
2	*2437.00	93.3 AV			1.15 H	84	95.8	-2.5
3	4874.00	58.2 PK	74.0	-15.8	1.23 H	90	56.3	1.9
4	4874.00	46.3 AV	54.0	-7.7	1.23 H	90	44.4	1.9
5	7311.00	68.6 PK	74.0	-5.4	1.08 H	84	60.8	7.8
6	7311.00	53.6 AV	54.0	-0.4	1.08 H	84	45.8	7.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	95.4 PK			3.35 V	306	97.9	-2.5
2	*2437.00	86.2 AV			3.35 V	306	88.7	-2.5
3	4874.00	52.0 PK	74.0	-22.0	3.34 V	336	50.1	1.9
4	4874.00	39.5 AV	54.0	-14.5	3.34 V	336	37.6	1.9
5	7311.00	65.1 PK	74.0	-8.9	2.57 V	344	57.3	7.8
6	7311.00	50.0 AV	54.0	-4.0	2.57 V	344	42.2	7.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.0 PK			1.17 H	92	105.5	-2.5
2	*2462.00	93.7 AV			1.17 H	92	96.2	-2.5
3	2483.50	55.9 PK	74.0	-18.1	1.17 H	92	58.5	-2.6
4	2483.50	43.5 AV	54.0	-10.5	1.17 H	92	46.1	-2.6
5	4924.00	59.0 PK	74.0	-15.0	1.22 H	87	57.0	2.0
6	4924.00	46.6 AV	54.0	-7.4	1.22 H	87	44.6	2.0
7	7386.00	68.5 PK	74.0	-5.5	1.00 H	83	60.6	7.9
8	7386.00	53.5 AV	54.0	-0.5	1.00 H	83	45.6	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	95.7 PK			3.38 V	287	98.2	-2.5
2	*2462.00	86.5 AV			3.38 V	287	89.0	-2.5
3	2483.50	54.3 PK	74.0	-19.7	3.38 V	287	56.9	-2.6
4	2483.50	41.6 AV	54.0	-12.4	3.38 V	287	44.2	-2.6
5	4924.00	51.6 PK	74.0	-22.4	3.34 V	351	49.6	2.0
6	4924.00	39.0 AV	54.0	-15.0	3.34 V	351	37.0	2.0
7	7386.00	65.4 PK	74.0	-8.6	2.56 V	356	57.5	7.9
8	7386.00	50.0 AV	54.0	-4.0	2.56 V	356	42.1	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.8 PK	74.0	-7.2	1.20 H	92	69.2	-2.4
2	2390.00	51.6 AV	54.0	-2.4	1.20 H	92	54.0	-2.4
3	*2412.00	108.7 PK			1.20 H	92	111.0	-2.3
4	*2412.00	99.1 AV			1.20 H	92	101.4	-2.3
5	4824.00	67.1 PK	74.0	-6.9	1.13 H	97	65.2	1.9
6	4824.00	53.5 AV	54.0	-0.5	1.13 H	97	51.6	1.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.4 PK	74.0	-13.6	3.39 V	291	62.8	-2.4
2	2390.00	48.2 AV	54.0	-5.8	3.39 V	291	50.6	-2.4
3	*2412.00	101.4 PK			3.39 V	291	103.7	-2.3
4	*2412.00	91.8 AV			3.39 V	291	94.1	-2.3
5	4824.00	49.2 PK	74.0	-24.8	1.00 V	329	47.3	1.9
6	4824.00	47.3 AV	54.0	-6.7	1.00 V	329	45.4	1.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 2	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.4 PK	74.0	-17.6	1.13 H	77	58.8	-2.4
2	2390.00	44.0 AV	54.0	-10.0	1.13 H	77	46.4	-2.4
3	*2417.00	103.9 PK			1.13 H	77	106.3	-2.4
4	*2417.00	94.0 AV			1.13 H	77	96.4	-2.4
5	4834.00	59.3 PK	74.0	-14.7	1.27 H	93	57.4	1.9
6	4834.00	46.8 AV	54.0	-7.2	1.27 H	93	44.9	1.9
7	7251.00	69.4 PK	74.0	-4.6	1.13 H	109	61.3	8.1
8	7251.00	53.5 AV	54.0	-0.5	1.13 H	109	45.4	8.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.1 PK	74.0	-19.9	3.33 V	291	56.5	-2.4
2	2390.00	41.2 AV	54.0	-12.8	3.33 V	291	43.6	-2.4
3	*2417.00	107.4 PK			3.33 V	291	109.8	-2.4
4	*2417.00	87.4 AV			3.33 V	291	89.8	-2.4
5	4834.00	51.9 PK	74.0	-22.1	3.29 V	329	50.0	1.9
6	4834.00	39.4 AV	54.0	-14.6	3.29 V	329	37.5	1.9
7	7251.00	65.9 PK	74.0	-8.1	2.52 V	339	57.8	8.1
8	7251.00	50.6 AV	54.0	-3.4	2.52 V	339	42.5	8.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.7 PK			1.17 H	91	106.2	-2.5
2	*2437.00	93.5 AV			1.17 H	91	96.0	-2.5
3	4874.00	58.8 PK	74.0	-15.2	1.17 H	89	56.9	1.9
4	4874.00	46.7 AV	54.0	-7.3	1.17 H	89	44.8	1.9
5	7311.00	70.0 PK	74.0	-4.0	1.15 H	104	62.2	7.8
6	7311.00	53.6 AV	54.0	-0.4	1.15 H	104	45.8	7.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.4 PK			3.43 V	304	108.9	-2.5
2	*2437.00	86.3 AV			3.43 V	304	88.8	-2.5
3	4874.00	51.7 PK	74.0	-22.3	3.31 V	341	49.8	1.9
4	4874.00	39.4 AV	54.0	-14.6	3.31 V	341	37.5	1.9
5	7311.00	64.5 PK	74.0	-9.5	2.62 V	345	56.7	7.8
6	7311.00	49.6 AV	54.0	-4.4	2.62 V	345	41.8	7.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	104.1 PK			1.16 H	93	106.6	-2.5
2	*2462.00	94.0 AV			1.16 H	93	96.5	-2.5
3	2483.50	56.8 PK	74.0	-17.2	1.16 H	93	59.4	-2.6
4	2483.50	44.3 AV	54.0	-9.7	1.16 H	93	46.9	-2.6
5	4924.00	58.7 PK	74.0	-15.3	1.27 H	93	56.7	2.0
6	4924.00	46.4 AV	54.0	-7.6	1.27 H	93	44.4	2.0
7	7386.00	69.8 PK	74.0	-4.2	1.17 H	103	61.9	7.9
8	7386.00	53.5 AV	54.0	-0.5	1.17 H	103	45.6	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	107.0 PK			3.34 V	293	109.5	-2.5
2	*2462.00	86.9 AV			3.34 V	293	89.4	-2.5
3	2483.50	54.3 PK	74.0	-19.7	3.34 V	293	56.9	-2.6
4	2483.50	41.5 AV	54.0	-12.5	3.34 V	293	44.1	-2.6
5	4924.00	52.3 PK	74.0	-21.7	3.35 V	333	50.3	2.0
6	4924.00	39.5 AV	54.0	-14.5	3.35 V	333	37.5	2.0
7	7386.00	65.2 PK	74.0	-8.8	2.58 V	342	57.3	7.9
8	7386.00	50.2 AV	54.0	-3.8	2.58 V	342	42.3	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.8 PK	74.0	-16.2	1.15 H	86	60.2	-2.4
2	2390.00	45.3 AV	54.0	-8.7	1.15 H	86	47.7	-2.4
3	*2422.00	99.0 PK			1.15 H	86	101.4	-2.4
4	*2422.00	90.2 AV			1.15 H	86	92.6	-2.4
5	4844.00	59.2 PK	74.0	-14.8	1.26 H	77	57.3	1.9
6	4844.00	46.7 AV	54.0	-7.3	1.26 H	77	44.8	1.9
7	7266.00	67.6 PK	74.0	-6.4	1.21 H	81	59.5	8.1
8	7266.00	53.7 AV	54.0	-0.3	1.21 H	81	45.6	8.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.5 PK	74.0	-19.5	3.33 V	296	56.9	-2.4
2	2390.00	42.1 AV	54.0	-11.9	3.33 V	296	44.5	-2.4
3	*2422.00	94.4 PK			3.33 V	296	96.8	-2.4
4	*2422.00	84.5 AV			3.33 V	296	86.9	-2.4
5	4844.00	52.3 PK	74.0	-21.7	3.31 V	346	50.4	1.9
6	4844.00	39.9 AV	54.0	-14.1	3.31 V	346	38.0	1.9
7	7266.00	65.4 PK	74.0	-8.6	2.58 V	351	57.3	8.1
8	7266.00	50.1 AV	54.0	-3.9	2.58 V	351	42.0	8.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	98.7 PK			1.14 H	84	101.2	-2.5
2	*2437.00	90.3 AV			1.14 H	84	92.8	-2.5
3	4874.00	59.5 PK	74.0	-14.5	1.16 H	92	57.6	1.9
4	4874.00	47.0 AV	54.0	-7.0	1.16 H	92	45.1	1.9
5	7311.00	68.2 PK	74.0	-5.8	1.18 H	85	60.4	7.8
6	7311.00	53.6 AV	54.0	-0.4	1.18 H	85	45.8	7.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	94.1 PK			3.40 V	288	96.6	-2.5
2	*2437.00	84.2 AV			3.40 V	288	86.7	-2.5
3	4874.00	52.2 PK	74.0	-21.8	3.31 V	350	50.3	1.9
4	4874.00	39.5 AV	54.0	-14.5	3.31 V	350	37.6	1.9
5	7311.00	64.8 PK	74.0	-9.2	2.51 V	348	57.0	7.8
6	7311.00	49.5 AV	54.0	-4.5	2.51 V	348	41.7	7.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	98.6 PK			1.16 H	92	101.1	-2.5
2	*2452.00	90.1 AV			1.16 H	92	92.6	-2.5
3	2483.50	60.2 PK	74.0	-13.8	1.16 H	92	62.8	-2.6
4	2483.50	47.0 AV	54.0	-7.0	1.16 H	92	49.6	-2.6
5	4904.00	58.9 PK	74.0	-15.1	1.25 H	77	56.9	2.0
6	4904.00	46.4 AV	54.0	-7.6	1.25 H	77	44.4	2.0
7	7356.00	68.5 PK	74.0	-5.5	1.18 H	80	60.6	7.9
8	7356.00	53.9 AV	54.0	-0.1	1.18 H	80	46.0	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	94.7 PK			3.34 V	294	97.2	-2.5
2	*2452.00	84.9 AV			3.34 V	294	87.4	-2.5
3	2483.50	55.4 PK	74.0	-18.6	3.34 V	294	58.0	-2.6
4	2483.50	43.1 AV	54.0	-10.9	3.34 V	294	45.7	-2.6
5	4904.00	52.5 PK	74.0	-21.5	3.31 V	326	50.5	2.0
6	4904.00	39.7 AV	54.0	-14.3	3.31 V	326	37.7	2.0
7	7356.00	65.4 PK	74.0	-8.6	2.59 V	331	57.5	7.9
8	7356.00	50.3 AV	54.0	-3.7	2.59 V	331	42.4	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz Data:


802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	39.89	30.2 QP	40.0	-9.8	1.50 H	298	39.8	-9.6
2	60.98	28.4 QP	40.0	-11.6	1.50 H	206	37.8	-9.4
3	148.25	26.3 QP	43.5	-17.2	1.50 H	203	34.4	-8.1
4	196.17	25.2 QP	43.5	-18.3	2.00 H	123	35.9	-10.7
5	240.01	38.8 QP	46.0	-7.2	1.50 H	252	48.1	-9.3
6	359.98	30.3 QP	46.0	-15.7	1.00 H	257	36.0	-5.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	40.71	36.0 QP	40.0	-4.0	1.00 V	5	45.4	-9.4
2	58.75	30.3 QP	40.0	-9.7	1.50 V	292	39.3	-9.0
3	84.23	28.0 QP	40.0	-12.0	2.00 V	160	41.9	-13.9
4	148.14	25.9 QP	43.5	-17.6	1.50 V	350	34.0	-8.1
5	240.01	33.3 QP	46.0	-12.7	1.00 V	222	42.6	-9.3
6	359.98	29.4 QP	46.0	-16.6	1.50 V	95	35.1	-5.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2018	Oct. 23, 2019
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 22, 2018	Oct. 21, 2019
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 06, 2018	Mar. 05, 2019
50 ohms Terminator	N/A	3	Oct. 22, 2018	Oct. 21, 2019
RF Cable	5D-FB	COCCAB-001	Sep. 28, 2018	Sep. 27, 2019
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 16, 2018	Mar. 15, 2019
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: Nov. 20, 2018

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.02	37.44	18.66	47.46	28.68	66.00	56.00	-18.54	-27.32
2	0.20469	10.04	39.48	23.68	49.52	33.72	63.42	53.42	-13.90	-19.70
3	0.28672	10.05	26.63	19.46	36.68	29.51	60.62	50.62	-23.94	-21.11
4	0.78281	10.10	22.77	11.15	32.87	21.25	56.00	46.00	-23.13	-24.75
5	2.98828	10.20	20.40	14.73	30.60	24.93	56.00	46.00	-25.40	-21.07
6	10.78125	10.57	16.68	11.58	27.25	22.15	60.00	50.00	-32.75	-27.85

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	9.93	34.65	21.36	44.58	31.29	65.18	55.18	-20.60	-23.89
2	0.20078	9.94	40.78	25.22	50.72	35.16	63.58	53.58	-12.86	-18.42
3	0.28672	9.95	27.36	22.10	37.31	32.05	60.62	50.62	-23.31	-18.57
4	0.79453	9.98	21.71	11.67	31.69	21.65	56.00	46.00	-24.31	-24.35
5	3.12109	10.08	18.82	13.07	28.90	23.15	56.00	46.00	-27.10	-22.85
6	7.40625	10.27	17.06	11.94	27.33	22.21	60.00	50.00	-32.67	-27.79

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	9.10	0.5	Pass
6	2437	9.10	0.5	Pass
11	2462	9.12	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.61	0.5	Pass
2	2417	16.62	0.5	Pass
6	2437	16.61	0.5	Pass
11	2462	16.63	0.5	Pass

802.11n (HT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	17.83	0.5	Pass
2	2417	17.84	0.5	Pass
6	2437	17.84	0.5	Pass
11	2462	17.84	0.5	Pass

802.11n (HT40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
3	2422	36.64	0.5	Pass
6	2437	36.62	0.5	Pass
9	2452	36.62	0.5	Pass

Spectrum Plot of Worst Value


802.11b / CH1




802.11g / CH1



802.11n (HT20) / CH1



802.11n (HT40) / CH6




4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

FOR PEAK POWER

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	10.28	10.12	30	Pass
6	2437	10.257	10.11	30	Pass
11	2462	8.166	9.12	30	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	362.243	25.59	30	Pass
2	2417	90.573	19.57	30	Pass
6	2437	93.111	19.69	30	Pass
11	2462	84.723	19.28	30	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	319.89	25.05	30	Pass
2	2417	81.658	19.12	30	Pass
6	2437	82.224	19.15	30	Pass
11	2462	73.114	18.64	30	Pass

802.11n (HT40)

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
3	2422	116.413	20.66	30	Pass
6	2437	114.815	20.60	30	Pass
9	2452	115.08	20.61	30	Pass

FOR AVERAGE POWER

802.11b

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	5.649	7.52
6	2437	5.636	7.51
11	2462	4.477	6.51

802.11g

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	39.537	15.97
2	2417	9.931	9.97
6	2437	10.023	10.01
11	2462	9.462	9.76

802.11n (HT20)

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	38.994	15.91
2	2417	9.705	9.87
6	2437	9.977	9.99
11	2462	9.226	9.65

802.11n (HT40)


Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
3	2422	12.677	11.03
6	2437	12.647	11.02
9	2452	12.218	10.87

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-23.06	8	Pass
6	2437	-22.64	8	Pass
11	2462	-23.54	8	Pass

802.11g

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-12.86	8	Pass
2	2417	-18.68	8	Pass
6	2437	-18.39	8	Pass
11	2462	-18.32	8	Pass

802.11n (HT20)


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-12.48	8	Pass
2	2417	-17.92	8	Pass
6	2437	-17.87	8	Pass
11	2462	-17.41	8	Pass

802.11n (HT40)


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
3	2422	-18.22	8	Pass
6	2437	-19.31	8	Pass
9	2452	-19.43	8	Pass

Spectrum Plot of Worst Value


802.11b / CH6




802.11g / CH1



802.11n (HT20) / CH1



802.11n (HT40) / CH3




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition



Same as Item 4.3.6

4.6.7 Test Results



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g



CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT20)


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT40)


CH 3




CH 6



CH 9



CH 3 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linkou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---