



TEST DATA

Test Data Number: 3166037MIN-001B
Project Number: 3166037

Testing performed on the
InterReach Fusion PCS

To
47 CFR, Part 24

For
ADC Telecommunications Inc.

Test Performed by:
Intertek Testing Services NA, Inc.
7250 Hudson Blvd., Suite 100
Oakdale, MN 55128

Test Authorized by:
ADC Telecommunications Inc.
1187 Park Place
Shakopee, MN 55379

Prepared by: Richard Blonigen
Richard Blonigen

Date: November 7, 2008

Reviewed by: Norman Shpilsher
Norman Shpilsher

Date: November 7, 2008

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.



TABLE OF CONTENTS

- 1.0 DESCRIPTION OF THE SAMPLE (EUT) 3**
- 2.0 TEST SUMMARY 4**
 - 2.1 Statement of the Measurement Uncertainty 4
- 3.0 TEST RESULTS 5**
 - 3.1 Spurious Radiated Emissions 5
 - 3.2 Environmental conditions..... 28
- 5.0 TEST EQUIPMENT.....30**



1.0 DESCRIPTION OF THE SAMPLE (EUT)

Model:	InterReach Fusion PCS
Type of EUT:	Indoor Fiber / Coaxial Repeater
Serial Number:	N/A
Company:	ADC Telecommunications Inc.
Customer:	Mr. Mark Miska
Address:	1187 Park Place Shakopee, MN 55379
Phone:	952-403-8340
Fax:	952-403-8858
Test Standards:	<input type="checkbox"/> EN 55022:2006, Class A <input type="checkbox"/> EN 55011:1998 + A1:1999 + A2:2002, Group <input type="checkbox"/> , Class <input type="checkbox"/> <input type="checkbox"/> 47 CFR, Part 15:2007, §15.107 and §15.109, Class A <input type="checkbox"/> 47 CFR, Part 22:2007 <input checked="" type="checkbox"/> 47 CFR, Part 24:2007 <input type="checkbox"/> 47 CFR, Part 90:2007 <input type="checkbox"/> EN 55014-1:2000 + A1:2001 + A2:2002 <input type="checkbox"/> EN 61326-1:2006 <input type="checkbox"/> Class <input type="checkbox"/> for Radiated and Conducted Emissions <input type="checkbox"/> EN 60601-1-2:2001 +A1:2006 <input type="checkbox"/> Class <input type="checkbox"/> Radiated and Conducted Emissions <input type="checkbox"/> EN 61000-6-3:2007 <input type="checkbox"/> EN 61000-6-4:2007 <input type="checkbox"/> EN 61000-3-2:2006 <input type="checkbox"/> EN 61000-3-3:1995 +A1:2001 +A2:2006 <input type="checkbox"/> Other <input type="checkbox"/>

2.0 TEST SUMMARY

Referring to the performance criteria and the operating mode during the tests specified in this report, the equipment complies with the requirements according to the following standards.

TEST STANDARD	TEST	RESULT
Part 24	Spurious Enclosure Radiated Emissions	Pass

2.1 Statement of the Measurement Uncertainty

Note: The measured result in this report is within the specification limits by more than the measurement uncertainty; the measured result indicates that the product tested complies with the specification limit.

The expanded uncertainty ($k = 2$) for radiated emissions from 30 to 1000 MHz has been determined to be: ± 4 dB at 10m and ± 5.4 dB at 3m

General notes:

1. Test was performed in RX mode with the EUT tuned to the low frequency (1.850MHz), middle frequency (1.880MHz), and upper frequency (1.910MHz) of the operating band.
2. Test was also performed in TX mode with the EUT tuned to the low frequency (1.930MHz), middle frequency (1.960MHz), and upper frequency (1.990MHz) of the operating band.
3. Testing was performed in frequency range from 30MHz to 20GHz. EUT tuned frequencies 1.850MHz, 1.880MHz, 1.910MHz, 1.930MHz, 1.960MHz, and 1.990MHz were excluded from the table.
4. The Spurious Radiated Power limits of -13dBm was correlated with field strength reference level of 82.2dB μ V/m during field strength measurements at 3m measurement distance

3.0 TEST RESULTS

3.1 Spurious Radiated Emissions

Tables 1-4 show detected Radiated Emissions.

Graphs 1 to 36 show the EUT peak Radiated Emissions.

No Emissions were detected above 18GHz (see graphs 25-36)

No emissions were chosen for substitution measurements as the maximum emission is more than 20dB below the reference limit.



TILE Instrument Control System EMI Measurement Software

Radiated Emissions from 30MHz to 1GHz

Date: 11-06-2008

Company: ADC Telecommunications Inc.
Model: InterReach Fusion, PCS_RX
Test Engineer: Uri Spector
Standard: FCC Part 24
Test Site: 3m Anechoic Chamber, 3m measurement distance
Note: The table shows the worst case radiated emissions
 Measurements were taken using a Peak detector

Table # 1

Frequency	Ant. Polarity	Peak Reading dB μ V	Ant.Factor dB1/m	Total at 3m dB μ V/m	QP Limit dB μ V/m	Margin dB
Operating Frequency 1850MHz						
36.771 MHz	V	32.4	17.0	49.3	82.2	-32.9
47.325 MHz	V	22.7	11.3	34.1	82.2	-48.2
98.412 MHz	V	18.6	11.5	30.1	82.2	-52.1
609.88 MHz	V	25.8	21.8	47.6	82.2	-34.6
970.34 MHz	V	15.9	25.6	41.5	82.2	-40.7
Operating Frequency 1880MHz						
30.794 MHz	H	14.4	20.1	34.5	82.2	-47.7
609.88 MHz	H	25.5	21.8	47.2	82.2	-35.0
977.52 MHz	H	15.7	25.7	41.4	82.2	-40.8
Operating Frequency 1880MHz						
30.416 MHz	V	14.6	20.3	34.9	82.2	-47.3
47.039 MHz	V	21.3	11.5	32.8	82.2	-49.4
100.3 MHz	V	19.0	11.9	30.8	82.2	-51.4
610.31 MHz	V	25.8	21.8	47.5	82.2	-34.7
Operating Frequency 1910MHz						
30.277 MHz	H	15.2	20.4	35.5	82.2	-46.7
87.764 MHz	H	19.9	9.7	29.7	82.2	-52.5
610.31 MHz	H	25.3	21.8	47.0	82.2	-35.2
972.41 MHz	H	15.8	25.6	41.4	82.2	-40.8
Operating Frequency 1910MHz						
30.0 MHz	V	14.4	20.5	35.0	82.2	-47.2
47.386 MHz	V	20.9	11.3	32.2	82.2	-50.0
117.76 MHz	V	21.2	13.7	34.9	82.2	-47.3
610.31 MHz	V	25.6	21.8	47.4	82.2	-34.8
949.07 MHz	V	16.0	25.3	41.3	82.2	-40.9
Operating Frequency 1910MHz						
30.416 MHz	H	14.8	20.3	35.1	82.2	-47.1
117.76 MHz	H	20.6	13.7	34.4	82.2	-47.8
610.31 MHz	H	24.9	21.8	46.7	82.2	-35.6
987.98 MHz	H	15.7	25.8	41.5	82.2	-40.7



TILE Instrument Control System EMI Measurement Software

Radiated Emissions from 30MHz to 1GHz

Date: 11-06-2008

Company: ADC Telecommunications Inc.
Model: InterReach Fusion, PCS_TX
Test Engineer: Uri Spector
Standard: FCC Part 24
Test Site: 3m Anechoic Chamber, 3m measurement distance
Note: The table shows the worst case radiated emissions
 Measurements were taken using a Peak detector

Table # 2

Frequency	Ant. Polarity	Peak Reading dBµV	Ant.Factor dB1/m	Total at 3m dBµV/m	QP Limit dBµV/m	Margin dB
Operating Frequency 1930MHz						
30.561 MHz	V	15.5	20.3	35.7	82.2	-46.5
131.95 MHz	V	15.3	13.4	28.8	82.2	-53.5
322.2 MHz	V	27.2	16.1	43.3	82.2	-38.9
609.89 MHz	V	26.1	21.8	47.9	82.2	-34.3
976.97 MHz	V	15.9	25.7	41.5	82.2	-40.7
Operating Frequency 1960MHz						
30.0 MHz	H	14.3	20.5	34.8	82.2	-47.4
120.97 MHz	H	15.4	13.7	29.1	82.2	-53.1
322.2 MHz	H	31.3	16.1	47.4	82.2	-34.8
609.89 MHz	H	25.1	21.8	46.8	82.2	-35.4
954.33 MHz	H	15.6	25.4	40.9	82.2	-41.3
Operating Frequency 1960MHz						
31.681 MHz	V	15.9	19.7	35.6	82.2	-46.6
352.3 MHz	V	33.1	17.0	50.1	82.2	-32.1
609.88 MHz	V	25.4	21.8	47.2	82.2	-35.0
973.83 MHz	V	16.1	25.6	41.7	82.2	-40.5
Operating Frequency 1990MHz						
30.28 MHz	H	14.9	20.4	35.3	82.2	-46.9
122.78 MHz	H	14.8	13.7	28.5	82.2	-53.7
352.3 MHz	H	36.1	17.0	53.2	82.2	-29.1
609.88 MHz	H	23.8	21.8	45.6	82.2	-36.6
980.09 MHz	H	15.3	25.7	41.0	82.2	-41.2
Operating Frequency 1990MHz						
30.047 MHz	V	16.3	20.5	36.8	82.2	-45.4
61.901 MHz	V	19.6	7.9	27.5	82.2	-54.7
64.974 MHz	V	19.3	7.8	27.0	82.2	-55.2
136.81 MHz	V	15.5	13.3	28.8	82.2	-53.4
382.19 MHz	V	30.7	18.0	48.8	82.2	-33.4
609.88 MHz	V	24.5	21.8	46.3	82.2	-35.9
996.2 MHz	V	15.3	25.9	41.2	82.2	-41.0
Operating Frequency 1990MHz						
31.214 MHz	H	15.5	19.9	35.4	82.2	-46.8
382.19 MHz	H	33.7	18.0	51.7	82.2	-30.5
609.88 MHz	H	23.0	21.8	44.8	82.2	-37.4
988.2 MHz	H	15.3	25.8	41.1	82.2	-41.1



TILE Instrument Control System EMI Measurement Software

Radiated Emissions from 1GHz to 18GHz

Date: 11-06-2008

Company: ADC Telecommunications Inc.
Model: InterReach Fusion, PCS_RX
Test Engineer: Uri Spector
Special Info:
Standard: FCC Part 24
Test Site: 3m Anechoic Chamber, 3m measurement distance
Note: The table shows the worst case radiated emissions
 All measurements were taken using a Peak detector

Table # 3

Frequency MHz	Antenna Polarity	Reading dBµV	Total C.F. dB1/m	Pre-Amp. Gain (dB)	Total at 3m dBµV/m	QP Limit dBµV/m	Margin dB
Operating Frequency 1850 MHz							
3.278 GHz	V	55.0	35.0	40.2	49.9	82.2	-32.4
4.5955 GHz	V	50.5	38.9	39.9	49.5	82.2	-32.7
5.3775 GHz	V	49.6	40.9	39.7	50.7	82.2	-31.5
8.038 GHz	V	44.3	45.0	39.3	50.0	82.2	-32.2
13.75 GHz	V	42.4	50.8	39.4	53.8	82.2	-28.4
17.974 GHz	V	40.7	56.6	38.4	58.9	82.2	-23.3
Operating Frequency 1880 MHz							
3.278 GHz	H	54.4	35.0	40.2	49.2	82.2	-33.0
4.5955 GHz	H	51.6	38.9	39.9	50.7	82.2	-31.5
11.251 GHz	H	41.0	48.6	38.6	51.0	82.2	-31.2
14.2 GHz	H	41.9	51.3	39.8	53.4	82.2	-28.8
17.966 GHz	H	41.3	56.5	38.4	59.4	82.2	-22.8
Operating Frequency 1910 MHz							
3.278 GHz	V	53.9	35.0	40.2	48.7	82.2	-33.5
5.3775 GHz	V	50.3	40.9	39.7	51.5	82.2	-30.7
7.171 GHz	V	43.5	43.4	40.1	46.8	82.2	-35.4
8.038 GHz	V	41.9	45.0	39.3	47.6	82.2	-34.6
13.767 GHz	V	43.0	50.8	39.4	54.4	82.2	-27.8
18.0 GHz	V	41.5	56.7	38.3	59.8	82.2	-22.4
Operating Frequency 1910 MHz							
1.6375 GHz	H	57.7	29.3	40.8	46.1	82.2	-36.1
3.278 GHz	H	54.4	35.0	40.2	49.3	82.2	-33.0
4.5955 GHz	H	51.7	38.9	39.9	50.7	82.2	-31.5
11.251 GHz	H	40.4	48.6	38.6	50.3	82.2	-31.9
13.894 GHz	H	42.9	50.8	39.5	54.2	82.2	-28.0
17.966 GHz	H	41.3	56.5	38.4	59.4	82.2	-22.8
Operating Frequency 1910 MHz							
1.6375 GHz	V	56.6	29.3	40.8	45.0	82.2	-37.2
4.5955 GHz	V	51.0	38.9	39.9	50.1	82.2	-32.1
5.3775 GHz	V	49.8	40.9	39.7	50.9	82.2	-31.3
8.038 GHz	V	43.4	45.0	39.3	49.1	82.2	-33.1
13.741 GHz	V	43.0	50.8	39.4	54.4	82.2	-27.8
18.0 GHz	V	41.0	56.7	38.3	59.4	82.2	-22.8
Operating Frequency 1910 MHz							
1.6375 GHz	H	56.8	29.3	40.8	45.3	82.2	-37.0
3.278 GHz	H	54.8	35.0	40.2	49.6	82.2	-32.6
4.5955 GHz	H	51.3	38.9	39.9	50.3	82.2	-31.9
11.251 GHz	H	39.5	48.6	38.6	49.5	82.2	-32.7
14.422 GHz	H	42.1	51.8	40.1	53.9	82.2	-28.3
18.0 GHz	H	40.9	56.7	38.3	59.3	82.2	-22.9



TILE Instrument Control System EMI Measurement Software


Radiated Emissions from 1GHz to 18GHz

Date: 11-06-2008


Company: ADC Telecommunications Inc.
Model: InterReach Fusion, PCS_TX
Test Engineer: Uri Spector
Special Info:
Standard: FCC Part 24
Test Site: 3m Anechoic Chamber, 3m measurement distance
Note: The table shows the worst case radiated emissions
 All measurements were taken using a Peak detector

Table # 4


Frequency MHz	Antenna Polarity	Reading dBµV	Total C.F. dB1/m	Pre-Amp. Gain (dB)	Total at 3m dBµV/m	QP Limit dBµV/m	Margin dB
Operating Frequency 1930 MHz							
1.6375 GHz	V	53.2	29.3	40.8	41.7	82.2	-40.6
4.5955 GHz	V	51.8	38.9	39.9	50.8	82.2	-31.4
5.3775 GHz	V	48.3	40.9	39.7	49.5	82.2	-32.8
8.038 GHz	V	43.4	45.0	39.3	49.1	82.2	-33.1
13.69 GHz	V	42.7	50.8	39.3	54.2	82.2	-28.0
18.0 GHz	V	40.1	56.7	38.3	58.5	82.2	-23.7
Operating Frequency 1960 MHz							
1.6375 GHz	H	55.3	29.3	40.8	43.8	82.2	-38.4
4.5955 GHz	H	54.8	38.9	39.9	53.8	82.2	-28.4
13.759 GHz	H	42.1	50.8	39.4	53.5	82.2	-28.7
17.966 GHz	H	40.4	56.5	38.4	58.6	82.2	-23.7
Operating Frequency 1960 MHz							
1.6347 GHz	V	53.2	29.2	40.8	41.6	82.2	-40.6
4.5927 GHz	V	51.1	38.9	39.9	50.1	82.2	-32.1
5.386 GHz	V	47.8	40.9	39.7	49.0	82.2	-33.2
8.038 GHz	V	43.1	45.0	39.3	48.8	82.2	-33.4
13.659 GHz	V	42.2	50.8	39.3	53.7	82.2	-28.5
17.955 GHz	V	40.9	56.5	38.4	58.9	82.2	-23.3
Operating Frequency 1990 MHz							
1.6347 GHz	H	55.9	29.2	40.8	44.3	82.2	-38.0
3.278 GHz	H	54.8	35.0	40.2	49.6	82.2	-32.6
4.5927 GHz	H	54.2	38.9	39.9	53.2	82.2	-29.0
8.038 GHz	H	41.9	45.0	39.3	47.6	82.2	-34.6
13.909 GHz	H	43.6	50.8	39.5	54.8	82.2	-27.4
17.955 GHz	H	40.7	56.5	38.4	58.8	82.2	-23.4
Operating Frequency 1990 MHz							
1.6347 GHz	V	52.8	29.2	40.8	41.2	82.2	-41.0
3.584 GHz	V	50.9	36.0	40.2	46.6	82.2	-35.6
4.5927 GHz	V	51.4	38.9	39.9	50.4	82.2	-31.8
5.386 GHz	V	48.7	40.9	39.7	49.8	82.2	-32.4
7.1653 GHz	V	44.9	43.4	40.1	48.2	82.2	-34.0
13.773 GHz	V	43.1	50.8	39.4	54.5	82.2	-27.7
17.955 GHz	V	40.8	56.5	38.4	58.8	82.2	-23.4
Operating Frequency 1990 MHz							
1.6347 GHz	H	56.5	29.2	40.8	44.9	82.2	-37.3
3.278 GHz	H	54.9	35.0	40.2	49.7	82.2	-32.5
4.5927 GHz	H	54.2	38.9	39.9	53.2	82.2	-29.0
5.386 GHz	H	45.9	40.9	39.7	47.1	82.2	-35.1
13.716 GHz	H	41.8	50.8	39.3	53.3	82.2	-28.9
17.921 GHz	H	41.0	56.3	38.5	58.9	82.2	-23.3




Graph 1




Graph 2




Graph 3




Graph 4




Graph 5




Graph 6




Graph 7




Graph 8




Graph 9




Graph 10




Graph 11




Graph 12




Graph 13




Graph 14




Graph 15




Graph 16




Graph 17




Graph 18




Graph 19




Graph 20




Graph 21




Graph 22




Graph 23




Graph 24




Graph 25




Graph 26




Graph 27




Graph 28




Graph 29




Graph 30




Graph 31




Graph 32




Graph 33



Graph 34



Graph 35



Graph 36

3.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 °C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

4.0 PHOTOS



Test Setup Photos



5.0 TEST EQUIPMENT

DESCRIPTION	MANUFACTURER	MODEL	SERIAL NO.	CAL DUE	USED
Spectrum Analyzer	R & S	FSP 40	100024	08/22/2009	<input checked="" type="checkbox"/>
Spectrum Analyzer	R & S	ESCI	100358	05/07/2009	<input checked="" type="checkbox"/>
Bicono-Log Antenna	Schaffner-Chase	CBL 6112 B	2630	09/26/2009	<input checked="" type="checkbox"/>
Horn Antenna	EMCO	3115	9507-4513	02/13/2009	<input checked="" type="checkbox"/>
Waveguide Horn Antenna	EMCO	3116	9904-2423	07/20/2009	<input checked="" type="checkbox"/>
Pre-Amplifier	MITEQ	AMF-5D-00501800-28-13P	1122951	04/28/2009	<input checked="" type="checkbox"/>
Pre-Amplifier	MITEQ	AMF-6F-16002600-25-10P	1222383	01/17/2009	<input checked="" type="checkbox"/>
System	TILE! Instrument Control		Ver. 3.4.K.29	VBU	<input checked="" type="checkbox"/>

