

FCC § 1.1307(b)(1) & § 2.1091-RF EXPOSURE

1. Applicable Standard

According to § 11310 and § 2.1091 (Mobile Devices)RF exposure is calculated.

| Frequency Range(Mhz) | Electric Field Stength(V/m) | Magnetic Field Stength(A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|-----------------------------|-----------------------------|-------------------------------------|-------------------------|
| Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |

f=frequency in MHz

*=Plane-wave equivalent power density

2. MPE Prediction

Predication of MPE limit at given distance, equation form OET Bulletin 65, Edition97-01

$$S=PG/4\pi R^2$$

Where: S = power density

P= power input to antenna

G= power gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the center of radiation of the antenna

850MHz Band

Maximum peak output power at antenna input terminal (dBm): 29.43

Maximum peak output power at antenna input terminal(mW): 880

Prediction distance(cm): 20

Prediction frequency(MHz): 859

Antenna Gain, typical(dBi): 1.5

Maximum Antenna Gain(Numeric): 1.4

Power density at predication frequency and distance (mW/cm²): 0.24

MPE limit for uncontrolled exposure at predication frequency (mW/ cm²): 0.57

1900MHz

Maximum peak output power at antenna input terminal (dBm): 29.70

Maximum peak output power at antenna input terminal(mW): 930

Prediction distance(cm): 20

Prediction frequency(MHz): 1922.5

Antenna Gain, typical(dBi): 1.5

Maximum Antenna Gain(Numeric): 1.4

Power density at predication frequency and distance (mW/cm²): 0.25

MPE limit for uncontrolled exposure at predication frequency (mW/ cm²): 1

3. Test Results

The device is compliant with the requirement MPE limit for uncontrolled exposure.