



Nemko Test Report No.:

5L0427RUS2

Applicant:

Samsung Telecommunications
America1301 E. Lookout Drive
Richardson, TX 75081

Equipment Under Test:

SCBS-519M V.5 Outdoor Base Station

In Accordance With:

FCC Part 24, Subpart E
Broadband PCS Base Station Transmitter

Tested By:

Nemko U.S.A., Inc.
802 N. Kealy
Lewisville, Texas 75057-3136

A handwritten signature in blue ink, appearing to read 'Tom Tidwell', is written over the printed name.

Authorized By:

Tom Tidwell, Frontline Group Manager

Date:

30 August, 2005

Table of Contents

Section 1. Summary of Test Results 3

Section 2. General Equipment Specification 5

Section 3. RF Power Output 7

Section 4. Occupied Bandwidth..... 8

Section 5. Spurious Emissions at Antenna Terminals 10

Section 6. Field Strength of Spurious 14

Section 7. Frequency Stability 18

Section 8. Test Equipment List..... 20

ANNEX A - TEST DETAILS 21

ANNEX B - TEST DIAGRAMS..... 27

Section 1. Summary of Test Results

Manufacturer: Samsung

Model No.: SCBS-519M V.5

Serial No.: None

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 24, Subpart E.

New Submission

Production Unit

Class II Permissive Change

Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE. NONE

Nemko U.S.A. Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko U.S.A. Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

This report applies only to the items tested.

Summary Of Test Data

NAME OF TEST	PARA. NO.	SPEC.	RESULT
RF Power Output	24.232	100W	Complies
Occupied Bandwidth (CDMA)	24.238		Complies
Spurious Emissions at Antenna Terminals	24.238(a)	-13 dBm	Complies
Field Strength of Spurious Emissions	24.238(a)	-13 dBm E.I.R.P.	Complies
Frequency Stability	24.235	± 0.05 ppm	Complies

Footnotes For N/A's:

Measurement uncertainty is expressed to a confidence level of 95%.

Section 2. General Equipment Specification

Supply Voltage Input:			
Frequency Bands: TX	<input checked="" type="checkbox"/>	Block A :	1930 – 1945 MHz
	<input checked="" type="checkbox"/>	Block D :	1945 – 1950 MHz
	<input checked="" type="checkbox"/>	Block B :	1950 – 1965 MHz
	<input checked="" type="checkbox"/>	Block E :	1965 – 1970 MHz
	<input checked="" type="checkbox"/>	Block F :	1970 – 1975 MHz
	<input checked="" type="checkbox"/>	Block C :	1975 – 1990 MHz
	Frequency Bands: RX	<input checked="" type="checkbox"/>	Block A :
<input checked="" type="checkbox"/>		Block B :	1865 – 1870 MHz
<input checked="" type="checkbox"/>		Block C :	1870 – 1885 MHz
<input checked="" type="checkbox"/>		Block D :	1885 – 1890 MHz
<input checked="" type="checkbox"/>		Block E :	1890 – 1895 MHz
<input checked="" type="checkbox"/>		Block F :	1895 – 1910 MHz
Type of Modulation and Designator:		CDMA (1M25G7W)	GSM (200KGXW)
	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	Output Impedance: 50 ohms		
RF Output (Rated): Per channel: 20W – 160 Watts combined			
Band Selection:	Software	Duplexer	Fullband
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

System Description

The SCBS-519M V.5 Outdoor Base Station is a 20 Watt/channel CDMA PCS band base station able to combine up to 8 carriers out at out diplexer output.

System Diagram

Refer to separate exhibit.

Section 3. RF Power Output

NAME OF TEST: RF Power Output	PARA. NO.: 2.1046
TESTED BY: David Light	DATE: 6/7/2005

Test Results: Complies.

Measurement Data:

Modulation Type	Measured Output Power (dBm)	Measured Output Power (W)
CDMA	43.5	22.4

Equipment Used: 1066-1472-1036

Measurement Uncertainty: +/- 1.6 dB

Temperature: 22 °C

Relative Humidity: 40 %

Section 4. Occupied Bandwidth

NAME OF TEST: Occupied Bandwidth (CDMA)	PARA. NO.: 2.1049
TESTED BY: David Light	DATE: 6/7/2005

Test Results: Complies.

Test Data: See attached plot(s).

Equipment Used: 1066-1472-1036


Measurement Uncertainty: +/- 1.6 dB

Temperature: 22 °C

Relative Humidity: 40 %

Test Data – 26 dB Bandwidth

	Delta 1 [T1]	RBW	30 kHz	RF Att	20 dB	
	Ref Lvl	1.11 dB	VBW	30 kHz	Mixer	-10 dBm
	50 dBm	1.37543086 MHz	SWT	7 ms	Unit	dBm



Date: 07.JUN.2005 10:23:48

Section 5. Spurious Emissions at Antenna Terminals

NAME OF TEST: Spurious Emissions @ Antenna Terminals	PARA. NO.: 2.1051
TESTED BY: David Light	DATE: 6/7/2005 & 8/16/2005

Test Results: Complies.

Test Data:


Equipment Used: 1066-1472-1036-1659

Measurement Uncertainty: +/- 1.6 dB

Temperature: 22 °C

Relative Humidity: 40 %


Test Data – Spurious Emissions at Antenna Terminal



Date: 16.AUG.2005 12:11:11

Lowest operating channel
1931.25 MHz
20 Watts


Test Data – Spurious Emissions at Antenna Terminal



Date: 16.AUG.2005 13:32:03

Highest operating channel
1988.75 MHz
20 Watts


Test Data – Spurious Emissions at Antenna Terminal



Date: 16.AUG.2005 13:35:18

Intermodulation Characteristics
20 Watts per carrier / 40 Watts composite

Test Data – Spurious Emissions at Antenna Terminal



Date: 16.AUG.2005 13:11:50

Intermodulation Characteristics
20 Watts per carrier / 40 Watts composite

Section 6. Field Strength of Spurious

NAME OF TEST: Field Strength of Spurious Emissions	PARA. NO.: 2.1051
TESTED BY: David Light	DATE: 6/7/2005

Test Results: Complies.

Test Data: There were no emissions detected above the noise floor which was at least 30 dB below the specification limit of -13 dBm. The spectrum was searched from 30 MHz to 20 GHz..

Equipment Used: 1036-1016-1484-1485-1304-791-1982-760-759

Measurement Uncertainty: +/- 1.6 dB

Temperature: 22 °C

Relative Humidity: 40 %

Photographs of Test Setup



Section 7. Frequency Stability

NAME OF TEST: Frequency Stability	PARA. NO.: 2.1055
TESTED BY: David Light	DATE: 6/9/2005

Test Results: Complies

Measurement Data: Standard Test Frequency: 1946.25 MHz
Standard Test Voltage: 27 Vdc

Test Data – Frequency Stability

Frequency Stability							
Page <u>1</u> of <u>1</u>							
Job No.:	5L0262R			Date: 6/9/2005			
Specification:	Part 24		Temperature(°C): <u>20</u>				
Tested By:	<u>David Light</u>		Relative Humidity(%) <u>50</u>				
E.U.T.:	<u>Outdoor base station</u>						
Configuration:	<u>Tx CDMA signal at mid band</u>						
Sample Number:	<u>1</u>						
Test Equipment Used							
Antenna:	_____			Directional Coupler: _____			
Pre-Amp:	_____			Cable #1: <u>1484</u>			
Filter:	_____			Cable #2: _____			
Receiver:	<u>1036</u>						
Attenuator #1	<u>1472</u>						
Attenuator #2:	_____						
Measurement Uncertainty:	<u>1x10⁻¹⁷ ppm</u>		Standard Test Frequency <u>1946.250000</u> MHz				
Temp (°C)	Measured Frequency (MHz)	Rho	Test Voltage	Frequency Error (Hz)	Limit (+/-Hz)	Error (ppm)	Comment
20	1946.250047	0.9982	27	47	973.1	0.024	
20	1946.250055	0.9983	23.0	55	973.1	0.028	
20	1946.250048	0.9980	31.0	48	973.1	0.025	
50	1946.250049	0.9982	27	49	973.1	0.025	
40	1946.250060	0.9983	27	60	973.1	0.031	
30	1946.250045	0.9984	27	45	973.1	0.023	
10	1946.250040	0.9982	27.0	40	973.1	0.021	
0	1946.250036	0.9981	27.0	36	973.1	0.018	
-10	1946.250037	0.9979	27.0	37	973.1	0.019	
-20	1946.250042	0.9980	27	42	973.1	0.022	
-30	1946.250048	0.9971	27	48	973.1	0.025	
Notes:							

Section 8. Test Equipment List

Nemko ID	Description	Manufacturer Model Number	Serial Number	Calibration Date	Calibration Due
1036	SPECTRUM ANALYZER	ROHDE & SCHWARZ FSEK30	830844/006	03/22/04	03/23/06
1484	Cable 2.0-18.0 Ghz	Storm PR90-010-072	N/A	08/26/04	08/26/05
1472	20db Attenuator DC 18 Ghz	Omni Spectra 20600-20db	NONE	CBU	N/A
1036	SPECTRUM ANALYZER	ROHDE & SCHWARZ FSEK30	830844/006	03/22/04	03/23/06
1485	Cable 2.0-18.0 Ghz	Storm PR90-010-216	N/A	08/02/04	08/02/05
1016	Pre-Amp	HEWLETT PACKARD 8449A	2749A00159	11/12/04	11/12/05
1304	HORN ANTENNA	ELECTRO METRICS RGA-60	6151	09/22/03	09/22/05
759	ANTENNA, LOG PERIODIC	A.H. SYSTEMS SAS-200/510	556	07/23/04	07/23/05
760	Antenna biconical	Electro Metrics MFC-25	477	06/22/04	06/22/05
791	PREAMP, 25dB	ICC LNA25	398	11/12/04	11/12/05
1982	CABLE, 7m	KTL RG223	N/A	10/25/00	N/A
1066	CABLE, 4M	STORM PR90-010-144	N/A	08/26/04	08/26/05
	Chart recorder ETL Asset 1244	Unk Unk		03/04/05	03/04/06
	Temp controller ETL asset 1154	Unk Unk		11/19/04	11/19/05
1659	Spectrum Analyzer	Rhode & Schwarz FSP	973353	10/02/03	10/02/05

ANNEX A - TEST DETAILS

NAME OF TEST: RF Power Output

PARA. NO.: 2.1046

Minimum Standard: Para. No.24.232. Base stations are limited to 1640 watts peak E.I.R.P. with an antenna height up to 300 meters HAAT. In no case may the peak output power of a base station transmitter exceed 100 watts.

Method Of Measurement: CDMA Per ANSI/J-STD-014
TDMA Per ANSI/J-STD-010

Detachable Antenna:

The peak power at antenna terminals is measured using an in-line peak power meter or a spectrum analyzer.

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 2.1049

Minimum Standard: Para. No. 24.238(b). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB.

Method Of Measurement:

CDMA Per ANSI/J-STD-014

Spectrum analyzer settings:

RBW: 30 kHz

VBW: \geq RBW

Span: 5 MHz

Sweep: Auto

GSM Per ANSI/J-STD-010

RBW: 3 kHz

VBW: \geq RBW

Span: 2 MHz

Sweep: Auto

NADC Per IS-136

RBW: 1 kHz

VBW: \geq RBW

Span: 1 MHz

Sweep: Auto

NAME OF TEST: Spurious Emission at Antenna Terminals PARA. NO.: 2.1051

Minimum Standard: Para. No.24.238(a). On any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

Method Of Measurement:

Spectrum analyzer settings:

CDMA Per ANSI/J-STD-014

GSM Per ANSI/J-STD-010

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 30 kHz (< 1MHz from Band Edge)
VBW: ≥ RBW
Sweep: Auto
Video Avg: 6 Sweeps

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: ≥ RBW
Sweep: Auto
Video Avg: Disabled

NADC Per IS-136

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 1 kHz (< 1 MHz from Band Edge)
VBW: ≥ RBW
Sweep: Auto
Video Avg: Disabled

To demonstrate compliance at band edges the frequency of the input signal is set to the lowest and highest assigned channel and the center frequency of the spectrum analyzer is set to the upper and lower edges of the appropriate frequency block.

NAME OF TEST: Field Strength of Spurious Radiation

PARA. NO.: 2.1053

Minimum Standard: Para. No.24.238(a). On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

Test Method:

The maximum field strength of the spurious emission is measured at a distance of 3 meters. The device under test is then replaced with a substitution antenna of known gain with respect to an isotropic radiator. A calibrated signal source is used to feed the substitution antenna. The rf level to the substitution antenna is adjusted to repeat the previously measured field strength. The rf input level to the substitution antenna is the effective isotropic radiated power of the spurious emission.

NAME OF TEST: Frequency Stability

PARA. NO.: 2.1055

Minimum Standard: Para. No. 24.235. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Method Of Measurement: CDMA Per ANSI/J-STD-014
TDMA Per ANSI/J-STD-010
NADC Per IS-136

Frequency Stability With Voltage Variation


The E.U.T. is placed in an environmental chamber and allowed to stabilize at +20 degrees Celsius for at least 15 minutes. With the voltage input to the E.U.T. set to 85% S.T.V., the frequency is measured in 30 second intervals for a period of 5 minutes. This procedure is repeated at 100% S.T.V. and 115% S.T.V.

Frequency Stability With Temperature Variation


The input voltage to the E.U.T. is set to S.T.V. and the temperature of the environmental chamber is varied in 10 degree steps from -30 degrees C to +50 degrees C. The E.U.T. is allowed to stabilize at each temperature and the frequency is measured in 30 second intervals for a period of 5 minutes.

ANNEX B - TEST DIAGRAMS


Para. No. 2.985 - R.F. Power Output




Para. No. 2.989 - Occupied Bandwidth



Para. No. 2.991 Spurious Emissions at Antenna Terminals



Para. No. 2.993 - Field Strength of Spurious Radiation



Para. No. 2.995 - Frequency Stability

