End User Card Comp 1-REV 8/4/00 1:51 PM Page 1

Bottom Panel



Bottom Panel Connections

- Antenna Connection: This connector connects directly to an antenna or to RF cable connected to an antenna. The connector is a TNC female connector.
- 2. Ethernet Interface: A standard 10/100 BaseT Ethernet jack.
- Power Port: Connects the Nokia RoofTop Wireless Router to the 12VDC power connector.
- NOTE: Use only the power device provided with the unit.
- 4. Strain Relief: For the 12VDC power cable

Connecting the Wireless Router to Your PC or LAN

Your wireless router is capable of providing Internet access for a single PC via a direct connection or to multiple PC's via a local area network (LAN).

Direct Connection: When connecting your wireless router to a single PC, connect the Ethernet port on the wireless router and the network interface on your PC with a "crossover" Ethernet cable.

LAN Connection: When connecting your wireless router to multiple PCs via a hub, router, or switch, use standard "straight-through" Ethernet cables throughout the entire network.

NOTE: Nokia RoofTop Wireless Routers are capable of providing Internet access for multiple PCs, however the actual number of PCs that can receive Internet connectivity via your wireless router will depend on the level of service you purchased from your Internet Service Provider.

Technical Support

Nokia provides technical support only for network operators and authorized resellers. Technical support for subscribers to a Nokia network is provided by your Internet Service Provider. If you experience problems with your service or have any questions regarding the performance of your wireless router, please contact the ISP that installed the equipment.

Disclaimer

Nokia is the manufacturer of the wireless router and provides no warranty service and repair. Nokia RoofTop Wireless Routers are Provided "AS IS" with no warranty.

NOKIA DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MECHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. NOKIA SHALL NOT BE LIABLE FOR SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES, INCLUDING BUT NOT LIMITED TO LOSS OF ANTICIPATED BENEFITS OR PROFITS, LOSS OF SAVINGS OR REVENUE, PUNITIVE DAMAGES, LOSS OF USE OF THE PRODUCT OR ANY ASSOCIATED EQUIPMENT, COST OF CAPITAL, COST OF ANY SUBSTITUTE EQUIPMENT OR FACILITIES, DOWNTIME, THE CLAIMS OF ANY THIRD PARTIES, INCLUDING CUSTOMERS, AND INJURY TO PROPERTY, RESULTING FROM THE PURCHASE OR USE OF THE PRODUCT OR ARISING FROM BREACH OF THE WARRANTY, BREACH OF CONTRACT, NEGLIGENCE, STRICT TORT, OR ANY OTHER LEGAL OR EQUITABLE THEORY, EVEN IF NOKIA KNEW OF THE LIKELIHOOD OF SUCH DAMAGES. NOKIA SHALL NOT BE LIABLE FOR DELAY IN RENDERING SERVICE UNDER THE LIMITED WARRANTY, OR LOSS OF USE DURING THE PERIOD THAT THE PRODUCT IS BEING REPAIRED.

If you experience any problem or malfunction of the $\,$ wireless router, please contact the ISP that installed the equipment.

COPYRIGHT

© 2000 Nokia Corporation. All rights reserved. Rights reserved under the copyright laws of the United States.

RESTRICTED RIGHTS LEGEND

Use, duplication, or disclosure by the Government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013.

TRADEMARKS

Nokia and Nokia RoofTop are registered trademarks of Nokia Corporation.

Other products mentioned in this document are trademarks or registered trademarks of their respective holders.

REGULATORY INFORMATION

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

This equipment must be installed by a professional installer.



Wireless Router Subscriber Guide



End User Card Comp 1-REV 8/4/00 1:51 PM Page 5

Introduction

Your Nokia RoofTop™ Wireless Router is a revolutionary new product, delivering high-speed wireless Internet access.

Nokia RoofTop Wireless Routers combine an RF modem with a digital IP router board and specialized wireless routing system, the Nokia AIR Operating System (OS). This combination creates an IP router that is "wireless and intelligent."

Your Nokia RoofTop Wireless Router not only provides you with fast "always-on" Internet access, but is also an integral part of the network infrastructure. Some routers may rely on others to reach the Internet. It is very important that your wireless router is always powered ON, even when you are not using it, as it may be forwarding and routing traffic for other routers in the network.

Warnings, Safety Instructions and Technical Support

Important User Information

The Nokia RoofTop Wireless Router was designed and manufactured to meet strict quality and safety standards. It complies with the FCC rules, Part 15 and with 21 CFR 1040.10 and 1040.11.

This wireless router and its associated components are Class B devices that must be installed and/or moved by a professional.

Some routers may rely on others to reach the Internet. It is very important that your wireless router is always powered ON, even when you are not using it, as it may be forwarding and routing traffic for other routers in the network.

Instructions

- Read and follow all safety and operating instructions
- · Heed all precautions and warnings in the instructions and on the equipment
- Keep instructions for future use

Hazard Warnings

- Environment Do not place the unit in a very hot, very cold, dusty, wet, or high humidity environment. The unit should be situated away from all heat sources such as radiators, heat registers, stoves, amplifiers, and other heatproducing appliances.
- Fire or Electric Shock Do not expose the wireless router to any type of moisture, including rain. Do not use or install near water- related environments such as sinks, bathtubs, laundry areas, spas, swimming pools, or in wet basements. Take care not to spill any liquids on the unit.

Grounding and Polarization

- To prevent electric shock, match the wide blade of the plug to the wide slot
 of the receptacle, then fully insert. Do not use this polarized plug with an
 extension cord, receptacle or other outlet unless the blades can be fully
 inserted to prevent blade exposure.
- If an outside antenna is connected to the unit, be sure the antenna system
 is grounded to provide protection from voltage surges and built-up static
 charges. Section 810 of the National Electrical Code ANSINFPA No 70-1984
 provides information about proper grounding of the mast and supporting
 structure, grounding of the lead-in wire to an antenna discharge unit,
 connection to grounding electrodes and requirements for the grounding
 electrode. All grounding should be performed by a professional.

RF Exposure

Maintain a distance of 35 cm (14 inches) from the antenna of the Wireless Router. If more than one Wireless Router is installed, or another wireless system is installed in conjunction with the Wireless Router, please consult the installer or service provider as to the proper distance.

Accessories

Use only Nokia approved accessories for all installations.

Cleaning the Unit

Clean the wireless router with a dry cloth or paper towel.
 Do not use any liquids to clean the unit.

Wireless Router Mounting

 Install the wireless router on a wall or on a desktop only in its special mounting holder, which provides ventilation and helps protect against spilled liquids.

Ventilation Openings

- The small openings on the bottom and sides of the unit provide necessary ventilation for the proper operation of the unit. Install the unit so that its location or position does not interfere with this ventilation.
- Take precautions so that small objects are not dropped into the ventilation openings.

Power

- Power Unit- Place the DC power unit out of the way, or tape it to the side of a vertical surface to prevent it from being stepped on or damaged.
- Power Cords- Cords should be routed so that they are not likely to be walked
 on or pinched by items placed on or against them. Pay particular attention to
 the point where cords, plugs, and convenience receptacles exit the unit. The
 DC cord should be placed in the strain relief to avoid accidental disconnection.


Interference

 The wireless router can cause interference to (and interfere with) other devices operating in the 2.4 to 2.435 GHz radio spectrum.

Service Only by Qualified Service Personnel

- Do not open the unit, reconfigure the software or change power supplies.
- The user should not make any attempt to service the wireless router.
- The unit should be serviced only by qualified service personnel.

Front Panel



Front Panel View

The front panel indicators provide a quick check of the status of the wireless router and its connections. The LEDs are labeled from left-to- right as follows:

- 1. Ethernet LAN shows the local area network activity.
- 2. Radio shows both transmit and receive radio activity.
- **3. Anchor** shows status in network and gives RF link information. If this light is off you do not have the connectivity to the network.
- 4. Power Indicator Steady light indicates the unit is powered on.