




MSL Level 1

ROHS-Y

승 인 원

제 품 명	칩 안테나		
사 용 자	텔리안		
적 용 모 델	I405(MGQ7180L)		
사용자 CODE			
공급자	주식회사 파트론		
공급자 CODE	ACS2450EBAI4		
텔리안	작성자	검토자	승인자
(주)파트론	작성자	품질합의	승인자
			
	개발 2P	품질보증파트	연구소
	전찬익	이광규	임병준
	06/04	06/04	06/04

2007 . 06. 04



경기도 화성시 반월동 33번지 나동 455-300

Tel : 031-201-7870~6

Fax : 031-201-7800

www.partron.co.kr




MSL Level 1

ROHS-Y

SPECIFICATION

MODEL : ACS2450EBAI4

3D Structure		
		
Top Pattern	Bottom Pattern	
작성자	검토자	승인자
		
개발 2P	품질보증파트	연구소
전찬익	이광규	임병준
06/04	06/04	06/04

2007 . 06. 04



경기도 화성시 반월동 33번지 나동 455-300

Tel : 031-201-7870~6

Fax : 031-201-7800

www.partron.co.kr

- 목 차 -

※ 표지	1 p
※ 목차	3 p
1. 이력 관리	4 p
2. 부품의 개요	5 p
3. 중점 관리 항목	5 p
4. 전기적 특성	6 p
5. 시험 방법	11 p
6. 내부 Block Diagram	13 p
7. 기본 동작 및 Application Note	13 p
8. 측정 Jig 사양	14 p
9. REFLOW PROFILE	15 p
10. 초기 검사 성적서	16 p
11. 신뢰성 보증 조건	17 p
12. 기구적 특성	19 p
13. 구조 및 재질	21 p
14. 주의 사항	22 p
15. 포장 사양	23 p
16. 관리 공정도	26 p
17. 유해물질 성적서	29 p

1. 이력관리


2. 부품의 개요 및 치수 규격

2.1 부품개요

본 제품은 유전체 무선 통신 기기 내장형 Chip Antenna로 직방의 형상을 갖는 유전체에 은(Ag) Paste로 패턴을 형성하여 특성을 구현한다.

2.2부품 치수규격

Type	Only Bulk Ceramic	
재 질	Dielectric Block	Mg_3SiO_4 (Magnesium Silicate)
	전극 Paste	Ag
크 기 [mm]	$W = 2.0 \pm 0.1$	
	$L = 5.4 \pm 0.1$	
	$T = 1.2 \pm 0.1$	
평탄도	0.04(소제기준)	
MSL LEVEL	MSL LEVEL 1	
ESD LEVEL	15 KV이상 (HBM CLASS 3B)	
Version	Revision 2.0	



3. 중점관리항목(CTF)

- 아래 항목에 대하여 중점관리 항목으로 지정하여 관리한다.

제품의 CTQ 항목	지정 사유
성형무게,치수	성형무게 및 치수에 따라 소성후 소체 SIZE가 결정되며 소체 SIZE가 인쇄 정밀도에 영향을 미침
소성치수	소성후 치수가 인쇄 정밀도에 영향을 줌
인쇄치수	인쇄치수 정밀도가 BT 안테나의 특성의 핵심적 항목임.

제품의 CTF 항목	지정 사유
단품측정 SWR	제품의 전기적 특성을 분별하는 주요 PARAMETER 임

- 아래 항목에 대하여 주의를 요함

항 목	내 용
보 관	상온에 장시간 보관시 밀봉하여 보관
동 작	임의의 설계 변경시 특성이 변경될 수 있음

4. 전기적 특성


4.1 단품 Spec

ITEM	SPEC
Frequency Range [MHz]	2400 ~ 2485
SWR [Max]	3 : 1 (Typ 2 : 1)
Input Impedance [Ω]	50
Polarization	Linear
Gain (Peak / Avg) [dBi]	2.5 / 0
Temperature [°C]	-40 ~ +80
Humidity [%]	At the normal temperature, RH 100

4.2 Set 실장 측정

ITEM	SPEC
Frequency Range [MHz]	2400 ~ 2485
SWR [Max]	3 : 1 (Typ 2.5 : 1)
Input Impedance [Ω]	50 Ohm
Polarization	Linear
Gain[dBi]	Active TRP [dBm]
	Peak
	Average
	Peak


4.3 Set 실장 측정 Graph



4.4 Test Fixture 측정


ITEM	SPEC
Frequency Range [MHz]	1950 ~ 2030
Lower frequency(1960MHz) SWR [Min~Max]	1.5 ~ 3.0 : 1 (Typ 2.0 : 1)
Upper frequency(2040MHz) SWR [Min~Max]	1.5 ~ 3.0 : 1 (Typ 2.0 : 1)



4.5 Test Fixture 측정 Graph






4.6 방사 패턴

Azimuth Plane	Elevation1 Plane	Elevation2 Plane
Theta	Vertical field of measured plane	
Phi	Horizontal field of measured plane	










5. 시험 방법


5.1 SWR/Return loss

Network Analyzer를 이용하여 SWR/Return loss 를 측정하며 표본 SPL을 선별 Test Fixture 또는 자동화 검사장비를 이용하여 양품과 불량품을 선별한다.


	Set Condition	Test Fixture Condition
Network Analyzer	Agilent HP8753D	Agilent HP8753D or Advantest R3765CH
Cable	RF cable(300mm)	RF cable(300mm)
Test condition		

5.2 Gain

당사가 보유한 전파 무반사실에서 상기4.1에서 측정된 Set를 이용하여 Antenna Gain을 측정한다.




5.3 Gain test block diagram



6. 내부 Block Diagram

본 제품은 유전체를 재료로 한 직방형의 Block 표면에 Ag Pattern의 구조적인 변경을 통하여 아래와 같은 구조적인 등가회로의 Value를 조절하여 성능을 구현하는 RF 부품이다.




3 Land Type

2 Land Type


7. 기본 동작 및 Application Note

본 제품은 무선 통신 기기 내장형 유전체 Chip Antenna로 전송선로를 따라 진행해온 전기적 신호를 자유공간파(FREE SPACE WAVE)로 변환하는 장치이다.

본 제품은 원하는 어떠한 위치에도 실장이 가능하며 실장 조건에 따라 그 설계를 달리 한다. 다만 본 제품은 방사 부품으로 주변 Boundary Condition에 따라 그 특성을 달리 하므로 위치 선정에 각별한 주의를 기울여야 한다.




본 제품은 실장 주변 조건에 맞추어 아래와 같이 다양한 Antenna Type으로 설계 변경이 용이하다.




8. 측정 Jig 사양

8.1 Test Fixture And GROUND Condition



※ Ev B'd 와 Test fixture Jig 는 동일함(Ev B'd 는 접촉 방식이 납땜, Test Fixture 는 동편 Contact 방식)

8.2 PCB Layout & Soldering Pad Dimension




Top Layout

Bottom Pattern


Parameter	A	B	C	D	E	F	G	H
Value[mm]	0.9	0.5	0.8	2.5	2.2	more than 1.5	more than 5.6	more than 3.7

Unit : mm
Unless specified tolerances are ± 0.1

8.3 Matching Circuit And Reference Value




π Matching



T Matching

9. REFLOW PROFILE

9.1 표준 열경화(Reflow) 조건



9.2 수동 납땜 (납땜 인두기를 사용할 경우)

예 열 : 120°C / 시 간 : 60 ~ 300 sec.


인두온도 : 340°C ± 5°C / 시 간 : 각 단 최대 5 sec.

9.3 Recommend PCB Pattern Design

PCB Land Pattern은 제시한 Antenna의 Land Dimension 보다

아래 그림에서 보여지는 것과 같이 0.1mm 이상 외각으로 확장된 형태로 설계된다.

* 8.2 PCB Layout & Soldering Pad Dimension 항목과 동일함



10. 초기 검사 성적서

검사항목	단품특성 [MHz] 		Ev B'd특성 [MHz]		치수 [mm]		
규격	VSWR 3.0 Max		VSWR 3.0 Max		W=2.0±0.1	L=7.0±0.1	T=1.2±0.1
	1950	2030	1950	2030			
1	1930	2010	1960	2040	2.02	7.01	1.23
2	1.62	1.73	1.95	2.42	2.03	7.02	1.23
3	1.71	1.65	2.44	1.96	2.03	7.03	1.23
4	1.67	1.66	1.95	2.43	2.03	7.01	1.22
5	1.67	1.68	2.24	2.10	2.02	7.01	1.23
6	1.63	1.61	2.50	2.02	2.04	7.01	1.24
7	1.70	1.61	2.08	2.82	2.02	7.02	1.24
8	1.59	1.80	2.23	2.22	2.03	7.02	1.22
9	1.61	1.78	1.70	2.89	2.02	7.02	1.24
10	1.60	1.78	1.99	2.88	2.03	7.02	1.24
11	1.58	1.77	2.22	1.86	2.03	7.03	1.23
12	1.68	1.70	1.67	1.78	2.02	7.03	1.24
13	1.62	1.67	1.86	1.65	2.04	7.02	1.22
14	1.67	1.75	2.03	2.37	2.02	7.01	1.23
15	1.60	1.72	1.86	2.77	2.03	7.01	1.23
16	1.62	1.74	2.07	1.78	2.03	7.02	1.24
17	1.70	1.60	1.69	1.80	2.02	7.03	1.22
18	1.74	1.57	1.86	1.62	2.04	7.03	1.24
19	1.76	1.55	2.04	1.76	2.02	7.01	1.23
20	1.66	1.62	1.82	1.77	2.02	7.02	1.24
Min	1.67	1.61	1.91	1.69	2.02	7.01	1.22
Max	1.58	1.55	1.67	1.62	2.04	7.03	2.24
X	1.76	1.8	2.5	2.89	2.02	7.01	1.23
σ	1.67	1.66	2.01	2.13	0.01	0.01	0.01
Cpk	0.05	0.07	0.09	0.09	3.28	3.38	2.91
판정	OK	OK	OK	OK	OK	OK	OK

11. 신뢰성 보증조건

11.1 환경 시험

항목	시험 조건	판정기준
고온동작	85°C ±3°C에서 1시간 방치후 시험온도 상태에서 측정한다	시험후 4.3. 항의 특성규격 을 만족해야함.
고온방치	+85°C ±3°C, 120hr ±2hr 방치한다	
저온동작	-40°C ±3°C에서 1시간 방치후 시험온도 상태에서 측정한다	
저온방치	-40°C ±3°C, 120hr ±2hr 방치한다	
내습동작	+85±3°C, RH85%에서 1시간 방치후 시험온도 상태에서 측정한다	
내습방치	+85±3°C, RH85%, 120hr ±2hr 방치한다	

11.2 열충격, REFLOW시험

항목	조건	판정기준
열충격	조건 : -40°C ±3°C / 1min ↔ +85°C ±3°C / 1min 시험 CYCLE : 32 cycle 온도변환시간 : 5min 미만일것	시험후 4.3. 항의 특성규격 을 만족해야함.
Reflow	Pre Heating : 200±5°C, 30~60 sec Peak Heating : 260°C ±5°C, 30sec Max	

11.3 기계적 시험

항목	조건	판정기준
진동시험	주파수 : 10~500Hz, 가속도 : 10 × 9.8m/s²(G) Sweep time : 15min, X.Y.Z each 5 times	시험후 4.3. 항의 특성규격 을 만족해야함.
낙하시험	- 조건 : 152cm에서 낙하하이그를 이용하여 18회 자유낙하(6면3회) - 지그 : 120g±20g 플라스틱 지그 사용 - 바닥 : 콘크리트 or 철판	

*진동 및 낙하시험은 Ev B'd 납땜하여 실시할 것

11.4 MSL LEVEL 시험


1) JEDEC J-STD-020C 조건

	Floor Life		Soak Requirements	
	Time	Conditions	Time	Conditions
1	Unlimited	= < 30°C / 85%RH	168+5/-0	= < 85°C / 85%RH

2) Test 조건


항목	조건	비고
Soak Requirements	+85±3°C, RH85% 168hr ±2hr 방치후 Aging 없이 Reflow 실시 2회 실시	시험후 4.3. 항의 특성규격 을 만족해야함.

11.5 신뢰성 시험 FLOW




12. 기구적 특성

12.1 안테나 패턴 도면



12.2 Pin name




12.3 LOT 번호 표기법

7	1	1
①	②	③

- ① Year : 7 - 2007
- ② Month : 1 - January, 2 - February, 9 - September, A - October, B - November ..
- ③ Date : 1 - 1st , 2 - 2nd, A - 10th, B - 11th

12.4 Marking 사양



◀	1	4	7	1	1
①	②	③	④	⑤	

- ① Input Signal
- ② Serial
- ③ Year; 1 - 2001, 2 - 2002, 7 - 2007
- ④ Month ; 1 - January, 2 - February, 9 - September, A - October, B - November
- ⑤ Date : 1 - 1st , 2 - 2nd, A - 10th, B - 11th

12.5 Marking 종류


Ink marking - Black Ink 사용

13. 구조 및 재질


13.1 구현방법

직방체의 형상을 갖는 유전체 소체에 은(Ag) Paste로 패턴을 형성하여 특성을 구현함

13.2 구조



13.3 내부 단면도



13.4 재질

구분	재질	제조사	인쇄패턴 사양
Dielectric Block	POWDER	후지	
PATTERN	Ag Paste	METECH	인쇄두께 : TYP 10 μ m
PAD	Ag paste	METECH	인쇄두께 : Min 10 μ m (TYP 16~20 μ m)

14. 주의 사항

14.1 온도 조건

	온도범위	unit
사용온도	-40 ~ +100°C	°C
보관온도	-40 ~ + 70°C	°C

14.2 온도조건 TEST 조건

	항목	온도범위
사용온도	저온	-75°C에서 24시간 정상동작
	고온	+150°C에서 24시간 정상동작
보관온도	저온	-75°C에서 1000HR 방치시 정상동작
	고온	+85°C에서 1000HR 방치시 정상동작


* 고온방치시 포장재 보관온도 문제로 85°C 이상 불가함




15. 포장 사양

15.1 Carrier/Reel 사양

품목	재질	표면저항	정전기 발생량	포장방식
Carrier tape	A-PET	Typical $10^8 \Omega$	10V MAX	열 압착식
Cover tape	PET	Typical $10^8 \Omega$	30V MAX	
Reel	PS	Typical $10^8 \Omega$	30V MAX	



DKC DWG. No.	D-1208-048	TITLE	CARRIER TAPE 2*5.4*1.2P			
DIMENSIONAL UNIT	MM				NAME	SPEC.
UNTOLERANCED DIMENSION	± 0.1				W	12.0 ± 0.2
CAD FILE NAME	041222		PART.	CARRIER TAPE	E	1.75 ± 0.1
DESIGNED BY	K. M. J		MATERIAL	C-PET	F	5.5 ± 0.1
SCALE	1/1		LENGTH	49.6M	Do	1.5 ± 0.1
			COUNT	6200P	P	8.0 ± 0.1
					Po	4.0 ± 0.1
					P2	2.0 ± 0.1
					Ao	2.3 ± 0.1
					Bo	5.7 ± 0.1
					Ko	1.4 ± 0.1
					T	0.3 ± 0.05



Model : ACS2450EBAI4
L*****
Sec code :

Quantity :



Lot No



MSL Level 1



15.2 BOX 사양



15.2 포장 실물 사진



Reel 사진



내상 Box 사진

16. 관리공정도

제품		발행 /개정		품질관리공정도					관리번호	기안	심의	결정		
CHIP ANTENNA		Issued Revised	04.04.06 05.04.03						PRCP-C001					
투입자재	FLOW CHART		공정명	요인관리				품질특성관리						
	준비	본공정		설비명	관리항목	조건	관리주기	기록관리	관리항목	관리한계	검사방법	관리주기	기록관리	
세라믹 파우더			수입검사						수축율 유전율	작업지도서 참조	Micrometer Network	10개/LOT	C/sheet	반품
파우더 윤활제			분말	Mixer					溷합	파우더:윤활 제	저울	溷합시	-	폐기
			성형 CTQ공정 (무게, 치수)	프레스	양압 금형상태	작업지도서 참조	매LOT 1회/일	parameter C/SHEET	치수 무게 밀도 외관	작업지도서 참조	Micrometer 저울 Calculated Visual	5/100개검 사 10개/LOT	LOT CARD	폐기
			소성	소성로	SETTER 외관 온도 PROFILE	작업지도서 참조	전수 2회/일 1회/월	C/sheet						
			소체 CTQ공정 (치수)						폭 길이 모양	검사지도서 참조	Micrometer Calipers 목시	20개/LOT 20개/LOT 전수	C/sheet	폐기
AG PASTE			SIDE1 PAD 인쇄 CTQ공정 (인쇄치수)	인쇄기 screen	스크류 속도 /압력 SNAP	작업지도서 참조	1회/일	-	PATTERN치수 외관	작업지도서 참조	측정기 현미경	10개/3Jig	c/sheet	재작업
			건조	건조기 건조Jig	온도 Belt speed	작업지도서 참조	1회/주	Parameter	건조상태 인쇄상태 파손	작업지도서 참조	목시	전수검사	Lot card	재작업

제품		발행 / 개정		품질관리공정도					관리번호	기안	심의	결정		
CHIP ANTENNA		Issued Revised	04.04.06. 05.04.03						PRCP-C001					
투입자재	FLOW CHART		공정명	요인관리					품질특성관리					
	준비	본공정		설비명	관리항목	조건	관리주기	기록관리	관리항목	관리한계	검사방법	관리주기	기록관리	조치사항
AG PASTE		<input type="radio"/>	SIDE 2 PAD 인쇄 CTQ공정 (인쇄치수)	인쇄기 screen	스퀴즈 속도 /압력 SNAP	작업지도서 참조	1회/일	-	PATTERN치수 외관	작업지도서 참조	측정기 현미경	10개 /3Jig	c/sheet	재작업
		<input type="radio"/>	건조	건조기 건조Jig	온도 Belt speed	작업지도서 참조	1회/주	Parameter	건조상태 인쇄상태 파손	작업지도서 참조	목시	전수검사	Lot card	재작업
		<input type="radio"/>	소부	소부로 mesh망	온도 Belt speed	작업지도서 참조	1회/주	Parameter C/Sheet	소체파손 오염	작업지도서 참조	목시	전수	Lot card	폐기 재작업
AG PASTE		<input type="radio"/>	TOP 인쇄 CTQ공정 (인쇄치수)	인쇄기 screen	스퀴즈 속도 /압력 SNAP	작업지도서 참조	1회/일	-	PATTERN치수	작업지도서 참조	측정기	10개 /3Jig	c/sheet	재작업
		<input type="radio"/>	건조	건조기 건조Jig	온도 Belt speed	작업지도서 참조	1회/주	Parameter	건조상태 인쇄상태 파손	작업지도서 참조	목시	전수검사	Lot card	재작업
AG PASTE		<input type="radio"/>	BOTTOM PAD 인쇄 CTQ공정 (인쇄치수)	인쇄기 screen	스퀴즈 속도 /압력 SNAP	작업지도서 참조	1회/일	-	PATTERN치수 외관	작업지도서 참조	측정기 현미경	10개 /3Jig	c/sheet	재작업

제품		발행 /개정		품질관리공정도					관리번호	기안	심의	결정		
CHIP ANTENNA		Issued Revised	04.04.06. 05.04.03						PRCP-C001					
투입자재	FLOW CHART		공정명	요인관리					품질특성관리					
	준비	본공정		설비명	관리항목	조건	관리주기	기록관리	검사항목	관리한계	검사방법	관리주기	기록관리	조치사항
		○	건조	건조기 건조Jig	온도 Belt speed	작업지도서 참조	1회/주	Parameter	건조상태 인쇄상태 파손	작업지도서 참조	목시	전수검사	Lot card	재작업
		○	소부	소부로 mesh망	온도 Belt speed	작업지도서 참조	1회/주	Parameter C/Sheet	소체파손 오염	작업지도서 참조	목시	전수	Lot card	폐기 재작업
		◇	외관검사						제품외관	한도견본 작업지도서 참조	목시 현미경	전수	Lot card 생산일보	폐기 수리
		○	MARKING	마킹기					마킹외관	한도견본	목시	전수	Lot card 생산일보	재작업 폐기
		◇	특성검사 CTF공정	NETWORK 검사지그	교정상태	작업지도서 참조	1회/반	C/sheet	전기적 특성	작업지도서 참조	Network	전수	Lot card 생산일보	폐기 수리
		◇	외관검사						제품외관 제품치수	한도견본 작업지도서 참조	목시 현미경	전수	Lot card 생산일보	폐기 수리
Carrier cover reel		○	Taping						수량 역삼 외관	작업지도서 참조	수작업	전수	Lot card 생산일보	재작업
		◇	출하검사	NETWORK 검사지그	교정상태	작업지도서 참조	1회/반	C/sheet	전기적특성 제품외관 포장상태	검사지도서	Network 현미경 목시	작업 지도서	성적서	return 폐기
포장 box label		○	포장	bar code pr inter					포장상태 기종호입 포장수량	포장작업 지도서	목시	전수	-	재작업
		◇	포장검사						포장상태 기종호입 포장수량	포장작업 지도서	목시	전수	-	return

17. 유해물질 성적서

1) Ceramic Powder

Parts Name	White Powder (MMS-08)
Tester Organization	SGS Taiwan LTD.
Measurement Tester	Please see the 'method' in the test report
Measurement Data	Please see the report under the table

<div style="text-align: center; margin-bottom: 10px;"> </div> <div style="text-align: center;"> Test Report </div> <p>FUJI TITANIUM IND. CO., LTD. 12-8, SENGEN-CHO, HIRATSUKA-CITY, KANAKAWA-PREF. JAPAN. (T) 81-463-32-0210</p> <p>Report No. : CE/2006/75167 Date : 2006/07/25 Page : 1 of 4</p> <p>The following sample(s) was/were submitted and identified by/on behalf of the client as :</p> <p>Sample Description : MIXTURE OF (1) MAGNESIUM SILICATE (2) STRONTIUM ZIRCONATE (3) BARIUM TITANATE Style/Item No : MMS-08 (B) Sample Received : 2006/07/18 Testing Period : 2006/07/18 TO 2006/07/25</p> <p>Test Results: Please see the next page(s) -</p> <p style="margin-top: 20px;"> Daniel Yen, M.R. Operation Manager Signed for and on behalf of SGS TAIWAN LTD. </p> <p><small>The content of this PDF file is in accordance with the original issued reports for reference only. This Test Report cannot be reproduced, except in full, without prior written permission of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS TAIWAN LIMITED NO. 1, Wu Kung Road, WuFu Industrial Zone, Taipei county, Taiwan 2266-01-07202001 1000-02-2709-0201 www.sgs.com.tw</small> </p>	<div style="text-align: center; margin-bottom: 10px;"> </div> <div style="text-align: center;"> Test Report </div> <p>FUJI TITANIUM IND. CO., LTD. 12-8, SENGEN-CHO, HIRATSUKA-CITY, KANAKAWA-PREF. JAPAN. (T) 81-463-32-0210</p> <p>Report No. : CE/2006/75167 Date : 2006/07/25 Page : 2 of 4</p> <p>Test Result(s)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>PART NAME NO.1</th> <th>Test Item (s)</th> <th>Unit</th> <th>Method</th> <th>MDL</th> <th>Result No.1</th> </tr> </thead> <tbody> <tr> <td>WHITE POWDER</td> <td>PBBs (Polybrominated biphenyls)</td> <td>---</td> <td>---</td> <td>---</td> <td>---</td> </tr> <tr> <td></td> <td>Monobromobiphenyl</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Dibromobiphenyl</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Tribromobiphenyl</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Tetrabromobiphenyl</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Pentabromobiphenyl</td> <td>%</td> <td>With reference to USEPA1540C. Analysis was performed by HPLC/DAD.</td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Hexabromobiphenyl</td> <td>%</td> <td>LC/MS or GC/MS.</td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Heptabromobiphenyl</td> <td>%</td> <td>(prohibited by 2002/95/EC (RoHS), 83/264/EEC, and 76/769/EEC)</td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Octabromobiphenyl</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Nonabromobiphenyl</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Decabromobiphenyl</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Total PBBs (Polybrominated biphenyls)/Sum of above</td> <td>%</td> <td></td> <td>-</td> <td>N.D.</td> </tr> <tr> <td></td> <td>PBDEs(PBDEs) (Polybrominated biphenyl ethers)</td> <td>---</td> <td>---</td> <td>---</td> <td>---</td> </tr> <tr> <td></td> <td>Monobromobiphenyl ether</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Dibromobiphenyl ether</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Tribromobiphenyl ether</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Tetrabromobiphenyl ether</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Pentabromobiphenyl ether</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Hexabromobiphenyl ether</td> <td>%</td> <td>With reference to USEPA1540C. Analysis was performed by HPLC/DAD.</td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Heptabromobiphenyl ether</td> <td>%</td> <td>LC/MS or GC/MS.</td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Octabromobiphenyl ether</td> <td>%</td> <td>(prohibited by 2002/95/EC (RoHS), 83/264/EEC, and 76/769/EEC)</td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Decabromobiphenyl ether</td> <td>%</td> <td></td> <td>0.0005</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Total PBDEs (Polybrominated biphenyl ethers)/Sum of above</td> <td>%</td> <td></td> <td>-</td> <td>N.D.</td> </tr> <tr> <td></td> <td>Total of Mono to Nonabrominated biphenyl ether. (Note 4)</td> <td>%</td> <td></td> <td>-</td> <td>N.D.</td> </tr> </tbody> </table> <p><small>The content of this PDF file is in accordance with the original issued reports for reference only. This Test Report cannot be reproduced, except in full, without prior written permission of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS TAIWAN LIMITED NO. 1, Wu Kung Road, WuFu Industrial Zone, Taipei county, Taiwan 2266-01-07202001 1000-02-2709-0201 www.sgs.com.tw</small> </p>	PART NAME NO.1	Test Item (s)	Unit	Method	MDL	Result No.1	WHITE POWDER	PBBs (Polybrominated biphenyls)	---	---	---	---		Monobromobiphenyl	%		0.0005	N.D.		Dibromobiphenyl	%		0.0005	N.D.		Tribromobiphenyl	%		0.0005	N.D.		Tetrabromobiphenyl	%		0.0005	N.D.		Pentabromobiphenyl	%	With reference to USEPA1540C. Analysis was performed by HPLC/DAD.	0.0005	N.D.		Hexabromobiphenyl	%	LC/MS or GC/MS.	0.0005	N.D.		Heptabromobiphenyl	%	(prohibited by 2002/95/EC (RoHS), 83/264/EEC, and 76/769/EEC)	0.0005	N.D.		Octabromobiphenyl	%		0.0005	N.D.		Nonabromobiphenyl	%		0.0005	N.D.		Decabromobiphenyl	%		0.0005	N.D.		Total PBBs (Polybrominated biphenyls)/Sum of above	%		-	N.D.		PBDEs(PBDEs) (Polybrominated biphenyl ethers)	---	---	---	---		Monobromobiphenyl ether	%		0.0005	N.D.		Dibromobiphenyl ether	%		0.0005	N.D.		Tribromobiphenyl ether	%		0.0005	N.D.		Tetrabromobiphenyl ether	%		0.0005	N.D.		Pentabromobiphenyl ether	%		0.0005	N.D.		Hexabromobiphenyl ether	%	With reference to USEPA1540C. Analysis was performed by HPLC/DAD.	0.0005	N.D.		Heptabromobiphenyl ether	%	LC/MS or GC/MS.	0.0005	N.D.		Octabromobiphenyl ether	%	(prohibited by 2002/95/EC (RoHS), 83/264/EEC, and 76/769/EEC)	0.0005	N.D.		Decabromobiphenyl ether	%		0.0005	N.D.		Total PBDEs (Polybrominated biphenyl ethers)/Sum of above	%		-	N.D.		Total of Mono to Nonabrominated biphenyl ether. (Note 4)	%		-	N.D.
PART NAME NO.1	Test Item (s)	Unit	Method	MDL	Result No.1																																																																																																																																																		
WHITE POWDER	PBBs (Polybrominated biphenyls)	---	---	---	---																																																																																																																																																		
	Monobromobiphenyl	%		0.0005	N.D.																																																																																																																																																		
	Dibromobiphenyl	%		0.0005	N.D.																																																																																																																																																		
	Tribromobiphenyl	%		0.0005	N.D.																																																																																																																																																		
	Tetrabromobiphenyl	%		0.0005	N.D.																																																																																																																																																		
	Pentabromobiphenyl	%	With reference to USEPA1540C. Analysis was performed by HPLC/DAD.	0.0005	N.D.																																																																																																																																																		
	Hexabromobiphenyl	%	LC/MS or GC/MS.	0.0005	N.D.																																																																																																																																																		
	Heptabromobiphenyl	%	(prohibited by 2002/95/EC (RoHS), 83/264/EEC, and 76/769/EEC)	0.0005	N.D.																																																																																																																																																		
	Octabromobiphenyl	%		0.0005	N.D.																																																																																																																																																		
	Nonabromobiphenyl	%		0.0005	N.D.																																																																																																																																																		
	Decabromobiphenyl	%		0.0005	N.D.																																																																																																																																																		
	Total PBBs (Polybrominated biphenyls)/Sum of above	%		-	N.D.																																																																																																																																																		
	PBDEs(PBDEs) (Polybrominated biphenyl ethers)	---	---	---	---																																																																																																																																																		
	Monobromobiphenyl ether	%		0.0005	N.D.																																																																																																																																																		
	Dibromobiphenyl ether	%		0.0005	N.D.																																																																																																																																																		
	Tribromobiphenyl ether	%		0.0005	N.D.																																																																																																																																																		
	Tetrabromobiphenyl ether	%		0.0005	N.D.																																																																																																																																																		
	Pentabromobiphenyl ether	%		0.0005	N.D.																																																																																																																																																		
	Hexabromobiphenyl ether	%	With reference to USEPA1540C. Analysis was performed by HPLC/DAD.	0.0005	N.D.																																																																																																																																																		
	Heptabromobiphenyl ether	%	LC/MS or GC/MS.	0.0005	N.D.																																																																																																																																																		
	Octabromobiphenyl ether	%	(prohibited by 2002/95/EC (RoHS), 83/264/EEC, and 76/769/EEC)	0.0005	N.D.																																																																																																																																																		
	Decabromobiphenyl ether	%		0.0005	N.D.																																																																																																																																																		
	Total PBDEs (Polybrominated biphenyl ethers)/Sum of above	%		-	N.D.																																																																																																																																																		
	Total of Mono to Nonabrominated biphenyl ether. (Note 4)	%		-	N.D.																																																																																																																																																		


Test Report

FUJI TITANIUM IND. CO., LTD.
12-8, SENGEN-CHO, HIRATSUKA-CITY, KANAKAWA-PREF. JAPAN. (T) 81-463-32-0210

Report No. : CE/2006/75167
Date : 2006/07/25
Page : 3 of 4



Test Item (s):	Unit	Method	MDL	Result No.1
Chromium VI (Cr+6)	ppm	UV-VIS(US EPA 7196A) after reference to US EPA 3060A.	2	N.D.
Cadmium (Cd)	ppm	ICP-AES after reference to EN 1122, method B:2001 or other acid digestion.	2	N.D.
Mercury (Hg)	ppm	ICP-AES after reference to US EPA 3052 or other acid digestion.	2	N.D.
Lead (Pb)	ppm	ICP-AES after reference to US EPA 3050B or other acid digestion.	2	19.3


NOTE: (1) N.D. = Not Detected (<MDL)
 (2) ppm = mg/kg
 (3) MDL = Method Detection Limit
 (4) Decabromobiphenyl ether (DecaBDE) in polymeric applications is exempted by
 Commission Decision of 13 Oct 2005 amending Directive 2002/95/EC notified
 under document 2005/717/EC.
 (5) PBBe's=PBDBe's=Polybrominated Diphenyl Ethers=PBDOS=PBBOs.
 (6) - " = Not Regulation
 (7) - ... " = Not Applicable

The content of this PDF file is in accordance with the original issued reports for reference only. This Test Report cannot be reproduced, except in full,
 without prior written permission of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and
 offenders may be prosecuted to the fullest extent of the law.


Test Report

FUJI TITANIUM IND. CO., LTD.
12-8, SENGEN-CHO, HIRATSUKA-CITY, KANAKAWA-PREF. JAPAN. (T) 81-463-32-0210

Report No. : CE/2006/75167
Date : 2006/07/25
Page : 4 of 4




** End of Report **

The content of this PDF file is in accordance with the original issued reports for reference only. This Test Report cannot be reproduced, except in full,
 without prior written permission of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and
 offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Limited | NO. 10, Lane 229, Section 2, Neihu Industrial Zone, Taipei, Taiwan, Taiwan
SGS-ZL-20030929-TW0502-3209-2007 | www.sgs.com.tw


2) Ag Paste

Parts Name	Silver Paste
Tester Organization	SGS Testing KOREA co. Ltd.
Measurement Tester	Please see the 'method' in the test report
Measurement Data	Please see the report under the table

<p style="text-align: center;">SGS</p> <p>Test Report No. F690501/LF-CTSGP06-26952 Date: October 27, 2006 Page 1 of 2</p> <p>To: METECH KOREA CO., LTD. 8-801 Dongyang Paragon officetel 17-2 Jeongja-dong Bundang-gu Sungham-city GYEONGGI-DO Korea</p> <p>The following merchandise was submitted and identified by the client as:</p> <p>Commodity : PCC11937HV SGS File No. : GP06-26952 Received Date : October 20, 2006 Test Performing Date : October 23, 2006 Test Performed : SGS Testing Korea tested the sample(s) selected by applicant with following results Test Results : For further details, please refer to following page(s)</p> <p style="text-align: right;">Pluto Kim Patrick An Monet Jeong Jinhee Song Testing Person</p> <p style="text-align: center;">SGS Testing Korea Co. Ltd.  Jeff Jang / Chemical Lab Mgr</p> <p><small>The above certificate is the accredited test items by Korea Laboratory Accreditation Scheme (KOLAS), which signed the ILAC-MRA This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full, without prior written permission of the Company.</small></p>	<p style="text-align: center;">SGS</p> <p>Test Report No. F690501/LF-CTSGP06-26952 Date: October 27, 2006 Page 2 of 2</p> <p>Sample No. : GP06-26952.001 Sample Description : PCC11937HV Item No./Part No. : N/A Comments : Material is silver paste.</p> <p>Heavy Metals</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Test Items</th> <th>Unit</th> <th>Test Method</th> <th>MDL</th> <th>Results</th> </tr> </thead> <tbody> <tr> <td>Cadmium (Cd)</td> <td>mg/kg</td> <td>US EPA 3050B(1996), US EPA 6010B(1996), ICP</td> <td>0.5</td> <td>N.D.</td> </tr> <tr> <td>Lead (Pb)</td> <td>mg/kg</td> <td>US EPA 3050B(1996), US EPA 6010B(1996), ICP</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Mercury (Hg)</td> <td>mg/kg</td> <td>US EPA 3050(1998), US EPA 6010B(1996), ICP</td> <td>2</td> <td>N.D.</td> </tr> <tr> <td>Hexavalent Chromium (Cr VI)</td> <td>mg/kg</td> <td>US EPA 3060A(1996), US EPA 7196A(1992), UV</td> <td>1</td> <td>N.D.</td> </tr> </tbody> </table> <p style="text-align: center;">Picture of Sample as Received:</p>  <p style="text-align: center;">*** End ***</p> <p><small>NOTE: (1) N.D. = Not detected (>MDL) (2) ppm = mg/kg (3) MDL = Method Detection Limit (4) Estimated expanded uncertainty U with a coverage factor k = 2, corresponding to a level of confidence of about 95%</small></p> <p><small>The above certificate is the accredited test items by Korea Laboratory Accreditation Scheme (KOLAS), which signed the ILAC-MRA This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full, without prior written permission of the Company.</small></p>	Test Items	Unit	Test Method	MDL	Results	Cadmium (Cd)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	0.5	N.D.	Lead (Pb)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	5	N.D.	Mercury (Hg)	mg/kg	US EPA 3050(1998), US EPA 6010B(1996), ICP	2	N.D.	Hexavalent Chromium (Cr VI)	mg/kg	US EPA 3060A(1996), US EPA 7196A(1992), UV	1	N.D.
Test Items	Unit	Test Method	MDL	Results																						
Cadmium (Cd)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	0.5	N.D.																						
Lead (Pb)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	5	N.D.																						
Mercury (Hg)	mg/kg	US EPA 3050(1998), US EPA 6010B(1996), ICP	2	N.D.																						
Hexavalent Chromium (Cr VI)	mg/kg	US EPA 3060A(1996), US EPA 7196A(1992), UV	1	N.D.																						

3) Marking Ink

Parts Name	Black Ink
Tester Organization	SGS Testing KOREA co. Ltd.
Measurement Tester	Please see the 'method' in the test report
Measurement Data	Please see the report under the table

<div style="border-bottom: 1px solid black; margin-bottom: 10px;"> SGS </div> <p>Test Report No. F690501/LF-CTSGP06-27074 Date: October 27, 2006 Page 1 of 3</p> <p>To: IMAJE KOREA CO., LTD 1302, Daeyang Techno Town 7th Kasan-dong Gwangju-si Seoul Korea</p> <p>The following merchandise was submitted and identified by the client as:</p> <p>Commodity : ink-513SE black ink</p> <p>SGS File No. : GP06-27074</p> <p>Received Date : October 20, 2006</p> <p>Test Performing Date : October 23, 2006</p> <p>Test Performed : SGS Testing Korea tested the sample(s) selected by applicant with following results</p> <p>Test Results : For further details, please refer to following page(s)</p> <p style="text-align: right;">Pluto Kim Monet Jeong Jully Oh Jerry Jung Testing Person</p> <p style="text-align: center;"> Jeff Jang / Chemical Lab Mgr</p> <p>This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues detailed therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full, without prior written permission of the Company.</p>	<div style="border-bottom: 1px solid black; margin-bottom: 10px;"> SGS </div> <p>Test Report No. F690501/LF-CTSGP06-27074 Date: October 27, 2006 Page 2 of 3</p> <p>Sample No. : GP06-27074.001</p> <p>Sample Description : Ink-513SE black ink</p> <p>Style/Item No. : N/A</p> <p>Heavy Metals</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Test Items</th> <th>Unit</th> <th>Test Method</th> <th>MDL</th> <th>Results</th> </tr> </thead> <tbody> <tr> <td>Cadmium (Cd)</td> <td>mg/kg</td> <td>US EPA 3050B(1996), US EPA 6010B(1996), ICP</td> <td>0.5</td> <td>N.D.</td> </tr> <tr> <td>Lead (Pb)</td> <td>mg/kg</td> <td>US EPA 3050B(1996), US EPA 6010B(1996), ICP</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Mercury (Hg)</td> <td>mg/kg</td> <td>US EPA 3052(1996), US EPA 6010B(1996), ICP</td> <td>2</td> <td>N.D.</td> </tr> <tr> <td>Hexavalent Chromium (Cr VI)</td> <td>mg/kg</td> <td>US EPA 3050A(1996), US EPA 7196A(1992), UV</td> <td>1</td> <td>N.D.</td> </tr> </tbody> </table> <p>Flame Retardants-PBBs/PBDEs</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Test Items</th> <th>Unit</th> <th>Test Method</th> <th>MDL</th> <th>Results</th> </tr> </thead> <tbody> <tr> <td>Monobromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Dibromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Tribromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Tetra bromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Penta bromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Hexabromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Heptabromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Octabromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Nonabromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Decabromobiphenyl</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Monobromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Dibromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Tribromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Tetra bromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Penta bromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Hexabromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Heptabromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Octabromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Nonabromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> <tr> <td>Decabromobiphenyl ether</td> <td>mg/kg</td> <td>US EPA 3540C, GC/MS</td> <td>5</td> <td>N.D.</td> </tr> </tbody> </table> <p>NOTE: (1) N.D. = Not detected. (<MDL) (2) ppm = mg/kg (3) MDL = Method Detection Limit (4) - = No regulation (5) * = Qualitative analysis (No Unit) (6) ** = Quantitative analysis (No Unit) (7) Negative = Undetectable / Positive = Detectable</p> <p>This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues detailed therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full, without prior written permission of the Company.</p>	Test Items	Unit	Test Method	MDL	Results	Cadmium (Cd)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	0.5	N.D.	Lead (Pb)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	5	N.D.	Mercury (Hg)	mg/kg	US EPA 3052(1996), US EPA 6010B(1996), ICP	2	N.D.	Hexavalent Chromium (Cr VI)	mg/kg	US EPA 3050A(1996), US EPA 7196A(1992), UV	1	N.D.	Test Items	Unit	Test Method	MDL	Results	Monobromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Dibromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Tribromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Tetra bromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Penta bromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Hexabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Heptabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Octabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Nonabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Decabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Monobromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Dibromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Tribromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Tetra bromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Penta bromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Hexabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Heptabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Octabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Nonabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.	Decabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Test Items	Unit	Test Method	MDL	Results																																																																																																																															
Cadmium (Cd)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	0.5	N.D.																																																																																																																															
Lead (Pb)	mg/kg	US EPA 3050B(1996), US EPA 6010B(1996), ICP	5	N.D.																																																																																																																															
Mercury (Hg)	mg/kg	US EPA 3052(1996), US EPA 6010B(1996), ICP	2	N.D.																																																																																																																															
Hexavalent Chromium (Cr VI)	mg/kg	US EPA 3050A(1996), US EPA 7196A(1992), UV	1	N.D.																																																																																																																															
Test Items	Unit	Test Method	MDL	Results																																																																																																																															
Monobromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Dibromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Tribromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Tetra bromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Penta bromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Hexabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Heptabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Octabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Nonabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Decabromobiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Monobromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Dibromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Tribromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Tetra bromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Penta bromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Hexabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Heptabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Octabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Nonabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															
Decabromobiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.																																																																																																																															

<div style="border-bottom: 1px solid black; margin-bottom: 10px;"> SGS </div> <p>Test Report No. F690501/LF-CTSGP06-27074 Date: October 27, 2006 Page 3 of 3</p> <p>Picture of Sample as Received:</p> <div style="text-align: center;">  </div> <p>*** End ***</p> <p>NOTE: (1) N.D. = Not detected. (<MDL) (2) ppm = mg/kg (3) MDL = Method Detection Limit (4) - = No regulation (5) * = Qualitative analysis (No Unit) (6) Negative = Undetectable / Positive = Detectable</p> <p>This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues detailed therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full, without prior written permission of the Company.</p>
