

RF Exposure**MPE Calculation****KDB 447498****Prediction of MPE limit at a given distance**

Equation from IEEE C95.1

$$S = \frac{EIRP}{4\pi R^2} \text{ re - arranged } R = \sqrt{\frac{EIRP}{S4\pi}}$$

where:

S = power density

R = distance to the centre of radiation of the antenna

EIRP = EUT Maximum power

Note:

The EIRP was calculated by addition of the maximum conducted carrier power plus the antenna gain

Result

GFSK Modulation						
Prediction Frequency (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (mW)	Minimum Distance (cm)	Power density at distance (mW/cm ²)	Power density limit (S) (mW/cm ²)
2402	8.31	4.81	20.51	20	0.00408	1
2440	8.36	4.48	19.23	20	0.00383	1
2480	8.26	4.77	20.09	20	0.00400	1

QPSK Modulation						
Prediction Frequency (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (mW)	Minimum Distance (cm)	Power density at distance (mW/cm ²)	Power density limit (S) (mW/cm ²)
2402	9.09	4.81	24.55	20	0.00488	1
2440	9.08	4.48	22.70	20	0.00452	1
2480	9.05	4.77	24.10	20	0.00479	1

8PSK Modulation						
Prediction Frequency (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (mW)	Minimum Distance (cm)	Power density at distance (mW/cm ²)	Power density limit (S) (mW/cm ²)
2402	9.39	4.81	26.30	20	0.00523	1
2440	9.4	4.48	24.43	20	0.00486	1
2480	9.35	4.77	25.82	20	0.00514	1

Bluetooth Low Energy						
Prediction Frequency (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (mW)	Minimum Distance (cm)	Power density at distance (mW/cm ²)	Power density limit (S) (mW/cm ²)
2402	4.05	4.81	7.69	20	0.00153	1
2440	4.27	4.48	7.50	20	0.00149	1
2480	4.32	4.77	8.11	20	0.00161	1