

LELUX ELECTRONICS LTD.

PRODUCT SPECIFICATION

MODEL: 615PR

VERSION: 1.0

ENGINEER: HJS

DATE: 28-FEB-06

APPROVAL: ZENG

COUNTRY: INT'L

ITEM	CONDITION		SPEC.	UNIT
1	WORKING VOLTAGE		6	V
2	STANDBY CURRENT		<40	uA
3	WORKING CURRENT (RF Transmitting)		<20	mA
4	WORKING DELAY TIME		55±5	SEC.
5	BATTERY LOW DETECT		5.2+0.3	V
6	RF Frequency		433.92±75KHz	MHz
7	System RF Modulation		ASK	
8	Output Power(30cm away)		≥-15	dBm
9	RF Transmit Distance ----T015 (open area 25℃)		≥90	METER
10	PIR Detection Angle (horizontal & vertical)		H:110° V:30°	Degree
11	PIR Detection Distance (2M height)		≥8	METER
12	BATTERY LIFE (STANDBY)		ABOUT 8 MONTHS	
13	BATTERY TYPE	6LR61(9V) *1	PCS	
14	OPERATING TEMPERATURE		0℃ ~ 35℃	
15	STORAGE TEMPERATURE		-10℃ ~ 60℃	
NOTE:				