

National Certification Laboratory

**8370 Court Avenue, Suite B-1
Ellicott City, Maryland 21043
(410) 461-5548**

FCC REPORT OF RADIO INTERFERENCE

FOR

**Microhard Systems, Inc.
#110, 1144 – 29th Ave., N.E.
Calgary
Alberta, Canada T2E 7P1**

FCC ID: NS900P3

September 19, 2000



TABLE OF CONTENTS

- 1.0 Introduction
- 1.1 Summary
- 2.0 Description of Equipment Under Test (EUT)
- 2.1 EMI Countermeasure
- 3.0 Test Program
- 4.0 Test Configuration
- 5.0 Conducted Emissions Scheme
- 6.0 Radiated Emissions Scheme

TABLES

- Table 1. Support Equipment
- Table 2. Interface Cables
- Table 3. Measurement Equipment

EXHIBITS

- Exhibit 1. EUT Photographs
- Exhibit 2. Schematic Diagram
- Exhibit 3. User Manual

NCL PROJ.# Microhard-557



1.0 Introduction:

This report has been prepared on behalf of **Microhard Systems, Inc.**, to support the attached Application for a Certification of a Part 15 Spread Spectrum Transmitter module. The Equipment Under Test (EUT) was the Model: **CompactRF-900 Wireless Modem Transceiver /OEM Module**.

Radio-Noise Emissions tests were performed according to *FCC Public Notice 54797, titled "Guidance on Measurement for Direct Sequence SST"*. The measuring equipment conforms to ANSI C63.2 Specifications for Electromagnetic Noise and Field Strength Instrumentation.

Testing was performed at National Certification Laboratory in Ellicott City, MD. Site description and site attenuation data have been placed on file with the FCC's sampling and Measurements Branch. FCC acceptance was granted on May 26, 1993.

1.1 Summary:

The Microhard Systems, Inc., Model: **CompactRF-900 Wireless Modem Transceiver /OEM Module** complies with the FCC limits (15.247) for a Frequency Hopping SST.



2.0 Description of Equipment Under Test (EUT):

The EUT features:

Reverse Polarity SMA Antenna Connector per 15.203

+30 dBm RF Output Max.

902-928 MHz Frequency Range

350 kHz 20 dB Emission Bandwidth

64 Hopping Channels

400 kHz Channel Separation

86.4 kbps Data Rate (Radio Link)

115.2 kbps Max Data Rate (DCE)

3.0 Test Program:

This report contains measurement charts and data as evidence for the following tests performed:

1. (15.247b) Peak RF output power.
2. (15.247c) Field Strength of harmonics and spurious out-of-band emissions.
3. (15.247c) RF Antenna Conducted of harmonics and spurious out-of-band emissions.
4. (15.247a) 20 dB Emission Bandwidth.
5. (15.207) Power Line Conducted Emissions.
6. (15.247c) Band Edge emissions.



4.0 Test Configuration:

RF antenna output tests such as Bandwidth, Spurious/Harmonics, Power output, were taken with the transmitter antenna connector feeding directly into the spectrum analyzer via external 30 db attenuator. The analyzer's internal attenuator was adjusted to prevent overloading of the front end. The transmitter is modulated at 86.4 kbps which is the highest available data rate.

Field strength measurements were taken with the transmitter feeding a yagi, or omni antenna aimed at the receiving antenna. Testing was performed using the highest gain antenna from each design family (yagi, omni) with the power setting at 1 Watt for the omni antenna, and 100 mW for the higher gain yagi.

A list of all antennas that will be sold with the **CompactRF900** Wireless Module follows:

Antennex - 11 dBi Yagi Antenna

2.5 dBi Omni Antenna - 900 MHz Rubber Ducky

Antennex - 6 dBi Omni Antenna



PEAK POWER TEST RESULTS

Limit: 1 watt (30 dBm)

Condition: Transmitter is set to a single FM modulated channel

Reading from spectrum analyzer with 1 MHz Resolution Bandwidth setting:

Channel 1: 902.8 MHz - (+29.8 dBm)

Channel 32: 914.7 MHz - (+30.0 dBm)


Channel 64: 927.1 MHz - (+29.8 dBm)

SEE FOLLOWING THREE (3) PLOTS OF MODULATED CARRIER



PEAK RF POWER – MODULATED CARRIER (1 MHz RES. BW)


Channel 1





PEAK RF POWER – MODULATED CARRIER (1 MHz RES. BW)


Channel 32





PEAK RF POWER – MODULATED CARRIER (1 MHz RES. BW)

Channel 64





20 dB EMISSION BANDWIDTH

Maximum 20 dB BW: 0.500 MHz
RBW Setting on S.A.: 10 kHz

Condition: Transmitter is set to a single channel FM modulated at 86.4 kbps

Reading from Spectrum Analyzer:


| | | | |
|--------------------|------------------|----------|----------------|
| Channel 1: | 902.8 MHz | - | 342 kHz |
| Channel 32: | 914.7 MHz | - | 346 kHz |
| Channel 64: | 927.1 MHz | - | 350 kHz |

SEE FOLLOWING THREE (3) PLOTS OF MODULATED CARRIER



20 dB EMISSION BANDWIDTH – MODULATED CARRIER (10 kHz RES. BW)


Channel 1





20 dB EMISSION BANDWIDTH – MODULATED CARRIER (10 kHz RES. BW)


Channel 32





20 dB EMISSION BANDWIDTH – MODULATED CARRIER (10 kHz RES. BW)

Channel 64





RF ANTENNA CONDUCTED SPURIOUS/HARMONICS EMISSIONS

Limit: 20 dB below Carrier Level Measured with 100 kHz RBW

RBW Setting on S.A.: 100 kHz

Condition: Transmitter is set to a single FM modulated channel.
RF Power = 30 dBm

Three separate measurements are performed to show harmonic and spurious emissions generated with the transmitter tuned to low, middle, and high parts of the spectral range.

SEE FOLLOWING THREE (3) PLOTS & DATA TABLES



FCC Part 15.247(c) – Conducted Spurious Emissions

Frequency of Carrier = 902.8 MHz

Limit = 20 dBc

Condition: Transmitter is set to a single FM modulated channel.

TEST RESULTS

LIMIT: -20 dB FROM PEAK CARRIER

| <u>Component</u> | <u>Frequency (MHz)</u> | <u>Result (dB From Peak)</u> |
|------------------|------------------------|------------------------------|
| Harmonic | 1805.60 | -50.2 |
| Harmonic | 2708.40 | -64.0 |
| Harmonic | 3611.20 | -73.0 |
| Harmonic | 4514.00 | -73.0 |
| Harmonic | 5416.80 | -74.0 |
| Harmonic | 6319.60 | -75.0 |
| Harmonic | 7222.40 | -75.0 |
| Harmonic | 8125.20 | -75.0 |
| Harmonic | 9028.00 | -75.0 |



FCC Part 15.247(c) – Conducted Spurious Emissions

Frequency of Carrier = 914.70 MHz

Limit = 20 dBc

Condition: Transmitter is set to a single FM modulated channel.

TEST RESULTS

LIMIT: -20 dB FROM PEAK CARRIER

| <u>Component</u> | <u>Frequency (MHz)</u> | <u>Result (dB From Peak)</u> |
|------------------|------------------------|------------------------------|
| Harmonic | 1829.40 | -50.4 |
| Harmonic | 2744.10 | -73.0 |
| Harmonic | 3658.80 | -73.0 |
| Harmonic | 4573.50 | -73.0 |
| Harmonic | 5488.20 | -74.0 |
| Harmonic | 6402.90 | -74.0 |
| Harmonic | 7317.60 | -75.0 |
| Harmonic | 8232.30 | -75.0 |
| Harmonic | 9147.00 | -75.0 |



FCC Part 15.247(c) – Conducted Spurious Emissions

Frequency of Carrier = 927.1 MHz

Limit = 20 dBc

Condition: Transmitter is set to a single FM modulated channel.

TEST RESULTS


LIMIT: -20 dB FROM PEAK CARRIER

| <u>Component</u> | <u>Frequency (MHz)</u> | <u>Result (dB From Peak)</u> |
|------------------|------------------------|------------------------------|
| Harmonic | 1854.20 | -49.4 |
| Harmonic | 2781.30 | -73.0 |
| Harmonic | 3708.40 | -73.0 |
| Harmonic | 4635.50 | -73.0 |
| Harmonic | 5562.60 | -74.0 |
| Harmonic | 6489.70 | -74.0 |
| Harmonic | 7416.80 | -74.0 |
| Harmonic | 8343.90 | -75.0 |
| Harmonic | 9271.00 | -75.0 |



CONDUCTED HARMONICS EMISSIONS – MODULATED CARRIER (100 kHz RES. BW)

LOW CHANNEL




0 Fc 2Fc 3Fc 4Fc



CONDUCTED HARMONICS EMISSIONS- MODULATED CARRIER (100 kHz RES. BW)


MID CHANNEL





CONDUCTED HARMONICS EMISSIONS – MODULATED CARRIER (100 kHz RES. BW)

HIGH CHANNEL




0 Fc 2Fc 3Fc 4Fc




CONDUCTED BAND EDGE EMISSIONS – MODULATED CARRIER (100 kHz RES. BW)

LOW CHANNEL






CHANNEL UTILIZATION – RANDOM HOPPING SEQUENCE



5.0 Test Configuration for Conducted and Radiated Emissions:

The EUT was set up on the center of the test table, in a manner which follows the general guidelines of ANSI C63.4, Section 6 “General Operating Conditions and Configurations”.

This is described below:



6.0 Conducted Emissions Scheme:

The EUT is placed on an 80 cm high X 1.5 m non-conductive table. Power to the RF modem is provided through a Solar Corporation 50 ohm/50 uH Line Impedance Stabilization Network bonded to a 2.2 X 2 meter horizontal ground plane, and a 2.2 X 2 meter vertical ground plane. The LISN has its AC input supplied from a filtered AC power source. A separate LISN provides AC power to the peripheral equipment. I/O cables are moved about to obtain maximum emissions.

The 50 ohm output of the LISN is connected to the input of the spectrum analyzer and emissions in the frequency range of 450 kHz to 30 MHz are searched. The detector function is set to Quasi-Peak and the resolution bandwidth is set at 9 kHz, with all post detector filtering no less than 10 times the resolution bandwidth for final measurements. All emissions within 20 dB of the limit are recorded in the data tables.



FCC CLASS "B" CONDUCTED EMISSIONS DATA

CLIENT: MICROHARD SYSTEMS
EUT: COMPACTRF900

MODE: TRANSMIT

LINE 1-Neutral: Quasi-Peak Level **Date:** 09/13/2000

| FREQUENCY MHz | SPEC. Ana. dBuV | Calc. Volt. uV | FCC LIMIT uV | MARGIN dB | CONDITION |
|------------------|--------------------|-------------------|-----------------|--------------|-----------|
| 0.47 | 36.00 | 63.10 | 250.00 | 11.96 | PASS |
| 6.20 | 35.00 | 56.23 | 250.00 | 12.96 | PASS |
| 7.20 | 38.20 | 81.28 | 250.00 | 9.76 | PASS |
| 27.50 | 30.80 | 34.67 | 250.00 | 17.16 | PASS |

LINE 2-Phase: Quasi-Peak Level

| FREQUENCY MHz | SPEC. Ana. dBuV | Calc. Volt. uV | FCC LIMIT uV | MARGIN dB | CONDITION |
|------------------|--------------------|-------------------|-----------------|--------------|-----------|
| 0.52 | 35.60 | 60.26 | 250.00 | 12.36 | PASS |
| 4.80 | 34.60 | 53.70 | 250.00 | 13.36 | PASS |
| 6.20 | 34.80 | 54.95 | 250.00 | 13.16 | PASS |
| 23.90 | 33.40 | 46.77 | 250.00 | 14.56 | PASS |
| 28.40 | 32.00 | 39.81 | 250.00 | 15.96 | PASS |

TEST ENGINEER:

Brian Hahtalab



FCC RADIATED EMISSIONS DATA

CLIENT: MICROHARD SYSTEMS
EUT: COMPACTRF900
ANTENNA: YAGI
FREQ.: 902.8 MHZ
POWER: 100 mW

3 METER TEST

DATE: 09/13/2000

| FREQUENCY MHz | POLARITY | | SPEC A dBuV | AF/C dB/m | AMP Gain dB | Average Factor dB | Average E-Field dbuV/m | Average Limit dBuV/m | MARGIN dB | CONDITION |
|------------------|----------|---|----------------|--------------|----------------|----------------------|------------------------------|----------------------------|--------------|-----------|
| | H | V | | | | | | | | |
| 2,708.40 | H | | 40.00 | 35.00 | 25.00 | 0.00 | 50.00 | 54.00 | 4.00 | PASS |
| 3,611.20 | H | | 38.00 | 36.00 | 25.00 | 0.00 | 49.00 | 54.00 | 5.00 | PASS |
| 4,514.00 | H | | 34.00 | 39.00 | 25.00 | 0.00 | 48.00 | 54.00 | 6.00 | PASS |
| 5,416.80 | | V | 30.00 | 37.00 | 25.00 | 0.00 | 42.00 | 54.00 | 12.00 | PASS |
| 8,125.20 | | V | 32.00 | 38.00 | 25.00 | 0.00 | 45.00 | 54.00 | 9.00 | PASS |
| 9,028.00 | H | | 25.00 | 39.00 | 25.00 | 0.00 | 39.00 | 54.00 | 15.00 | PASS |

TEST ENGINEER:

Brian Haghtalab



FCC RADIATED EMISSIONS DATA

CLIENT: MICROHARD SYSTEMS
EUT: COMPACTRF900
ANTENNA: YAGI
FREQ.: 914.7 MHZ
POWER: 100 mW

3 METER TEST

DATE: 09/13/2000

| FREQUENCY MHz | POLARITY | | SPEC A dBuV | AF/C dB/m | AMP Gain dB | Average Factor dB | Average E-Field dbuV/m | Average Limit dBuV/m | MARGIN dB | CONDITION |
|------------------|----------|---|----------------|--------------|----------------|----------------------|------------------------------|----------------------------|--------------|-----------|
| | H | V | | | | | | | | |
| 2,744.10 | H | | 39.00 | 35.00 | 25.00 | 0.00 | 49.00 | 54.00 | 5.00 | PASS |
| 3,658.80 | H | | 39.00 | 36.00 | 25.00 | 0.00 | 50.00 | 54.00 | 4.00 | PASS |
| 4,573.50 | H | | 35.00 | 39.00 | 25.00 | 0.00 | 49.00 | 54.00 | 5.00 | PASS |
| 7,317.60 | | V | 32.00 | 37.00 | 25.00 | 0.00 | 44.00 | 54.00 | 10.00 | PASS |
| 8,232.30 | | V | 30.00 | 38.00 | 25.00 | 0.00 | 43.00 | 54.00 | 11.00 | PASS |
| 9,147.00 | H | | 27.00 | 39.00 | 25.00 | 0.00 | 41.00 | 54.00 | 13.00 | PASS |

TEST ENGINEER:

Brian Haghtalab



FCC RADIATED EMISSIONS DATA

CLIENT: MICROHARD SYSTEMS
EUT: COMPACTRF900
ANTENNA: YAGI
FREQ.: 927.1 MHZ
POWER: 100 mW

3 METER TEST

DATE: 09/13/2000

| FREQUENCY MHz | POLARITY | | SPEC A dBuV | AF/C dB/m | AMP Gain dB | Average Factor dB | Average E-Field dbuV/m | Average Limit dBuV/m | MARGIN dB | CONDITION |
|------------------|----------|---|----------------|--------------|----------------|----------------------|------------------------------|----------------------------|--------------|-----------|
| | H | V | | | | | | | | |
| 2,781.30 | H | | 40.00 | 35.00 | 25.00 | 0.00 | 50.00 | 54.00 | 4.00 | PASS |
| 3,708.40 | H | | 37.00 | 36.00 | 25.00 | 0.00 | 48.00 | 54.00 | 6.00 | PASS |
| 4,635.50 | H | | 35.00 | 39.00 | 25.00 | 0.00 | 49.00 | 54.00 | 5.00 | PASS |
| 7,416.80 | H | | 31.00 | 37.00 | 25.00 | 0.00 | 43.00 | 54.00 | 11.00 | PASS |
| 8,343.90 | H | | 28.00 | 38.00 | 25.00 | 0.00 | 41.00 | 54.00 | 13.00 | PASS |

TEST ENGINEER:

Brian Haghtalab



Table 1

Support Equipment

1. Host PC - Toshiba 740C Pentium Notebook
2. Microhard CompactRF Development Board (testing platform)



Table 2

Interface Cables Used

1. A 1.2 meter RS-232 serial shielded cable is used to connect the EUT to the Host computer.
2. Two feet of low-loss coaxial cable used to connect the EUT to the TX antenna (Reverse Polarity SMA to N connectors).



Table 3

Measurement Equipment Used

The following equipment is used to perform measurements:

| | |
|--|------------------------|
| HP 435A RF Peak Power Meter | - Serial No. 1362016 |
| EMCO Model 3110 Biconical Antenna | - Serial No. 1619 |
| Antenna Research MWH-1825B Horn Antenna | - Serial No. 1005 |
| EMCO Model 3115 Ridged Horn Antenna | - Serial No. 3007 |
| HP 8348A Preamplifier | - Serial No. 197-2564A |
| Solar 8012-50-R-24-BNC LISN | - Serial No. 924867 |
| Bird 8306-300-N 30dB Attenuator | - S/N: 29198391515 |
| HP 14IT w/8555A Spectrum Analyzer | - Serial No. 6-95-1124 |
| 4 Meter Antenna Mast | |
| Motorized Turntable | |
| Heliac FSJ1-50A 1/4" Superflex Coax Cable (12 Ft.) | |