

FCC BANDEDGE RADIATED EMISSIONS DATA

CLIENT: MICROHARD SYSTEMS
EUT: MHX-2400
ANTENNA: YAGI
FREQ.: 2481.26 MHZ
POWER: 100 mW

3 METER TEST DETECTOR - PEAK DATE: 01/31/2001

FREQUENCY MHz	POLARITY		SPEC A dBuV	AF/C dB/m	AMP Gain dB	Average Factor dB	PEAK E-Field dbuV/m	Average Limit dBuV/m	MARGIN dB	CONDITION
	H	V								
2,483.51	H		14.00	34.00	0.00	0.00	48.00	54.00	6.00	PASS
2,483.51		V	13.00	34.00	0.00	0.00	47.00	54.00	7.00	PASS

CLIENT: MICROHARD SYSTEMS
EUT: MHX-2400
ANTENNA: 6dBi OMNI
FREQ.: 2481.26 MHZ
POWER: 1000 mW

3 METER TEST DETECTOR - PEAK DATE: 01/31/2001

FREQUENCY MHz	POLARITY		SPEC A dBuV	AF/C dB/m	AMP Gain dB	Average Factor dB	PEAK E-Field dbuV/m	Average Limit dBuV/m	MARGIN dB	CONDITION
	H	V								
2,483.51	H		13.00	34.00	0.00	0.00	47.00	54.00	7.00	PASS
2,483.51		V	12.00	34.00	0.00	0.00	46.00	54.00	8.00	PASS