



# RF Exposure Evaluation Declaration

Product Name : MiniPCI BG 1W 2.4GHz  
Model No. : XBG24-30  
FCC ID : NS912XBG24-30  
IC : 3143A-12XBG2430

Applicant : Microhard Systems Inc.

Address : 150 Country Hills Landing NW Calgary Alberta Canada  
T3K 5P3

Date of Receipt : 29/03/2012  
Issued Date : 06/04/2012  
Report No. : 123S103R-RF-US  
Report Version : V1.1

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

# Test Report Certification

Issued Date : 06/04/2012

Report No. : 123S103R-RF-US



Product Name : MiniPCI BG 1W 2.4GHz  
 Applicant : Microhard Systems Inc.  
 Address : 150 Country Hills Landing NW Calgary Alberta Canada  
 T3K 5P3  
 Manufacturer : Microhard Systems Inc.  
 Address : 150 Country Hills Landing NW Calgary Alberta Canada  
 T3K 5P3  
 Model No. : XBG24-30  
 FCC ID : NS912XBG24-30  
 IC : 3143A-12XBG2430  
 EUT Voltage : DC 3.3V  
 Trade Name : Microhard  
 Applicable Standard : FCC OET 65  
 Test Result : Complied  
 Performed Location : Suzhou EMC Laboratory  
 No.99 Hongye Rd., Suzhou Industrial Park Loufeng  
 Hi-Tech Development Zone., Suzhou, China  
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098  
 FCC Registration Number: 800392; IC Lab Code: 4075B

Documented By : Alice Ni  
 (Engineering ADM: Alice Ni)  
 Reviewed By : Jame Yuan  
 (Senior Engineer: Jame Yuan)  
 Approved By : Marlin Chen  
 (Engineering Manager: Marlin Chen)

**Laboratory Information**

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

<b>Taiwan R.O.C.</b>	<b>:</b>	<b>BSMI, NCC, TAF</b>
<b>Germany</b>	<b>:</b>	<b>TUV Rheinland</b>
<b>Norway</b>	<b>:</b>	<b>Nemko, DNV</b>
<b>USA</b>	<b>:</b>	<b>FCC, NVLAP</b>
<b>Japan</b>	<b>:</b>	<b>VCCI</b>
<b>China</b>	<b>:</b>	<b>CNAS</b>

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site :<http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site :  
<http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

**HsinChu Testing Laboratory :**

No.75-2, 3rd Lin, Wangye Keng, Yongxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.  
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : [service@quietek.com](mailto:service@quietek.com)

**LinKou Testing Laboratory :**

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.  
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : [service@quietek.com](mailto:service@quietek.com)

**Suzhou Testing Laboratory :**

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China  
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : [service@quietek.com](mailto:service@quietek.com)

**1. RF Exposure Evaluation**

**1.1. Limits**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

**LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
<b>(A) Limits for Occupational/ Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
<b>(B) Limits for General Population/ Uncontrolled Exposures</b>				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

**Friis Formula**

Friis transmission formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

## 1.3. Test Result of RF Exposure Evaluation

Product	:	MiniPCI BG 1W 2.4GHz
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit by 802.11b

### Antenna Gain:

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0dBi or 1.58 in linear scale.

### Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
01	2412.00	711.2135	0.2242
06	2437.00	763.8358	0.2408
11	2462.00	731.1391	0.2305

Note: This copy report was based on Quietek report No: 089S060.

Product	:	MiniPCI BG 1W 2.4GHz
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-4
Test Mode	:	Mode 2: Transmit by 802.11g

**Antenna Gain:**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0dBi or 1.58 in linear scale.

**Output Power Into Antenna & RF Exposure Evaluation Distance:**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
01	2412.00	645.6542	0.2036
06	2437.00	855.0667	0.2696
11	2462.00	726.1060	0.2289

Note: This copy report was based on Quietek report No: 089S060.