

InterLab®

RF Exposure and Maximum ERP/EIRP Assessment

For

TOBY-L201 UMTS/HSPA/LTE Data Module

FCC ID XPYTOBYL201

IC: 8595A-TOBYL201

Assessment Reference: MDE_UBLOX_1502_MPEf rev2

Test Laboratory:

7Layers AG
Borsigstrasse 11
40880 Ratingen
Germany



Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7 layers AG
Borsigstrasse 11
40880 Ratingen, Germany
Phone: +49 (0) 2102 749 0
Fax: +49 (0) 2102 749 350
www.7Layers.com

Aufsichtsratsvorsitzender •
Chairman of the Supervisory Board:
Peter Mertel
Vorstand • Board:
Dr. H. Ansorge

Registergericht • registered in:
Düsseldorf, HRB 44096
USt-IdNr • VAT No.:
DE 203159652
TAX No. 147/5869/0385
A Bureau Veritas Group Company

Table of Contents

0	Summary	3
0.1	Technical Report Summary	3
1	Administrative Data	4
1.1	Testing Laboratory	4
1.2	Project Data	4
1.3	Applicant Data	4
1.4	Manufacturer Data	4
2	Test object Data	5
2.1	General EUT Description	5
2.2	EUT Main components	5
2.3	Ancillary Equipment	5
2.4	Auxiliary Equipment	6
2.5	Operating Modes	7
3	Evaluation Results	8
3.1	Maximum ERP / EIRP	8
3.2	RF Exposure Evaluation for Module	9
3.3	RF Exposure Evaluation for multiple transmitters in co-location	11

0 Summary

0.1 Technical Report Summary

Type of Report

RF Exposure and Maximum ERP/EIRP Assessment for a UMTS/LTE radio module. Including RF Exposure for use with co-located radios on generic host device.

Applicable FCC Rules

For RF Exposure:

OET Bulletin 65 Edition 97-01 August 1997

FCC 47 CFR §1.1307

FCC 47 CFR §1.1310

RSS-102 Issue 4 – March 2010

For Maximum ERP/EIRP:

FCC 47 CFR §22.913

IC SRSP-503 Issue 7, September 2008

FCC 47 CFR §24.232

IC SRSP-510 Issue 5, February 2009

FCC 47 CFR §27.50(d)

RSS-139, Issue 2 / SRSP-513

Report version control			
Version	Release date	Changes	Version validity
000	29.05.2015	Initial version	Not Valid
001	03.06.2015	Applied IC RSS-102 Issue 5 limits for RF Exposure	Not Valid
002	09.06.2015	WLAN and BT Seq/Slin values updated	Valid

Responsible for
Accreditation Scope:



Responsible
for Report:



1 Administrative Data

1.1 Testing Laboratory

Company Name: 7Layers AG
Address Borsigstr. 11
40880 Ratingen
Germany

This facility has been fully described in a report submitted to the FCC and accepted under the registration number 96716.

The test facility is also accredited by the following accreditation organisation:
Laboratory accreditation no.: DAKKS D-PL-12140-01-01

Responsible for Accreditation Scope: Dipl.-Ing. Bernhard Retka
Dipl.-Ing. Robert Machulec
Dipl.-Ing. Andreas Petz
Dipl.-Ing. Marco Kullik

Report Template Version: 2014-05-15

1.2 Project Data

Responsible for assessment and report: Mr. Andreas Tübel
Date of Report: 2015-05-29

1.3 Applicant Data

Company Name: u-blox AG
Address: Zürcherstrasse 68,
CH-8800 Thalwil
Switzerland
Contact Person: Giulio Comar

1.4 Manufacturer Data

Company Name: please see applicant data
Address:
Contact Person:

2 Test object Data

2.1 General EUT Description

Equipment under Test	UMTS/HSPA/LTE Data Module
Type Designation:	TOBY-L201
Kind of Device: GPRS/EDGE MSC	UMTS/LTE Data Module
GPRS Multi-slot class	12
FCC ID:	XPYTOBYL201
IC Number:	8595A-TOBYL201

General product description:

The EUT is Cellular radio module supporting WCDMA/HSDPA/HSUPA/LTE

2.2 EUT Main components

Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status
EUT A (Code: DE1015014aa01)	UMTS/LTE Module	TOBY-L201	358502060012807	218A02	09.81
EUT D (Code: DE1015014ae02)	UMTS/LTE Module	TOBY-L201	358502060012930	218A02	09.82
EUT E (Code: DE1015014ba04)	UMTS/LTE Module	TOBY-L201	358502060016972	218A03	09.84

Remark: EUT A is equipped with a temporary antenna connector. The Module is not sold with a predefined antenna.

NOTE: The short description is used to simplify the identification of the EUT in this test report.

2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	HW Status	SW Status	Serial no.	FCC ID
AE 1	AC/DC converter	UUX324-1215	-	-	E09-0291981	-
AE 2	Evaluation test board	EVB-WL3	NO_EVK_CS_191A00	-	-	-

2.4 Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
N/A						-

2.5 Operating Modes

This chapter describes the operating modes of the EUTs used for testing.

Op. Mode	Description of Operating Modes	Remarks
Op-mode 1	EUT transmitting in standalone configuration	Antenna-to-person distance > 20cm
Op-mode 2	EUT transmitting in the 850 MHz Band simultaneously with a generic Bluetooth radio.	Antenna-to-person distance > 20cm
Op-mode 3	EUT transmitting in the 1900 MHz Band simultaneously with a generic Bluetooth radio.	Antenna-to-person distance > 20cm
Op-mode 4	EUT transmitting in the 850 MHz Band simultaneously with a generic WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 5	EUT transmitting in the 1900 MHz Band simultaneously with a generic WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 6	EUT transmitting in the 850 MHz Band simultaneously with a generic Bluetooth radio and WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 7	EUT transmitting in the 1900 MHz Band simultaneously with a generic Bluetooth radio and WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 8	EUT transmitting in the 700 MHz Band simultaneously with a generic Bluetooth radio.	Antenna-to-person distance > 20cm
Op-mode 9	EUT transmitting in the 700 MHz Band simultaneously with a generic WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 10	EUT transmitting in the 700 MHz Band simultaneously with a generic Bluetooth radio and WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 11	EUT transmitting in the 1700 MHz Band simultaneously with a generic Bluetooth radio.	Antenna-to-person distance > 20cm
Op-mode 12	EUT transmitting in the 1700 MHz Band simultaneously with a generic WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 13	EUT transmitting in the 1700 MHz Band simultaneously with a generic Bluetooth radio and WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 14	EUT transmitting in the 750 MHz Band simultaneously with a generic Bluetooth radio.	Antenna-to-person distance > 20cm
Op-mode 15	EUT transmitting in the 750 MHz Band simultaneously with a generic WLAN radio.	Antenna-to-person distance > 20cm
Op-mode 16	EUT transmitting in the 750 MHz Band simultaneously with a generic Bluetooth radio and WLAN radio.	Antenna-to-person distance > 20cm

3 Evaluation Results

3.1 Maximum ERP / EIRP

Standard	Frequency Band
FCC 47 CFR §22.913 IC RSS-132, Issue 3	(850MHZ GSM/GPRS) (FDD5 WCDMA/HSUPA/HSDPA/LTE)
FCC 47 CFR §24.232 IC RSS-133 Issue 6	(1900MHZ GSM/GPRS) (FDD2 WCDMA/HSUPA/HSDPA/LTE)
FCC 47 CFR §27.50(d) RSS-139, Issue 2 / SRSP-513	(FDD4,7,17 UMTS/LTE)

3.1.1 Test Limits

For the 850MHz band, FCC §22.913 states that the maximum ERP of this device shall not exceed 7 Watts. IC SRSP-503 Issue 7, states that this device shall not exceed a maximum EIRP of 11.5 Watts
For the purposes of this test report, the 7 Watt ERP limit stipulated in FCC §22.913 has been converted to an equivalent ERIP value of 11.5 Watts.

For all other limits, refer to the values stipulated in the corresponding tables.

3.1.2 Test Protocol

Band	Mode	Duty Cycle (%)	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Freq of highest power	FCC / IC EIRP limit (mW)	Maximum antenna gain to meet EIRP Limit (dBi)
FDD 2	UMTS	100.0%	1850 - 1907.6	24.5	281.8382931	1907.60	2000	8.5
FDD 5	UMTS	100.0%	824 - 846.6	24.5	281.8382931	836.00	11484	16.1
eFDD 2	LTE	100.0%	1850-1910	22.58	181.1340093	1902.50	2000	10.4
eFDD 4	LTE	100.0%	1710-1755	23.24	210.862815	1732.50	1000	6.8
eFDD 5	LTE	100.0%	824 - 849	22.99	199.0673339	825.50	11484	17.6
eFDD13	LTE	100.0%	777-787	22.25	167.8804018	784.50	4920	14.7
eFDD 17	LTE	100.0%	704-716	23.05	201.8366364	710.00	4920	13.9

3.1.3 Conclusion

All gains in (dBi)					
Band	Max gain to be used to comply with EIRP Limits	Max gain to be used to comply with FCC MPE Limits	Max gain to be used to comply with IC MPE Limits	Maximum gain to be compliant with all limits	
FDD 2	8.5	12.5	9.1	8.5	
FDD 5	16.1	10.0	6.7	6.7	
eFDD 2	10.4	13.0	9.6	8.5	
eFDD 4	6.8	12.7	9.0	6.8	
eFDD 5	17.6	10.4	7.1	7.1	
eFDD13	14.7	10.2	6.9	6.9	
eFDD 17	13.9	9.8	6.7	6.7	

3.2 RF Exposure Evaluation for Module

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

3.2.1 Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Limits specified per RSS-102, Issue 5.

Frequency range (MHz)	Power density (W/m ²)	Power density (mW/cm ²)
300 – 6000	0.02619 $f^{0.6834}$	mW/cm ² = W/m ² * 0.1

Equation OET bulletin 65, page 18, edition 97-01:
$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where:

- S = power density
- P = power input to the antenna
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the centre of radiation of the antenna

3.2.2 Test Protocol

Maximum antenna gain to comply with MPE limits for FCC									
Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm ²)	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
FDD 2	UMTS	100.0%	1907.6	24.5	281.84	281.84	1.0000	12.5	20
FDD 5	UMTS	100.0%	836.0	24.5	281.84	281.84	0.5573	10.0	20
eFDD 2	LTE	100.0%	1902.5	24	251.19	251.19	1.0000	13.0	20
eFDD 4	LTE	100.0%	1732.5	24.3	269.15	269.15	1.0000	12.7	20
eFDD 5	LTE	100.0%	825.5	24	251.19	251.19	0.5503	10.4	20
eFDD13	LTE	100.0%	777.0	24	251.19	251.19	0.5180	10.2	20
eFDD 17	LTE	100.0%	710.0	24	251.19	251.19	0.4733	9.8	20

* Conducted output power values bases on "Tune-up" information provided by manufacturer.

Maximum antenna gain to comply with MPE limits for Industry Canada									
Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm ²)	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
FDD 2	UMTS	100.0%	1907.6	24.5	281.84	281.84	0.4571	9.1	20
FDD 5	UMTS	100.0%	836.0	24.5	281.84	281.84	0.2601	6.7	20
eFDD 2	LTE	100.0%	1902.5	24.0	251.19	251.19	0.4563	9.6	20
eFDD 4	LTE	100.0%	1732.5	24.3	269.15	269.15	0.4280	9.0	20
eFDD 5	LTE	100.0%	825.5	24.0	251.19	251.19	0.2579	7.1	20
eFDD13	LTE	100.0%	777.0	24.0	251.19	251.19	0.2474	6.9	20
eFDD 17	LTE	100.0%	710.0	24.0	251.19	251.19	0.2326	6.7	20

* Conducted output power values bases on "Tune-up" information provided by manufacturer.

3.2.3 Conclusion

Band	Max gain for FCC MPE Limits	Max gain for Industry Canada MPE Limits	Maximum gain to be compliant with all limits
FDD 2	12.5	9.1	9.1
FDD 5	10.0	6.7	6.7
eFDD 2	13.0	9.6	9.6
eFDD 4	12.7	9.0	9.0
eFDD 5	10.4	7.1	7.1
eFDD13	10.2	6.9	6.9
eFDD 17	9.8	6.7	6.7

3.3 RF Exposure Evaluation for multiple transmitters in co-location

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

3.3.1 Co-Location Considerations

The calculation below is used to consider situations in which simultaneous exposure to fields of different frequencies occur. The calculation is performed by the sum of each relative exposure for each equipment according to the following criteria.

$$\sum_{1}^N \frac{S_{eqn}}{S_{Limn}} = \frac{S_{eq1}}{S_{Lim1}} + \frac{S_{eq2}}{S_{Lim2}} + \dots + \frac{S_{eqN}}{S_{LimN}} \leq 1$$

Where:

S_{eq} is the power density of the electromagnetic field at a given distance by a specific transmitter and a defined frequency.

S_{lin} is the MPE limit for the frequency being evaluated.

3.3.2 Assumptions

1. Primary transmitter does not support power reduction for multiple time slots on the uplink.
2. Antenna separation from module to human body is ≥ 20 cm.
3. Separation distance between co-located transmitting antennas is 0cm.
4. Hypothetical Bluetooth radio is assumed to have an output power of 9.5dBm and an antenna gain of 4dBi.
5. Hypothetical WLAN radio is assumed to have an output power of 19dBm and an antenna gain of 5dBi.

3.3.3 Test Protocol

The below table is to determine the MPE values using the maximum gain values obtained in section 3.3.4 of this document.

OP mode-1 – FOR FCC ONLY

Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Equivalent conducted output power (mW)	MPE Limit (mW/cm ²)	MPE Value using Max gain	Separation distance (cm)	Verdict
FDD 2	UMTS	100.0%	1907.6	24.5	281.84	1.0000	0.2862	20	Pass
FDD 5	UMTS	100.0%	836.0	24.5	281.84	0.5573	0.4808	20	Pass
eFDD 2	LTE	100.0%	1902.5	24	251.19	1.0000	0.2551	20	Pass
eFDD 4	LTE	100.0%	1732.5	24.3	269.15	1.0000	0.1612	20	Pass
eFDD 5	LTE	100.0%	825.5	24	251.19	0.5503	0.4285	20	Pass
eFDD13	LTE	100.0%	777.0	24	251.19	0.5180	0.4742	20	Pass
eFDD 17	LTE	100.0%	710.0	24	251.19	0.4733	0.3890	20	Pass

* Conducted output power values bases on "Tune-up" information provided by manufacturer.

OP mode-1 – FOR Industry Canada ONLY

Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Equivalent conducted output power (mW)	MPE Limit (mW/cm ²)	MPE Value using Max gain	Separation distance (cm)	Verdict
FDD 2	UMTS	100.0%	1907.6	24.5	281.84	0.4571	0.2862	20	PASS
FDD 5	UMTS	100.0%	836.6	24.5	281.84	0.2602	0.1532	20	PASS
eFDD 2	LTE	100.0%	1902.5	24	251.19	0.4563	0.2551	20	PASS
eFDD 4	LTE	100.0%	1732.5	24.3	269.15	0.4280	0.1612	20	PASS
eFDD 5	LTE	100.0%	825.5	24	251.19	0.2579	0.1365	20	PASS
eFDD13	LTE	100.0%	777.0	24	251.19	0.2474	0.1467	20	PASS
eFDD 17	LTE	100.0%	710.0	24	251.19	0.2326	0.0963	20	PASS

MPE Values for the generic Bluetooth and WLAN radios operating alone. These values are used to calculate the relative exposure for simultaneous transmission with the primary transmitter.

MPE Calculation for Single Transmitter installed in Generic host for FCC								
Radio type	Duty Cycle	ERP (mW)	ERP Equivalent (mW)	MPE Limit (mW/cm ²)	Maximum antenna gain	Power density	Separation distance (cm)	Verdict
Bluetooth	64%	8.91	3.72	1.0000	4.0	0.0019	20	Pass
WLAN	100%	79.43	79.43	1.0000	5.0	0.0500	20	Pass

MPE Calculation for Single Transmitter installed in Generic host for Industry Canada								
Radio type	Duty Cycle	ERP (mW)	ERP Equivalent (mW)	MPE Limit (mW/cm ²)	Maximum antenna gain	Power density	Separation distance (cm)	Verdict
Bluetooth	64%	8.91	3.72	0.54	4.00	0.0019	20.00	Pass
WLAN	100%	79.43	79.43	0.54	5.00	0.0500	20.00	Pass

Below are the relative exposure values for the primary, secondary and combined primary + secondary transmitters for both FCC and Industry Canada limits.

OP mode-1

Relative exposure for Primary Transmitter for FCC							
OP-Mode	Mode	Output power	Frequency (MHZ)	S _{eq}	S _{lin} (mW/cm ²)	S _{eq} ----- S _{lin}	Verdict
FDD 2	UMTS	281.8383	1907.6	0.3969	1.0000	0.39694516	Pass
FDD 5	UMTS	281.8383	836.0	0.5233	0.5573	0.93889169	Pass
eFDD 2	LTE	251.1886	1902.5	0.3538	1.0000	0.35377775	Pass
eFDD 4	LTE	269.1535	1732.5	0.2563	1.0000	0.25628932	Pass
eFDD 5	LTE	251.1886	825.5	0.4664	0.5503	0.84743168	Pass
eFDD13	LTE	251.1886	777.0	0.4883	0.5180	0.94275914	Pass

eFDD 17	LTE	251.1886	710.0	0.4454	0.4733	0.94094323	Pass
---------	-----	----------	-------	--------	--------	------------	------

Relative exposure for Primary Transmitter for Industry Canada							
OP-Mode	Mode	Output power	Frequency (MHz)	S_{eq}	S_{lin} (mW/cm ²)	$\frac{S_{eq}}{S_{Lin}}$	Verdict
FDD 2	UMTS	281.8383	1907.6	0.3969	0.4571	0.868380341	Pass
FDD 5	UMTS	281.8383	836.0	0.2337	0.2601	0.898585162	Pass
eFDD 2	LTE	251.1886	1902.5	0.3538	0.4563	0.775362043	Pass
eFDD 4	LTE	269.1535	1732.5	0.2563	0.4280	0.598805414	Pass
eFDD 5	LTE	251.1886	825.5	0.2083	0.2579	0.807812487	Pass
eFDD13	LTE	251.1886	777.0	0.2232	0.2474	0.902155267	Pass
eFDD 17	LTE	251.1886	710.0	0.1425	0.2326	0.612413926	Pass

Relative exposure for Secondary transmitter for FCC					
OP-Mode	Transmitter	Output power	S_{eq} (mW/cm ²)	S_{lin} (mW/cm ²)	$\frac{S_{eq}}{S_{Lin}}$
2	Bluetooth	3.72	0.0019	1.0000	0.001856652
3	WLAN	79.43	0.0500	1.0000	0.049972435
4	Bluetooth	3.72	0.0019	1.0000	0.001856652
	WLAN	79.43	0.0500	1.0000	0.049972435

Relative exposure for Secondary transmitter for Industry Canada					
OP-Mode	Transmitter	Output power	S_{eq} (mW/cm ²)	S_{lin} (mW/cm ²)	$\frac{S_{eq}}{S_{Lin}}$
2	Bluetooth	3.72	0.0019	0.5410	0.003431873
3	WLAN	79.43	0.0500	0.5410	0.092370053
4	Bluetooth	3.72	0.0019	0.5410	0.003431873
	WLAN	79.43	0.0500	0.5410	0.092370053

Simultaneous exposure of Primary and Secondary transmitter installed in generic host device for FCC					
OP-Mode	Transmitter	Frequency (MHZ)	Maximum S_{eq} / S_{Lin}	Maximum $S_{pri} / S_{lim_pri} + S_{sec} / S_{lin_Sec}$	Compliance Maximum $(S_{pri} / S_{lim_pri}) + (S_{sec} / S_{lin_Sec}) < 1$
2	Bluetooth	2441	0.0019	0.9407	Compliant
	TOBY L201	836	0.9389		
3	Bluetooth	2441	0.0019	0.3988	Compliant
	TOBY L201	1907.6	0.3969		
4	WLAN	2437	0.0500	0.9889	Compliant
	TOBY L201	836	0.9389		
5	WLAN	2437	0.0500	0.4469	Compliant
	TOBY L201	1907.6	0.3969		
6	Bluetooth	2441	0.0019	0.9907	Compliant
	WLAN	2437	0.0500		
	TOBY L201	836	0.9389		
7	Bluetooth	2441	0.0019	0.4488	Compliant
	WLAN	2437	0.0500		
	TOBY L201	1907.6	0.3969		
8	Bluetooth	2441	0.0019	0.9428	Compliant
	TOBY L201	710	0.9409		
9	WLAN	2437	0.0500	0.9909	Compliant
	TOBY L201	710	0.9409		
10	Bluetooth	2441	0.0019	0.9928	Compliant
	WLAN	2437	0.0500		
	TOBY L201	710	0.9409		
11	Bluetooth	2441	0.0019	0.2581	Compliant
	TOBY L201	1740	0.2563		
12	WLAN	2437	0.0500	0.3063	Compliant
	TOBY L201	1740	0.2563		
13	Bluetooth	2441	0.0019	0.3081	Compliant
	WLAN	2437	0.0500		
	TOBY L201	1740	0.2563		
14	Bluetooth	2441	0.0019	0.9446	Compliant
	TOBY L201	777	0.9428		
15	WLAN	2437	0.0019	0.9446	Compliant
	TOBY L201	777	0.9428		
16	Bluetooth	2441	0.0019	0.9946	Compliant
	WLAN	2437	0.0500		
	TOBY L201	777	0.9428		

P

Simultaneous exposure of Primary and Secondary transmitter installed in generic host device for Industry Canada					
OP-Mode	Transmitter	Frequency (MHZ)	Maximum S_{eq} / S_{Lin}	Maximum $S_{pri} / S_{lim_pri} + S_{sec} / S_{lin_Sec}$	Compliance Maximum $(S_{pri} / S_{lim_pri}) + (S_{sec} / S_{lin_Sec}) < 1$
2	Bluetooth	2441	0.0034	0.9020	Compliant
	TOBY L201	836	0.8986		
3	Bluetooth	2441	0.0034	0.8718	Compliant
	TOBY L201	1907.6	0.8684		
4	WLAN	2437	0.0924	0.9910	Compliant
	TOBY L201	836	0.8986		
5	WLAN	2437	0.0924	0.9608	Compliant
	TOBY L201	1907.6	0.8684		
6	Bluetooth	2441	0.0034	0.9944	Compliant
	WLAN	2437	0.0924		
	TOBY L201	836	0.8986		
7	Bluetooth	2441	0.0034	0.9642	Compliant
	WLAN	2437	0.0924		
	TOBY L201	1907.6	0.8684		
8	Bluetooth	2441	0.0034	0.6158	Compliant
	TOBY L201	710	0.6124		
9	WLAN	2437	0.0924	0.7048	Compliant
	TOBY L201	710	0.6124		
10	Bluetooth	2441	0.0034	0.7082	Compliant
	WLAN	2437	0.0924		
	TOBY L201	710	0.6124		
11	Bluetooth	2441	0.0034	0.6022	Compliant
	TOBY L201	1740	0.5988		
12	WLAN	2437	0.0924	0.6912	Compliant
	TOBY L201	1740	0.5988		
13	Bluetooth	2441	0.0034	0.6946	Compliant
	WLAN	2437	0.0924		
	TOBY L201	1740	0.5988		
14	Bluetooth	2441	0.0034	0.9056	Compliant
	TOBY L201	777	0.9022		
15	WLAN	2437	0.0924	0.9945	Compliant
	TOBY L201	777	0.9022		
16	Bluetooth	2441	0.0034	0.9980	Compliant
	WLAN	2437	0.0924		
	TOBY L201	777	0.9022		

When operating the primary transmitter simultaneously with a generic Bluetooth and WLAN radio, the following antenna gains can be used with the module TOBY-L201 while still complying with the exposure limits.

Band	dBi (For FCC)	dBi (For Industry Canada)
700	9.5	4.55
750	9.9	6.5
850	9.7	6.2
1700	6.8	6.8
1900	8.5	8.5