

RF Exposure / RF Technical Brief

BABT TCB

Balfour House,
Churchfield Road,
Walton-on-Thames,
Surrey, KT12 2TD

ATTN: Reviewing Engineer

RF exposure information for the equipment VIP4G (FCC ID: NS9VIP4GABGN20, IC: 3143A-VIP4GABGN20)

1. Introduction:

The device **VIP4G** (FCC ID: **NS9VIP4GABGN20**, IC: **3143A-VIP4GABGN20**) is designed to be used only for fixed and mobile applications.

This product integrates a **Novatel Wireless' Expedite® E371** PCI Express Mini Card (FCC ID: **PKRNVWE371**, IC: **3229A-E371**). The Novatel Wireless' Expedite® E371 PCI Express Mini Card is granted with a modular approval for mobile applications and the highest antenna gains allowed for use with this module for mobile RF exposure conditions are 3.5 dBi (850 MHz), 5.0 dBi (700 MHz), 5.0 dBi (1700 MHz), and 3.0 dBi (1900 MHz).

The antenna(s) used for **VIP4G** transmitter and the antenna used for **Novatel Wireless' Expedite® E371** PCI Express Mini Card are co-located and can transmit simultaneously.

All the antennas must be installed to provide a separation distance of at least 20 cm from all the persons.

2. MPE limits:

The table below is excerpted from RSS-102, Issue 4, 4.2, titled "RF Limits for Devices used by the General Public":

Frequency Range (MHz)	Power density (W/m ²)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	f (MHz)/150	f (MHz) /1500	6
1500 – 15000	10	1.0	6

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure:

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	f (MHz) /1500	30
1500 – 100.000	1.0	30

3. Compliance criteria:

Power density of individual transmitters is calculated using the equation:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

3.1. Standalone compliance criteria:

Power density must be lower than the MPE limits stated in item 2.

3.2. Simultaneous transmission compliance criteria

The sum of the MPE ratios (Power density/MPE limit) for all simultaneous transmitting antennas incorporated in the device based on the calculated power density is ≤ 1.0 .

4. Compliance calculations:

4.1. Standalone transmission - Novatel Wireless' Expedite® E371 PCI Express Mini Card

Generation	Frequency band	Frequency range (MHz)	Mode	Average power (dBm)	Antenna gain (dBi)	Total power (W)	Duty Cycle (%)	Evaluation distance (cm)	Power Density (mW/cm ²)	FCC-IC MPE limit (mW/cm ²)	MPE ratio (Power Density / FCC-IC MPE limit)
2G	GPRS 850	824,2 - 848,8	GPRS	32,50	3,5	3,98	25%	20	0,198	0,55	0,36
2G	EGPRS 850	824,2 - 848,8	EGPRS	26,04	3,5	0,90	50%	20	0,089	0,55	0,16
2G	GPRS 1900	1850,2 - 1909,8	GPRS	29,00	3	1,58	25%	20	0,079	1,00	0,08
2G	EGPRS 1900	1850,2 - 1909,8	EGPRS	25,00	3	0,63	50%	20	0,063	1,00	0,06
3G	FDD IV	1712,4 - 1752,6	UMTS, Rel 99	24,05	5	0,80	100%	20	0,160	1,00	0,16
3G	FDD IV	1712,4 - 1752,6	UMTS, HSDPA	23,90	5	0,78	100%	20	0,154	1,00	0,15
3G	FDD V	826,4 - 846,0	UMTS, Rel 99	24,33	3,5	0,61	100%	20	0,121	0,55	0,22
3G	FDD V	826,4 - 846,0	UMTS, HSDPA	24,35	3,5	0,61	100%	20	0,121	0,55	0,22
3G	FDD II	1852,4 - 1907,6	UMTS, Rel 99	23,53	3	0,45	100%	20	0,089	1,00	0,09
3G	FDD II	1852,4 - 1907,6	UMTS, HSDPA	23,70	3	0,47	100%	20	0,093	1,00	0,09
4G (LTE)	FDD 17	706,5 - 713,5	5MHz, QPSK	23,80	5	0,76	100%	20	0,151	0,47	0,32
4G (LTE)	FDD 17	706,5 - 713,5	5MHz, 16QAM	22,46	5	0,56	100%	20	0,111	0,47	0,24
4G (LTE)	FDD 17	709,0 - 711,0	10MHz, QPSK	23,85	5	0,77	100%	20	0,153	0,47	0,32
4G (LTE)	FDD 17	709,0 - 711,0	10MHz, 16QAM	23,54	5	0,71	100%	20	0,142	0,47	0,30
4G (LTE)	FDD 4	1710,7 - 1754,3	1.4MHz, QPSK	23,81	5	0,76	100%	20	0,151	1,00	0,15
4G (LTE)	FDD 4	1710,7 - 1754,3	1.4MHz, 16QAM	23,16	5	0,65	100%	20	0,130	1,00	0,13
4G (LTE)	FDD 4	1711,5 - 1753,5	3MHz, QPSK	23,90	5	0,78	100%	20	0,154	1,00	0,15
4G (LTE)	FDD 4	1711,5 - 1753,5	3MHz, 16QAM	22,79	5	0,60	100%	20	0,120	1,00	0,12
4G (LTE)	FDD 4	1712,5 - 1752,5	5MHz, QPSK	23,55	5	0,72	100%	20	0,142	1,00	0,14
4G (LTE)	FDD 4	1712,5 - 1752,5	5MHz, 16QAM	22,68	5	0,59	100%	20	0,117	1,00	0,12
4G (LTE)	FDD 4	1715,0 - 1750,0	10MHz, QPSK	23,75	5	0,75	100%	20	0,149	1,00	0,15
4G (LTE)	FDD 4	1715,0 - 1750,0	10MHz, 16QAM	22,39	5	0,55	100%	20	0,109	1,00	0,11
4G (LTE)	FDD 4	1717,5 - 1747,5	15MHz, QPSK	23,53	5	0,71	100%	20	0,142	1,00	0,14
4G (LTE)	FDD 4	1717,5 - 1747,5	15MHz, 16QAM	23,02	5	0,63	100%	20	0,126	1,00	0,13
4G (LTE)	FDD 4	1720,0 - 1745,0	20MHz, QPSK	23,53	5	0,71	100%	20	0,142	1,00	0,14
4G (LTE)	FDD 4	1720,0 - 1745,0	20MHz, 16QAM	22,87	5	0,61	100%	20	0,122	1,00	0,12

Maximum MPE ratio: 0,36

4.2. Standalone transmission - VIP4G

Frequency band	Frequency range (MHz)	Mode	Average power (dBm)	Antenna gain (dBi)	Total power (W)	Duty Cycle (%)	Evaluation distance (cm)	Power Density (mW/cm ²)	FCC-IC MPE limit (mW/cm ²)	MPE ratio (Power Density / FCC-IC MPE limit)
2,4 GHz	2412 - 2462	802.11b	15,91	2	0,06	100%	20	0,012	1,00	0,01
2,4 GHz	2412 - 2462	802.11g	14,51	2	0,04	100%	20	0,009	1,00	0,01
2,4 GHz	2412 - 2462	802.11n - 20 MHz	15,31	2	0,05	100%	20	0,011	1,00	0,01
2,4 GHz	2422 - 2452	802.11n - 40 MHz	13,28	2	0,03	100%	20	0,007	1,00	0,01
5,75 GHz	5745 - 5825	802.11a	16,61	2	0,07	100%	20	0,014	1,00	0,01
5,75 GHz	5745 - 5825	802.11n - 20 MHz	18,41	2	0,11	100%	20	0,022	1,00	0,02
5,75 GHz	5755 - 5795	802.11n - 40 MHz	16,61	2	0,07	100%	20	0,014	1,00	0,01

Maximum MPE ratio: 0,02

4.3. Simultaneous transmission

Maximum MPE ratio of Novatel Wireless' Expedite® E371 PCI Express Mini Card: 0,36

+

Maximum MPE ratio of VIP4G: 0,02

= 0,38 \leq 1

Signed on behalf of Microhard Systems Inc in Calgary on Feb. 19, 2013



Hany Shenouda / President
 Tel/Fax: +1 403 248-0028 / +1 403 248-2762
 Email: Shenouda@microhardcorp.com
 Company: Microhard Systems Inc
 Address: 150 Country Hills Landing N.W.
 Calgary Alberta T3K 5P3 Canada