

Nemko Test Report No.:

2L0101RUS1

Applicant:

Communication Components
89 Leuning Street 299 Forest Avenue
Hackensack, NJ 07606

Equipment Under Test:

DAB-1819-100

In Accordance With:

FCC Part 24, Subpart E
Broadband PCS Repeaters

Tested By:

Nemko Dallas Inc.
802 N. Kealy
Lewisville, Texas 75057-3136



Authorized By:

Tom Tidwell, RF Group Manager

Date:

3/29/02

Total Number of Pages:

33

Table of Contents

Section 1. Summary of Test Results3

Section 2. General Equipment Specification5

Section 3. RF Power Output.....7

Section 4. Occupied Bandwidth9

Section 5. Spurious Emissions at Antenna Terminals..... 12

Section 6. Field Strength of Spurious..... 21

Section 7. Test Equipment List..... 24

ANNEX A - TEST DETAILS 25

ANNEX B - TEST DIAGRAMS..... 31

EQUIPMENT: DAB-1819-100

Section 1. Summary of Test Results

Manufacturer: Communication Components, Inc.

Model No.: DAB-1819-100

Serial No.: None

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 24, Subpart E.

New Submission

Production Unit

Class II Permissive Change

Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.: NONE

See “ Summary of Test Data”.

Nemko Dallas Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company’s employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Dallas Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

EQUIPMENT: **DAB-1819-100**

Summary Of Test Data

NAME OF TEST	PARA. NO.	SPEC.	RESULT
RF Power Output	24.232	<100W	Complies
Occupied Bandwidth (CDMA)	24.238	Input/Output	N/A
Occupied Bandwidth (GSM)	24.238	Input/Output	Complies
Occupied Bandwidth (NADC)	24.238	Input/Output	N/A
Spurious Emissions at Antenna Terminals	24.238(a)	-13 dBm	Complies
Field Strength of Spurious Emissions	24.238(a)	-13 dBm E.I.R.P.	Complies
Frequency Stability	24.235	N/A	N/A

Footnotes:

- (1) Modulation characteristics were not tested since the E.U.T. processes but does not produce a modulated waveform.
- (2) Since this is an amplifier and does not translate the rf input, frequency stability is not applicable.

Measurement uncertainty for each test configuration is expressed to 95% probability.

EQUIPMENT: **DAB-1819-100**

Section 2. General Equipment Specification


Frequency Bands:	Downlink:	<input checked="" type="checkbox"/> Block A : 1930 – 1945 MHz <input checked="" type="checkbox"/> Block D : 1945 – 1950 MHz <input checked="" type="checkbox"/> Block B : 1950 – 1965 MHz <input checked="" type="checkbox"/> Block E : 1965 – 1970 MHz <input checked="" type="checkbox"/> Block F : 1970 – 1975 MHz <input checked="" type="checkbox"/> Block C : 1975 – 1990 MHz
Frequency Bands:	Uplink:	<input type="checkbox"/> Block A : 1850 – 1865 MHz <input type="checkbox"/> Block B : 1865 – 1870 MHz <input type="checkbox"/> Block C : 1870 – 1885 MHz <input type="checkbox"/> Block D : 1885 – 1890 MHz <input type="checkbox"/> Block E : 1890 – 1895 MHz <input type="checkbox"/> Block F : 1895 – 1910 MHz
System Gain:	10 dB	
Output Impedance:	50 ohms	
	Not tested. The Uplink path is always connected with coaxial connections to a BTS.	
	Per channel: 100 W Total: 100 W	
	F1-F1	F1-F2
	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Software	Duplexer
	<input type="checkbox"/>	<input type="checkbox"/>
	Fullband	<input checked="" type="checkbox"/>
	CDMA (G7W)	GSM (GXW)
	<input type="checkbox"/>	<input checked="" type="checkbox"/>
	NADC (DXW)	<input type="checkbox"/>

EQUIPMENT: DAB-1819-100

Description of Operation

The EUT is an RF Amplifier to boost either a PCS or Cellular signal. The amplifier would be operated in an equipment rack and the antenna would be mounted on a pole or tower. The forward direction is wireless but the reverse direction is connected directly to a Base Station Transmitter via coaxial cables.

System Diagram



EQUIPMENT: DAB-1819-100

Section 3. RF Power Output

NAME OF TEST: RF Power Output	PARA. NO.: 2.1046
TESTED BY: D. Light	DATE:3/14/02

Test Results: Complies.

Measurement Data:

Frequency (MHz)	Modulation Type	Per Channel Output Power (dBm)	Composite Output Power (dBm)	Maximum Power Output Delivered to the Antenna (dBm)
1930.2*	GSM	34.7	** N/A	+33.9
1930.3	GSM	50.8	N/A	+50.0
1960	GSM	50.8	N/A	+50.0
1989.7	GSM	50.8	N/A	+50.0
1989.8*	GSM	33.6	N/A	+33.9
Intermodulation (Lower bandedge)	GSM	36.2	***39.2	+38.4
Intermodulation (Upper bandedge)	GSM	40.4	43.4	+42.6

*Power must be reduced at the bandedges to meet emission requirements. Refer to plots in Section 5 of this document.

** This is one carrier only.

***This reading was measured with two carriers at each bandedge.

Footnote – The amplifier is rated at 100 watts(+ 50 dBm) but was tested at maximum level(+50.8 dBm) to compensate for any path loss between the amplifier and antenna. There will always be a duplexer and coaxial cable between the output of the EUT and the transmit antenna. The output of the transmitter is set so that a rf output power not exceeding 100 watts is delivered to the transmit antenna.

Equipment Used: 1036-1629-1055-1064

Measurement Uncertainty: +/- 1.7 dB

Nemko Dallas

FCC PART 24, SUBPART E
BROADBAND PCS REPEATERS
PROJECT NO.: **2L0101RUS1**

EQUIPMENT: **DAB-1819-100**

EQUIPMENT: **DAB-1819-100**

Section 4. Occupied Bandwidth

NAME OF TEST: Occupied Bandwidth (GSM)	PARA. NO.: 2.1049
TESTED BY: David Light	DATE:3/14/2002

Test Results: Complies.

Test Data: See attached plot(s).

Measurement Uncertainty: +/- 1.6 dB


EQUIPMENT: DAB-1819-100

Test Data – Occupied Bandwidth



Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

Nemko Dallas, Inc.



EQUIPMENT: **DAB-1819-100**

Section 5. Spurious Emissions at Antenna Terminals

NAME OF TEST: Spurious Emissions @ Antenna Terminals	PARA. NO.: 2.1051
TESTED BY: David Light	DATE: 2/26/2002

Test Results: Complies.

Test Data: See attached plot(s).

Measurement Uncertainty: +/- 1.7 dB

EQUIPMENT: **DAB-1819-100**

Test Data – Spurious Emissions at Antenna Terminals



Nemko Dallas, Inc.

Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

Data Plot		BANDEDGE DATA																					
Page <u>1</u> of <u>6</u>		Date: <u>2/26/2002</u>		Complete <u>X</u>																			
Job No.: <u>2L0101R</u>		Temperature(°C): <u>22</u>		Preliminary: _____																			
Specification: <u>24.238</u>		Relative Humidity(%): <u>50</u>																					
Tested By: <u>David Light</u>																							
E.U.T.: <u>PCS BAND GSM BOOSTER</u>																							
Configuration: <u>TX</u>																							
Sample Number: <u>1</u>																							
Location: <u>Lab 1</u>		RBW: <u>2 kHz</u>		Measurement																			
Detector Type: <u>Peak</u>		VBW: <u>2 kHz</u>		Distance: <u>N/A</u> m																			
Test Equipment Used																							
Antenna: _____		Directional Coupler: <u>1055</u>																					
Pre-Amp: _____		Cable #1: <u>1629</u>																					
Filter: _____		Cable #2: _____																					
Receiver: <u>1036</u>		Cable #3: _____																					
Attenuator #1: <u>1064</u>		Cable #4: _____																					
Attenuator #2: _____		Mixer: _____																					
Additional equipment used: _____																							
Measurement Uncertainty: <u>+/-1.7 dB</u>																							
<table border="0"> <tr> <td></td> <td>Ref Lvl</td> <td>RBW</td> <td>2 kHz</td> <td>RF Att</td> <td>50 dB</td> </tr> <tr> <td></td> <td>60.8 dBm</td> <td>VBW</td> <td>2 kHz</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>SWT</td> <td>400 ms</td> <td>Unit</td> <td>dBm</td> </tr> </table>							Ref Lvl	RBW	2 kHz	RF Att	50 dB		60.8 dBm	VBW	2 kHz					SWT	400 ms	Unit	dBm
	Ref Lvl	RBW	2 kHz	RF Att	50 dB																		
	60.8 dBm	VBW	2 kHz																				
		SWT	400 ms	Unit	dBm																		
Date: <u>26.FEB.2002 12:08:09</u> Center <u>1.93 GHz</u> <u>62.5 kHz</u> Span <u>625 kHz</u>																							
Notes: LOWER BANDEDGE - FREQUENCY 1930.2 MHz OUTPUT POWER = 34.7 dBm																							


EQUIPMENT: DAB-1819-100

Test Data – Spurious Emissions at Antenna Terminals



Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

Nemko Dallas, Inc.




EQUIPMENT: DAB-1819-100

Test Data – Spurious Emissions at Antenna Terminals



Nemko Dallas, Inc.

Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667




EQUIPMENT: DAB-1819-100

Test Data – Spurious Emissions at Antenna Terminals



Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

Nemko Dallas, Inc.




EQUIPMENT: DAB-1819-100

Test Data – Spurious Emissions at Antenna Terminals



Nemko Dallas, Inc.

Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667




EQUIPMENT: DAB-1819-100

Test Data – Spurious Emissions at Antenna Terminals



Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

Nemko Dallas, Inc.




EQUIPMENT: DAB-1819-100

Test Data – Spurious Emissions at Antenna Terminals



Dallas Headquarters:
 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

Nemko Dallas, Inc.



EQUIPMENT: **DAB-1819-100**

Section 6. Field Strength of Spurious

NAME OF TEST: Field Strength of Spurious Emissions	PARA. NO.: 2.1051
TESTED BY: David Light	DATE: 2/26/2002

Test Results: Complies.

Test Data: See attached table.

Measurement Uncertainty: +/- 3.6 dB

EQUIPMENT: **DAB-1819-100**

Test Data - Radiated Emissions - Downlink



Nemko Dallas, Inc.

Dallas Headquarters:


802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

<u>Field Strength of Spurious Emissions</u>										
Page <u>1</u> of <u>1</u>								Complete <u>X</u>		
Job No.:	2L0101R	Date:	3/5/2002				Preliminary			
Specification:	PT 24	Temperature(°C):	22							
Tested By:	David Light	Relative Humidity(%)	50							
E.U.T.:	120 WATT AMPLIFIER									
Configuration:	TX FULL POWER INTO DUMMY LOAD									
Sample No:	1									
Location:	AC 3	RBW:	1 MHz				Measurement			
Detector Type:	Peak	VBW:	1 MHz				Distance:	3 m		
Test Equipment Used										
Antenna:	1304	Directional Coupler:								
Pre-Amp:	1016	Cable #1:	1484							
Filter:		Cable #2:	1485							
Receiver:	1464	Cable #3:								
Attenuator #1		Cable #4:								
Attenuator #2:		Mixer:								
Additional equipment used:										
Measurement Uncertainty:	+/-3.6 dB									
Frequency (MHz)	Meter Reading (dBm)	Correction Factor (dB)	Pre-Amp Gain (dB)	Substitution Antenna Gain (dBd)	Limit (dBm)	ERP (dBm)	ERP (mW)	Polarity	Comments	
3920	-37.5	35.5	33.3	8.6	-13	-26.8	0.0021	H		
5880	-37.5	37.8	32.7	9.3	-13	-23.1	0.0049	H		
7840	-35.0	41.5	33.7	9.2	-13	-18.1	0.0157	H		
9800	-33.2	43.3	36	10.3	-13	-15.6	0.0274	H		
11760	-46.5	47.0	35.5	10.5	-13	-24.6	0.0035	H		
13720	-57.3	47.7	33.3	10.6	-13	-32.4	0.0006	H		
15680	-57.0	45.5	33.2	12.9	-13	-31.8	0.0007	H		
3920	-36.7	43.3	33.3	8.6	-13	-18.1	0.0154	V		
5880	-35.3	39.8	32.7	9.3	-13	-18.9	0.0128	V		
7840	-36.0	41.8	33.7	9.2	-13	-18.7	0.0134	V		
9800	-33.2	41.8	36	10.3	-13	-17.1	0.0194	V		
11760	-49.0	42.8	35.5	10.5	-13	-31.2	0.0008	V		
<p>Notes: Scanned to the 10th harmonic All emissions within 20 dB of the limit were recorded</p>										


EQUIPMENT: **DAB-1819-100**

Photographs of Test Setup

FRONT VIEW



REAR VIEW



EQUIPMENT: **DAB-1819-100**

Section 7. Test Equipment List

Nemko ID	Description	Manufacturer Model Number	Serial Number	Calibration Date
1036	SPECTRUM ANALYZER	ROHDE & SCHWARZ FSEK30	830844/006	12/18/01
1055	DUAL DIRECTIONAL COUPLER	NARDA 3022	73393	CBU
1629	CABLE, 6 ft	MEGAPHASE 10311 1GVT4	N/A	CBU
1064	ATTENUATOR	NARDA 776B-20	NONE	09/13/01
1464	Spectrum analyzer	Hewlett Packard 8563E	3551A04428	01/02/01
1484	Cable 2.0-18.0 Ghz	Storm PR90-010-072	N/A	06/01/01
1485	Cable 2.0-18.0 Ghz	Storm PR90-010-216	N/A	06/01/01
1304	HORN ANTENNA	ELECTRO METRICS RGA-60	6151	07/30/01
1016	Pre-Amp	HEWLETT PACKARD 8449A	2749A00159	05/30/01

ANNEX A - TEST DETAILS

NAME OF TEST: RF Power Output	PARA. NO.: 2.1046
-------------------------------	-------------------

Minimum Standard: Para. No.24.232. Base stations are limited to 1640 watts peak E.I.R.P. with an antenna height up to 300 meters HAAT. In no case may the peak output power of a base station transmitter exceed 100 watts.

Method Of Measurement:

Detachable Antenna:

The peak power at antenna terminals is measured using an in-line peak power meter. Power output is measured with the maximum rated input level.

Integral Antenna:

If the antenna is not detachable from the circuit then the Peak Power Output is derived from the peak radiated field strength of the fundamental emission by using the plane wave relation $GP/4\pi R^2 = E^2/120\pi$ and proceeding as follows:

$$P = \frac{E^2 R^2}{30G} = \frac{E^2 3^2}{30G}$$

where,

P = the equivalent isotropic radiated power in watts

E = the maximum measured field strength in V/m

R = the measurement range (3 meters)

G = the numeric gain of the transmit antenna in relation to an isotropic radiator

EQUIPMENT: DAB-1819-100

NAME OF TEST: Occupied Bandwidth	PARA. NO.: 2.1047
---	--------------------------

Minimum Standard: Para. No. 24.238(b). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB.

Method Of Measurement:

CDMA

Spectrum analyzer settings:

RBW: 30 kHz

VBW: \geq RBW

Span: 5 MHz

Sweep: Auto

Mask: Set markers to -26 dB from peak of CW.

GSM

RBW: 3 kHz

VBW: \geq RBW

Span: 2 MHz

Sweep: Auto

Mask: Set markers to -26 dB from peak of CW.

NADC

RBW: 1 kHz

VBW: \geq RBW

Span: 1 MHz

Sweep: Auto

Mask: Set markers to -26 dB from peak of CW.

NAME OF TEST: Spurious Emission at Antenna Terminals PARA. NO.: 2.1051

Minimum Standard: Para. No.24.238(a). On any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

Method Of Measurement:

Spectrum analyzer settings:

CDMA

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 30 kHz (< 1MHz from Band Edge)
VBW: ≥ RBW
Sweep: Auto
Video Avg: 6 Sweeps

GSM

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: ≥ RBW
Sweep: Auto
Video Avg: Disabled

NADC

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: ≥ RBW
Sweep: Auto
Video Avg: Disabled

To demonstrate compliance at band edges the frequency of the input signal is set to the lowest and highest assigned channel and the center frequency of the spectrum analyzer is set to the upper and lower edges of the appropriate frequency block.

EQUIPMENT: **DAB-1819-100**

NAME OF TEST: Field Strength of Spurious Radiation	PARA. NO.: 2.1053
---	--------------------------

Minimum Standard: Para. No.24.238(a). On any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

Test Method: TIA/EIA-603-1992, Section 2.2.12

The antenna substitution method was used to determine the equivalent radiated power at spurious frequencies. The spurious emissions were measured at a distance of 3 meters. The EUT was then replaced with a reference substitution antenna with a known gain referenced to a dipole. This antenna was fed with a signal at the spurious frequency. The level of the signal was adjusted to repeat the previously measured level. The resulting erp is the signal level fed to the reference antenna corrected for gain referenced to a dipole.

EQUIPMENT: DAB-1819-100

NAME OF TEST: Frequency Stability	PARA. NO.: 2.1055
--	--------------------------

Minimum Standard: Para. No. 24.235. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Method Of Measurement:

Frequency Stability With Voltage Variation

The E.U.T. is placed in an environmental chamber and allowed to stabilize at +20 degrees Celsius for at least 15 minutes. The frequency counter and signal generator are phase locked with the same 10 MHz reference frequency by connecting the 10 MHz ref. out of the counter to the 10 MHz ref, in of the signal generator. With the voltage input to the E.U.T. set to 85% S.T.V., the frequency is measured in 30 second intervals for a period of 5 minutes. This procedure is repeated at 100% S.T.V. and 115% S.T.V.


Frequency Stability With Temperature Variation

The input voltage to the E.U.T. is set to S.T.V. and the temperature of the environmental chamber is varied in 10 degree steps from -30 degrees C to +50 degrees C. The E.U.T. is allowed to stabilize at each temperature and the frequency is measured in 30 second intervals for a period of 5 minutes.


ANNEX B - TEST DIAGRAMS

EQUIPMENT: DAB-1819-100

Para. No. 2.985 - R.F. Power Output





Para. No. 2.989 - Occupied Bandwidth




EQUIPMENT: DAB-1819-100

Para. No. 2.991 Spurious Emissions at Antenna Terminals



EQUIPMENT: DAB-1819-100

Para. No. 2.993 - Field Strength of Spurious Radiation



Para. No. 2.995 - Frequency Stability

