ONE WORLD OUR APPROVAL



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at device output terminal:	<u>32.96</u> dBm
Cable and Jumper loss:	<u>0.0</u> dB
Maximum peak output power at antenna input terminal:	<u>32.96</u> dBm
	1976.96964 mW
Single Antenna gain (typical):	<u>13</u> dBi
Number of Antennae:	1
Total Antenna gain (typical):	<mark>13</mark> dBi
	19.95262315 (numeric)
Prediction distance:	<u>60</u> cm
Prediction frequency:	<u>2338</u> MHz
MPE limit for uncontrolled exposure at prediction frequency:	<u> </u>
Power density at prediction frequency:	0.871942 mW/cm ²
	8.719421 W/m ²
Tx On time:	1.000000 ms
Tx period time:	1.000000 ms
Average Factor:	100.000000 %
Average Power density at prediction frequency:	8.719421 W/m ²

Margin of Compliance: 0.595123648 dB

Maximum allowable antenna gain: 13.59512365 dBi