

FCC  
Federal Communications Commission

*Peter de Wit*  
27 June 2003  
Phone +31 6 22470055  
Fax +31 46 4422192

**RF exposure requirements - FCC ID: NT8-14B4093KAFSW2 and  
FCC ID: NT8-14B4094KAFSW2**

Dear Application Examiner,

The maximum measured power output is 0,703 mW (-1,53 dBm), the maximum antenna gain is 2 dBi = numeric gain 1,585 (see also FCC test report - Exhibit B)

The maximum permissible exposure is defined in 47 CFR 1.1310 with 1 mW/cm<sup>2</sup>. The distance from the EUT's transmitting antenna where the exposure level reaches the maximum permitted level is calculated using the general equation:

$$S = P * G / 4\pi R^2$$

$S_{\max} = 1\text{mW/cm}^2$ ,  $P = 0,703\text{ mW}$ , linear power gain relative to the isotropic radiator = 2,0 dBi = 1,585 (numeric gain),  $R = \text{distance in cm}$

Solving for  $R$ , the 1mW/cm<sup>2</sup> limit is reached in a distance of 0,298 cm to the transmitting antenna.

The module has to be integrated in a way that the minimum distance of 0,298 cm is ensured so a statement in the users manual is not necessary.

Please contact us if you have any additional questions.

Best Regards

7layers AG