



FCC LISTED, REGISTRATION  
 NUMBER: 2764.01

ISED LISTED REGISTRATION  
 NUMBER: 23595-1

Test report No:  
 3727ERM.002A1

## Partial Test report

USA FCC Part 15.247, 15.209, 15.207  
 CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and  
 5725 - 5850 MHz

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and License-  
 Exempt Local Area Network (LE-LAN) Devices.

(*) Identification of item tested	Sense Line Assembly (SLA)
(*) Trademark	Visteon
(*) Model and /or type reference tested	SLA8
Other identification of the product	FCC ID: NT8-SLA8 IC: 3043A-SLA8
(*) Features	Cell Monitoring Unit in Wireless Battery Management
Manufacturer	Visteon Corporation One Village Center Drive, Van Buren Township, MI 48111, USA.
Test method requested, standard	USA FCC Part 15.247, 10-1-20 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz USA FCC Part 15.209, 10-1-20 Edition: Radiated emission limits; general requirements CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (March 2019). 558074 D01 15.247 Meas. Guidance v05r02 (April 2019): Guidance for Compliance Measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under section §15.247 of the FCC Rules ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	See Appendix A
Approved by (name / position & signature)	Domingo Galvez EMC&RF Lab Manager
Date of issue	09-22-2022
Report template No	FDT08_23 (*) "Data provided by the client"

## Index

COMPETENCES AND GUARANTEES .....	3
GENERAL CONDITIONS .....	3
UNCERTAINTY .....	3
DATA PROVIDED BY THE CLIENT .....	4
USAGE OF SAMPLES .....	4
TEST SAMPLE DESCRIPTION.....	5
IDENTIFICATION OF THE CLIENT .....	6
TESTING PERIOD AND PLACE .....	6
DOCUMENT HISTORY .....	6
MODIFICATIONS TO THE REFERENCE TEST REPORT.....	7
ENVIRONMENTAL CONDITIONS .....	7
REMARKS AND COMMENTS.....	8
TESTING VERDICTS.....	8
SUMMARY .....	8
LIST OF EQUIPMENT USED DURING THE TEST .....	9
APPENDIX A: TEST RESULTS (PROPRIETARY PROTOCOL) .....	10

## Competences and guarantees

DEKRA Certification Inc. is a testing laboratory accredited by A2LA (The American Association for Laboratory Accreditation), to perform the tests indicated in the Certificate 2764.01

DEKRA Certification Inc. is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

## General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies.

## Uncertainty

Uncertainty (factor k=2) was calculated according to the DEKRA Certification internal document PODT000.

Test case	Frequency (MHz)	U(k=2)	Units
RF Power and PSD	2402-2483	0.88	dB
Occupied Bandwidth		1.87	%
Band Edge		0.64	dB
Radiated Spurious Emission	30-180	4.27	dB
	180-1000	3.14	dB
	1000-18000	3.30	dB
	18000-40000	3.49	dB

## Data provided by the client

---

The DUT is an Electronic module intended to monitor battery module cell groups voltages and module temperatures from the High Voltage battery bus in addition to activate cell balancing to improve battery cells life.

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Usage of samples

---

Samples used for test have been selected by: The client.

**Sample S/01** is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
3625/01	CMUr (MTF Radiated)	SLA8	1122070EM4550132	05/02/2022

Following Auxiliary items were used with Sample S/01 to perform testing:

Control N°	Description	Model	Serial N°
DEKRA 10	Transceiver USB 1	-	-

---

1. Sample S/01 was used for following test(s)  
All Radiated tests indicated in appendix A.

**Sample S/02** is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
3773/01	CMUr (MTF Conducted)	SLA8	2122224EM4560105	09/06/2022

Following Auxiliary items were used with Sample S/01 to perform testing:

Control N°	Description	Model	Serial N°
DEKRA 10	Transceiver USB 1	-	-

---


1. Sample S/02 was used for following test(s)  
All Conducted tests indicated in appendix A.

## Test sample description

Ports..... :	Port name and description	Cable					
		Specified length [m]	Attached during test	Shielded	Coupled to patient		
		Main connector/harness	1.5	<input type="checkbox"/>	<input type="checkbox"/>	N/A	
				<input type="checkbox"/>	<input type="checkbox"/>	N/A	
				<input type="checkbox"/>	<input type="checkbox"/>	N/A	
Supplementary information to the ports..... :	No Data Provided						
Rated power supply .....	Voltage and Frequency	Reference poles					
		L1	L2	L3	N	PE	
		<input type="checkbox"/> AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
		<input type="checkbox"/> AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
		<input checked="" type="checkbox"/> DC: 29.2 V					
	<input type="checkbox"/> DC:						
Rated Power..... :	Current in normal mode: 7 mA						
Clock frequencies..... :	40 MHz						
Other parameters .....	No Data Provided						
Software version .....	SWO100-28104-004F00						
Hardware version .....	VPNAMU-14B115-PA						
Dimensions in cm (W x H x D) ... :	810.43 mm X 266.80 mm						
Mounting position .....	<input type="checkbox"/>	<i>Table top equipment</i>					
	<input type="checkbox"/>	<i>Wall/Ceiling mounted equipment</i>					
	<input type="checkbox"/>	<i>Floor standing equipment</i>					
	<input type="checkbox"/>	<i>Hand-held equipment</i>					
	<input checked="" type="checkbox"/>	<i>Other: Integrated in-side electric vehicle battery pack.</i>					
Modules/parts..... :	Module/parts of test item	Type			Manufacturer		
	No Data Provided						

Accessories (not part of the test item) .....	Description	Type	Manufacturer
	Harness		
	URT dongle		
Documents as provided by the applicant .....	Description	File name	Issue date
	Declaration Equipment Data	FDT30_18 Declaration Equipment Data_SLA8_July 12, 2022.pdf	06/12/2022

**Copy of marking plate:**



## Identification of the client

VISTEON CORPORATION  
 One Village Center Drive. Van Buren Township, MI. 48111, USA.

## Testing period and place

<b>Test Location</b>	DEKRA Certification Inc.
<b>Date (start)</b>	06-16-2022
<b>Date (finish)</b>	09-15-2022

## Document history

Report number	Date	Description
3727ERM.002	08-12-2022	First release
3727ERM.002A1	09-22-2022	Second release

## Modifications to the reference test report

It was introduced the following modifications in respect to the test report number 3727ERM.002 related with the same samples, in the next clauses and sub-clauses:

Clauses/ Sub-Clauses	Modification	Justification
Page 9: List of equipment use during the test	Included Conducted Measurements table	Conducted results were added in the test report
Pages 14-21: TEST A.1: MAXIMUM PEAK OUTPUT POWER AND ANTENNA GAIN	Conducted measurement test setup added and output power test results updated	Conducted output power measured as per TCB request

This modification test report cancels and replaces the test report 3727ERM.002

## Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 30 % Max. = 75 %
<b>Air pressure</b>	Min. = 860 mbar Max. = 1060 mbar

In the semi anechoic chamber, the following limits were not exceeded during the test.

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 30 % Max. = 75 %
<b>Air pressure</b>	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 30 % Max. = 60 %
<b>Air pressure</b>	Min. = 860 mbar Max. = 1060 mbar

## Remarks and comments

The tests have been performed by the technical personnel: Sravani Gollamudi, Nasir Khan, Lourdes Maria Valverde and Koji Nishimoto.

## Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

## Summary

FCC PART 15 PARAGRAPH (Proprietary protocol)					
Section	FCC Spec Clause	RSS Spec Clause	Test Description	Verdict	Remark
-	§ 2.1049	RSS-GEN 6.7	99% Occupied Bandwidth	N/M	Refer 1
-	§15.247 (a) (2)	RSS-247 5.2 (a)	6dB Bandwidth	N/M	Refer 1
A.1	§ 15.247 (b) (3)	RSS-247 5.4 (d)	Maximum Peak Output Power and antenna gain	P	N/A
-	§ 15.247 (d)	RSS-247 5.5	Band-edge conducted emissions compliance (Transmitter)	N/M	Refer 1
-	§ 15.247 (e)	RSS-247 5.2 (b)	Power Spectral Density	N/M	Refer 1
-	§15.247 (d)	RSS-247 5.5	Emission limitations Conducted (Transmitter)	N/A	Refer 1
A.2	§15.247 (d)	RSS-247 5.5	Emission limitations Radiated (Transmitter)	P	N/A
<u>Supplementary information and remarks:</u> 1. Not requested.					



## List of equipment used during the test

### Conducted Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
1038	TS8997 TEST SYSTEM	Rohde & Schwarz	TS8997	N/A	N/A
1107	ETHERNET SNMP THERMOMETER	HW GROUP	HWg-STE Plain	2022/08	2024/08
1313	WIRELESS MEASUREMENT SOFTWARE R&S WMS32	Rohde & Schwarz	N/A	N/A	N/A

### Radiated Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
0981	RF pre-amplifier	Bonn Elektronik	BLMA0118-2A	2020/11	2022/11
1012	EMI TEST RECEIVER	Rohde & Schwarz	ESR 26	2022/04	2024/04
1014	Spectrum analyzer	Rohde & Schwarz	FSV40	2021/05	2023/05
1056	Double-ridge Waveguide Horn antenna 18-40 GHz	ETS LINDGREN	3116C	2020/01	2023/01
1057	Double-ridge Waveguide Horn antenna 1-18 GHz	ETS LINDGREN	3115	2020/06	2023/06
1065	Biconical Log antenna	ETS LINDGREN	3142E	2020/08	2023/08
1108	Ethernet SNMP Thermometer- CR Room	HW Group	HWg-STE Plain	2020/08	2022/08
1111	ETHERNET SNMP THERMOMETER	HW GROUP	HWg-STE Plain	2020/08	2022/08
1179	Semi anechoic Absorber Lined Chamber	Frankonia	SAC 3 plus "L"	N/A	N/A
1314	WIRELESS MEASUREMENT SOFTWARE R&S EMC32	Rohde & Schwarz	N/A	N/A	N/A

## Appendix A: Test results (Proprietary Protocol)

## Appendix A Content

PRODUCT INFORMATION .....	12
DESCRIPTION OF TEST CONDITIONS .....	13
TEST A.1: MAXIMUM PEAK OUTPUT POWER AND ANTENNA GAIN .....	14
TEST A.2: EMISSION LIMITATIONS RADIATED (TRANSMITTER) .....	21

## PRODUCT INFORMATION

---

The following information is provided by the client

Information	Description
Modulation	GFSK
Adaptive	Non-adaptive equipment
Operation mode	
- Operating Frequency Range	2405 – 2480 MHz
- Nominal Channel Bandwidth	2 MHz
- RF Output Power	10 dBm
Antenna type	Integrated chip antenna
Antenna gain	2.6 dBi
Nominal Voltage	
- Supply Voltage	29.2 V nominal
- Type of power source	DC Power supply
Equipment type	Wireless Battery Management
Geo-location capability	No

## DESCRIPTION OF TEST CONDITIONS

---

TEST CONDITIONS	DESCRIPTION
TC#01	<p><u>Power supply (V):</u> <math>V_{\text{nominal}} = 29.2 \text{ V dc}</math></p> <p>Bandwidth: 2 MHz</p> <p><u>Test Frequencies for Conducted/ Radiated tests:</u> Lowest channel: 2405 MHz Middle channel: 2445 MHz Highest channel: 2480 MHz</p>

## TEST A.1: MAXIMUM PEAK OUTPUT POWER AND ANTENNA GAIN

<b>LIMITS:</b>	Product standard:	Part 15 Subpart C §15.247 and RSS-247
	Test standard:	Part 15 Subpart C §15.247(b)(3) and RSS-247 5.4(d)


### LIMITS

§15.247(b)(3) and RSS-247 5.4(d): For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).


RSS-247 5.4(d): The e.i.r.p. shall not exceed 4 W (36 dBm)

### TEST SETUP

Conducted measurements setup



Radiated measurements setup




CONDUCTED TESTING	
TESTED SAMPLES:	S/02
TESTED CONDITIONS MODES:	TC#01
TEST RESULTS:	PASS

Maximum declared antenna gain: +2.6 dBi


	Lowest frequency 2405 MHz	Middle frequency 2445 MHz	Highest frequency 2480 MHz
Maximum conducted power (dBm)	8.4	7.9	8.2
Maximum EIRP power (dBm)	11.0	10.5	10.8

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power limit is not required to be reduced from the stated values.

**Lowest Channel**



**Middle Channel**



TEST RESULTS (Cont.):	CONDUCTED PEAK POWER		
<b>Highest Channel</b>			
Peak Power			
<p>The graph displays the peak power level in dBm across a frequency range from 2475.5 MHz to 2484.5 MHz. The y-axis ranges from -20 dBm to 25 dBm. A blue curve represents the power level for Connector 1, which peaks at approximately 8 dBm at 2480 MHz. A red 'x' marks this peak. The legend indicates that the blue line is for Connector 1 and the red 'x' is for Peak Connector 1.</p>			
<b>Measurement</b>			
Setting	Instrument Value	Instrument Value	Instrument Value
Start Frequency	2.40050 GHz	2.44050 GHz	2.47550 GHz
Stop Frequency	2.40950 GHz	2.44950 GHz	2.48450 GHz
Span	9.000 MHz	9.000 MHz	9.000 MHz
RBW	3.000 MHz	3.000 MHz	3.000 MHz
VBW	10.000 MHz	10.000 MHz	10.000 MHz
Sweep Points	101	101	101
Sweep time	1.271 $\mu$ s	1.271 $\mu$ s	1.271 $\mu$ s
Reference Level	20.000 dBm	20.000 dBm	20.000 dBm
Attenuation	35.000 dB	35.000 dB	35.000 dB
Detector	Max Peak	Max Peak	Max Peak
Sweep Count	100	100	100
Filter	3 dB	3 dB	3 dB
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep type	FFT	FFT	FFT
Preamp	off	off	off
Stable mode	Trace	Trace	Trace
Stable value	0.50 dB	0.50 dB	0.50 dB
Run	4 / max. 150	4 / max. 150	4 / max. 150
Stable	3 / 3	3 / 3	3 / 3
Max Stable Difference	0.02 dB	0.03 dB	0.04 dB




RADIATED TESTING	
<b>TESTED SAMPLES:</b>	S/01
<b>TESTED CONDITIONS MODES:</b>	Pre-scan to determine worst DUT orientation
<b>TEST RESULTS:</b>	See following

The following table shows the measured fundamental signal levels at 2405 MHz with the three different DUT orientations shown in the photos below.

- Rotating the DUT from 0-360 degrees (turntable).
- Moving RX antenna from 1-4m in boresight mode according to ANSI 63.10 (horizon to 45 degrees).


DUT Orientation	PK+_MAXH (dBµV/m)	PK+_MAXH (dBm)
Orientation X*	99.9	4.7
Orientation Y	97.3	2.1
Orientation Z	97.7	2.5



\* The following test results were based on the worst DUT orientation X.

<b>TESTED SAMPLES:</b>	S/01
<b>TESTED CONDITIONS MODES:</b>	TC#01
<b>TEST RESULTS:</b>	PASS

Lowest channel




— PK+\_MAXH

Frequency (MHz)	PK+_MAXH (dBµV/m)	PK+_MAXH (dBm)	Pol
2405.500000	99.9	4.7	H

EIRP (dBm) = E (dBµV/m) + 20log(D) - 104.8; where D is the measurement distance in meter

**TEST RESULTS (Cont.):**

Middle channel




— PK+\_MAXH

Frequency (MHz)	PK+_MAXH (dBµV/m)	PK+_MAXH (dBm)	Pol
2444.500000	101.7	6.5	H

**TEST RESULTS (Cont.):**

Highest channel



— PK+\_MAXH

Frequency (MHz)	PK+_MAXH (dBµV/m)	PK+_MAXH (dBm)	Pol
2444.500000	100.9	5.7	H

**TEST A.2: EMISSION LIMITATIONS RADIATED (TRANSMITTER)**

<b>LIMITS:</b>	Product standard:	Part 15 Subpart C §15.247 and RSS-247
	Test standard:	Part 15 Subpart C §15.247 (d) and RSS-Gen 8.9 and 8.10

LIMITS

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

**TEST SETUP**

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is located at 3 m for the frequency range 30-1000 MHz (Bilog antenna) and 1-18 GHz (Double ridge horn antenna), and 1m for the frequency range 18 GHz- 26 GHz (Double ridge horn antenna).

For radiated emissions in the range 18 - 26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

**TEST SETUP (CONT.)**


Radiated measurements Setup  $f < 1$  GHz



Radiated measurements setup  $f > 1-18$  GHz



Radiated measurements setup  $f > 18$  GHz




<b>TESTED SAMPLES:</b>	S/01
<b>TESTED CONDITIONS MODES:</b>	TC#01
<b>TEST RESULTS:</b>	Pass


The preliminary test was performed in three different DUT orientations (X, Y and Z) to determine the worst case. The worst-case results were shown in the following test results.

**Frequency range 1 GHz – 26 GHz**

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).








**TEST RESULTS (Cont.):** **1-18 GHz (Highest Channel)**

**Highest Channel**




- AVG\_MAXH
- PK+\_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)	Comment
2480.500000	100.9	98.0	H	---	---	Fundamental

**TEST RESULTS (Cont.):** **18 – 26 GHz**

**Lowest Channel**




- AVG\_MAXH
- PK+\_MAXH
- TX limits to Spurious Emission FCC15.247 (1GHz to 26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1GHz to 26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
23951.500000	52.3	43.3	H	10.7	54.0

**TEST RESULTS (Cont.):** **18 – 26 GHz**

**Middle Channel**




- AVG\_MAXH
- PK+\_MAXH
- TX limits to Spurious Emission FCC15.247 (1GHz to 26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1GHz to 26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
23949.000000	52.4	42.8	H	11.2	54.0

**TEST RESULTS (Cont.):** **18 – 26 GHz**

**Highest Channel**



- AVG\_MAXH
- PK+\_MAXH
- TX limits to Spurious Emission FCC15.247 (1GHz to 26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1GHz to 26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
22630.500000	51.4	41.5	V	12.5	54.0

